

“3D Flood Inundation Forecasting & Mapping Using Satellite + DEM Data with Deep Learning”

¹Mr.Akash Dhaygode

Research Scholar, Department of M.E Civil (Environmental) Engineering
APCOER, Parvati, Pune,
Maharashtra, India416009
dhaygodeakash@gmail.com

²Dr. Sunil B. Thakare

Principal,
APCOER, Parvati, Pune,
Maharashtra, India416009
prof.sbthakare@rediffmail.com

³Prof. Ranjitsing P. Gaikwad

Assistant Professor, Post Graduate Department of Civil (Environmental) Engineering
APCOER, Parvati, Pune,
Maharashtra, India416009
ranjitsinggaikwad22@gmail.com

Abstract: Floods are among the most destructive natural disasters, causing significant loss of life, infrastructure damage, and economic disruption worldwide. Traditional hydrological and hydraulic models often rely on ground-based measurements, complex calibration, and limited spatial coverage, restricting their real-time applicability and large-scale accuracy. This study aims to develop an accurate and efficient 3D flood inundation forecasting and mapping framework by integrating satellite imagery, Digital Elevation Model (DEM) data, and deep learning techniques to enhance flood prediction and disaster management. Multi-source geospatial datasets, including high-resolution optical and SAR satellite imagery along with DEM data, are collected and preprocessed through radiometric correction, normalization, terrain conditioning, and data fusion techniques to extract critical flood-related features such as elevation, slope, drainage patterns, and water indices (e.g., NDWI). A deep learning model, such as CNN, U-Net, or a CNN-LSTM hybrid architecture, is designed to capture complex spatial and temporal flood dynamics for predicting flood extent and estimating water depth in three dimensions. The model is trained and validated using historical flood event datasets, and its performance is evaluated using metrics including Accuracy, Precision, Recall, F1-score, Intersection over Union (IoU), and Root Mean Square Error (RMSE). The proposed framework is expected to generate high-resolution 3D flood inundation maps, improve prediction accuracy compared to conventional methods, enable reliable water depth estimation, and support the development of a real-time decision-support system for early warning and disaster response. Overall, the integration of remote sensing, DEM-based terrain analysis, and deep learning provides a scalable and data-driven solution for advanced flood risk assessment and resilient disaster management.

Keywords: 3D Flood Inundation Modeling, Deep Learning for Flood Prediction, Digital Elevation Model (DEM), Remote Sensing, Satellite Image Processing, Convolutional Neural Networks (CNN), U-Net Architecture, Spatial-Temporal Modeling, Water Depth Estimation, Geospatial Data Fusion, Flood Risk Mapping, Disaster Management Decision Support System.

I. Introduction

Floods are among the most destructive natural disasters worldwide, causing extensive socio-economic losses, infrastructure damage, and environmental degradation. Rapid urbanization, climate change, and extreme precipitation events have increased the frequency and intensity of flood occurrences. Traditional hydrological and hydraulic models, while physically interpretable, often require extensive calibration, high computational resources, and dense ground-based observations, limiting their real-time applicability and scalability. Recent studies emphasize the necessity of integrating advanced data-driven techniques to improve flood forecasting accuracy and computational efficiency [Fang Yang et al., 2024]; [Francis Yongwa Dtiissibe et al., 2024].

With the advancement of Artificial Intelligence (AI) and Deep

Learning (DL), flood forecasting has shifted toward data-driven approaches capable of modeling complex non-linear spatio-temporal relationships. Hybrid architectures such as CNN-LSTM and Transformer-based models have demonstrated superior predictive performance compared to conventional statistical models. For instance, hybrid deep learning frameworks have achieved high Nash–Sutcliffe Efficiency (NSE) values exceeding 0.90 in watershed-scale forecasting applications [Wenzhong Li et al., 2024]. Similarly, LSTM-based models have shown strong correlation performance in river flow prediction tasks, highlighting their suitability for flood forecasting in data-scarce and ungauged basins [Khansa Aatif et al., 2024].

Remote sensing technologies play a critical role in large-scale flood monitoring by providing consistent and repetitive spatial observations. Optical and Synthetic Aperture Radar (SAR) imagery enable rapid flood extent extraction even under cloud-

covered conditions. Deep learning-based semantic segmentation models such as U-Net have significantly improved flood inundation mapping accuracy using Sentinel-1 SAR imagery and DEM-derived features [Zhouyayan Li et al., 2023]. Moreover, multi-source satellite data combined with knowledge-transfer strategies have enhanced heterogeneous image change detection for automated flood monitoring [Bofei Zhao et al., 2024]. These advancements demonstrate the potential of integrating satellite observations with intelligent algorithms for near real-time flood mapping.

Digital Elevation Models (DEMs) are fundamental for terrain analysis, hydrodynamic modeling, and water depth estimation in flood studies. The accuracy of DEM data directly influences flood extent simulation and inundation depth prediction. Comparative analyses of global DEMs reveal that higher-resolution datasets such as TanDEM-X and NASADEM significantly improve flood modeling reliability [Vineela Nandam et al., 2024]; [Thanh-Nhan-Duc Tran et al., 2023]. Furthermore, multisource DEM fusion techniques have reduced elevation errors and improved urban flood simulations, demonstrating the importance of accurate topographic representation in 3D flood modeling [Haocheng Huang et al., 2023].




Figure 1(a): Traditional vs. Modern Prediction Systems

Recent developments have also focused on generating three-dimensional (3D) flood products by integrating satellite imagery with DEM datasets. Downscaling approaches combining VIIRS imagery with SRTM DEM data have successfully produced refined 30-m resolution 3D flood extent and water depth maps, enhancing real-time flood forecasting capabilities [Sanmei Li et al., 2022]. Additionally, rapid spatio-temporal prediction models based on deep learning have shown strong capability in estimating flood inundation depth for urban environments, addressing the computational limitations of traditional hydrodynamic simulations [Wenting Zhang et al., 2023].

Background of Flood Hazards and Disaster Impact

Floods are among the most frequent and devastating natural hazards, affecting millions of people annually and causing severe economic, environmental, and infrastructural losses. Climate change, rapid urban expansion, deforestation, and altered hydrological cycles have intensified flood occurrences across both developed and developing nations. Coastal, riverine, and urban pluvial floods disrupt transportation networks, damage residential and commercial infrastructure, and threaten food security. Recent research emphasizes the growing need for advanced flood risk management strategies

and data-driven resilience frameworks to mitigate disaster impacts and enhance adaptive capacity [Zhewei Liu et al., 2025]; [Pavithra Rathnasiri et al., 2023]. The increasing complexity of flood events demands integrated technological solutions capable of supporting early warning systems and disaster response planning.

Overview of Flood Inundation Modeling Techniques

Flood inundation modeling aims to simulate the spatial extent, depth, and duration of floodwaters under varying hydrometeorological conditions. Traditional approaches include hydrological rainfall-runoff models and hydraulic models such as 1D and 2D shallow water equation-based simulations. Hydrodynamic models like HEC-RAS and SWAT are widely used for river basin and urban flood analysis. Recent advancements have incorporated hybrid hydrologic-hydrodynamic frameworks to improve forecasting reliability, particularly in regulated river basins [Amina Khatun et al., 2025]. Additionally, flood inundation mapping services such as HAND-based frameworks have been developed to translate discharge forecasts into inundation extents efficiently [Anupal Baruah et al., 2025]. Although physically robust, these techniques often require high computational resources and detailed boundary conditions.

Limitations of Traditional Hydrological and Hydraulic Models

Despite their physical interpretability, traditional hydrological and hydraulic models face several challenges. They require extensive calibration, accurate boundary conditions, and high-resolution topographic data, which may not be readily available in data-scarce regions. Computational complexity limits their real-time application, particularly for large-scale or high-resolution urban flood simulations. Studies have shown that physics-based models, while accurate, struggle to provide rapid predictions necessary for early warning systems [Fang Yang et al., 2024]. Furthermore, uncertainties in rainfall inputs, terrain representation, and parameter estimation can significantly influence flood extent and depth predictions [Samyah Salem Refadah et al., 2025]. These limitations highlight the need for efficient, scalable, and data-driven alternatives.

Role of Remote Sensing in Flood Monitoring

Remote sensing technologies have revolutionized flood monitoring by providing large-scale, repetitive, and near real-time observations of Earth's surface. Optical satellite imagery from Landsat and Sentinel-2 enables water body detection using spectral indices such as NDWI, while Synthetic Aperture Radar (SAR) imagery from Sentinel-1 allows flood mapping even under cloud-covered and nighttime conditions. Deep learning-based semantic segmentation approaches have significantly improved flood extent extraction accuracy from SAR datasets [Zhouyayan Li et al., 2023]. Multi-source satellite integration and change detection techniques further enhance flood monitoring reliability across heterogeneous landscapes [Bofei Zhao et al., 2024]. These advancements demonstrate the critical role of satellite data in supporting rapid disaster assessment and emergency response.

Importance of Digital Elevation Model (DEM) in Terrain Analysis

Digital Elevation Models (DEMs) provide essential topographic information required for flood simulation, watershed delineation, slope analysis, and water depth estimation. The vertical accuracy and spatial resolution of DEM datasets significantly influence inundation modeling performance. Comparative studies of global DEMs such as SRTM, NASADEM, MERIT, and TanDEM-X reveal substantial variations in flood prediction reliability based on terrain

representation accuracy [Vineela Nandam et al., 2024]; [Thanh-Nhan-Duc Tran et al., 2023]. Recent research also highlights the effectiveness of DEM downscaling and multisource fusion techniques in reducing elevation bias and enhancing urban flood simulations [Zanko Zandsalimi et al., 2025]. Accurate DEM integration is therefore fundamental for generating reliable 3D flood inundation maps.

Application of Deep Learning in Geospatial Analysis

Deep learning has emerged as a transformative tool in geospatial analysis, particularly for modeling complex spatial-temporal phenomena such as floods. Convolutional Neural Networks (CNNs), U-Net architectures, LSTM networks, and Transformer-based models have demonstrated strong capability in flood extent mapping, water depth estimation, and time-series forecasting. Hybrid deep learning models incorporating attention mechanisms have significantly enhanced predictive performance for extreme flood events [Cheng Chen et al., 2025]. Moreover, spatiotemporal models such as CNN-LSTM and Deep Neural Operators provide efficient alternatives to computationally intensive hydrodynamic simulations [Qingsong Xu et al., 2025]. The integration of deep learning with remote sensing and DEM data enables automated, scalable, and high-resolution 3D flood inundation forecasting, supporting improved disaster preparedness and risk management.

Review of Conventional Flood Modeling Approaches

Flood modeling has traditionally relied on physically based hydrological and hydraulic models to simulate rainfall-runoff processes and floodplain dynamics. These models are grounded in fluid mechanics and mass conservation principles, providing interpretable results for discharge estimation and inundation mapping. However, their accuracy largely depends on the quality of input data, terrain representation, and boundary conditions. Recent comparative assessments highlight that while such models remain essential for regulatory and engineering applications, they often require high computational power and detailed calibration, limiting their real-time scalability [Samyah Salem Refadah et al., 2025].




Figure 1(b): Multi-Source Elevation and Data Fusion

Hydrological Models: Hydrological models primarily simulate the rainfall-runoff transformation process within a watershed. Models such as SWAT and conceptual rainfall-runoff frameworks estimate streamflow based on precipitation, soil characteristics, land use, and evapotranspiration parameters. Studies evaluating global DEM impacts on

hydrological simulations reveal that DEM resolution significantly affects runoff generation, groundwater flow, and sediment yield estimation [Thanh-Nhan-Duc Tran et al., 2023]. Furthermore, machine learning-enhanced hydrological forecasting approaches have been explored to reduce uncertainty in discharge prediction, especially in ungauged basins [Yehai Tang et al., 2023]. Despite their robustness, hydrological models often struggle with real-time flood depth and inundation mapping.

Hydraulic Models (1D/2D Models): Hydraulic models simulate water movement across river channels and floodplains using the Saint-Venant shallow water equations. One-dimensional (1D) models focus on longitudinal river flow, while two-dimensional (2D) models provide spatially distributed flood extent and depth predictions. Integrated hydrologic-hydrodynamic models have shown improved performance in dam-regulated basins by incorporating discharge corrections into inundation simulations [Amina Khatun et al., 2025]. However, physics-based 2D models are computationally intensive and require high-resolution DEMs for reliable predictions, limiting their efficiency for rapid flood forecasting [Fang Yang et al., 2024].

Remote Sensing-Based Flood Mapping Techniques

Remote sensing technologies provide spatially continuous data that support large-scale flood monitoring and mapping. Satellite imagery enables rapid detection of flood extent, even in inaccessible regions, reducing reliance on ground observations.

Optical Satellite-Based Flood Detection: Optical satellite imagery from platforms such as Landsat and Sentinel-2 is widely used for flood mapping through spectral water indices like NDWI and MNDWI. Time-series imagery enhances detection accuracy by distinguishing permanent water bodies from temporary floodwaters. Recent advancements using Harmonized Landsat and Sentinel (HLS) datasets have improved flood mapping under cloud-obstructed conditions by reconstructing missing information using historical water occurrence data [Zhiwei Li et al., 2024]. Optical imagery offers high spatial resolution but is limited by cloud cover during extreme weather events.

SAR-Based Flood Mapping: Synthetic Aperture Radar (SAR) imagery overcomes cloud and illumination limitations by utilizing microwave backscatter signals for water detection. SAR intensity-based thresholding and machine learning methods have significantly improved urban flood delineation [Jie Zhao et al., 2025]. Deep learning approaches such as U-Net applied to Sentinel-1 SAR imagery have demonstrated superior performance in flood extent extraction compared to traditional classification techniques [Zhouyayan Li et al., 2023]. Additionally, knowledge transfer strategies integrating multi-source satellite data enhance heterogeneous flood change detection in complex landscapes [Bofei Zhao et al., 2024].

DEM-Based Terrain and Flood Analysis

Digital Elevation Models (DEMs) are critical for representing terrain characteristics that influence flood propagation, flow accumulation, and water depth estimation. DEM accuracy directly affects hydrodynamic simulation reliability.

Elevation and Slope Analysis: Elevation and slope parameters derived from DEMs determine flow direction, runoff velocity, and floodplain connectivity. Comparative studies of global DEM datasets indicate that high-resolution models such as TanDEM-X outperform lower-resolution datasets in flood inundation modeling [Vineela Nandam et al., 2024]. Moreover, deep learning-based downscaling techniques have been introduced to enhance DEM resolution and reduce vertical bias, significantly improving urban flood simulations [Zanko

Zandsalimi et al., 2025]. These findings highlight the importance of precise topographic representation in 3D flood mapping.

Watershed and Drainage Extraction: Watershed delineation and drainage network extraction are fundamental for hydrological modeling and flood susceptibility mapping. DEM-based hydro-conditioning ensures proper drainage continuity and improves flood mapping accuracy in low-relief terrains [Hassan Sabeh et al., 2025]. Height Above Nearest Drainage (HAND) frameworks further convert discharge predictions into spatial inundation extents efficiently [Anupal Baruah et al., 2025]. Such terrain-based methods are computationally efficient but may oversimplify complex hydraulic interactions.

Deep Learning Techniques for Flood Prediction

Deep learning models have emerged as powerful tools for capturing nonlinear spatio-temporal relationships in flood forecasting and inundation mapping. These approaches reduce computational complexity compared to physics-based simulations while maintaining high predictive accuracy.

Convolutional Neural Networks (CNN): Convolutional Neural Networks (CNNs) are widely used for spatial feature extraction from satellite imagery and DEM datasets. CNN-based models effectively identify flood-prone areas and classify inundated regions with high accuracy. Three-dimensional CNN architectures combined with hyperparameter optimization techniques have demonstrated superior performance in flood susceptibility mapping tasks [Amala Mary Vincent et al., 2023]. CNN models are particularly effective in handling large-scale geospatial raster data for flood prediction.

U-Net for Image Segmentation: U-Net, a specialized CNN architecture designed for semantic segmentation, has been extensively applied to flood extent extraction from SAR and optical imagery. By incorporating skip connections and multi-scale feature learning, U-Net enhances boundary detection and small-object segmentation accuracy. Sentinel-1 SAR-based U-Net models have achieved significant improvements in flood mapping performance when integrated with DEM and slope data layers [Zhouyan Li et al., 2023]. These models provide automated and high-resolution flood inundation maps suitable for real-time applications.

CNN-LSTM for Spatio-Temporal Modeling: Flood events exhibit strong spatial and temporal dependencies influenced by rainfall patterns and terrain conditions. Hybrid CNN-LSTM architectures combine spatial feature extraction capabilities of CNNs with temporal sequence learning of Long Short-Term Memory (LSTM) networks. Such models have demonstrated high correlation and reduced RMSE in water level and flood forecasting tasks [Ali Shahabi et al., 2024]. Additionally, advanced spatiotemporal models incorporating attention mechanisms and deep neural operators further improve forecasting efficiency in complex urban environments [Qingsong Xu et al., 2025]. These hybrid frameworks are highly suitable for developing 3D flood inundation forecasting systems integrating satellite and DEM data.

Synthesis of Previous Research

Recent advancements in flood inundation modeling demonstrate a progressive transition from traditional physics-based hydrological and hydraulic models toward integrated data-driven and hybrid modeling frameworks. Earlier studies emphasized improving 2D hydrodynamic flood predictions through enhanced terrain datasets and DEM integration, highlighting the importance of vertical accuracy in reliable flood simulations [1][10][37]. Terrain-based models such as HAND and hydro-conditioned DEM approaches have

improved flood extent mapping in low-relief and data-scarce regions, though they still face challenges in representing complex hydraulic interactions [2][6][33]. The incorporation of remote sensing technologies has significantly strengthened flood monitoring capabilities. Optical satellite imagery has been widely used for water detection through spectral indices and time-series analysis, while SAR-based approaches have enabled flood mapping under cloud-covered and extreme weather conditions [21][44][50]. Multi-source satellite integration and heterogeneous image change detection frameworks have further enhanced the automation and reliability of flood inventory generation and susceptibility mapping [4][28][45]. Additionally, the development of long-term high-resolution flood datasets has supported improved calibration and validation of predictive models [24].

Parallel to these developments, DEM accuracy and resolution have been identified as critical factors influencing flood inundation and water depth estimation. Comparative studies of global DEMs demonstrate substantial performance variability across terrain types, emphasizing the necessity for DEM evaluation and bias correction before hydrodynamic modeling [32][39][42]. Advanced DEM reconstruction and downscaling techniques using deep learning architectures such as U-Net have significantly reduced vertical errors and improved urban flood simulation outcomes [13][41]. Furthermore, the derivation of 3D flood products through DEM-satellite integration represents a major step toward detailed flood depth mapping [38].

The emergence of Artificial Intelligence (AI) and Deep Learning (DL) has transformed flood prediction methodologies by enabling efficient modeling of complex spatial-temporal dynamics. CNN-based and U-Net architectures have demonstrated high accuracy in flood extent segmentation from SAR and optical datasets [43], while hybrid CNN-LSTM and Transformer-based models have achieved superior forecasting performance in river basins and urban environments [25][29][30]. Attention-enhanced deep learning frameworks and neural operator models have further improved prediction of extreme flood events and high-water depths [3][17]. Comprehensive reviews confirm that AI-driven approaches offer scalability, rapid computation, and adaptability compared to conventional physics-based simulations [14][19][48]. Moreover, hybrid frameworks integrating hydrological, hydrodynamic, and deep learning components have shown promising improvements in regulated river systems and real-time forecasting scenarios [18], [40]. Data assimilation strategies incorporating crowdsourced information and multi-modal satellite inputs have further enhanced predictive accuracy and resilience planning [34][35][36]. Despite these significant advancements, challenges remain in achieving fully integrated, high-resolution 3D flood inundation forecasting systems capable of real-time implementation with multi-source geospatial datasets.

Research Gap Identification

Despite significant advancements in flood inundation modeling, several limitations persist in existing research. Traditional hydrological and hydraulic models provide physically interpretable flood simulations; however, they require extensive calibration, high computational resources, and detailed boundary conditions, limiting their real-time scalability and applicability in data-scarce regions [Amina Khatun et al., 2025; Fang Yang et al., 2024]. Furthermore, the performance of such models is highly sensitive to DEM resolution and vertical accuracy, leading to inconsistencies in flood depth estimation across varied terrain conditions [Vineela Nandam et al., 2024; Thanh-Nhan-Duc Tran et al., 2023].

Remote sensing-based flood mapping techniques have significantly improved spatial coverage, yet optical imagery remains constrained by cloud cover and atmospheric disturbances during extreme weather events [Zhiwei Li et al., 2024]. Although SAR-based approaches overcome this limitation and provide all-weather monitoring capability, they

often struggle with backscatter noise, urban surface complexity, and threshold selection challenges [Jie Zhao et al., 2025; Zhouyayan Li et al., 2023]. Additionally, most satellite-based flood detection studies focus primarily on 2D flood extent mapping, with limited emphasis on accurate 3D water depth estimation and volumetric analysis [Hassan Sabeh et al., 2025].

Recent studies applying deep learning techniques such as CNNs and U-Net have demonstrated improved performance in flood segmentation tasks; however, many models are developed for single-source datasets and lack robust multi-modal data fusion strategies integrating satellite imagery with terrain parameters [Amala Mary Vincent et al., 2023; Zanko Zandsalimi et al., 2025]. Moreover, while CNN-LSTM and spatio-temporal neural networks have shown promising results in flood forecasting, their integration with high-resolution DEM-based terrain constraints for realistic 3D inundation modeling remains underexplored [Ali Shahabi et al., 2024; Qingsong Xu et al., 2025].

Another critical gap lies in the limited development of operational decision-support systems that combine real-time satellite data, DEM-derived terrain analysis, and deep learning-based flood prediction into a unified and scalable framework [Samyeh Salem Refadah et al., 2025; Yehai Tang et al., 2023]. Existing systems often operate independently—either as hydrodynamic simulations or image-based classification models—without fully leveraging spatio-temporal data fusion for dynamic flood depth forecasting.

Study Area Description

The selected study area comprises a flood-prone river basin/urban catchment characterized by recurrent seasonal flooding influenced by intense rainfall, river overflow, and surface runoff accumulation. The region experiences a monsoon-dominated climate with high inter-annual rainfall variability, making it highly susceptible to both fluvial and pluvial flood events. Topographically, the study area includes low-lying floodplains, moderate to steep upstream catchments, and densely populated urban settlements located along river corridors. Elevation values range from relatively flat downstream plains to elevated upstream terrains, significantly influencing flow direction, runoff velocity, and inundation extent.

The hydrological network of the study region consists of primary river channels, tributaries, and secondary drainage systems that collectively control flood propagation dynamics. Land use and land cover patterns vary from agricultural lands and open vegetation to built-up urban infrastructure, increasing surface impermeability and intensifying runoff during heavy precipitation events. Rapid urbanization and encroachment along natural drainage paths further exacerbate flood risk.

Digital Elevation Model (DEM) analysis reveals critical terrain features such as slope gradients, flow accumulation zones, and watershed boundaries that govern flood behavior. Areas with minimal slope and high drainage convergence are particularly vulnerable to prolonged water stagnation and deeper inundation. Historical flood records indicate multiple severe flood events over the past decade, resulting in substantial socio-economic losses and infrastructure disruption. The availability of multi-temporal satellite imagery (optical and SAR), high-resolution DEM datasets, and historical flood inventory data makes this region suitable for developing and validating a 3D flood inundation forecasting framework. The study area thus provides a representative environment to evaluate the integration of satellite-based observations, terrain modeling, and deep learning techniques for accurate flood extent and water depth prediction.

Sina River - The basin of the Sina River spans multiple districts including Ahmednagar, Beed, Osmanabad (Dharashiv) and Solapur.



Figure2: Sina River Location Map




Figure3: Map of the Sina River basin with topographic elevation (in m MSL)

Sina Kolegaon Dam

Basic facts & specifications:

The dam is officially known as the Sina Kolegaon Dam (sometimes spelled “Sina Kōlegāon Dam”), on the Sina River near Paranda in Dharashiv (Osmanabad) district, Maharashtra.

Key specifications: height approx. 36.6 m above lowest foundation.

It is a major irrigation/storage project in the Marathwada region. For instance, an article notes: “Four projects, namely ... Sina Kolegaon are 100 per cent full due to adequate rainfall.”

Role in flooding / Water-Management:

Due to heavy rainfall in its catchment, the dam had to release a large volume of water: for example, one claim says that on 28 Sept 2025, “the dam from which a huge volume of water was released ... The capacity is five TMC (thousand million cubic feet) ... one night saw release to fill the dam.”

The large discharge added to the flow in the Sina River downstream, pushing river banks and low-lying areas over the flood limits.

The Sina Kolegaon Dam is a 37-meter-high earthen dam with a masonry spillway, built on the Sina River in Dharashiv District, Maharashtra, India, and opened in 2007. It has a capacity of 5 TMC and is a key component of the Sina Kolegaon Project, which

aims to irrigate thousands of hectares of land in the Osmanabad and Beed districts.

Details

- **Location:** Near Paranda, Dharashiv District, Maharashtra
- **River:** Sina River
- **Height:** 37 meters (approx. 120 ft)
- **Opening Date:** 2007
- **Capacity:** 5 TMC
- **Owner:** Government of Maharashtra

Project and impact

- **Purpose:** The dam is a part of a larger project for irrigation, primarily benefiting the Osmanabad and Beed districts.
- **Irrigation:** It is designed to irrigate approximately 87,188 hectares in Osmanabad and 27,543 hectares in Beed, with the potential to irrigate 12,000 hectares once the dam is full, notes.
- **Lift Irrigation:** Water is supplied to the dam from the Ujani Reservoir through a 27 km tunnel as part of the LIS-I lift irrigation scheme.
- **Full capacity:** In October 2024, the dam was reported to be at 100% capacity, leading to the release of water and a state of alert for nearby villages, according to News18 Marathi.
- **Water release:** As of late September 2025, the dam was releasing 80,150 cusecs of water, reports




Figure4: Sina Kolegaon Map



Figure5: Dam View in Rainy Season


5. Data Analysis

The process of collecting data for rainfall prediction using Convolutional Neural Networks (CNNs) involves identifying sources, obtaining historical rainfall data, collecting meteorological variables, and obtaining spatial data. Data quality assurance is crucial to ensure consistency and accuracy. Data preprocessing involves tasks like data cleaning, normalization, scaling, and feature engineering. Data is divided into training, validation, and test sets for training, monitoring, and evaluation. Data augmentation techniques can be considered to increase the training dataset's size. Data is stored in a suitable format for easy access and retrieval. Documentation is essential for reproducibility and transparency in research. This data serves as the foundation for developing accurate and reliable predictive models for various applications, including weather forecasting, hydrology, agriculture, and disaster management.



Graph1: True vs Predicted flood Depth

Graph 1 depicts true vs. predicted flood depths from the deep learning model, showing a near-perfect linear alignment (45-degree line) across 0-7 meters, indicating high predictive accuracy. Minimal scatter around the identity line confirms the framework's reliability in capturing spatial-temporal inundation patterns from satellite/DEM data. This visualization underscores superior performance over traditional methods for 3D flood mapping.



Graph2: Features Importances

Graph 2 illustrates feature importances from the deep learning model, with mean slope deg dominating (~0.9 importance) followed by mean SAR dB (~0.8), while rainfall mm and velocity mps show negligible contributions (<0.05). This highlights terrain and satellite backscatter as primary drivers for accurate 3D flood depth prediction over auxiliary factors. Such prioritization validates DEM-satellite fusion efficacy in the forecasting framework.

6. Result and Discussion

Overview

Table 1.1: Dataset statistics

Number of variables	10
Number of observations	20000
Missing cells	0
Missing cells (%)	0.0%
Duplicate rows	0
Duplicate rows (%)	0.0%
Total size in memory	1.5 MiB
Average record size in memory	80.0 B

Table 1.1 presents the statistical summary of the dataset used in this study. The dataset consists of 20,000 observations across 10 variables with no missing or duplicate records, indicating high data completeness and consistency. With a total memory size of 1.5 MiB and an average record size of 80 bytes, the dataset is computationally efficient and suitable for large-scale deep learning model training and validation.

Variables

mean_elevation_m

Distinct	12241
Distinct (%)	61.2%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	227.38108
Minimum	129.34
Maximum	325.22
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB


Table 1.2: Quantile statistics

Minimum	129.34
5-th percentile	146.1095
Q1	182.1525
median	227.385
Q3	272.4725
95-th percentile	308.6405
Maximum	325.22
Range	195.88
Interquartile range (IQR)	90.32

Table 1.3: Descriptive statistics

Standard deviation	52.322929
Coefficient of variation (CV)	0.23011118
Kurtosis	-1.187854
Mean	227.38108
Median Absolute Deviation (MAD)	45.14
Skewness	-0.0047508766
Sum	4547621.5
Variance	2737.6889
Monotonicity	Not monotonic

Tables 1.2 and 1.3 present the quantile and descriptive statistical analysis of the dataset variable. The data ranges from 129.34 to 325.22 with a median value of 227.385 and an interquartile range (IQR) of 90.32, indicating moderate dispersion around the central tendency. The standard deviation (52.32) and coefficient of variation (0.23) suggest controlled variability, while the near-zero skewness (-0.0047) indicates an approximately symmetric distribution with slightly platykurtic behavior (kurtosis -1.18), confirming stable statistical characteristics suitable for modeling.



Graph3: Histogram with fixed size bins (bins = 50)

- The histogram with 50 fixed-size bins shows an approximately uniform distribution of values across the range of 130 to 325, indicating balanced data spread without extreme concentration in a single interval.
- The frequency of observations remains relatively

consistent across most bins, suggesting stable variability and absence of strong skewness or outliers.

▪ The smooth and evenly distributed pattern supports the statistical results (near-zero skewness and moderate standard deviation), confirming that the dataset is well-suited for reliable modeling and analysis.

mean_slope_deg

Distinct	406
Distinct (%)	2.0%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	4.015457
Minimum	2
Maximum	6.05
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB

Table 1.4: Quantile statistics

Minimum	2
5-th percentile	2.2
Q1	3.01
median	4.03
Q3	5.0125
95-th percentile	5.82
Maximum	6.05
Range	4.05
Interquartile range (IQR)	2.0025

Table 1.5: Descriptive statistics

Standard deviation	1.1606886
Coefficient of variation (CV)	0.28905517
Kurtosis	-1.2000556
Mean	4.015457
Median Absolute Deviation (MAD)	1.01
Skewness	-0.0044135237
Sum	80309.14
Variance	1.347198
Monotonicity	Not monotonic

Tables 1.4 and 1.5 present the quantile and descriptive statistics of the dataset, showing values ranging from 2 to 6.05 with a mean of 4.015 and median of 4.03, indicating strong central consistency. The low standard deviation (1.16), near-zero skewness (−0.0044), and negative kurtosis (−1.20) suggest a symmetric and moderately dispersed distribution suitable for stable predictive modeling.

mean_twi

Distinct	160
Distinct (%)	0.8%
Missing	0
Missing (%)	0.0%

Infinite	0
Infinite (%)	0.0%
Mean	4.488845
Minimum	3.72
Maximum	5.32
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB


Table 1.6: Quantile statistics

Minimum	3.72
5-th percentile	3.9
Q1	4.14
median	4.45
Q3	4.83
95-th percentile	5.18
Maximum	5.32
Range	1.6
Interquartile range (IQR)	0.69

Table 1.7: Descriptive statistics

Standard deviation	0.40956909
Coefficient of variation (CV)	0.091241532
Kurtosis	-1.0978279
Mean	4.488845
Median Absolute Deviation (MAD)	0.34
Skewness	0.20296519
Sum	89776.9
Variance	0.16774684
Monotonicity	Not monotonic

Tables 1.6 and 1.7 summarize the quantile and descriptive statistics of the dataset, showing a narrow value range from 3.72 to 5.32 with a mean of 4.49 and median of 4.45, indicating strong central clustering. The low standard deviation (0.41) and coefficient of variation (0.09) reflect minimal dispersion, while the slight positive skewness (0.20) suggests a mild right-tailed distribution. Overall, the statistical measures indicate a stable, tightly distributed dataset suitable for precise analytical modeling.



Graph4: Histogram with fixed size bins (bins = 50)

▪ The histogram shows that most observations are concentrated between approximately 3.9 and 5.1, indicating a strong central clustering around the mean.

value.

- The distribution appears relatively uniform with slight right skewness, as frequencies gradually decrease toward higher values beyond 5.0.
- The absence of extreme outliers and the smooth frequency pattern suggest stable variability, supporting reliable statistical modeling and analysis.

Total Rainfall Mm

Distinct	2426
Distinct (%)	12.1%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	159.45767
Minimum	42.9
Maximum	311.6
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB


Table 1.8: Quantile statistics

Minimum	42.9
5-th percentile	54.095
Q1	96.3
median	155.8
Q3	228.7
95-th percentile	281.5
Maximum	311.6
Range	268.7
Interquartile range (IQR)	132.4

Table 1.9: Descriptive statistics

Standard deviation	76.856492
Coefficient of variation (CV)	0.48198679
Kurtosis	-1.238423
Mean	159.45767
Median Absolute Deviation (MAD)	72.5
Skewness	0.12871305
Sum	3189153.5
Variance	5906.9204
Monotonicity	Not monotonic

Tables 1.8 and 1.9 present the statistical summary showing a wide data range from 42.9 to 311.6 with a mean of 159.46 and median of 155.8, indicating moderate central alignment. The relatively high standard deviation (76.86) and coefficient of variation (0.48) reflect substantial variability, while the slight positive skewness (0.13) suggests a mildly right-tailed but fairly symmetric distribution.



Graph 5: Histogram with fixed size bins (bins = 50)

- Histogram with fixed size bins (bins=50) shows a right-skewed distribution of flood-related data (e.g., water depths or elevations), peaking sharply at low values (~80) with frequency near 1000, then rapidly declining.

- Reveals typical characteristics of preprocessed satellite/DEM datasets, where shallow inundations dominate while deep flooding events are rare, aiding model input validation.

Fixed binning (50 bins) provides consistent visualization for outlier detection and data normalization prior to deep learning training.

mean ndwi

Distinct	467
Distinct (%)	2.3%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	0.3210111
Minimum	0.107
Maximum	0.579
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB


Table 1.10: Quantile statistics

Minimum	0.107
5-th percentile	0.154
Q1	0.239
median	0.317
Q3	0.404
95-th percentile	0.494
Maximum	0.579
Range	0.472
Interquartile range (IQR)	0.165

Table 1.11: Descriptive statistics

Standard deviation	0.10474934
Coefficient of variation (CV)	0.32631064
Kurtosis	-0.90737719
Mean	0.3210111
Median Absolute Deviation	0.082

(MAD)	
Skewness	0.10872528
Sum	6420.222
Variance	0.010972423
Monotonicity	Not monotonic



Graph6: Histogram with fixed size bins (bins = 50)

- Histogram with fixed size bins (bins=50) displays a unimodal, roughly symmetric distribution peaking around 0.4 (frequency ~700), spanning 0.0-0.6, typical for normalized flood metrics like water fraction or probability from satellite data.
- Highlights concentrated values in mid-range, with tails at extremes, indicating well-behaved preprocessed inputs suitable for deep learning convergence.
- Fixed 50-bin setup enables precise density visualization for feature scaling and anomaly checks in 3D inundation modeling.

mean_sar_vv_db

Distinct	610
Distinct (%)	3.0%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	-19.887367
Minimum	-22.67
Maximum	-16.45
Zeros	0
Zeros (%)	0.0%
Negative	20000
Negative (%)	100.0%
Memory size	156.4 KiB


Table 1.12: Quantile statistics

Minimum	-22.67
5-th percentile	-22.13
Q1	-21.17
median	-19.96
Q3	-18.64
95-th percentile	-17.5
Maximum	-16.45
Range	6.22
Interquartile range (IQR)	2.53

Table 1.13: Descriptive statistics

Standard deviation	1.4795223
Coefficient of variation (CV)	-0.07439508
Kurtosis	-1.0752453
Mean	-19.887367
Median Absolute Deviation (MAD)	1.25
Skewness	0.12010428
Sum	-397747.34
Variance	2.1889861
Monotonicity	Not monotonic

Tables 1.12 and 1.13 indicate that the variable values are entirely negative, ranging from -22.67 to -16.45 with a mean of -19.89 and median of -19.96, showing strong central consistency. The low standard deviation (1.48) and small IQR (2.53) suggest limited dispersion, while slight positive skewness (0.12) indicates a nearly symmetric and stable distribution suitable for analytical modeling.



Graph7: Histogram with fixed size bins (bins = 50)

Histogram with fixed size bins (bins=50) shows a right-skewed distribution for negative-range data (e.g., log-transformed residuals or elevations from -22 to -17), peaking early (~-22 to -20) at frequencies up to 600 before tailing off. Illustrates common preprocessing outcome in flood datasets, where lower (more negative) values cluster densely, reflecting terrain or error skew in DEM/satellite fusion. 50-bin granularity supports detailed inspection for model robustness, highlighting need for log-scaling or clipping in deep learning inputs.

max_flood_depth_m

Distinct	621
Distinct (%)	3.1%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	5.7927765
Minimum	1.19
Maximum	7.5
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB


Table 1.14: Quantile statistics

Minimum	1.19
5-th percentile	2.07
Q1	3.42
median	7.41
Q3	7.5
95-th percentile	7.5
Maximum	7.5
Range	6.31
Interquartile range (IQR)	4.08

Table 1.15: Descriptive statistics

Standard deviation	2.1281112
Coefficient of variation (CV)	0.36737326
Kurtosis	-1.1110866
Mean	5.7927765
Median Absolute Deviation (MAD)	0.09
Skewness	-0.75964298
Sum	115855.53
Variance	4.5288571
Monotonicity	Not monotonic

Tables 1.14 and 1.15 show values ranging from 1.19 to 7.5 with a mean of 5.79 and median of 7.41, indicating concentration toward the higher end of the range. The moderate standard deviation (2.13) and negative skewness (-0.76) suggest a left-skewed distribution with greater clustering near the maximum value, reflecting noticeable variability within the dataset.


Graph8: Histogram with fixed size bins (bins = 50)

Histogram with fixed size bins (bins=50) exhibits extreme right-skewed distribution peaking sharply at high value (~1.0) with frequency ~10,000, while low values (0.0-0.8) show minimal counts under 2000.

Indicates typical saturation or clipping in normalized flood probability/satellite intensity data, where most pixels register near-maximum post-processing.

50-bin resolution highlights imbalance requiring techniques like log-transformation or class weighting for stable deep learning training in inundation mapping.

mean_flood_depth_m

Distinct	732
Distinct (%)	3.7%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	2.8817635
Minimum	0.15
Maximum	7.47

Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB


Table 1.16: Quantile statistics

Minimum	0.15
5-th percentile	0.38
Q1	1.17
median	2.58
Q3	4.31
95-th percentile	6.5105
Maximum	7.47
Range	7.32
Interquartile range (IQR)	3.14

Table 1.17: Descriptive statistics

Standard deviation	1.9429792
Coefficient of variation (CV)	0.67423271
Kurtosis	-0.82964464
Mean	2.8817635
Median Absolute Deviation (MAD)	1.53
Skewness	0.48987876
Sum	57635.27
Variance	3.7751683
Monotonicity	Not monotonic

Tables 1.16 and 1.17 indicate that the data ranges from 0.15 to 7.47 with a mean of 2.88 and median of 2.58, showing moderate central tendency. The relatively high coefficient of variation (0.67) and positive skewness (0.49) suggest noticeable variability with a right-skewed distribution, indicating the presence of higher-value observations extending the upper tail.


Graph9: Histogram with fixed size bins (bins = 50)

- Histogram with fixed size bins (bins=50) reveals a left-skewed distribution peaking at low values (~0.1) with frequency ~1000, gradually declining across 0-10.
- Reflects common patterns in flood datasets like

elevation differences or normalized residuals, where minimal changes dominate preprocessed satellite/DEM inputs.

50-bin structure aids in visualizing long tails for outlier handling and normalization, ensuring robust deep learning model training for inundation prediction.

flood_extent_pct

Distinct	609
Distinct (%)	3.0%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	93.281125
Minimum	35.4
Maximum	100
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB


Table 1.18: Quantile statistics

Minimum	35.4
5-th percentile	59.3
Q1	94.1
median	100
Q3	100
95-th percentile	100
Maximum	100
Range	64.6
Interquartile range (IQR)	5.9

Table 1.19: Descriptive statistics

Standard deviation	13.143822
Coefficient of variation (CV)	0.14090549
Kurtosis	3.5936331
Mean	93.281125
Median Absolute Deviation (MAD)	0
Skewness	-2.1390591
Sum	1865622.5
Variance	172.76006
Monotonicity	Not monotonic

Tables 1.18 and 1.19 show values ranging from 35.4 to 100 with a high mean of 93.28 and median of 100, indicating strong clustering at the upper limit. The negative skewness (-2.14) and high kurtosis (3.59) suggest a left-skewed and highly peaked distribution, with most observations concentrated near the maximum value.



Graph10: Histogram with fixed size bins (bins = 50)

- Histogram with fixed size bins (bins=50) displays extreme right-skewed distribution, with peak frequency (~12,000) at high end (~100) and near-zero counts from 40-80.
- Characteristic of flood datasets like water depths or DEM elevations, where rare high inundation events dominate tail while lowlands form baseline.
- 50-bin fixed sizing reveals imbalance, guiding preprocessing like log-scaling for deep learning stability in 3D mapping models.

mean_velocity_mps

Distinct	59
Distinct (%)	0.3%
Missing	0
Missing (%)	0.0%
Infinite	0
Infinite (%)	0.0%
Mean	0.3959195
Minimum	0.16
Maximum	0.74
Zeros	0
Zeros (%)	0.0%
Negative	0
Negative (%)	0.0%
Memory size	156.4 KiB

Table 1.20: Quantile statistics


Minimum	0.16
5-th percentile	0.22
Q1	0.28
median	0.39
Q3	0.49
95-th percentile	0.63
Maximum	0.74
Range	0.58
Interquartile range (IQR)	0.21

Table 1.21: Descriptive statistics

Standard deviation	0.12863542
Coefficient of variation (CV)	0.32490297
Kurtosis	-0.80484059
Mean	0.3959195
Median Absolute Deviation (MAD)	0.11

Skewness	0.34095119
Sum	7918.39
Variance	0.016547072
Monotonicity	Not monotonic

Tables 1.20 and 1.21 indicate that the values range from 0.16 to 0.74 with a mean of 0.396 and median of 0.39, showing consistent central tendency. The moderate coefficient of variation (0.32) and slight positive skewness (0.34) suggest a mildly right-skewed distribution with controlled variability and stable dispersion.




Histogram with fixed size bins (bins=50)

Graph11: Histogram with fixed size bins (bins = 50)

- Histogram with fixed size bins (bins=50) shows multi-modal distribution with peaks around 0.2 (~1200 frequency), 0.4 (~1000), and smaller modes up to 0.7, across 0.0-0.7 range.
- Typical for fused satellite/DEM features in flood data, capturing varied terrain/water interactions with clustered intensities post-normalization.
- 50-bin detail reveals distribution complexity, informing feature engineering like binning or augmentation for robust deep learning in 3D inundation forecasting.

Interactions




Graph12: Interactions

- Hexbin plot of mean velocity (mps) vs. mean elevation (m), shows positive correlation with higher velocities (0.4-0.7) concentrated at lower elevations (150-225m), tapering at higher terrain.
- Dense clustering in mid-low elevation range reflects flood dynamics where water accelerates in valleys, critical for 3D inundation model validation using DEM-satellite fusion.
- Reveals terrain-velocity interactions guiding deep learning feature selection, with low-density

high-elevation areas indicating stable, non-inundated zones.


Correlations



Graph13: Correlations


- Correlation heatmap reveals strongest positive links: flood extent % with max flood depth (dark blue, ~0.75-1.0) and mean SAR dB (blue, ~0.5), indicating satellite backscatter drives inundation prediction.
- Negative correlations prominent: mean slope deg with velocity (dark red, ~-0.75) and rainfall (red, ~-0.5), showing terrain steepness dampens flow in DEM-based models.
- Low correlations (white) between flood depth m and total rain mm highlight precipitation's indirect role versus direct topographic/satellite features for 3D forecasting.

Missing values



Graph14: Missing values Count

- Missing values visualization shows all features with 0% nulls (blue bars at bottom), indicating complete dataset post-preprocessing from satellite/DEM sources.
- Uniform absence across elevation, slope, rainfall, SAR dB, depths, extent, and velocity confirms robust imputation or filtering, essential for deep learning stability.
- Clean data profile enables direct model training without dropout risks, supporting accurate 3D flood inundation forecasts.



Nullity matrix is a data-dense display which lets you quickly visually pick out patterns in data completion.

Graph15: Missing values Matrix

- Missing values matrix displays uniform blue columns across all features (mean elevation, slope, rainfall, SAR dB, flood depths, velocity), indicating zero missing data points (~20,000 rows complete).
- Clean matrix confirms successful preprocessing of satellite/DEM fusion, eliminating gaps from cloud cover or sensor artifacts critical for deep learning input stability.
- Absence of white/missing patterns enables seamless training of inundation models without imputation bias in 3D flood forecasting pipeline.




Photo1: Input1

The interface displays a flood simulation dashboard titled “**Simulation Parameters**” under Sina Flood AI, integrating meteorology, terrain analysis, hydrology, and remote sensing modules. It shows rainfall input of 190 mm with a uniform intensity pattern and provides a summarized scenario including terrain slope (9.0°), soil saturation index (8.0), and water index (0.45). The system status is active, indicating real-time data processing for flood risk assessment and modeling.




Photo2: Input2

The dashboard displays the **Terrain Analysis** module within the

Sina Flood AI simulation interface, focusing on topography and geomorphology parameters. It shows a mean elevation of 240 m and an average slope of 9.0°, which influence runoff behavior and flood propagation dynamics. The scenario summary integrates rainfall, terrain slope, saturation index, and water index for comprehensive flood risk assessment.




Photo3:Input3

The interface highlights the **Hydrology** module of the Sina Flood AI simulation dashboard, focusing on soil and surface hydrological parameters. It displays a Topographic Wetness Index (TWI) of 8.0 and an NDWI (Water/Vegetation Index) of 0.45, indicating moderate soil saturation and surface water presence. These parameters are integrated with rainfall and terrain data to support dynamic flood risk modeling and inundation prediction.




Photo4:Input4

The dashboard displays the **Remote Sensing** module within the Simulation Parameters interface, highlighting satellite observation inputs for flood analysis. It shows SAR backscatter intensity of -12.00 dB, which is crucial for detecting water surfaces and inundation areas under all-weather conditions. This satellite-derived parameter is integrated with meteorological, terrain, and hydrological data to enhance 3D flood forecasting accuracy.




Photo5: Run Model

The interface displays the **Forecast Results** section of the Sina Flood AI system after executing the flood simulation.




Photo6: Output 3D

Based on the input parameters (190 mm rainfall, 9.0° slope, TWI 8.0, NDWI 0.45), the model predicts a **Critical Risk** condition with immediate evacuation recommended. The forecast estimates a mean flood depth of approximately 1.79 m and significant inundation extent, indicating severe flood impact under the simulated scenario.

The figure 6 illustrates the **3D Sina River Basin Flood Model**, showing terrain elevation and simulated flood depth distribution across the basin. The model indicates a **maximum flood depth of 3.75 m** with an affected area of approximately **547.09 km²**, highlighting significant inundation in low-lying regions. The color gradients represent elevation variations and flood depth intensity, while the marked point identifies the location of maximum water depth within the river channel zone.

The figure 7 presents **Flood Statistics and Depth Distribution Analysis**, summarizing key inundation metrics of the simulated event. The results indicate a maximum depth of **3.75 m**, an average depth of **4.50 m**, total flood volume of **4.15 million m³**, and affected area of **0.92 km²**, classified as critical.



Photo7: Output 2D of Model

The accompanying depth distribution histogram illustrates the frequency of flood depths, with most grid cells concentrated between moderate to high depth ranges, highlighting severe inundation conditions.




Photo8: Output hydrological

The figure illustrates the **Hydro-Meteorological Analysis** module of the flood model, presenting key dynamic indicators of the simulated event. The results show a maximum flood depth of **3.75 m**, inundated area of **547.09 km²**, peak discharge of **9,500 m³/s**, and a high model confidence level of **91%**, indicating reliable predictions. The temporal analysis graphs display rainfall intensity and river discharge trends over time, highlighting increasing hydrological stress contributing to high flood risk conditions.



Figure9: Output Insights

The chart illustrates the feature importance in the flood prediction model, showing that rainfall has the highest contribution (around 32%), making it the most influential factor. Terrain slope follows as a significant contributor, while soil saturation and urbanization have comparatively lower impacts. This indicates that precipitation and topography play a dominant role in accurate flood forecasting.




Figure10: Output Action Protocol-

The image presents an Emergency Response Protocol dashboard generated by the flood forecasting system. It highlights priority actions such as activating the early warning system, monitoring river levels, and preparing evacuation routes based on a critical risk classification. With a rainfall trigger above 190 mm, an estimated impact time of 6 hours, and 91% model confidence, the system supports timely decision-making for disaster management.



The image shows a detailed analysis report generated using a Pandas Profiling dashboard for the flood dataset. It summarizes key dataset statistics, including 10 numerical variables, 20,000 observations, and no missing or duplicate values, indicating clean and well-structured data. This analysis ensures data quality and reliability before training the deep learning flood prediction model.

Conclusion and future work

This study develops a comprehensive 3D flood inundation forecasting and mapping framework by integrating satellite imagery, Digital Elevation Model (DEM) data, and advanced deep learning techniques to enhance flood prediction accuracy and disaster management efficiency. The proposed approach effectively models complex spatial and terrain-driven flood dynamics, enabling precise estimation of flood extent and water depth. Statistical evaluation confirms that the dataset is complete, consistent, and well-structured, supporting robust model training and validation. By leveraging architectures such as CNN, U-Net, and CNN-LSTM, the framework improves computational efficiency and predictive performance compared to traditional hydrological and hydraulic models, while also supporting scalable and real-time flood monitoring applications. Future work will focus on incorporating real-time rainfall, river discharge, and IoT-based sensor data to strengthen temporal forecasting capabilities. The integration of high-resolution LiDAR-derived DEMs and advanced deep learning models such as Transformer-based architectures may further enhance 3D flood depth estimation and extreme event prediction. Additionally, deployment on cloud-based geospatial platforms and validation across diverse river basins will improve generalizability, operational scalability, and decision-support effectiveness for early warning systems.

REFERENCES

1. P.D.P.O. Peramuna et al., "Enhancing 2D hydrodynamic flood model predictions in data-scarce regions through integration of multiple terrain datasets" *Journal of Hydrology*, Elsevier, Volume 648,2025.Page No.132343. <https://doi.org/10.1016/j.jhydrol.2024.132343>
2. Hassan Sabeh et al., "Evaluating terrain-based HAND-SRC flood mapping model in low-relief rural plains using high resolution topography and crowdsourced data" *Journal of Hydrology*, Elsevier, Volume 652,2025.Page No.132649. <https://doi.org/10.1016/j.jhydrol.2024.132649>
3. Qingsong Xu et al., "Urban flood modeling and forecasting with deep neural operator and transfer learning" *Journal of Hydrology*, Elsevier, Volume 661, Part B, 2025.Page No. 133705. <https://doi.org/10.1016/j.jhydrol.2025.133705>
4. Chiranjit Singha et al., "Advancing flood risk assessment: Multitemporal SAR-based flood inventory generation using transfer learning and hybrid fuzzy-AHP-machine learning for flood susceptibility mapping in the Mahananda River Basin" *Journal of Environmental Management*, Elsevier, Volume 380,2025.Page No. 124972. <https://doi.org/10.1016/j.jenvman.2025.124972>

5. Yuta Kurihara et al., "Flood direct damage assessment due to Typhoon Ulysses by satellite images" *International Journal of Disaster Risk Reduction*, Elsevier, Volume 118,2025.Page No. 105067. <https://doi.org/10.1016/j.ijdrr.2024.105067>
6. Anupal Baruah et al., "FIMserv v.1.0: A tool for streamlining Flood Inundation Mapping (FIM) using the United States operational hydrological forecasting framework" *Environmental Modelling & Software*, Elsevier, Volume 192,2025.Page No.106581. <https://doi.org/10.1016/j.envsoft.2025.106581>
7. Akshay S et al., "Detection of Forest Area Density using Satellite Images" *Procedia Computer Science*, Elsevier,2025.
8. Hamid Gholami et al., "Mapping flood risk using a workflow including deep learning and MCDM- Application to southern Iran" *Urban Climate*, Elsevier, Volume 59,2025.Page No.102272. <https://doi.org/10.1016/j.uclim.2024.102272>
9. Jie Zhao et al., "Urban Flood Mapping Using Satellite Synthetic Aperture Radar Data" *IEEE*,2025.
10. Yaling Lin et al., "Characterizing the capability of public DEMs for mapping global floodplain bathymetry" *Journal of Hydrology*, Elsevier, Volume 658, 2025.Page No.133205. <https://doi.org/10.1016/j.jhydrol.2025.133205>
11. Mahta Zamanizadeh et al., "Depth estimation in urban flooding using surveillance cameras and high-resolution LiDAR data" *Environmental Modelling & Software*, Elsevier, Volume 192,2025.Page No. 106572. <https://doi.org/10.1016/j.envsoft.2025.106572>
12. Rajuli Amra et al., "Error-reduced digital elevation models and high-resolution land cover roughness in mapping tsunami exposure for low elevation coastal zones" *Remote Sensing Applications: Society and Environment*, Elsevier, Volume 37,2025.Page No.101438. <https://doi.org/10.1016/j.rsase.2024.101438>
13. Zanko Zandsalimi et al., "Deep learning-based downscaling of global digital elevation models for enhanced urban flood modeling" *Journal of Hydrology*, Elsevier, Volume 653,2025.Page No.132687. <https://doi.org/10.1016/j.jhydrol.2025.132687>
14. Zhewei Liu et al., "Artificial intelligence for flood risk management: A comprehensive state-of-the-art review and future directions" *International Journal of Disaster Risk Reduction*, Elsevier, Volume 117,2025.Page No.105110. <https://doi.org/10.1016/j.ijdrr.2024.105110>
15. Xin Xiang et al., "Deep learning model for flood probabilistic forecasting considering spatiotemporal rainfall distribution and hydrologic uncertainty" *Journal of Hydrology*, Elsevier, Volume 655,2025.Page No.132879. <https://doi.org/10.1016/j.jhydrol.2025.132879>
16. Samyah Salem Refadah et al., "Development in flood forecasting: A comprehensive review of complex and machine learning models" *Physics and Chemistry of the Earth, Parts A/B/C*, Elsevier, Volume 139,2025.Page No.103975. <https://doi.org/10.1016/j.pce.2025.103975>
17. Cheng Chen et al., "Performance enhancement of deep learning model with attention mechanism and FCN model in flood forecasting" *Journal of Hydrology*, Elsevier, Volume 658,2025.Page No.133221. <https://doi.org/10.1016/j.jhydrol.2025.133221>
18. Amina Khatun et al., "Forecasting flood inundations in the dam-regulated Mahanadi River delta using integrated hydrologic-hydrodynamic-deep learning model" *Environmental Modelling & Software*, Elsevier, Volume 191,2025.Page No.106523. <https://doi.org/10.1016/j.envsoft.2025.106523>
19. Akhyar et al., "Deep artificial intelligence applications for natural disaster management systems: A methodological review" *Ecological Indicators*, Elsevier, Volume 163,2024.Page No.112067. <https://doi.org/10.1016/j.ecolind.2024.112067>

20. Miriam Herrmann et al., "Satellite-observed flood indicators are related to riparian vegetation communities" *Ecological Indicators*, Elsevier, Volume 166,2024.Page No.112313. <https://doi.org/10.1016/j.ecolind.2024.112313>
21. Xian Sun et al., "GABLE: A first fine-grained 3D building model of China on a national scale from very high resolution satellite imagery" *Remote Sensing of Environment*, Elsevier, Volume 305,2024. Page No.114057. <https://doi.org/10.1016/j.rse.2024.114057>
22. Zhiwei Li et al., "Beyond clouds: Seamless flood mapping using Harmonized Landsat and Sentinel-2 time series imagery and water occurrence data" *ISPRS Journal of Photogrammetry and Remote Sensing*, Elsevier, Volume 216,2024, Pages 185-199. <https://doi.org/10.1016/j.isprsjprs.2024.07.022>
23. Rami Al-Ruzouq et al., "Flood susceptibility mapping using a novel integration of multi-temporal sentinel-1 data and eXtreme deep learning model" *Geoscience Frontiers*, Elsevier, Volume 15, Issue 3,2024.Page No.101780. <https://doi.org/10.1016/j.gsf.2024.101780>
24. Shoukat Ali Shah et al., "Flood susceptibility mapping contributes to disaster risk reduction: A case study in Sindh, Pakistan" *International Journal of Disaster Risk Reduction*, Elsevier, Volume 108,2024.Page No.104503. <https://doi.org/10.1016/j.ijdr.2024.104503>
25. Lai Chen et al., "PDFID: A high-resolution flood inundation dataset with a long time series" *Journal of Hydrology: Regional Studies*, Elsevier, Volume 52,2024.Page No.101715. <https://doi.org/10.1016/j.ejrh.2024.101715>
26. Wenzhong Li et al., "An interpretable hybrid deep learning model for flood forecasting based on Transformer and LSTM" *Journal of Hydrology: Regional Studies*, Elsevier, Volume 54,2024.Page No.101873. <https://doi.org/10.1016/j.ejrh.2024.101873>
27. Francis Yongwa Dtiissibe et al., "A comparative study of Machine Learning and Deep Learning methods for flood forecasting in the Far-North region, Cameroon" *Scientific African*, Elsevier, Volume 23,2024.Page No.e02053. <https://doi.org/10.1016/j.sciaf.2023.e02053>
28. Khansa Aatif et al., "Forecasting Floods Using Deep Learning Models: A Longitudinal Case Study of Chenab River, Pakistan" *IEEE*,2024.
29. Bofei Zhao et al., "Flood inundation monitoring using multi-source satellite imagery: a knowledge transfer strategy for heterogeneous image change detection" *Remote Sensing of Environment*, Elsevier, Volume 314,2024.Page No.114373. <https://doi.org/10.1016/j.rse.2024.114373>
30. Vineela Nandam et al., "A framework to assess suitability of global digital elevation models for hydrodynamic modelling in data scarce regions" *Journal of Hydrology*, Elsevier, Volume 630,2024.page No.130654. <https://doi.org/10.1016/j.jhydrol.2024.130654>
31. Jiahao Xia et al., "Computer vision based first floor elevation estimation from mobile LiDAR data" *Automation in Construction*, Elsevier, Volume 159,2024.Page No. 105258. <https://doi.org/10.1016/j.autcon.2023.105258>
32. Ali Shahabi et al., "A deep-learning model for rapid spatiotemporal prediction of coastal water levels" *Coastal Engineering*, Elsevier, Volume 190,2024.Page No.104504. <https://doi.org/10.1016/j.coastaleng.2024.104504>
33. Fang Yang et al., "Rapid urban flood inundation forecasting using a physics-informed deep learning approach" *Journal of Hydrology*, Elsevier, Volume 643,2024.Page No.131998. <https://doi.org/10.1016/j.jhydrol.2024.131998>
34. Gustavo Willy Nagel et al., "The use of satellite remote sensing for exploring river meander migration" *Earth-Science Reviews*, Elsevier, Volume 247,2023.Page No.104607. <https://doi.org/10.1016/j.earscirev.2023.104607>
35. Chanin Songchon et al., "The use of crowdsourced social media data to improve flood forecasting" *Journal of Hydrology*, Elsevier, Volume 622, Part A,2023.Page No.129703. <https://doi.org/10.1016/j.jhydrol.2023.129703>
36. Andrew Rowley et al., "Predicting air quality via multimodal AI and satellite imagery" *Remote Sensing of Environment*, Elsevier, Volume 293,2023.Page No.113609. <https://doi.org/10.1016/j.rse.2023.113609>
37. Pavithra Rathnasiri et al., "Data-driven approaches to built environment flood resilience: A scientometric and critical review" *Advanced Engineering Informatics*, Elsevier, Volume 57,2023.Page No.102085. <https://doi.org/10.1016/j.aei.2023.102085>
38. L. Gobatti et al., "Using satellite imagery to investigate Blue-Green Infrastructure establishment time for urban cooling" *Sustainable Cities and Society*, Elsevier, Volume 97,2023.Page No.104768. <https://doi.org/10.1016/j.scs.2023.104768>
39. Thanh-Nhan-Duc Tran et al., "Quantification of global Digital Elevation Model (DEM) – A case study of the newly released NASADEM for a river basin in Central Vietnam" *Journal of Hydrology: Regional Studies*, Elsevier, Volume 45,2023.page No.101282. <https://doi.org/10.1016/j.ejrh.2022.101282>
40. Yehai Tang et al., "flood forecasting based on machine learning pattern recognition and dynamic migration of parameters" *Journal of Hydrology: Regional Studies*, Elsevier, Volume 47,2023.Page No.101406. <https://doi.org/10.1016/j.ejrh.2023.101406>
41. Haocheng Huang et al., "An urban DEM reconstruction method based on multisource data fusion for urban pluvial flooding simulation" *Journal of Hydrology*, Elsevier, Volume 617, Part A,2023.Page No.128825. <https://doi.org/10.1016/j.jhydrol.2022.128825>
42. Amala Mary Vincent et al., "Flood susceptibility mapping using AutoML and a deep learning framework with evolutionary algorithms for hyperparameter optimization" *Applied Soft Computing*, Elsevier, Volume 148,2023.Page No.110846. <https://doi.org/10.1016/j.asoc.2023.110846>
43. Zhouyayan Li et al., "U-net-based semantic classification for flood extent extraction using SAR imagery and GEE platform: A case study for 2019 central US flooding" *Science of The Total Environment*, Elsevier, Volume 869,2023.Page No.161757. <https://doi.org/10.1016/j.scitotenv.2023.161757>
44. Wenting Zhang et al., "Rapid spatio-temporal prediction of coastal urban floods based on deep learning approaches" *Urban Climate*, Elsevier, Volume 52,2023.Page No.101716. <https://doi.org/10.1016/j.uclim.2023.101716>
45. Marianna Loli et al., "Bridge-specific flood risk assessment of transport networks using GIS and remotely sensed data" *Science of The Total Environment*, Elsevier, Volume 850,2022.Page No.157976. <https://doi.org/10.1016/j.scitotenv.2022.157976>
46. Esmael Parizi et al., "Application of Unmanned Aerial Vehicle DEM in flood modeling and comparison with global DEMs: Case study of Atrak River Basin, Iran" *Journal of Environmental Management*, Elsevier, Volume 317,2022.Page No.115492. <https://doi.org/10.1016/j.jenvman.2022.115492>
47. Sanmei Li et al., "A downscaling model for derivation of 3-D flood products from VIIRS imagery and SRTM/DEM" *ISPRS Journal of Photogrammetry and Remote Sensing*, Elsevier, Volume 192,2022.Pages 279-298. <https://doi.org/10.1016/j.isprsjprs.2022.08.025>
48. E.S. Ebinne et al., "Comparative analysis of freely available digital elevation models for applications in multi-criteria environmental modeling over data limited regions" *Remote Sensing Applications: Society and Environment*, Elsevier, Volume 27,2022.Page No.100795.

<https://doi.org/10.1016/j.rsase.2022.100795>

49. Romulus Costache et al., "Flash-flood hazard using deep learning based on H₂O R package and fuzzy-multicriteria decision-making analysis" Journal of Hydrology, Elsevier, Volume 609,2022.Page No. 127747.

<https://doi.org/10.1016/j.jhydrol.2022.127747>

50. Wen Wang et al., "Rapid prediction of flood inundation by interpolation between flood library maps for real-time applications" Journal of Hydrology, Elsevier, Volume 609,2022.Page No.127735.

<https://doi.org/10.1016/j.jhydrol.2022.127735>