

# A Conceptual study of Wind Load with Different Types of Lateral Load Resisting Methods in 15-Storey Structure

*Ms. Diksha Kamble*

PG Student, Civil Engineering Department

*Dr. Mahesh V. Raut*

Assistant Professor, Civil Engineering Department

G.H. Raisoni Institute of Engineering and Technology, Nagpur, India

**Abstract**— Traditionally, outrigger and belt truss additions are used to strengthen the rigidity of tall buildings with central cores in order to control displacements. At the top of the structure, a single level outrigger can efficiently reinforce a building. The lateral stiffness of each outrigger level rises, although not as much as that of the top level. The primary lateral force-resisting elements of high-rise building structures are shear walls. Higher-performance shear walls are necessary because to the ever-increasing building code requirements and the rising height of high-rise and super high-rise structures. The conventional reinforced concrete shear wall is not very ductile, has a limited capacity to dissipate energy, and is not very deformable. Specifically, the base of a typical shear wall is particularly vulnerable to earthquake damage and is highly challenging to restore. In high-rise and super high-rise buildings, steel plate shear walls (SPSWs) and steel plate reinforced concrete composite shear walls (SPCSWs) are frequently used in place of regular reinforced concrete shear walls or shaped steel reinforced concrete composite shear walls to improve the seismic performance of building structures. Numerous structural methods seem to be able to withstand lateral stresses brought on by earthquakes, blasts, and wind. The more crucial it is to choose the optimal structural arrangement to counteract opposing horizontal loads.

**Keywords**— High-rise structure, Outrigger, Shearwall, Damper etc.

## I. INTRODUCTION

High-rise buildings are prevalent in many countries, particularly in emerging economies, thanks to the rapid technological evolution in several areas related to building materials, construction technologies, and the development of sophisticated structural analysis and design using computer software. Aside from the growing need for tall buildings due to the scarcity of land in urban areas, high-rise buildings also play a crucial role as essential structures in contemporary cities and metropolises, where they are viewed as a sustainable solution from the social, economic, and ecological perspectives. A building's specific structures are all subject to various loads, including the structure's own weight. Gravity is the reason for this. A

similar load, known as overload, must be supported by the structure due to the weight of the people, furniture, furnishings, etc. In order for the structure to withstand loads, such as wind and earthquakes, it must do so. Buildings and other structures, as well as additional parts and finishing touches, must always be built to withstand wind loads. The term "wind load" refers to the force that the wind has on a structure. The entire surface of the structure is subject to this load. As the structure's height rises, the size of this load also grows. Compared to low-rise buildings, tall buildings are more vulnerable to wind effects.

## II. MOTIVATION

- In this project we are study Wind Load with Different Types of Lateral Load Resisting Methods on bare frame with damper, shear wall and outrigger. So that we title this project that "A Conceptual Study of Wind Load with Different Types of Lateral Load Resisting Methods in Unsymmetrical 20-Storey Structure".
- An lateral load shows massive damage from an unexpected seismic movement affecting incomplete structures of varying magnitudes, causes total or partial damage. This structural damage directly affects living and non-living goods. To clear the catastrophic distraction and eradicate the minimization of the cost of the recession, it is preferable to prevent a preventive seismic assessment and a stiff reinforcement of the building' replacement
- 

## III. PROBLEM STATEMENT

This work use 15-storey model consider lateral loading. The construction also has a shear wall, outrigger and FVD damper. The structure's storeys have 3m height each storeys. The entire building is vulnerable to wind loads and located in the first terrain category. The bending moment, shear force, joint displacement, and storey thrift of several structure shapes were compared and examined in ETABS software to incorporate variety into the study. The results were analyzed in ETABS software.

#### IV. OBJECTIVES

- To study the effect of outriggers, shear wall and dampers under wind load on lateral displacement.
- To compare the lateral deflection and story drift in all three cases.
- To study the Static Response of building i.e. finding out the most vulnerable modal & suggest optimum lateral load resisting method of outrigger, damper and shear wall in high rise building.
- To study importance of dynamic wind loading and methods for the same.

#### V. LITERATURE SURVEY

**Gao Hui, et al. (2021) [1]** this work presents an ideal design method based on output feedback-controlled theory to design the damped inertial viscosity (vid) parameters for vibration damping of multimode cables. The cable speed at the damper position was the only feedback used while designing vid, which was regarded as a particular output feedback-controlled system. By reducing the advantage of the cable-based vid system for a given inertia, the optimal attenuation coefficient for vid was obtained. When the performance value reaches its minimum peak value, the vid inertia could be changed to produce the ideal design parameters. By comparing the proposed design approach with other design methods and using a cable prototype design as an example, the authors highlight how effectively the method worked. The outcomes demonstrate that the modular cable's attenuation ratio obtained using this technique satisfies the Owen criterion. Vids could improve controlled performance compared to viscous dampers by attenuating multimode vibrations in cables. The advantages of the first cable technique and the better design method, on the other hand, tended to diminish as the order of cable design methods increased.

**Al Agha Wesam and Nambiappan Umamaheswari (2021) [2]** The corresponding function static approach and the response spectrum method for seismic loading in monolithic reinforced concrete buildings with shear wall systems and double-frame shear walls, as well as the other measured parameters, were presented in this article through an analytical study. Base shear, bending moments, and displacements were caused by reinforced concrete wall and frame structures. Because the period refers to the same earthquake and did not change in the case studied, the research findings demonstrate that the value of the time was constant when comparing the two methodologies. Since the mass of the model was constant for both techniques, the rise in the fundamental shear value was related to the greater acceleration spectrum utilized; more steel bars are required, particularly ribs that call for a specific degree of ductility, in order to raise the value of the bending moment in the case of spectral response. The displacement values in the response spectrum case represent the actual performance of the irregular building, especially in the y direction, which was otherwise higher than the comparable static displacement values. Because seismic loads are unpredictable and have a

high degree of uncertainty, they must be managed differently than other types of loads. As a result, the basis of today's design standards is performance-based design.

**Varma V. Naresh Kumar, et al. (2021) [3]** buildings with shear walls had a greater impact on a floor's stiffness than structures without shear walls. Floor displacements were less in shear-wall-taken structures than in structures without shear walls. This study shows that the low tension also rose when the pore size increased by 40%. The performance of the shear structure was superior to the performance of the frame structure after the stress was greatly raised, according to analysis and design. Shear walls near the corners of the frame perform better than shear walls in the middle of the span. Shear walls were advised for use in earthquake-prone locations because of their high seismic load capacity. As could be seen, the overall displacement increases more when the aperture is located close to the wall's edge than when it is in the middle of the wall. Greater than the superstructure was the substructure. The deviation value fell considerably at first as the layer height rose, then gradually.

**Azandariani, Mojtaba Gorji and Mohammad Ali Kafi (2021) [4]** in this study, a novel hybrid steel plate shear wall system (HLCS) is recommended, and mathematical and analytical methods are used to examine its final strength. This system includes two closest columns and a sheet steel shear wall (SPSW) joined through connecting beams. The aim of this work is to develop a novel shear resistance system for various kinds of earthquakes as well as analytical connections in order to determine the actual capacity of the current HLCS system. In this article, we investigate the coupling ratio and final capacity characteristics of a multistage HLCS system using analytical and numerical methods. Analytical relationships can be used for calculating the HLCS system's final output and coupling ratio using the limit analysis method. Mathematical methods were used to carry out extensive parametric analyses in order to confirm the validity of the analytical interactions. 30 prototype multilayer HLC systems with various coupling ratios and structural height parameters were built, modeled, and assessed as part of a parametric study. We carried out a verification based on findings from experiments to evaluate the accuracy of the mathematical model. The numerical findings were in good agreement with the analytical forecasts of the coupling ratio and final capacitance characteristics. According to parametric research, the bond ratio parameter, particularly for higher-order structures, significantly affects the structure's weight. An ideal trim ratio of roughly 30–50% was recommended, taking into account performance metrics, flowed methods, and weight reduction.

**Amad Shaik Akhil, and K. V. Pratap (2021) [5]** The purpose of this study was to look at the position of shear walls in different g+20 residential high-rise structures as well as the features of seismically unstable structures using response spectrum analysis approaches. Analysis of torsion deviations, base shear, maximum acceptable displacement,

and floor displacement in g+20 tall structures. The following was 1893 (part-1). In 2016, the entire structure was examined and modeled, which included Fem Software Etabs 2015. In this research, typed iii dynamic analysis was conducted. Structures with symmetrically positioned shear walls (such as case c) and structures with plane defects in every applicable location (for example, foundations in soft soil). It had been determined that the results were greater than those of structures (like example c) without shear walls. Parameters for earthquakes. Case b was similar to Case a, which had a shear wall at one end.

**Liu Yanhui, et al. (2020) [6]** this paper proposes an optimized design method for TMD design. In the frequency domain, the genetic algorithm is used in random excitation, the damping control effect is the optimization goal, and the constraint is the damping success. The 168-meter-high rise with dampers functioned as a technical example for carrying out numerical studies, and the design parameters of the dampers were determined using optimization methods. Furthermore, the eddy current damper is designed using the optimal design method and introduced into the 7-story reduced structure model. The performance of the damper designed using the optimal design method was evaluated by shake table testing and compared with the damper designed using the Hartog's method. The damper established in this way has a limited damping stroke, according to calculations, and its control efficiency is comparable to the Den-Hartog method. The recommended approach properly limits the damper stroke while obtaining good control performance. With the recommended structure method, the damper's maximum displacement is 0.78 m, which is significantly lower than the 0.95 m measured with the Hartog formula. Other experiments generated similar findings. As a result, the shock absorber's durability can be increased while its chance of failure is reduced due to the proposed optimal design approach.

**Liu Yang, et al. (2020) [7]** This study provides a spectrum-based pressure transmission analysis (SPA) for RC shear wall systems for rapidly determining seismic needs by altering the usual roof displacement prediction equation. The success of the spa method for quickly calculating the seismic demands for such structures was examined using two examples of load-bearing RC wall systems. The impact of the input target spectrum of scaled ground motion (IGM) on the accuracy of the spa method was studied by selecting and scaling the IGM. The ideal spectra were the ASCE design spectrum and the parametric average spectrum. The nonlinear response history analysis (NLRHA), two other high-pressure region multimodal analysis approaches, and seismic requirements obtained using the spa approach were all compared. The SPA technique offers excellent and consistent accuracy in estimating the seismic requirements of load-bearing RC wall structures, according to a comparison of the seismic needs. As a result, by using many target spectra that convey varying levels of seismic intensity, the SPA analysis can be considered a method of

rapidly predicting seismic demands for load-bearing RC wall systems in various locations.

**Alhaddad Wael, et al. (2020) [8]** the purpose of this research was to provide a simplified modeling and optimization method (SMOM) for obtaining the optimum initial design for high-rise buildings with cantilever systems and staircases. The simplified method was based on flexibility in structural modeling, which defines new finite elements by grouping and processing a collection of finite elements. A genetic algorithm was used to optimize the initial design, which regulates the updating of the design variables, represented by the volume of the structural elements, to reduce the cost of the construction while taking into account design restrictions (e.g., superstructure). Capabilities for streaming and creation. Furthermore, in terms of linear and nonlinear responses to lateral loads, the SMOM results were compared to the detailed finite element model results. To ensure the optimization algorithm's performance, five study situations were also evaluated, with the optimum design variables in each case being modified. MATLAB software was used to generate and carry out this approach. Although the simplified technique has excellent accuracy in predicting lateral displacement, essential period, and central stress, it was discovered that stress prediction for huge columns, braced frames, and restrained frames is insufficient. Furthermore, five case studies show that the suggested evolutionary algorithm can lower total cost by up to 34.6% while cutting processing time. This implies that the critical parameters governing the operation of a stabilizer-transmitter system are well understood.

**Petrini Francesco and Agathoklis Giaralis (2020) [9]** The study offers a new optimal damper design to address occupant comfort issues in wind-driven high-rise buildings and elongated buildings vulnerable to vortex shedding (vs. wind-driven variable dampers). Maximum partial kinetic energy at its highest level. It turns wind energy into electricity, which could then be used in massive structures. The focus was on examining the advantages of dampers with varying damper properties (i.e., mass, secondary weight, and momentum) designed with various topologies defined by the circuit covered by the damper. An additional component connects to the frame of the building. By calculating the ground floor optimization problem of a 305.9-meter-tall example building with an objectively calibrated height and width and a gap greater than 6, optimally designed dampers for different inertial characteristics and three different topologies may be developed. Measures that were related Analysis of wind energy output's impact on wind energy production. For complicated and moderate impacts, a model of blocking performance based on damper inertia was supplied, as were all levels of blocking structure performance in terms of occupant comfort (i.e., maximum acceleration to the higher floor). This was due to the measurement that it provides sufficient friction. Furthermore, if the secondary mass was coupled to the main structure by rigidity, increasing the friction or covering more floors would increase the damper's



resistance to the main structure's characteristics and the reference wind speed. The quantity of energy that could be obtained from massive structures exposed to wind would also rise due to the insertion of electromagnetic motors into shock absorbers that had different damping qualities, which would further improve energy generation. Lowering morphology and friction separated over several layers were used for this.

**Pietrosanti Daniele (2020) [10]** This work employed a new shaking platform test program to determine the nonlinear structural response of a harmonically damped vibration damper (TMDI) in the structure and the separation of the nonlinear inertial device from an ideal linear inertial element stationary constant. The force of the movement is roughly proportional. Let's take a look at a real-world one-degree of freedom (SDOF) structure that has a TMDI. To support the increased mass of the TMDDI, the author designed a unique rack-and-pinion flywheel inactivation device with nonlinear behavior due to the effects of friction and reaction. For SDOF and TMDI constructions, high-damping rubber bearings (HDRBs) with nonlinear elastic damping behavior offer damping and elastic qualities. Continuous stimulation with three different amplitudes was utilized for analyzing nine specimens with different secondary masses and elastic categories, and the complete analysis findings in the time and frequency domains are given. Furthermore, from the experimental results, two different nonlinear parametric numerical models that precisely describe the HDRB response are produced, one of which uses a nonlinear mechanical model to represent an elastic device and the other an ideal linear elastic element. When compared to the data acquired, the nonlinear features of the inertial device had no effect on the displacement, acceleration, or shear response of the original single-degree-of-freedom building work.

**Aditya Verma, Ravindra Kumar Goliya (2016) [11]** The goal of this research is to compare the results of various wind loading codes and standards to the Indian wind loading code and standard. The distinctions between these parameters are explained in this study. For the dynamic study of high-rise buildings, the first mode of natural frequencies is also provided. Procedures and instructions for assessing wind load and wind impact on high-rise structures are included in all international wind loading guidelines and standards. The response of structures to wind loads is compared in this study utilising four distinct wind loading codes from four different countries. The codes used in this study are from Japan (AIJ-RLB-2004), India (IS 875-3), Hong Kong (CP-2004), and New Zealand (AS/NZS1170.2:2002). On a 200m high rise rectangular structure, static wind properties, or static analysis, were investigated.

**Mohammed Asim Ahmed, et al. (2015) [12]** The current study is an excellent source of information on deflection variation as model height increases and % change in deflection of the same model in different terrain categories. As the model's height grows, so does the amount of deflection on the top floor. Model-3 deflection is greater than

model-2 and model-1 due to wind load. On the top storey, TG-1 deflects 6 per cent, 19 per cent, and 38.3 per cent more than TG-2, TG-3, and TG-4 in Model-1. On the top storey, TG-1 deflects 5 per cent, 15%, and 24.5 per cent more than TG-2, TG-3, and TG-4 in Model 2. On the top storey, TG-1 deflects 4 per cent, 13 per cent, and 18.9 per cent more than TG-2, TG-3, and TG-4 in Model-3. However, the percentage deviation between TG-1 and TG-4 is greatest at the third level in all three models.

**J. A. Amin, A. K. Ahuja (2014) [13]** The findings of wind tunnel testing on rectangular building models with the same plan area and height but varying side ratios of 1, 1.56, 2.25, 3.06, and 4 are presented in this work. The models were created on a 1:300 scale out of a perspex sheet. Pressure recordings taken in a closed-circuit wind tunnel under boundary layer flow for wind directions of 0° to 90° at a 15° interval were used to calculate the wind pressure coefficients for all models. The mean responses of rectangular tall structures with various side ratios were also calculated using wind loads acquired experimentally. For wind directions of 0° to 90° at a 15° interval, the effectiveness of the building side ratio in modifying surface pressure distribution and mean responses of prototype structures are evaluated. The wind pressures on leeward and sidewalls are significantly affected by the side ratio of structures, however, the wind pressure on the windward wall is essentially unaffected by the side ratio. Furthermore, the buildings' wind incidence angles and side ratios have a substantial impact on mean displacements and torque.

## Research Gap

- After study more than 15 papers we can noticed that most of research use seismic load to study with shear wall and bracings.
- Some of researcher use belt wall and damper for comparative analysis.
- Most of the work performs on symmetrical shape of models.
- Different storey of building need to be taken for regular and irregular structures as per IS: 1893-2016
- Not so much research work has been done so far on the buildings having the combine effect of shear wall, outrigger and damper.
- Various researchers have carried out work on the only lateral load resisting for particular seismic zone, there will be large scope for future study in lateral load resisting system for different shapes of high rise buildings by considering all type of seismic zone with different soil interaction.

## VI. FINDINGS

- Optimizing the performance rating of the cable-VID system yields the optimal damping coefficients of the

VID for a given inertance. Whenever the lowest peak of the performance rating occurs, varying the inertance of the VID generates optimal design parameters. [1]

- It is essential to calculate seismic parameters such as base shear, fundamental expected duration, displacement, and bending moment values utilizing the Corresponding Static and Response Spectrum technique. [2]
- Because shear walls frequently have openings, it is vital to investigate the effect of those on storey drift, stiffness, shear and moments, and tension within the shear walls. [3]
- When a coupling ratio parameter grows, the demand for ductile in the link beams rises. A high coupling ratio indicates fewer requirements for resistive forces in the steel plate shear wall, which reduces the steel plate shear wall's design dimension. [4]
- The torsional force irregularities are found as a result of load case EQ + X in Global X-direction for Case C, while for the remaining two cases, A and B, the building stays safe with torsional irregularity, demonstrating that the building for the current study needs additional stiffness to reduce displacements in all seismic zones of India. [5]
- The recommended optimization technique provides the same regulatory effect as Den Hartog's solution when a stroke is limited to less than the stroke of the TMD developed by Den Hartog's solution. [6]
- The SPA examination can be considered a solution for fast seismic demand estimation of RC shear wall buildings for various locations, with different target spectra serving as seismic intensity claims. [8]
- To describe the structure, the simplification method relies on supplements and dominant-degrees-of-freedom techniques, where a new form of a finite element is established by gathering and analysing a set of finite elements. [9]
- Increased accessible power for harvesting in wind-excited high-rise structures can be obtained through the use of electromagnetic motors in TMDIs with varying damping characteristics, whereas TMDI structures with inerters spanning more floors achieve both decreased floor acceleration and increased obtainable energy for harvesting. [10]

## VII. CONCLUSION

- Maximum value of joint displacement in bare frame occurs due to load combination of 1.2(DL+LL+WL) is 101.16mm. This value of displacement reduced with application of outrigger is 75.52mm. With the help of damper reduced value of joint displacement was 53.61mm. And when consider shear wall in bare frame value of occurred joint displacement was 48.07mm. Maximum reduction in displaced was in case-4 and minimum change was in case-2.[1]
- Maximum value of storey drift in bare frame occurs due to load combination of 1.2(DL+LL+WL) is 0.003399.

This value of drift reduced with application of outrigger is 0.00211. With the help of damper reduced value of drift was 0.001463. And when consider shear wall in bare frame value of occurred drift was 0.00121. Maximum reduction in drift was in case-4 and minimum change was in case-3.[2]

- Maximum value of bending moment in bare frame occurs due to load combination of 1.2(DL+LL+WL) is 464.54kN-m. This value of bending moment reduced with application of outrigger is 323.36kN-m. With the help of damper reduced value of bending moment was 255.08kN-m. And when consider shear wall in bare frame value of occurred bending moment was 93.67kN-m. Maximum reduction in bending moment was in case-4 and minimum change was in case-2.[3]
- Maximum value of shear force in bare frame occurs due to load combination of 1.2(DL+LL+WL) is 176.63kN. This value of shear force reduced with application of outrigger is 130.62kN. With the help of damper reduced value of shear force was 53.73kN. And when consider shear wall in shear force value of occurred shear force was 41.19kN. Maximum reduction in shear force was in case-4 and minimum change was in case-2.[4]
- Maximum value of stiffness in bare frame occurs due to load combination of 1.2(DL+LL+WL) is 2192181kN/m. This value of stiffness increased with application of outrigger is 3250868kN/m. With the help of damper increased value of stiffness was 6426931kN/m. And when consider shear wall in stiffness value of occurred stiffness was 11841651kN/m. Maximum increment in stiffness was in case-4 and minimum change was in case-2.[5]
- Maximum value of base reaction in bare frame occurs due to load combination of 1.5(DL+WL-X) is 418814.31kN. This value of base reaction increased with application of outrigger is 419667.44kN. With the help of damper increased value of base reaction was 431370.49kN. And when consider shear wall in base reaction value of occurred base reaction was 433210.07kN. Maximum increment in base reaction was in case-4 and minimum change was in case-2.[6]
- Maximum value of base reaction in bare frame occurs due to load combination of 1.2(DL+LL+WL) is 389051.45kN. This value of base reaction increased with application of outrigger is 389733.951kN. With the help of damper increased value of base reaction was 396792.75kN. And when consider shear wall in base reaction value of occurred base reaction was 400568.05kN. Maximum increment in base reaction was in case-4 and minimum change was in case-2.[8]

## REFERENCES

- [1] GAO, Hui, et al. 2021. "Optimum design of viscous inerter damper targeting multi-mode vibration mitigation of stay cables." *Engineering Structures* 226 111375.
- [2] Al Agha, Wesam, and Nambiappan Umamaheswari, 2021. "Analytical study of irregular reinforced concrete building with shear wall and dual Framed-Shear wall system by using Equivalent Static and Response Spectrum Method." *Materials Today: Proceedings* 43: 2232-2241.
- [3] Varma, V. Naresh Kumar, and Uppuluri Praveen Kumar, 2021. "Seismic response on multi-storied building having shear walls with and without openings." *Materials Today: Proceedings* 37: 801-805.
- [4] Azandariani, Mojtaba Gorji, Mohammad Ali Kafi, and Majid Gholhaki, 2021. "Innovative hybrid linked-column steel plate shear wall (HLCS) system: Numerical and analytical approaches." *Journal of Building Engineering* 43: 102844.
- [5] amad, Shaik Akhil, and K. V. Pratap, 2021. "Dynamic analysis of G+ 20 multi storied building by using shear walls in various locations for different seismic zones by using Etabs." *Materials Today: Proceedings* 43 (): 1043-1048
- [6] Liu, Yanhui, et al, 2020. "Experimental and numerical studies on the optimal design of tuned mass dampers for vibration control of high-rise structures." *Engineering Structures* 211- 110486.
- [7] Liu, Yang, et al, 2020. "Spectrum-based pushover analysis for the quick seismic demand estimation of reinforced concrete shear walls." *Structures*. Vol. 27. Elsevier
- [8] Alhaddad, Wael, et al, 2020. "Optimum design method for simplified model of outrigger and ladder systems in tall buildings using genetic algorithm." *Structures*. Vol. 28. Elsevier,
- [9] Petrini, Francesco, Agathoklis Giaralis, and Zixiao Wang, 2020. "Optimal tuned mass-damper-inerter (TMDI) design in wind-excited tall buildings for occupants' comfort serviceability performance and energy harvesting." *Engineering Structures* 204: 109904
- [10] Pietrosanti, Daniele, Maurizio De Angelis, and Agathoklis Giaralis, 2020. "Experimental study and numerical modeling of nonlinear dynamic response of SDOF system equipped with tuned mass damper inerter (TMDI) tested on shaking table under harmonic excitation." *International Journal of Mechanical Sciences* 184- 105762.
- [11] Wang, Qinhua, et al, 2020. "Seismic response control of adjacent high-rise buildings linked by the Tuned Liquid Column Damper-Inerter (TLCDI)." *Engineering Structures* 223: 111169.
- [12] Samadi, M., and N. Jahan, 2019. "Determining the effective level of outrigger in preventing collapse of tall buildings by IDA with an alternative damage measure." *Engineering Structures* 191 -104-116.
- [13] Wang, Wei, et al, 2019. "Experimental study of the hysteretic behaviour of corrugated steel plate shear walls and steel plate reinforced concrete composite shear walls." *Journal of Constructional Steel Research* 160-136-152.
- [14] Ahzhang, Jie, et al, 2007. "Safety analysis of optimal outriggers location in high-rise building structures." *Journal of Zhejiang University-Science* 8.2- 264-269.