

A High-Torque, Multi-Motor Smart CNC Plotter for Precision Civil Engineering Drafting

Suparna pal¹, Abhigyan Adarsh², Abhinav Kumar³, Aditya Tiwari⁴, Pritam Das⁵, Suman Kumar Sarma⁶, Sandeep Kumar Das⁷, Ashis Kumar Mandal⁸

¹Assistant Professor, Dept. of EE, JIS College of Engineering, Kalyani, WB, India

²⁻⁸UG Student, Dept. of EE, JIS College of Engineering, Kalyani, WB, India

Abstract - This paper introduces a computer numerical control (CNC) drafting system designed to deliver high precision at significantly reduced cost. Instead of relying on expensive proprietary components, the system employs a custom architecture that addresses common failure modes in low-cost open-loop designs through redundancy. Each linear axis is powered by four low-cost, gear-reduced 20BYJ-46 stepper motors operating in parallel. These motors drive two synchronized timing belt assemblies, with the moving elements directly coupled to the belts. The parallel belt configuration allows the torque from each motor to combine, producing a strong, balanced propulsive force. This distributed drive reduces step loss and prevents gantry deflection, ensuring accuracy and stability.

Motor commands are issued simultaneously to all drivers via shared microcontroller control pins, guaranteeing synchronized actuation. To enhance reliability, a mechanical fault detection system is integrated: a roller limit switch is positioned against the belt surface. As the belt moves, the roller rotates; if the belt breaks, slips excessively, or a motor stalls, the roller stops, triggering the switch and signaling a failure.

By combining distributed motor actuation with mechanical fault detection, the system achieves a robust, reliable, and highly accurate CNC drafting platform. Compared to commercial alternatives, this architecture can be built at a fraction of the cost, while maintaining superior performance. The synergy of the distributed drive system and mechanical motion sensor establishes a CNC plotter design that is both economical and dependable.

Key Words: Computer Numerical Control (CNC) plotter, Step loss, ULN2003 driver boards, Geared stepper motors, Roller-lever limit switch.

1. INTRODUCTION

The multi-motor distributed drive architecture effectively addresses the precision–cost tradeoff in CNC plotters. Rather than relying on a single expensive motor per axis, the design employs multiple low-cost stepper motors. Specifically, four 20BYJ-46 motors operate in parallel to drive synchronized timing belt assemblies. This configuration allows torque contributions from each contact point to combine, generating sufficient force to overcome resistance. The added torque minimizes step loss and enhances stability.

To further improve reliability, a low-cost mechanical belt monitoring system is integrated. A lever-actuated limit switch keeps its roller pressed against the belt surface during operation. As the belt moves, the roller rotates; if the belt slips, breaks, or stalls, the roller stops, triggering the switch to send a fault signal. The controller then halts the machine, preventing wasted motion and material.

This integrated approach—combining distributed drive mechanics with fault detection—delivers both accuracy and reliability. At the same time, it remains compatible with open-source components and straightforward assembly methods, making it a practical and cost-effective alternative to commercial CNC systems.

2. Reason For Precision Breaks Down in Affordable CNC Systems

From hands-on experience, the biggest frustration with low-cost CNC drafting systems is their lack of precision. The culprit is usually step loss—that moment when a stepper motor is told to move but simply doesn't. It's not that the command is wrong; it's that the motor is fighting against friction, the weight of the moving parts, or other resistance that's stronger than its torque at that instant.

Most budget systems rely on open-loop control. The processor sends a command and assumes the move happened. No feedback, no confirmation. So when a step

is missed, the controller still believes the motor reached its target. Over time, these tiny errors pile up. The result? Bent lines, measurements that don't match the design, and final drawings that are simply unusable.

3. Limitation in Single-Motor Drives

The traditional fix is to put one motor on each axis. But here's the catch: that motor has to be big and powerful enough to overcome all resistance. High-torque motors are expensive, and that cost clashes with the goal of building a low-cost system.

Cheap stepper motors like the 20BYJ-46 are everywhere, but they don't have the torque or stability to handle precision jobs on their own. Even if you wire several together without coordination, they still can't deliver the strength needed. And because these systems are open-loop, they don't notice when a timing belt slips or breaks. The motors keep running, but nothing moves. Materials get ruined, time is wasted, and frustration builds.

Closed-loop systems with encoders could solve this, but they add complexity and cost—sometimes several times higher than the base system. That defeats the whole point of DIY-friendly, affordable CNC machines.

4. The Gaps We Need to Close

All of this points to a clear need in the CNC drafting world: a design that balances affordability with precision. The solution must:

- Eliminate step loss using low-cost, widely available components instead of premium motors or complex electronics.
- Work seamlessly with open-source software, the backbone of the DIY CNC community.
- Detect mechanical failures reliably, especially timing belt slips or breaks, without adding significant cost or complexity.

5. Solution Proposed

Our CNC plotter system was designed to address two major problems we observed in low-cost plotters: motors losing steps and the motion assembly falling out of alignment. To overcome these issues, we combined two core ideas—distributed motor drive and a belt monitoring device. Together, these innovations deliver accuracy while keeping the design affordable and compatible with open-source components.

We built the machine's frame using modular aluminum extrusion profiles. This choice gave us three key benefits: rigidity to resist bending, light weight for faster acceleration and deceleration, and modularity for easy resizing or reassembly. These qualities ensure that the foundation remains stable and vibration-free during operation.

For the motion assembly, we designed a horizontal gantry and pen carriage optimized to reduce mass while maintaining durability. Lower mass means less load on the motors, which improves responsiveness, reduces step loss, and keeps displacement errors under control.

Instead of relying on one large, expensive motor per axis, we implemented a distributed multi-motor drive. Our system uses eight low-cost 20BYJ-46 stepper motors—four for the X-axis and four for the Y-axis—working in synchronized pairs. Each motor drives a parallel timing belt, and together they generate enough torque to overcome friction, inertia, and other resistances. This shared load prevents step failures and keeps the gantry aligned. Balanced force distribution across the gantry stops twisting or skewing, ensuring straight, accurate motion.

For vertical motion, we used a stepper motor to control pen elevation. Unlike a servo, the stepper provides precise positional control, allowing fine adjustments to pen pressure and height. This keeps line quality consistent and prevents damage to the pen.


On the electronics side, we chose the Arduino Uno R3 running GRBL firmware as the control core. GRBL interprets G-code instructions from the computer and translates them into motor signals. Each motor is connected through a ULN2003 driver module, which amplifies the microcontroller's signals to the current levels required by the motor coils. To guarantee synchronization, all drivers for a given axis share identical control pins, ensuring perfectly timed execution. The system runs on a 12V, 5A power supply, providing stable energy for both motors and electronics.

A key innovation we introduced is the mechanical failure detection system. Open-loop control systems usually cannot detect when a belt slips, breaks, or stalls. To solve this, we added a lever-actuated limit switch with a roller pressed against the belt surface. As long as the belt moves, the roller turns. If the belt stops, the roller halts, the lever shifts, and the switch sends a fault signal to the microcontroller. The controller immediately stops all motors, preventing wasted material and alerting the operator.

Finally, we integrated the workflow with open-source software. Designs are created in CAD tools like


AutoCAD, converted into G-code using CAM programs such as Inkscape, and executed in real time through tools like Universal G-code Sender. The microcontroller processes each line of G-code instantly, turning it into synchronized motor commands that drive the plotter with precision.

In summary, our solution blends affordable hardware, distributed drive mechanics, and simple fault detection into a CNC plotter that is reliable, accurate, and DIY-friendly. We believe this approach demonstrates that high performance can be achieved without high cost.



SYSTEM LAYOUT DIAGRAM





6. Advantages

- **Accuracy with Affordability:** Our design bridges the gap between costly precision systems and cheap, low-performance machines by using smart component choices and a novel layout.
- **No Step Loss:** With four synchronized motors per axis, combined torque eliminates step failures, ensuring reliable and precise output.
- **Reliable Failsafe Protection:** A simple belt-monitoring roller detects rupture or slippage early, sending fault signals to stop the machine—at far lower cost than encoder systems.
- **Stable Operation:** Distributed load across multiple motors and belts reduces vibration, minimizes wear, and keeps motion smooth and consistent.

7. Research Findings

- **Dimension Accuracy:** X-axis line measured +0.4 mm, Y-axis line measured −0.4 mm, circle radius was exact.
- **Repeatability:** Across 5 plots, there was almost zero shift—showing perfect consistency.

8. Industrial Aspects

- **Cost Efficiency:** Total build cost was about ₹3,000 cheaper than commercial plotters priced above ₹50,000.
- **Sustainability:** The design supports local repair and reuse, aligning with circular economy principles.

8.1 Hardware Cost Breakdown

8 Stepper Motors: ₹708	Timing Belts: ₹192
Drivers & Optos: ₹193	Misc & Wood: ₹1465
Arduino Uno: ₹219	Total Cost: Almost ₹3,000

9. Future Scope

- **Wireless Integration:** Adding ESP32 modules for smartphone/cloud connectivity.
- **Auto-Pen Changer:** Rack-and-pinion system to switch pen colors and line weights.
- **Scaling Up:** Upgrading rails to steel box sections for full A1-size plotting, ideal for architectural work.

10. Conclusion

Our CNC plotter design proves that precision and affordability can coexist. By using a distributed multi-motor drive with synchronized 20BYJ-46 stepper motors and parallel timing belts, we eliminated step loss and gantry racking. A simple belt slip sensor based on a roller lever switch provides failsafe protection without costly encoders.

Built with Arduino, GRBL firmware, and modular aluminum framing, the system is DIY-friendly, reliable, and scalable. It empowers educators, hobbyists, and small enterprises to achieve professional-quality plotting at a fraction of the cost, bridging the gap between low-cost kits and high-end equipment.

ACKNOWLEDGEMENT

We would like to extend our heartfelt thanks to everyone who contributed to this research effort. We are deeply grateful to our guide, Ms. Suparna Pal, for her invaluable guidance and insight. We also wish to thank

the faculty and staff of JIS College of Engineering for providing the resources and support that made this work possible.

We appreciate the constructive feedback from our peers and the encouragement from our families and friends. Finally, we extend our gratitude to the publisher, the International Journal of Scientific Research in Engineering and Management (IJSREM), for considering our work for publication.

REFERENCES

- [1] Hasan, M. M., Khan, M. R., Noman, A. T., Rashid, H., Ahmed, N., & Reza, S. M. T. (2019). Design and Implementation of a Microcontroller Based Low Cost Computer Numerical Control (CNC) Plotter using Motor Driver Controller. 6, 1–5.
- [2] R. Patel and V. Sharma, "Design and Fabrication of a Low-Cost 3-Axis CNC Plotter for Educational Applications," *IJERT*, 2021.
- [3] Espalin, D, Muse, D. W., MacDonald, E., & Wicker, R. B. (2014). 3D Printing multi functionality: structures with electronics. *The International Journal of Advanced Manufacturing Technology*, 72(5-8), 963-978.
- [4] A. Kumar and J. Singh, "A Distributed Drive System for Step Loss Reduction in Cartesian Robots," *IEEE Trans. on Ind. Electronics*, 2022.
- [5] Hashim, N. S. (2012). Design of mini machines (Doctoral dissertation, UMP).
- [6] S. Iyer, "Microstepping and Torque Control Strategies for 28BYJ-48 Geared Stepper Motors," *JRC*, 2020.
- [7] 3) Jayachandraiah, B., Krishna, O. V., Khan, P. A., & Reddy, R. A. (2014). Fabrication of Low Cost 3-Axis Router. *International Journal of Engineering Science Invention*, 3(6), 01-10.
- [8] L. Chen and H. Wang, "Implementation of GRBL Firmware on Arduino-based Platforms," *ICAM*, 2019.
- [9] J. M. Pearce, "Building Research Equipment with Free, Open-Source Hardware," *Science*, 2012.
- [10] Kumar M. A., Krishnaraj J. and Reddy B. G. S. 2017. Mini CNC 2D Sketcher for Accurate Building Drawing. *IJCIET*. 8(6), 543–549.