

# A Review on IOT Based Smart Grid System to Monitor and Control Renewable Energy Source

Priyanka Madhukar Gawali<sup>1</sup>, Prof.S.V.Murkute<sup>2</sup>

<sup>1</sup> Department of Electrical Engineering, People's Education Society College of Engineering, Nagsen vana, Aurangabad, India

<sup>2</sup> Department of Electrical Engineering, People's Education Society College of Engineering, Nagsen vana, Aurangabad, India

\*\*\*

**Abstract** - This article provides a brief overview of grid integration and power quality issues linked to the integration of renewable energy systems into the grid, as well as the role of power electronic devices and flexible AC transmission networks. This project introduces late patterns in power devices for coordinating wind and sunlight-based power generation. Conversations regarding current and future trends in solar and wind energy frameworks are introduced with the goal of maintaining quality and developing each invention. The application of various approaches used to alleviate specific Power Quality concerns is also suggested for consideration. Power Electronics interface not only plays an important role in the efficient coordination of wind and solar energy frameworks, but it also has an influence on power-age framework activity, particularly when renewable energy sources play a unique role in the overall framework limit.


**Key Words:** Solar power, Controlling Unit, , wind power, Renewable Energy .

## 1. INTRODUCTION

It is a high level metering innovation including setting astute meters to peruse, interaction and input the information to clients. It estimates energy utilization, from a distance changes the stock to clients and remotely controls the most extreme power utilization. Brilliant metering framework utilizes the high level metering foundation framework innovation for better execution. These are equipped for conveying in the two bearings. They can send the information to the utilities like energy utilization, boundary values, cautions, and so forth and furthermore can get data from utilities, for example, programmed meter understanding framework, reconnect/disengage guidelines, overhauling of meter programming's and other significant messages. These meters diminish the need to visit while taking or perusing month to month bill. Modems are utilized in these savvy meters to work with correspondence frameworks, for example, phone, remote, fiber link, power line interchanges. One more benefit of savvy metering is finished a version of altering of energy meter where there is extent of involving power in an unlawful manner.

Three main factors are impacting the future electric systems of the world; government policies, efficiency need of the consumer, and the introduction of new intelligent computer and hardware technologies. Environmental concern have

created the governmental policies around the world, including at the federal and state levels, which on flow the entire energy system to efficiency, conservation, and renewable sources of electricity . These factors are the main drivers that are expanding the use of all sorts of new renewable energy and storage technologies on one hand and new energy efficiency and conservation techniques on the other hand.



For example, sunlight based, wind, and hydrogen. The savvy lattice interfaces an assortment of dispersed energy asset resources for the power network. By utilizing the Internet of Things (IoT) to gather information on the shrewd matrix, utilities can rapidly distinguish what's more, resolve administration issues through consistent self assessments. Since utilities never again need to rely upon clients to report blackouts, this self-recuperating ability is essential part of the brilliant lattice. Buyers are turning out to be more proactive and are being enabled to participate in the energy utilization choices influencing their everyday lives. Simultaneously, they are growing their energy needs. Model are shopper interest will at last incorporate broad utilization of electric vehicles (the two vehicles and trucks), controller of in-home apparatuses to advance energy protection, responsibility for conveyed age from always sustainable power sources, and the board of power stockpiling to locally match supply to that interest.

The availability of new technologies such as more aware about SCADA sensors, secure 2-way communications, integrated data management, and intelligent, autonomous controllers has open up opportunities that did not exist even a decade.

## 2. Literature Review

H. Gharavi and R. Ghafurian[1] says that “A smart grid (SG), also called next generation power grid, is generally defined as the aggregation of emerging technologies, hardware, software and practice that make the existing infrastructure of power grid more reliable, accommodating, secure, resilient and ultimately more beneficial for consumers”.

A. Thomas[2] says that “In conventional power grid a large number of customers are generally fed from a few central generators while in the smart grid bi-directional transfer of power .The recent development in the power system allows the seamless integration of alternate form of energy production sources into the existing power grid”.

X.P. Zhang [3] said that “However, the alternating and discrete characteristics of these sources is the major barrier in integration to the smart grids that can be handled by the deployment and effective use of control modes. This not only cause the improvement in performance but also the operational hours of these sources will be increased”. The most exploited renewable energy sources are hydel energy, wind and photovoltaic source. The share of the renewable energy production to global electricity demand is increasing continuously and it was about 20% at the end of 2011. However, these sources vary in requirements for their abstract in main streamline. Issues such as the efficiency, reliability and security in power system forces the operators to exploit widely distributed renewable energy sources and deploy them rapidly into grid.

These sources are helpful to environment and also to human health due to less pollution generated. Risk associated with others plants such as disruptions in fuel supply due to international conflicts, problems in transportation and unavailability of unit can also be overcome by the onsite small scale renewable generations. Renewable energy resources can be used for power generation as isolated system but their benefits are significantly enhanced when they are integrated into electric utility system. Integration of variable natural renewable energy resources require a huge modification in existing network operation which may in due time lead to increase in electricity cost. In ref. U. Helman said that [4] “problems are mentioned related to intermittent nature of RER” and “these problems are clearly demonstrated in ref. [5] said by S. Kiliccote”.

Cameron W. Potter [6] also describes For the ability and stability of modern grid, the understanding of this variability is vital”. Manageable power sources moreover called green power sources consolidate the breeze, hydro, sun situated, biomass, ocean and streaming energy sources. These resources have a promising future on account of their present situation pleasant nature and wide availability.

In ref. [16] a scheme for demand side management is proposed. It also allows load shifting from peak loads to low demands. It is also proposed how to utilize available energy by using EVs.


The paper at ref. [17] presents a general overview of present power electronics technologies to be used in renewable energy resources for integration in smart grid. These are applicable where utility companies and consumers are working together to attain sustainable energy consumption, by increased use of renewable energy sources,

bringing generation closer to customers and making a commitment to rational and efficient consumption.

In ref. [18] an energy management system (EMS) is suggested to optimize operation of smart grid. Integration of demand side management (DSM) and active management schemes (AMS) gives a better exploitation of renewable energy sources. The effectiveness of the proposed EMS was verified on a 23-bus 11-kV distribution network. Results proved that the combined operations of RES and Price Responsive Demand mitigate network constraints while satisfying higher demand levels and reducing the energy costs.

### 2.1 Wind Power

Wind energy is considered as one of the most strong and potential substitute energy resource due to its boundless and clean nature. The engine energy of wind is changed over into mechanical energy with the help of wind turbine that is related with the rotor edges. The rotor is further coupled to the generator (by and large doubly dealt with acknowledgment generator) for the change of mechanical energy into electrical energy. The power got from the breeze turbine at express region generally depends on the breeze speed, at tower height and turbine speed ascribes.




Total capability of turbine and generator notwithstanding the way that having no risky effect and power creation at sensible cost from wind energy there are similarly certain disadvantages, for instance, weakness of openness, uncontrolled power yield, etc Because of its haphazardness and stochastic lead, probability based showing systems are required and its ideal task can be looked out by the usage of groundbreaking estimations.

### 2.2 Solar Power

Daylight based energy is for the most part coursed over the area and it might be handled by the use of different genuinely propelling advances for instance sun fueled warm power, Solar photovoltaic (PV) that are requested in light of their instrument of getting the sun fueled radiations and its change into electrical energy. Sun situated thermal power plant is an indirect methodology for moving sun controlled energy into electrical energy, in which thermal power is made by collecting the sunlight radiations also, a

while later steam is made that drives the turbine generator as in the event of customary nuclear energy plants.




The photovoltaic power plant, primary type of sun powered energy, is an immediate technique for changing over the sun powered radiations into power. Photodiodes are utilized in these plants for the effective assimilation of daylight. This entire framework is for the most part created of battery powered battery, regulator, inverters, load bank and so on PV power plants can be utilized as independent wellspring of energy and it can likewise be associated with primary power lattice.

### 3. Proposed System

In this project we produce power through various sustainable assets like breeze and sun oriented power. The working of the framework is with the end goal that when the MSEB Power is off the power load consequently turned on the Solar Power or on the Wind Power. For that naturally exchanging of Power Load we use Change over Switch Circuit. In this project we likewise utilize the snubber circuit for the presentation improvement of the framework. A snubber is a circuit that is utilized in semiconductor gadgets for insurance and execution upgrades. They have various purposes, to be specific the decrease of force dissemination in power electronic exchanging networks.

A snubber circuit cutoff points or stops exchanging voltage abundance and its pace of rise, hence lessening power dispersal. In its least complex structure, a snubber circuit essentially comprises of a resistor and capacitor associated across the thyristor. They can do numerous things, including:

- ⌚ Reducing or eliminating voltage and/or current Spikes.
- ⌚ Limiting  $di/dt$  or  $dV/dt$  .
- ⌚ shaping the load line to keep it within the safe Operating area.
- ⌚ Reducing total switching losses.
- ⌚ Reducing EMI by damping voltage; and
- ⌚ Transferring power dissipation from the switch to a resistor (or a useful load).



### 4. CONCLUSIONS

Smart grid technology is an extension of analogue technology that has been established to regulate the use of appliances via two-way communication. However, the widespread availability of Internet connectivity in most houses has made the smart grid more feasible to adopt. Smart grid devices broadcast data in a way that allows regular users, operators, and automated devices to react swiftly to changes in smart grid condition systems. Appropriate execution, dependability, and the strength of the force being consumed and generated should be ensured. As a result, it is critical to measure, test, and break down the power consumption of each component of the force framework for its presentation and performance under normal and extreme operating conditions.

### 5. ACKNOWLEDGEMENT

I wish to acknowledge the help provided by the technical and support staff in the Electrical and Power department of the Education Society College of Engineering, Aurangabad. I would also like to show my deep appreciation to my coordinator who helped me finalize my project.

### REFERENCES

- [1] H. Gharavi and R. Ghafurian, Smart Grid: The Electric Energy System of the Future, IEEE Proceedings (2011).
- [2] A. Thomas, Wind Power in Power System, John Wiley and Sons, Ltd. (2005).
- [3] X.P. Zhang, A Framework for Operation and Control of Smart Grids with Distributed Generation, Power and Energy Society General Meeting - Conversion and Delivery of Electrical Energy in the 21st Century, IEEE Proceedings (2008).
- [4] U. Helman, California Independent System Operator (2010).
- [5] S. Kiliccote et al., LNBL-2195E, Lawrence Berkeley National Laboratory, Berkeley, CA (2009).

- [6] C.W. Potter, Building a Smarter Smart Grid through Better Renewable Energy Information, Power Systems Conference and Exposition, PSCE'09, IEEE/PES (2009).
- [7] H.Chandler, Harnessing Variable Renewables: A Guide to the Balancing Challenge, OECD/IEA (2011).
- [8] J. DeCesaro, K. Porter and M. Milligan, The Electricity Journal 22 (2009) 34.
- [9] M.R. Patel, Wind and Solar Power Systems: Design, Analysis and Operation, CRC press (2005).
- [10] R. Chedid, H. Akiki and S. Rahman, Energy Conversion, IEEE Transactions 13 (1998) 10.
- [11] J.A. Duffie and W.A. Beckman, NASA STI/Recon Technical Report 81 (1980).
- [12] T. Markvart, Solar Electricity, John Wiley & Sons (2000).
- [13] Y. Liu et al., Applied Mechanics and Materials 341 (2013) 2846.
- [14] C. Huddleston-Holmes and J. Hayward, CSIRO report for the prepared as input to the Garnaut Review Update. <http://www.csiro.au/en/Outcomes/Energy/Renewables-andSmartSystems/Garnaut2011-geothermalenergy.aspx> (2011).
- [15] T.J. Hammons, Tidal Power, Proceedings of the IEEE 81 (1993) pp. 419-433.
- [16] M. Marwan and F. Kamel, Optimum Demand Side Response of Smart Grid with Renewable Energy Source and Electrical Vehicles, 21st Australasian Universities Power Engineering Conference (AUPEC), (2011) pp. 1-5.
- [17] J. M. Carrasco, Power Electronics for the Integration of Renewable Energies into Smart Grids, Power Engineering, Energy and Electrical Drives (POWERENG), International Conference (2011) 1.
- [18] C. Cecati, C. Citro and P. Siano, Sustainable Energy, IEEE Transactions 2 (2011) 468.
- [19] K. W. Cheung, Smart Dispatch for Grid Integration of Wind Generation, Innovative Smart Grid Technologies (ISGT Europe), 2nd IEEE PES International Conference and Exhibition (2011) 1-8.
- [20] X.-F. Song et al., East China Electric Power 39 (2011) 1443.
- [21] E. Bitar, P. P. Khargonekar and K. Poolla, Systems and Control Opportunities in the Integration of Renewable Energy into the Smart Grid, Proc. of IFAC World Congress (2011) pp. 4927-4932.