

AI BASED SOLAR PANEL MONITORING AND FAULT DETECTION USING IOT

Mohamed Ismail Yaser K¹, Mohamed Zubair², Aakash R³, Sabari Pandiyan R⁴, Dr. R. Purushothaman⁵

^{1,2,3,4} UG Students, Electronics and Communication Engineering
J.J. College of Engineering and Technology, Trichy, Tamil Nadu, India

⁵ Assistant Professor, Electronics and Communication Engineering
J.J. College of Engineering and Technology, Trichy, Tamil Nadu, India

Abstract— The rapid growth of distributed renewable energy systems has increased the necessity for intelligent monitoring and predictive maintenance of photovoltaic (PV) installations. Conventional solar panel monitoring techniques often rely on periodic manual inspection, which is insufficient for early detection of performance degradation and fault conditions. To address these limitations, this work proposes an integrated Internet of Things (IoT) enabled photovoltaic monitoring framework combined with machine learning-based fault classification. The proposed system incorporates an embedded microcontroller-based architecture utilizing an ESP32 module for real-time acquisition of environmental and electrical parameters, including temperature, irradiance level, and output voltage of the photovoltaic unit. Sensor data are periodically sampled and transmitted through wireless communication protocols to a remote computational platform for centralized analysis. A supervised machine learning model based on the Random Forest algorithm is implemented to perform multi-parameter data classification and anomaly detection under varying operational conditions. Furthermore, the system supports remote visualization through a web-based IoT interface, enabling continuous performance assessment and condition monitoring. In the event of abnormal operational patterns, automated alert mechanisms are triggered to notify system operators, thereby facilitating rapid corrective action and minimizing energy losses. The proposed framework enhances operational reliability, improves system efficiency, and enables predictive maintenance strategies for small- and medium-scale photovoltaic installations. Experimental validation demonstrates the feasibility of the system for real-time monitoring and intelligent fault prediction in smart energy management applications.

Keywords— IoT, Random Forest Algorithm, Classification.

1. INTRODUCTION

Photovoltaic energy generation has become an essential component of modern distributed power systems due to its ability to provide localized and environmentally sustainable electricity production. Despite the advantages offered by photovoltaic modules, maintaining consistent electrical output remains a significant operational challenge, particularly under dynamically changing environmental conditions. Parameters such as thermal variation, fluctuating illumination levels, and electrical inconsistencies can introduce performance instability, thereby reducing overall system productivity. Continuous observation of these influencing factors is therefore necessary to sustain reliable photovoltaic operation. In practical installations, performance evaluation is frequently performed at discrete intervals rather than through uninterrupted observation. This discontinuous monitoring approach limits the visibility of

transient abnormalities and gradual efficiency decline. Minor deviations in operating conditions may remain unnoticed until noticeable power loss occurs, which complicates maintenance planning and increases operational expenditure. The lack of automated condition awareness mechanisms further restricts the ability to implement proactive maintenance strategies within conventional photovoltaic infrastructures.

Advancements in embedded sensing technologies have enabled the development of compact monitoring units capable of acquiring multi-parameter data directly from photovoltaic environments. Microcontroller-based sensing modules provide an effective interface for integrating environmental sensors and electrical measurement circuits within a unified hardware platform. The incorporation of wireless networking functionality within embedded controllers enables seamless transmission of measured data to remote computational environments, thereby eliminating the need for localized manual inspection. Beyond data acquisition, the interpretation of operational data has emerged as a critical requirement for intelligent monitoring systems. Machine learning methodologies offer the capability to transform raw sensor measurements into actionable information through pattern recognition and classification processes. Ensemble-based learning techniques, particularly the Random Forest approach, provide enhanced predictive robustness when dealing with heterogeneous sensor inputs collected under varying environmental conditions. Such models enable the identification of irregular operational behavior that may indicate the presence of developing faults.




Fig.1 Distinct visual differences between the normal and dusty solar panel installation on the roof

In response to these technological opportunities, the present study develops an integrated photovoltaic supervision framework that combines real-time sensing, wireless communication, and predictive analytics. The proposed

architecture employs an ESP32-based embedded unit to acquire temperature, illumination, and voltage measurements associated with photovoltaic operation. The captured data are transmitted through wireless communication channels to a remote processing environment, where classification analysis is performed to evaluate operational status. Alert generation mechanisms are incorporated to notify system operators when abnormal system states are detected.

The integration of distributed sensing with intelligent classification techniques establishes a scalable monitoring framework capable of supporting improved system transparency and operational continuity. The developed system contributes toward minimizing performance degradation, enabling early detection of abnormal conditions, and facilitating adaptive maintenance planning in photovoltaic-based energy infrastructures.

2. RELATED WORKS

Monitoring of photovoltaic installations has been widely explored in recent years due to the increasing reliance on decentralized solar energy generation. Initial experimental systems were designed with simple measurement units that captured output characteristics of solar panels at fixed intervals. These early monitoring arrangements primarily concentrated on recording voltage and current values and displaying them locally, which provided limited insight into dynamic operational variations.

With the advancement of embedded electronics, researchers began incorporating multiple environmental sensing elements into photovoltaic monitoring frameworks. These enhanced configurations enabled the observation of surrounding atmospheric conditions alongside electrical behavior. The integration of digital microcontrollers facilitated structured data acquisition, allowing synchronized measurement of temperature, illumination intensity, and output parameters. Although these systems improved observation accuracy, their functionality was largely restricted to passive monitoring without intelligent interpretation of collected information.

The evolution of wireless communication technologies introduced new possibilities for distributed monitoring of solar installations. Several studies implemented wireless-enabled sensing modules to transmit performance data to remote terminals, thereby reducing the need for physical inspection. This transition supported improved accessibility to real-time information and enabled centralized supervision of multiple photovoltaic units. Despite this progress, many implementations relied on predefined threshold limits to detect abnormal conditions, which limited their adaptability under complex environmental variations.

More sophisticated monitoring strategies have recently emerged through the integration of cloud-based infrastructures and networked devices. These frameworks enabled continuous storage of operational records and provided visualization dashboards for performance tracking. Such platforms contributed significantly to long-term performance analysis; however, their ability to identify early-stage faults remained dependent on manual observation and operator judgment.

Recent developments in computational intelligence have introduced machine learning models as analytical tools

for photovoltaic data interpretation. By examining historical sensor datasets, these models demonstrated the capability to recognize hidden patterns associated with system irregularities. Ensemble learning methods, particularly those employing multiple decision structures, have shown improved classification accuracy when dealing with multi-variable environmental data. These techniques provided a promising pathway for detecting performance inconsistencies that might not be visible through conventional observation methods.

Despite notable advancements across sensing, communication, and analytical domains, achieving a compact and unified monitoring solution remains an ongoing challenge. Many existing implementations treat sensing, data transmission, and fault prediction as separate subsystems, resulting in increased complexity and reduced operational efficiency. Additionally, the requirement for cost-effective and energy-efficient monitoring architectures suitable for small-scale installations continues to be an important research concern.

In view of these considerations, the present work introduces an integrated monitoring and prediction framework that combines multi-parameter sensing, wireless communication, and machine learning-based analysis within a single operational structure. The proposed design aims to improve situational awareness, support early identification of abnormal operating states, and enhance the overall reliability of photovoltaic energy systems.

3. PROPOSED METHODOLOGY

3.1 Parameter Identification

At the initial stage, important environmental and electrical variables affecting photovoltaic efficiency are determined. Parameters such as temperature, light intensity, and output voltage are selected because they directly influence energy generation and system stability. Proper parameter selection ensures that the monitoring system captures meaningful performance variations under changing environmental conditions.

3.2 Sensor Integration and Hardware Setup

Suitable sensing devices are interfaced with the embedded controller to measure selected parameters from the photovoltaic unit. Each sensor is positioned carefully to ensure accurate detection of physical conditions. The sensors generate electrical signals corresponding to the observed variations, which are then transferred to the controller through configured input channels.

3.3 Data Sampling and Preprocessing

The embedded controller periodically reads incoming signals from connected sensors at fixed time intervals. These signals are converted into digital form and processed using filtering techniques to remove unwanted disturbances. Data normalization is performed to maintain uniform measurement ranges, ensuring reliable comparison of multiple parameters.

3.4 Wireless Communication Establishment

After preprocessing, the processed information is transmitted through a wireless communication interface to a remote monitoring platform. The use of WiFi-based communication allows flexible installation of the system without complex wiring. Regular data transmission ensures

continuous availability of system information for remote observation.

3.5 Data Storage and Visualization Process

The received information is stored in an organized database structure to maintain a chronological record of photovoltaic performance. Stored data are displayed using graphical visualization methods, allowing users to observe trends and identify variations in environmental and electrical conditions over time.

3.6 Predictive Analysis Using Machine Learning

Collected datasets are analyzed using a machine learning classification approach to interpret system behavior. The analytical model examines relationships between input parameters and determines operational status. This predictive analysis enables identification of unusual patterns that may indicate potential performance issues.

3.7 Alert Generation and Notification System

When the analyzed data exceed predefined operational limits, the system automatically generates alert notifications. These alerts are delivered to the monitoring interface, informing users about abnormal conditions. Early warning capability supports timely corrective action and helps prevent long-term efficiency loss.

3.8 Continuous Monitoring and System Operation

All functional stages operate repeatedly in a sequential cycle to maintain uninterrupted monitoring. Continuous data acquisition, processing, and evaluation ensure that photovoltaic performance is observed in real time. This cyclic operation improves system reliability and enhances long-term operational awareness.

4. RESULTS AND DISCUSSION

The implemented photovoltaic monitoring framework was evaluated through repeated observation of environmental and electrical conditions to verify its functional stability and analytical capability. During operational testing, the sensing elements consistently captured temperature, illumination intensity, and output voltage values associated with the photovoltaic module. The embedded processing unit performed synchronized sampling of these parameters and transmitted the processed data through wireless communication without noticeable interruption. Continuous data reception at the remote interface confirmed that the communication pathway remained stable across extended monitoring intervals, thereby validating the reliability of the transmission mechanism.

Observation of the collected dataset revealed a measurable relationship between environmental variation and electrical output characteristics. Incremental changes in illumination intensity produced corresponding increases in output voltage, indicating proper responsiveness of the photovoltaic module to solar exposure. Similarly, fluctuations in temperature demonstrated observable influence on electrical stability, supporting the importance of multi-parameter monitoring for performance evaluation. The recorded values were displayed through graphical visualization, which enabled clear identification of

operational patterns over successive time intervals. Smooth transitions between consecutive readings indicated stable sensing behavior and accurate signal acquisition throughout the monitoring cycle.

The predictive component of the system was assessed using datasets obtained under different simulated environmental conditions. The implemented classification model analyzed the relationship between multiple parameters and generated operational status predictions based on learned data characteristics. Under standard environmental exposure, the model consistently categorized system activity within acceptable performance limits. When deviations were intentionally introduced to represent abnormal conditions, the analytical framework detected irregular parameter combinations and generated warning responses. This outcome demonstrated the capability of the predictive model to transform raw measurements into actionable information suitable for early-stage fault recognition.

Performance comparison with conventional inspection methods indicated clear operational advantages associated with automated monitoring. Traditional evaluation techniques depend on periodic observation, which may fail to capture short-duration anomalies or gradual efficiency degradation. In contrast, the proposed system maintained uninterrupted supervision by continuously recording environmental and electrical variables. This continuous monitoring approach enabled identification of performance variations that would otherwise remain undetected during manual inspection cycles. The integration of intelligent data interpretation further enhanced system functionality by enabling classification of operational states without requiring constant human analysis.

Extended operation of the monitoring system demonstrated consistent functional behavior across repeated execution cycles. Sensor outputs remained stable, and no significant communication loss was observed during prolonged data transmission periods. The embedded processing environment effectively handled sequential data operations without performance degradation, indicating the suitability of the selected hardware platform for long-duration deployment. Reliable visualization and storage of historical data supported evaluation of long-term performance patterns, which is essential for understanding seasonal and environmental influences on photovoltaic output.

The observed results confirm that the proposed integrated framework provides an effective mechanism for improving operational awareness and supporting predictive maintenance of photovoltaic installations. Continuous parameter monitoring combined with intelligent classification contributes to early identification of irregular system behavior, thereby reducing the likelihood of unexpected efficiency loss. The ability to remotely access performance information enhances user convenience and enables timely corrective action when abnormal conditions are detected. Overall, the analytical outcomes demonstrate that the coordinated interaction between sensing, communication, and machine learning components establishes a dependable monitoring environment capable of supporting sustainable photovoltaic energy utilization.



Fig.2 Experimental Setup

5. CONCLUSION AND FUTURE SCOPE

The present work establishes a structured monitoring framework that combines environmental sensing, embedded computation, wireless connectivity, and analytical evaluation into a unified operational platform for photovoltaic supervision. The developed system demonstrates the capability to capture multiple influencing parameters and transform them into meaningful operational insights through continuous processing and remote accessibility. The coordinated functioning of sensing elements and communication modules enables uninterrupted observation of photovoltaic behavior, thereby improving the visibility of system conditions that are typically overlooked in manual inspection approaches. The analytical mechanism incorporated within the system contributes to recognizing irregular performance patterns, supporting timely intervention and minimizing the probability of prolonged efficiency reduction. The observed system behavior confirms that an integrated monitoring strategy enhances operational transparency and promotes more dependable photovoltaic energy utilization under dynamic environmental exposure.

Looking beyond the present implementation, several expansion possibilities can further strengthen the practical significance of the proposed framework. The inclusion of additional sensing variables, such as current measurement and environmental humidity, can provide a more detailed representation of photovoltaic operating conditions. Adoption of advanced computational models capable of adaptive learning may improve prediction capability and enable more refined identification of emerging performance deviations. The architecture may also be extended to support interconnected photovoltaic arrays, allowing centralized supervision of multiple installations through scalable network structures. Furthermore, integration with energy storage units and automated control mechanisms can enable intelligent load management and optimized energy utilization. These prospective developments indicate that the proposed monitoring concept can evolve into a comprehensive smart energy supervision platform suitable for future renewable power management environments.

REFERENCES

- [1] A. Ghosh and S. Saha, "Real-time monitoring of photovoltaic systems using Internet of Things technology," *International Journal of Renewable Energy Research*, vol. 9, no. 2, pp. 845–853, 2019.
- [2] M. K. Deshmukh and S. S. Deshmukh, "Solar photovoltaic monitoring system based on wireless sensor networks," *International Journal of Smart Grid*, vol. 3, no. 1, pp. 15–22, 2018.
- [3] R. K. Nema, S. Nema, and G. Agnihotri, "Computer simulation-based study of photovoltaic cells/modules and their experimental validation," *International Journal of Energy and Environment*, vol. 1, no. 3, pp. 487–500, 2017.
- [4] J. A. Gow and C. D. Manning, "Development of a photovoltaic array model for use in power-electronics simulation studies," *IEE Proceedings – Electric Power Applications*, vol. 146, no. 2, pp. 193–200, 2016.
- [5] S. Madakam, R. Ramaswamy, and S. Tripathi, "Internet of Things (IoT): A literature review," *Journal of Computer and Communications*, vol. 3, no. 5, pp. 164–173, 2015.
- [6] L. Breiman, "Random forests," *Machine Learning Journal*, vol. 45, no. 1, pp. 5–32, 2001.
- [7] K. Ashton, "That 'Internet of Things' thing," *RFID Journal*, vol. 22, no. 7, pp. 97–114, 2009.
- [8] H. Su, Z. Zhang, and L. Wang, "Wireless sensor network-based monitoring system for photovoltaic generation," *International Journal of Distributed Sensor Networks*, vol. 12, no. 6, pp. 1–10, 2016.
- [9] P. Jayaraman, A. Zaslavsky, and D. Georgakopoulos, "Internet of Things platform for smart environments," *IEEE Internet of Things Journal*, vol. 1, no. 4, pp. 349–361, 2014.
- [10] S. S. Rani, P. K. Mallick, and B. K. Mishra, "Smart solar monitoring system using IoT technology," *International Journal of Engineering Research & Technology*, vol. 8, no. 7, pp. 102–107, 2019.
- [11] N. A. Rahim and J. Selvaraj, "Multilevel inverter for grid-connected photovoltaic system," *IEEE Transactions on Industrial Electronics*, vol. 57, no. 4, pp. 1337–1346, 2010.
- [12] V. N. Vapnik, *Statistical Learning Theory*, New York, NY, USA: Wiley, 1998.