International Journal of Scientific Research in Engineering and Management (IJSREM)
Volume: 10 Issue: 10 | Oct - 2026 SJIF Rating: 8.659 ISSN: 2582-3930

AI Smart Industrial Material Transport Robot

Ms. Raskar S.S E&TC Dept. JSPM's BSP
Ms. Zunjare D.U E&TC Dept. JSPM's BSP
Ms. Pawale N.A E&TC Dept. JSPM's BSP
Ms. Mudgal R.Y E&TC Dept. JSPM's BSP
Mr. Takale V.B E&TC Dept. JSPM's BSP

Abstract -
Industrial material handling is an essential activity in manufacturing and storage environments, but conventional transportation methods generally depend on continuous human effort and may require considerable time. This paper presents the design of an AI Smart Industrial Material Transport Robot intended to provide an intelligent and automated approach to internal material movement. The proposed system combines Artificial Intelligence with an ESP32 controller, RFID module, load cell, ultrasonic sensor, camera module, motor driver, DC motors and IoT/Wi-Fi connectivity. RFID is used for material identification, while the load cell provides weight-related information and the ultrasonic sensor supports obstacle detection. Camera information is considered for image processing and AIbased decision making. The ESP32 coordinates the control process and operates the motors through the L298N motor driver. The proposed architecture is aimed at reducing manual handling, improving workplace safety, reducing transportation time and supporting efficient industrial operations. Experimental performance results are not included at this stage because the prototype is under development.

Key Words: Artificial Intelligence, ESP32, RFID, Industrial Automation, Material Handling, Obstacle Detection, IoT, Mobile Robot.

1. INTRODUCTION

Industrial automation is increasingly being adopted to improve productivity, safety and operational efficiency. Material transportation is one of the routine activities in factories, warehouses and other industrial environments. When this activity is performed manually, workers may spend significant time moving materials between different locations. Repetitive material handling can also increase the possibility of human error and workplace risk.

The proposed AI Smart Industrial Material Transport Robot is designed to address these requirements through an integrated sensing, processing and movement system. The robot uses sensor information to understand the material and its surroundings and then assists in selecting a suitable movement route. By combining AI-based processing with embedded control and IoT monitoring, the proposed system provides a foundation for smart industrial material handling.

The robot is intended to reduce manual effort and improve the efficiency of material transportation within industrial areas. It can be designed to detect obstacles, identify the required movement path and transport materials from one location to another with minimum human intervention. The use of wireless communication and IoT technology can also support real-time monitoring of the robot's status and movement.

Such an automated system can be useful in manufacturing units, warehouses, workshops, logistics centers and storage facilities, where materials need to be moved regularly. The integration of AI, sensors, RFID and mobile/IoT-based monitoring makes the proposed robot a flexible solution for modern industrial automation. The prototype is currently under development and focuses on demonstrating the basic concept of intelligent material transportation.

2. PROBLEM STATEMENT

Conventional material transportation methods require human involvement and may be time-consuming. Workers involved in material movement can also be exposed to operational safety risks, particularly in busy industrial environments. Traditional transport arrangements may not provide intelligent obstacle detection or adaptive route selection. Therefore, an automated system is required that can identify materials, sense nearby obstacles and control movement with minimum manual intervention. The proposed robot is intended to provide such an integrated solution.

3. OBJECTIVES

To develop an AI-based robotic system for automated industrial material transportation

To identify and track industrial materials using RFID technologies.

To automate the movement of materials within an industrial environment with minimum human intervention.

To detect obstacles and select a suitable route using sensors and AI-based decision-making.

To reduce manual handling, transportation time, and operational effort in industrial material handling.

4. PROPOSED SYSTEM

The proposed system consists of input sensors, an AI processing stage, an ESP32 controller, an L298N motor driver, DC motors and wheels, and an IoT/Wi-Fi monitoring interface. The sensors collect information related to material identity, weight, obstacles and visual surroundings. The AI processing unit analyses the available information and assists in deciding the required destination and safe route. The ESP32 acts as the embedded control unit and sends appropriate commands to the motor driver. The motor driver then controls the DC motors to move the robot.

5. SYSTEM ARCHITECTURE

The system architecture follows a sensing–processing–control–actuation approach. RFID provides material identification information and the load cell provides weight-related input. The ultrasonic sensor observes obstacles in the robot's path, while the camera supplies visual information for image processing. The AI processing unit analyses these inputs. The ESP32 coordinates the control operation and communicates with the L298N motor driver. The DC motors and wheels provide the physical movement of the robot. IoT/Wi-Fi is included to support monitoring and status updates.




Fig. 1. System architecture

6. AI-BASED DECISION MAKING

The proposed AI layer is intended to support intelligent interpretation of material and environmental information. Machine Learning is identified in the project design for material and obstacle detection, while Python provides the processing environment and OpenCV supports camera/image processing. The purpose of this stage is to assist the robot in understanding the available input and selecting a suitable movement response. The final algorithm and trained model can be refined during prototype development and testing.

7. SENSOR INTEGRATION

Multiple sensing technologies are incorporated so that the robot can use more than one type of information. RFID supports identification of the material being transported. The load cell supplies weight-related information. Ultrasonic sensing is used to identify obstacles in the robot's path, while the camera provides visual information. The combination of these inputs can provide a broader representation of the operating environment than a single sensor alone.

8. CONTROL AND MOTOR OPERATION

The ESP32 serves as the central embedded controller. After receiving the required control information, it provides signals to the L298N motor driver. The motor driver controls the DC motors connected to the robot's wheels. This arrangement separates the control logic from the motor-driving stage and provides a practical interface between the microcontroller and the mechanical drive system.

9. IoT MONITORING

IoT/Wi-Fi connectivity is included to support monitoring and status updates. The connected monitoring approach can provide information about the robot's operating state and can support future expansion toward connected industrial systems. The proposed communication layer therefore complements the sensing and control functions of the robot.




Fig. 2. System connection / circuit diagram.

10. WORKING PRINCIPLE

The robot begins by acquiring information from the connected sensors. RFID is used to identify the material and the load cell provides weight-related information. The ultrasonic sensor checks for obstacles in the surrounding area, while the camera captures visual information. The AI processing stage analyses the available information and assists in selecting a suitable route. The ESP32 executes the control logic and sends movement commands to the L298N driver. The driver operates the DC motors, allowing the robot to move the material toward the required location. IoT/Wi-Fi can provide the corresponding status information for monitoring.

11. FUNCTIONAL ARCHITECTURE

The functional architecture integrates sensing, AI processing, embedded control, motor actuation and monitoring. The input sensors provide information about material identity, weight, obstacles and the visual environment. The AI processing stage interprets the information and assists with material and obstacle analysis. The ESP32 acts as the control unit and provides commands to the motor driver. The motor driver controls the robot motion, while IoT/Wi-Fi supports monitoring.




Fig. 3. Functional architecture of the proposed robot.

12. SYSTEM OPERATION SEQUENCE

- The sensors acquire material and environmental information.
- RFID identifies the material and the load cell provides weight information.
- The ultrasonic sensor and camera provide obstacle and visual information.
- The AI processing stage analyses the available inputs and assists route selection.
- The ESP32 processes the control logic and sends commands to the L298N motor driver.
- The motor driver operates the DC motors and the robot moves the material.
- IoT/Wi-Fi provides monitoring and status updates.

13. HARDWARE COMPONENTS

13.1 ESP32 Controller




Fig.ESP32 Controller

The ESP32 is the embedded controller responsible for robot operation and sensor integration. It receives information from the connected sensing elements and coordinates the control process. The controller communicates with the motor driver to produce the required robot movement.

13.2 RFID Module



Fig. RFID Module

The RFID module is used for material identification. It provides an identification input that can be processed by the controller as part of the material-handling workflow.

13.3 Load Cell



Fig. Load cell

The load cell provides weight-related information. This information can be used to identify or monitor the material load before and during transportation.

13.4 Ultrasonic Sensor



Fig. ultrasonic sensor

The Ultrasonic Sensor Supports obstacle detection by sensing objects in the robot's path. Its input can be considered by the control logic for safer movement

13.5 Camera Module



Fig. Camera Module

The camera provides visual information for image processing. The project identifies OpenCV and Python as suitable technologies for processing camera/image information and supporting AI-based decisions.

13.6 L298N Motor Driver



Fig. L28N Motor Driver

The L298N motor driver acts as the interface between the ESP32 control unit and the DC motors. It receives control signals and drives the motors required for robot movement.

13.7 DC Motors, Wheels and Chassis




Fig. DC Motors, Wheels and Chassis

DC motors and wheels provide physical robot movement. The chassis provides the mechanical structure for mounting the electronics, sensors, motors and materialcarrying arrangement.

14. SOFTWARE AND TECHNOLOGIES

14.1 Arduino IDE

Arduino IDE is used as the programming environment for the ESP32. It supports writing, compiling and uploading the embedded control program.

14.2 Python

Python is identified for AI and image-processing tasks. It can be used for processing information and supporting the development of the AI decision-making layer.

14.3 OpenCV

OpenCV is identified for camera and image-processing functions. It can support extraction and processing of visual information supplied by the camera module.

14.4 Machine Learning

Machine Learning is considered for material and obstacle detection and for supporting intelligent decision making. The final model can be refined during prototype development and testing.

14.5 IoT / Wi-Fi

IoT/Wi-Fi connectivity supports monitoring and status updates. It can provide a communication link between the robot and a monitoring interface.

14.6 Embedded C/C++

Embedded C/C++ can be used to implement the controller logic and hardware interfacing required for ESP32-based operation.

15. DESIGN CONSIDERATIONS

- Appropriate sensor placement is required for reliable sensing.
- The robot requires a stable power supply and suitable motor control.
- The chassis must support the material and electronic components.
- Wireless communication should remain suitable for monitoring.
- Actual load capacity, navigation performance, obstacle response and battery operation require prototype testing.

16. EXPECTED CONTRIBUTION

The proposed work combines material identification, sensing, AI-oriented processing, embedded control, motor actuation and IoT monitoring in a single industrial material transport platform. Its intended contribution is an integrated approach to reducing manual material movement and supporting safer and more efficient internal transportation. Numerical performance results are not claimed because the prototype is under development.

17. APPLICATIONS

- Factories and industrial material handling.
- Warehouses and storage facilities.
- Manufacturing and assembly environments.
- Logistics and internal transport operations.
- Hospitals and controlled material movement.
- E-commerce storage and distribution facilities.
- Automobile and electronics industries.

18. ADVANTAGES

- Reduces manual material-handling effort.
- Can reduce transportation time in repetitive internal movement.
- RFID supports material identification.
- Ultrasonic sensing supports obstacle detection.
- AI processing can assist intelligent route selection.
- IoT/Wi-Fi supports monitoring and status updates.

19. LIMITATIONS

- Sensor reliability can affect the quality of system inputs.
- AI processing performance depends on the implemented mode land available computing resources.
- Camera-based processing may be affected by environmental conditions.
- Wireless communication may affect monitoring when connectivity is poor.
- Actual load capacity, navigation accuracy, obstacle detection performance, response time and battery endurance require practical testing.
- The prototype is still under development, so numerical experimental results are not included.

20. FUTURE SCOPE

- Improved AI models for material and obstacle detection.
- Automatic navigation and more advanced path .
- Voice-control capability for selected operations.

- Live tracking and improved monitoring.
- Higher load capacity and improved mechanical design.
- Better obstacle detection and adaptive movement.
- Multi-robot coordination for larger industrial environments.
- Integration with advanced industrial automation and IoT platforms.

21. PROPOSED IMPLEMENTATION FLOW

The implementation can be organized as a sequence of sensing, identification, analysis, control and actuation. First, the connected sensors acquire information from the operating environment. RFID identifies the material while the load cell provides weight information. Ultrasonic and camera inputs contribute obstacle and visual information. The AI processing stage interprets these inputs. The ESP32 then applies the control logic and sends commands to the L298N motor driver. Finally, the DC motors move the robot and IoT/Wi-Fi provides monitoring information.

22. SYSTEM INTEGRATION

The strength of the proposed concept lies in combining several functions in one platform. Material identification is handled through RFID, weight information through the load cell, obstacle sensing through the ultrasonic sensor and visual input through the camera. These inputs are connected to the embedded control system so that the robot can perform coordinated movement. The IoT/WiFi interface provides a path toward remote status monitoring and future connected-automation features.

23. PRELIMINARY PERFORMANCE CONSIDERATIONS

Because the prototype is under development, this paper does not claim measured accuracy, navigation time, payload capacity or battery performance. These values should be established after implementation through controlled testing. Future experiments can evaluate obstacle-detection response, material-identification reliability, movement time, payload handling and communication stability.

24. SAFETY AND OPERATIONAL CONSIDERATIONS

The robot should be operated in a controlled environment during prototype testing. Sensor placement, mechanical stability, motor control and battery operation should be verified before extended operation. Obstacle detection should be tested under representative conditions, and the movement logic should be evaluated with different material loads.

25. CONCLUSION

The Al Smart Industrial Material Transport Robot presents an integrated approach automated material movement in industrial environments. The proposed architecture combines RFID-based material identification, load-cell weight sensing, ultrasonic obstacle detection, camera-based visual information, Al processing, ESP32 control, L298N motor driving, DC motors and IoT/Wi-Fi monitoring. The combination intended to reduce manual handling, support safer movement and improve the efficiency of repetitive internal transportation. The project is currently at the prototype-development stage; therefore, final experimental measurements are not included. Practical testing will be required to establish load capacity, navigation performance, obstacle response, battery endurance and

26. REFERENCES

[1] K. Ellithy et al., “AGV and Industry 4.0 in Warehouses,” International Journal of Advanced Manufacturing Technology, 2024.
[2] T. Lackner et al., “Autonomous Mobile Robots in Intralogistics,” Procedia CIRP, 2024. [3] W. X. Oh et al., “Autonomous Mobile Robot for Transporting Goods,” 2024.
[4] N. P. Panta et al., “Autonomous Mobile Robot for Material Handling,” 2024.
[5] “Autonomous Industrial Mobile Warehouse,” Applied Sciences, 2024.
[6] Y. Gong and R. B. M. de Koster, “Autonomous Mobile Robot Systems,” Transportation Science, 2024. [7] “Digital Twin-Based Reinforcement Learning for AMR,” International Journal of Computer Integrated Manufacturing, 2024.
[8] N. Demir et al., “Autonomous Mobile Robot Using ROS,” International Journal of 3D Printing Technologies, 2024.
[9] D. Selvaraj et al., “AGV for Material Handling Using RFID,” 2024.
[10] “IoT-Based Robotic Arm for Product Sorting,” Electronics, 2025.

27. AUTHOUR BIOGRAPHIES



Ms. Raskar S.S
Diploma student in Electronics & Telecommunication Engineering. Academic interests include AI, embedded systems, IoT and industrial automation.



Ms. Zunjare D.U
Diploma student in Electronics & Telecommunication Engineering. Academic interests include AI, embedded systems, IoT and industrial automation.



Ms. Pawale N.A
Diploma student in Electronics & Telecommunication Engineering. Academic interests include AI, embedded systems, IoT and industrial automation.



Ms. Mudgal R.Y
Diploma student in Electronics & Telecommunication Engineering. Academic interests include AI, embedded systems, IoT and industrial automation.



Mr.Takale.V.B
in Diploma lecturer in Electronics and Telecommunications Engineering Department at JSPM's Bhivrabai Sawant Polytechnic, Wagholi