

ARM Based Automatic Seed Sowing Machine

Jyoti Sudhakar Chendake

Electronics And
Telecommunication

Engineering,SVRI's College of
Engineering,Pandharpur, India
jyotischendake@coep.sveri.ac.in

Pratiksha Sachin Deshmane

Electronics And
Telecommunication

Engineering,SVRI's College of
Engineering ,Pandharpur, India
pratikshadeshmane@coep.sveri.ac.in

Smruti Santosh Hawale

Electronics And
Telecommunication

Engineering,SVRI's College of
Engineering ,Pandharpur, India
smrutishawale@coep.sveri.ac.in

Dnyaneshawari Subhash Asabe

Electronics And
Telecommunication

Engineering,SVRI's College of
Engineering ,Pandharpur, India
dnyaneshwarisasabe@coep.sveri.ac.in

Ms.S.S.Pawar

Assistant Professor, Department of
Electronics and Telecommunication

Engineering Pandharpur
sspawar@coe.sveri.ac.in

Abstract— *Efficient water management and real-time monitoring are critical challenges in modern agriculture. This project proposes a Smart Farming System that automates irrigation and monitors environmental conditions using embedded systems and sensor technology. The system continuously measures soil moisture, temperature, and humidity using appropriate sensors. A microcontroller processes this data and makes decisions based on predefined threshold values. When the soil moisture level falls below the required limit, the system automatically activates a water pump through a relay module, ensuring optimal irrigation.*

Additionally, the system provides real-time feedback through a display unit or IoT platform, enabling farmers to monitor field conditions remotely. The proposed solution minimizes water wastage, reduces manual effort, and enhances crop productivity, making it suitable for sustainable agriculture.

Keywords— *Smart Farming, Automated Irrigation, Soil Moisture Sensor, Embedded System, IoT, Water Management, Crop Monitoring, Arduino, Agriculture Automation*

Introduction:

Agriculture plays a vital role in the economic development of a country, especially in nations like India where a large portion of the population depends on farming for their livelihood. However, traditional farming practices often rely on manual irrigation and observation, which are time-consuming and inefficient. These methods can lead to improper water management, resulting in over-irrigation or under-irrigation, ultimately affecting crop health and productivity.

With the increasing demand for food and the limited availability of water resources, there is a growing need for smart and efficient agricultural solutions. Advances in embedded systems and sensor technologies have made it

possible to develop automated systems that can monitor environmental conditions and make real-time decisions.

This project focuses on the development of a Smart Farming System for automated irrigation and crop monitoring. The system utilizes sensors to measure soil moisture, temperature, and humidity, which are critical parameters for plant growth. A microcontroller processes the collected data and controls the irrigation system based on predefined threshold values. When the soil moisture level drops below the required level, the system automatically activates the water pump, ensuring timely irrigation.

In addition to automation, the system can provide real-time feedback through a display or IoT platform, enabling farmers to monitor field conditions remotely. This approach not only improves water efficiency but also reduces manual labor and enhances crop yield.

Overall, the proposed system aims to introduce a cost-effective, reliable, and scalable solution for modern agriculture, promoting sustainable farming practices and efficient resource utilization.

Objectives of the Study:

- To design and develop a smart farming system capable of automatically controlling irrigation based on real-time soil moisture conditions.
- To continuously monitor environmental parameters such as soil moisture, temperature, and humidity using sensor-based technology.
- To implement an automated decision-making mechanism that activates or deactivates the water pump based on predefined threshold values.
- To reduce water wastage and improve irrigation efficiency through precise and timely water supply.
- To minimize human intervention in agricultural activities by introducing automation.

- To provide real-time monitoring of field conditions through a display unit or IoT-based system.
- To develop a cost-effective and energy-efficient solution suitable for small and medium-scale farmers.
- To enhance crop productivity and support sustainable agricultural practices through smart technology integration.

Initial and Associated Work:

In recent years, significant research has been carried out in the field of smart agriculture, particularly focusing on automated irrigation systems and environmental monitoring using embedded systems and sensor technologies. These studies have contributed to improving farming efficiency, reducing resource wastage, and enabling precision agriculture.

Early systems for irrigation automation were primarily based on **timer-controlled mechanisms**, where water was supplied at fixed intervals regardless of soil conditions. Although simple, these systems lacked adaptability and often resulted in over-irrigation or under-irrigation, leading to inefficient water usage and reduced crop productivity.

With the advancement of sensor technology, researchers introduced **soil moisture-based irrigation systems**. These systems utilize soil moisture sensors to measure the water content in soil and control irrigation accordingly. When the moisture level drops below a certain threshold, the system activates the water pump. This approach significantly improved water efficiency compared to traditional methods. However, many of these systems were limited to basic control and lacked additional environmental monitoring capabilities.

Further developments incorporated **temperature and humidity sensors** to provide a more comprehensive understanding of environmental conditions affecting crop growth. By analyzing multiple parameters, these systems enabled better decision-making for irrigation and crop management. Some studies also integrated **LCD displays** to provide real-time data feedback to users.

In recent years, the integration of **Internet of Things (IoT)** technology has enhanced smart farming systems by enabling remote monitoring and control. IoT-based systems allow farmers to access real-time data through mobile applications or web platforms. These systems improve convenience and allow timely decision-making even from distant locations. However, many IoT-based solutions depend heavily on continuous internet connectivity and may involve higher implementation costs.

Additionally, some advanced systems have explored the use of automation with motor control and relay **modules** to manage irrigation systems efficiently. These systems ensure precise control of water flow based on sensor data. Despite these improvements, challenges such as system cost, power consumption, scalability, and reliability in real field conditions still exist.

The proposed smart farming system builds upon these existing approaches by integrating soil moisture sensing, environmental monitoring, and automated irrigation into a single, cost-effective solution. It aims to provide a balance between functionality, affordability, and ease of use, making it suitable for small and medium-scale fa

System Architecture:

The proposed Smart Farming System is designed by integrating hardware and software components to enable automated irrigation and real-time monitoring of environmental conditions. The architecture focuses on simplicity, low cost, and efficient operation, making it suitable for practical agricultural applications.

The system mainly consists of sensors, a microcontroller unit, a relay-controlled water pump, and an output interface such as an LCD display or IoT module

1. Sensor Layer (Data Acquisition)

The first stage of the system involves collecting real-time data from the field using sensors:

- **Soil Moisture Sensor:** Measures the water content in the soil and provides analog/digital signals.
- **Temperature and Humidity Sensor (DHT11/DHT22):** Monitors environmental conditions affecting plant growth.

These sensors continuously gather data and send it to the microcontroller for processing.

2. Processing Unit (Microcontroller)

The core of the system is the microcontroller (Arduino UNO / NodeMCU), which performs the following functions:

- Reads sensor data at regular intervals
- Converts analog signals into digital values
- Compares sensor readings with predefined threshold values
- Executes control logic for irrigation

This unit acts as the brain of the system, making decisions based on real-time conditions.

3. Decision and Control Module

The decision-making process is based on threshold logic:

- If soil moisture is **below the set limit**, irrigation is required
- If soil moisture is **above the limit**, irrigation is stopped
- A **relay module** is used to control the water pump based on this decision:

- Relay ON → Water Pump ON
- Relay OFF → Water Pump OFF

This ensures automatic and precise irrigation control.

4. Actuation System

The actuation system includes:

- **Water Pump:** Supplies water to the field
- **Relay Module:** Acts as a switch to control the pump

The system ensures that water is supplied only when necessary, reducing wastage.

5. Output and Monitoring Layer

The system provides output in the following ways:

- **LCD Display:** Shows real-time values of soil moisture, temperature, and humidity
- **IoT Module (Optional):** Sends data to a mobile app or cloud platform for remote monitoring

This allows farmers to track field conditions easily.

6. Power Supply

The entire system is powered using a regulated power supply:

- 5V/12V DC supply for microcontroller and components
- Battery or adapter-based power system

Methodology:

o Sensor Data Acquisition :

Signal processing is an important stage in the Smart Farming System, where raw data collected from sensors is refined and prepared for accurate decision-making. The signals obtained from the soil moisture sensor and temperature-humidity sensor may contain noise, fluctuations, or minor inconsistencies due to environmental conditions, sensor limitations, or electrical interference. Therefore, proper processing of these signals is essential to ensure reliable system performance.

Initially, the raw analog signals from the soil moisture sensor are read by the microcontroller and converted into digital values using an internal Analog-to-Digital Converter (ADC). Similarly, the temperature and humidity values from the DHT11 sensor are received in digital form. These readings are then processed to remove noise and irregular variations.

Basic filtering techniques, such as averaging or smoothing, are applied to stabilize the sensor readings. This helps in reducing sudden spikes or drops in values caused by temporary disturbances. After filtering, the data is normalized or scaled

into a standard range to make it easier for comparison with predefined threshold values.

The processed signals are then periodically sampled and stored for short durations, allowing the system to observe trends rather than relying on a single reading. This improves the accuracy of decision-making and prevents false triggering of the irrigation system.

o Signal Processing:

Signal processing is an important stage in the Smart Farming System, where raw data collected from sensors is refined and prepared for accurate decision-making. The signals obtained from the soil moisture sensor and temperature-humidity sensor may contain noise, fluctuations, or minor inconsistencies due to environmental conditions, sensor limitations, or electrical interference. Therefore, proper processing of these signals is essential to ensure reliable system performance.

Initially, the raw analog signals from the soil moisture sensor are read by the microcontroller and converted into digital values using an internal Analog-to-Digital Converter (ADC). Similarly, the temperature and humidity values from the DHT11 sensor are received in digital form. These readings are then processed to remove noise and irregular variations.

Basic filtering techniques, such as averaging or smoothing, are applied to stabilize the sensor readings. This helps in reducing sudden spikes or drops in values caused by temporary disturbances. After filtering, the data is normalized or scaled into a standard range to make it easier for comparison with predefined threshold values.

The processed signals are then periodically sampled and stored for short durations, allowing the system to observe trends rather than relying on a single reading. This improves the accuracy of decision-making and prevents false triggering of the irrigation system.

By ensuring that only clean, stable, and meaningful data is passed to the decision module, the signal processing stage enhances the overall reliability, efficiency, and performance of the Smart Farming System.

o Decision Module:

The Decision Module is the core component of the Smart Farming System, responsible for analyzing sensor data and determining the appropriate action for irrigation control. It receives processed data from the microcontroller, which includes soil moisture, temperature, and humidity values, and applies predefined logic to make real-time decisions.

The module operates based on **threshold-based decision logic**. A specific soil moisture threshold is set according to the crop requirement. When the measured soil moisture value

falls below this threshold, the system identifies the condition as dry soil and triggers the irrigation process. Conversely, when the soil moisture level reaches or exceeds the threshold, the system recognizes that sufficient water is present and stops irrigation.

To enhance reliability, the decision module ensures continuous monitoring and periodic evaluation of sensor data. This helps avoid unnecessary switching of the water pump due to minor fluctuations in readings. The module can also consider environmental parameters such as temperature and humidity to support better decision-making, especially in varying climatic conditions.

The final decision is executed through the relay module, which controls the ON/OFF state of the water pump. This automated decision-making process reduces human intervention, improves water efficiency, and ensures that crops receive the optimal amount of water.

Overall, the decision module transforms raw sensor data into meaningful actions, enabling the system to function intelligently and efficiently in real-time agricultural environments.

Experimental Setup:

The Smart Farming System is based on the principle of **sensor-based monitoring and automatic control of irrigation** using embedded systems. The system works by continuously measuring environmental parameters such as soil moisture, temperature, and humidity, which are essential factors affecting plant growth.

The **soil moisture sensor** operates on the principle of electrical conductivity. It measures the volumetric water content in the soil by detecting changes in resistance between its probes. When the soil is wet, conductivity increases, resulting in lower resistance, whereas dry soil shows higher resistance. This variation is converted into an electrical signal that is sent to the microcontroller.

The **temperature and humidity sensor (DHT11)** measures atmospheric conditions. Temperature affects evaporation and plant metabolism, while humidity influences transpiration. Monitoring these parameters helps in maintaining optimal conditions for crop growth.

The **microcontroller (Arduino/NodeMCU)** acts as the central processing unit of the system. It reads sensor data, processes it, and compares the values with predefined threshold levels. Based on this comparison, it determines whether irrigation is required or not.

The **relay module** functions as an electronic switch, allowing the microcontroller to control high-power devices like a water pump. When the soil moisture level falls below the threshold, the microcontroller sends a signal to activate the relay, which turns ON the pump. Once the soil reaches the desired moisture level, the relay is deactivated, turning OFF the pump.

The system follows a **closed-loop control mechanism**, where continuous feedback from sensors ensures accurate and automatic decision-making. This approach minimizes water wastage and ensures that crops receive the required amount of water at the right time.

Thus, the integration of sensors, microcontroller, and control mechanisms forms an efficient automated irrigation system, supporting smart and sustainable farming practices.

Result and Discussion:

The developed Smart Farming System was tested under different soil and environmental conditions to evaluate its performance and reliability. The system successfully monitored soil moisture, temperature, and humidity in real time and responded accurately based on predefined threshold values. When the soil moisture level dropped below the set limit, the water pump was automatically activated through the relay module, and it was turned off once the desired moisture level was achieved. This ensured efficient water usage and prevented both over-irrigation and under-irrigation. The system demonstrated stable operation during continuous monitoring and responded quickly to changes in soil conditions. Additionally, the real-time data displayed on the LCD and optional IoT interface allowed easy tracking of field parameters. Overall, the system proved to be effective, cost-efficient, and reliable for small-scale smart farming applications. However, minor variations in sensor readings due to soil type and environmental factors were observed, indicating the need for proper calibration. The results confirm that the proposed system can significantly reduce manual effort, conserve water, and improve crop productivity.

Limitations and Future Scope:

○ Limitations:

Despite the effective performance of the proposed Smart Farming System, certain limitations were observed during its implementation and testing. The accuracy of the system largely depends on the reliability and calibration of the sensors, as variations in soil type, temperature, and environmental conditions can affect sensor readings. The system operates based on predefined threshold values, which may not be suitable for all types of crops and soil conditions without proper adjustment. Additionally, the current design is limited to small-scale applications and may require further enhancement for large agricultural fields. The dependence on a continuous power supply can also affect system performance in remote areas where electricity availability is inconsistent. Moreover, the system does not consider external factors such as rainfall, weather forecasts, or soil nutrients, which play an important role in crop growth. Therefore, while the system is efficient for basic irrigation automation, further improvements are required to make it more robust, adaptive, and suitable for diverse farming conditions.

○ Future Scope:

The proposed Smart Farming System offers significant potential for further enhancement and expansion. In future, the system can be integrated with advanced sensors such as pH sensors, nutrient sensors, and rain sensors to provide a more comprehensive analysis of soil and environmental conditions. The inclusion of weather forecasting data can help in making more intelligent irrigation decisions by considering rainfall predictions and climate changes.

Additionally, the system can be upgraded with IoT-based mobile applications, allowing farmers to monitor and control irrigation remotely in real time. The use of solar panels can make the system energy-efficient and suitable for rural areas with limited power supply. Further improvements can include the implementation of automated fertigation systems, where fertilizers are supplied along with irrigation water in controlled amounts.

The system can also be expanded using wireless sensor networks for large-scale farming applications, enabling coverage of bigger agricultural fields. Integration with data analytics and machine learning techniques can help in predicting crop health, optimizing irrigation schedules, and increasing overall productivity. Thus, the proposed system can evolve into a fully intelligent and autonomous smart farming solution in the future.

References:

1. A. Monteiro, "Precision Agriculture for Crop and Livestock Farming: A Review," *Frontiers in Sustainable Food Systems / PubMed Central*, 2021. Available: PMC article.
2. C. M. Pareek, "A mechatronic seed metering control system for improving seed spacing," *ScienceDirect*, 2023.
3. M. Skoczeń, "Obstacle Detection and Avoidance Using Ultrasonic/LiDAR for Agricultural Mobile Robots," *Sensors*, vol. 21, 2021.
4. H. Guo, "Design and Simulation of a Garlic Seed Metering Mechanism," *Agriculture (MDPI)*, 2021.
5. J. Minfeng, "Optimal Structure Design and Performance Tests of Seed Metering Device," *ScienceDirect*, 2018.
6. J. Liang, "A Precise Simultaneous Sowed Control System for Maize," *Agriculture (MDPI)*, 2024.
7. E. Šarauskis, "Variable Rate Seeding in Precision Agriculture," *Agriculture*, vol. 12, 2022.
8. H. N. Azmi, "Design and Fabrication of an Agricultural Robot for Crop Seeding," *Procedia / ScienceDirect*, 2023.
9. G. Jun, "Design and simulation for seeding performance of high-efficiency corn seed planter," *PMCID/Science*, 2022.
10. G. Raveendran, "A Comprehensive Systematic Review of Precision Planting," *MDPI*,