

Digital Twin-Based Aircraft Engine Nacelle Inspection

Dr. S Ramasubramanian V1, Uma Karthika V2, Dharshini Devi C S3, Naveen Kumar K H4,
Purvika Singh L S5,

1 Associate Professor, Department of Aviation, Vels Institute of Science, Technology &
Advanced Studies, Chennai 600117, Tamil Nadu, India

2 Program Coordinator, MH Cognition Private Limited – 600117, Tamil Nadu, India

3 Student, Department of Aviation, Vels Institute of Science, Technology & Advanced Studies,
Chennai 600117, Tamil Nadu

Abstract - Aircraft engine nacelles serve as essential structural elements that endure severe operational conditions which include vibration and thermal stress and aerodynamic loads which result in crack development throughout time. The identification of these defects at an early stage proves vital for maintaining the safety and dependability of aircraft operations. The digital twin-based crack detection system developed in this study establishes a framework for evaluating crack severity through the application of image processing and artificial intelligence methods. The proposed system uses image preprocessing techniques that begin with grayscale conversion and Gaussian filtering before using Canny edge detection to find crack boundaries. The system employs an asset-based damage assessment method that calculates damage severity through pixel analysis which displays the findings in both graphical form and an interactive dashboard. The nacelle 3D digital twin model was created using Autodesk Fusion 360 to replicate actual structural conditions. The system provides automatic inspection capability while decreasing the need for human work and enabling organizations to implement predictive maintenance procedures. The results allow for successful

crack detection which displays distinct crack progression patterns that demonstrate how computer vision technology and digital twin systems work together to improve aviation structural health monitoring systems.

Key words: Engine nacelle, crack detection, digital twin, image processing, OpenCV, YOLO, structural health monitoring, severity analysis

1.INTRODUCTION

Aircraft structures endure extreme operational requirements which include repeated load cycles and high-frequency vibrations and extreme temperature changes. The combination of these factors leads to structural deterioration which produces defects that include fatigue cracks and corrosion and material degradation. The engine nacelle serves three essential functions in aircraft design by protecting the engine and enhancing aerodynamic efficiency and supporting critical aircraft systems. The nacelles experience high risk from thermal and mechanical stress because they endure both types of stress throughout their operational life. The traditional inspection process requires two methods which involve manual visual inspection and non-

destructive testing (NDT) but those methods take a long time to complete and require specialized skills. The methods are not capable of identifying cracks in their initial stages because they do not provide continuous monitoring. Digital twin systems and computer vision techniques have developed into valuable tools for automated structural health monitoring because of the advancements brought by Industry 4.0 technologies. The project proposes an integrated system which uses image processing and AI-based detection and digital twin modelling to identify cracks and determine their severity and show the current state of the structure. The system will improve inspection operations by minimizing errors made by people and helping aviation companies implement predictive maintenance.

2.PROBLEM DESCRIPTION

Aircraft engine nacelles experience ongoing stress and environmental conditions which result in their components developing cracks over time. The cracks become dangerous because they spread until they cause complete structural failure. The current inspection methods depend on human workers to conduct scheduled inspections which only reveal defects after extensive damage has taken place. The current methods lack the ability to monitor situations in real time and to forecast future events.

An automatic intelligent system is required to identify cracks during their initial development stage and to assess the level of damages while delivering ongoing supervision. The current lack of integrated systems demonstrates the

necessity to create a digital twin-based crack detection system.

3.LITERATURE REVIEW

I. Digital Twin Technology in Aerospace Systems – Michael Grieves (2014)

The study establishes digital twin technology for aerospace through its creation of virtual aircraft system models which operate with actual sensor data from operational aircraft systems. The system dual monitoring and simulation process enables performance assessment through direct measurement of operational performance against established benchmarks. The study demonstrates that digital twin technology enables organizations to identify faults before they occur while decreasing their operational dangers and enhancing their maintenance operations which leads to predictive maintenance research development.

II. Digital Twin for Aircraft Structural Health Monitoring – David J. Ewins (2016)

The research investigates digital twin implementation for aircraft structural monitoring by uniting real-time sensor data that includes vibration and stress and temperature measurements. The study demonstrates that digital twins maintain continuous

structural monitoring which enables them to discover initial damage indicators that include cracks and deformation. The method enables maintenance staff to operate without manual inspections while achieving better maintenance productivity and workplace safety.

III. Machine Learning for Predictive Maintenance in Aerospace – Jay Lee (2018)

The research investigates how machine learning algorithms can process operational data to discover patterns which lead to equipment failure. Predictive models use vibration and temperature data to create forecasts that identify potential failures before they happen. The findings demonstrate how aerospace maintenance practices achieve better reliability and shorter downtime while they use more efficient maintenance scheduling methods which makes the research important for practical aerospace operations.

IV. Deep Learning for Crack Detection in Structures – Yoshua Bengio (2017)

The research proves that Convolutional Neural Networks (CNNs) can successfully identify cracks which exist in structural images. The model learns to identify defects through training on extensive datasets that simulate different operational scenarios. The study shows that deep learning technologies improve detection performance while decreasing inspection duration which marks a significant progress in automated structural assessment systems.

V. Predictive Digital Twins Using Probabilistic Graphical Models – Michael Kapteyn et al. (2020)

The research study shows that digital twin technology achieves better failure prediction results through its combination with Bayesian probabilistic modeling methods. The system combines real-time sensor data with mathematical modeling techniques which

allows for improved uncertainty evaluation and system behavior prediction capabilities. The research demonstrates its ability to help develop sophisticated predictive maintenance systems which operate within demanding engineering environments that include aircraft engines.

4. PROPOSED SYSTEM

The developed system functions as a smart system which detects and tracks cracks in aircraft engine nacelle systems through its monitoring capabilities. The system consists of three main components: image processing module, severity analysis module, and digital twin visualization.

OpenCV techniques are used to process the captured images which show the nacelle. The system identifies cracks through edge detection algorithms while determining their severity based on pixel density measurements. The results are stored and visualized through graphs which display the progression of cracks over time. A dashboard is developed using Gradio to enable user interaction and real-time monitoring. The design team creates a 3D digital twin model of the nacelle through Autodesk Fusion 360 which enables visualization of its structural conditions and simulation of crack growth.

Advantages of the Proposed System

1. Early Crack Detection

The system uses image processing to identify cracks during their initial phase which assists in preventing significant aircraft component structural failures.

2. Reduced Manual Effort

The system performs inspections through automation which decreases the need for human visual evaluations while also minimizing errors caused by user fatigue.

3. Faster Inspection Process

The system can process images at a higher speed than traditional methods which allows for immediate operational decisions.

4. Quantitative Severity Analysis

The system delivers severity measurements in percentage form which enhances maintenance decision accuracy through objective assessment.

5. Crack Progression Monitoring

The graph-based visualization method allows users to monitor crack development during different inspection processes.

6. Real-Time Visualization (Dashboard)

The interactive dashboard system provides users with immediate access to results which enhances their ability to monitor and access information.

7. Cost-Effective Solution

The system decreases the requirement for costly Non-Destructive Testing (NDT) tools and the necessity of conducting manual inspections.

8. Supports Predictive Maintenance

The system tracks crack growth patterns which enable maintenance work to be done before equipment breakdown happens.

9. Integration with Digital Twin Concept

The system delivers a virtual nacelle model which helps users understand and simulate the nacelle's structural performance.

10. Scalable and Extendable

The system allows for extension to additional aircraft parts which includes wings and fuselage while supporting advanced AI system connections.

11. Consistent and Reliable Results

The system uses algorithms for detection which produce consistent results through multiple inspection rounds.

12. Easy Implementation

The system uses commonly available technologies which include Python and OpenCV and Gradio to achieve easy deployment and replication.

5.METHODOLOGY

The procedure begins when researchers obtain images and then process the images through grayscale conversion and Gaussian blur methods to achieve better image quality. The Canny edge detection method detects crack boundaries by detecting sharp intensity gradients which define the crack path.

The analysis of severity requires researchers to measure the proportion of cracked pixels against the overall pixel count which produces an objective assessment of damage. The system stores its results in a dataset which users can explore through graphical representations that display crack development.

The system incorporates YOLO to perform object detection and create visual displays while Gradio enables the development of an interactive dashboard which users can use to monitor system activities.



Figure 1: workflow

6. SYSTEM ARCHITECTURE

The proposed system architecture is designed as a multi-stage pipeline that performs automated crack detection, analysis, and visualization for aircraft engine nacelles. The system operates through interconnected stages which work together to achieve its complete system functionality.

The system starts with image input which requires multiple nacelle images for different inspection stages to be collected and uploaded into the system. The analysis process uses these images as the main data source.

The next stage is image preprocessing, where the input images are enhanced to improve detection accuracy. The process involves two main steps which include converting images into grayscale format for lower processing requirements and using Gaussian blur to eliminate both noise and undesired image changes. The steps ensure that only essential elements are shown which include crack defects.

The Canny edge detection algorithm serves as the crack detection method which the system uses after the preprocessing stage. The method detects crack boundaries by locating areas in the image which show abrupt changes in brightness levels. The detected edges represent potential crack regions on the nacelle surface.

The system begins its process of determining crack severity after it detects cracks in the material. The system measures crack severity by calculating the crack pixel ratio which requires two values: the number of crack pixels which includes edge pixels and the complete pixel count of the image. The resulting percentage provides a quantitative measure of damage severity, which is further classified into categories such as low, moderate, and high damage.




Figure 2: System architecture

The data storage module holds the calculated results, which are stored in structured datasets that usually appear as CSV files. This allows easy retrieval, comparison, and further analysis of inspection data.

The system generates graphs which display various image severity values to show how cracks develop throughout different inspection times and stages. This method enables researchers to study crack development patterns while they evaluate future danger levels.

The system operates through a dashboard visualization module which Gradio and Power BI use as its development tools. The dashboard provides an interactive interface where users can upload images, view

detection outputs, analyze severity levels, and monitor crack progression in real time.

The system combines three components which include image processing and data analysis together with visualization to create a single framework that allows users to monitor structural health of aircraft nacelles with both high efficiency and precise results.



7. WORKING PRINCIPLES

The system operates through its use of image processing together with edge detection techniques. The nacelle surface cracks produce abrupt pixel intensity shifts which become visible after the image undergoes grayscale conversion. Gaussian blur functions as a noise reduction tool that enhances measurement precision. The Canny edge detection algorithm uses high intensity gradient detection to find crack boundaries. The system calculates severity by measuring the crack edge pixel ratio against total pixel count because higher edge density results in more extensive damage. The results undergo classification and visualization processes which enable complete monitoring and maintenance decision support.

WORKING FLOW

- The system receives multiple nacelle images which the user uploads.
- The system processes each image by converting it into grayscale format.
- Gaussian blur helps reduce noise which results in better detection accuracy.
- The Canny edge detection algorithm detects crack boundaries through its implementation.
- The system determines crack severity by assessing the quantity of edge pixels.
- The system classifies damage severity into three categories, which include low, moderate, and high damage levels.
- The results get preserved in a dataset, which researchers will use for their analyses.
- The inspection stages generate a graph which shows how cracks develop over time.
- The dashboard shows processed images together with their corresponding severity values and damage classification results.

8.FLOW CHART



GRAPH 1 CRACK ANALYSIS


9.RESULT AND DISCUSSION

The system evaluation used images that displayed crack progression stages which started from a hairline crack and reached full structural damage. The image processing pipeline results display a pattern of increasing severity values which progresses through each testing stage. The system successfully monitors crack development through its complete growth process.

The graphical analysis of severity (%) versus inspection stage shows a non-linear trend that displays slow severity increase during early phases which becomes steeper as the crack develops. This behavior matches crack propagation patterns which display slow growth during the first stages before reaching fast development through repeated stress exposure. The identified patterns serve as essential elements for both failure forecasting and maintenance scheduling.

GRAPH 1: Crack detection

Image Name	Severity (%)	Damage Level
IMG_01.jpg	2.35	Minor
IMG_02.jpg	7.81	Minor
IMG_03.jpg	15.62	Moderate
IMG_04.jpg	24.17	Moderate
IMG_05.jpg	38.91	Severe
IMG_06.jpg	55.34	Severe



GRAPH 2: Crack inspection

The system shows excellent ability to identify surface cracks through its implementation of edge detection methods. The extracted edges effectively display crack boundaries which enable accurate detection of damaged areas. The pixel density-based severity calculation presents a straightforward quantitative method that enables comparison between various inspection stages.

The system needs assessment of several performance factors which create essential operational requirements. The edge detection system experiences accuracy problems because various conditions exist due to different image quality and lighting conditions and background noise. The system detects edges incorrectly because it identifies non-crack elements such as shadows and surface textures which results in identification errors. The current method identifies only cracks which are visible on the surface while it fails to detect all underground structural damage.

The system operates successfully as an automated inspection and monitoring solution because it combines effective performance with reduced need for human intervention. Users can track real-time crack progression through the system's two

visual tools which include graph-based visualization and dashboard interfaces. The research results show that researchers can implement image processing together with digital twin technology to monitor structural health in aviation applications.

10.CONCLUSION AND FUTURE SCOPE

The project successfully demonstrates an automated crack detection and monitoring system for aircraft engine nacelles using image processing and digital twin concepts. The system detects surface cracks through its pixel-based analysis method which measures crack severity and displays crack development through its graphical and dashboard presentation system. The results demonstrate that crack growth stages correspond to different severity levels which confirms that the method works effectively. The system improves inspection operations by delivering dependable inspection results which help maintenance teams make better decisions while decreasing their need for manual inspections. The proposed solution increases aviation safety and reliability while advancing the development of smart structural health monitoring systems.

The system requires future development through the integration of advanced AI models which trained specifically for crack detection because this technology will enhance system performance through its accurate detection capabilities. The inclusion of real-time sensors and IoT-based data acquisition can enable continuous monitoring instead of periodic inspection. The system will gain real-world applicability through its extension which enables users to perform 3D crack analysis and subsurface defect detection. The

development of a cloud-based platform can allow remote monitoring of multiple aircraft, and the approach can be expanded to other structural components such as wings and fuselage. The system will become a complete predictive maintenance solution which organizations can use through these advancements.

REFERENCE

1. NASA,
“*Digital Twin Technology in Aerospace Applications*,” NASA Technical Reports, 2019.
2. OpenCV Documentation,
“*Image Processing and Edge Detection Techniques*,” Available at: <https://opencv.org>
3. Ultralytics YOLO Documentation,
“*YOLOv8 Object Detection Model*,” Available at: <https://docs.ultralytics.com>
4. International Civil Aviation Organization (ICAO),
“*Aircraft Maintenance and Inspection Standards*,” ICAO publication
5. Szeliski, R.,
“*Computer Vision: Algorithms and Applications*,” Springer, 2011.
6. Gonzalez, R. C., and Woods, R. E.,
“*Digital Image Processing*,” Pearson Education, 2018
7. Y. Liu et al.,
“*Crack Detection Using Deep Learning-Based Image Processing*,” IEEE Access, 2019.
8. Glaessgen, E., and Stargel, D.,
“*The Digital Twin Paradigm for Future NASA Systems*,” AIAA Journal, 2012

11. ACKNOWLEDGEMENT

The authors would like to thank their institution and faculty guides for their continuous support and guidance throughout this project.