International Journal of Scientific Research in Engineering and Management (IJSREM)
Volume: 10 Issue: 11 | Nov - 2026 SJIF Rating: 8.659 ISSN: 2582-3930

Dynamic Analysis of Noise and Vibration in Transportation Systems

Dr. M. Madhuri[1], Pilli Kodandaramayya[2]

[1]Associate Professor & Head of Department, Department of Civil Engineering, Sanketika Vidya Parishad Engineering College, Visakhapatnam, Andhra Pradesh, India

[2]M.Tech Student, Department of Civil Engineering, Sanketika Vidya Parishad Engineering College, Visakhapatnam, Andhra Pradesh, India

Abstract—Transportation systems are essential for urban development and economic growth; however, the operation of road and rail networks generates significant environmental noise and vibration. These impacts adversely affect human comfort, public health, sensitive equipment, and surrounding buildings. This paper presents a comprehensive study on the sources, propagation mechanisms, measurement descriptors, and environmental impacts of noise and vibration in transportation systems, with a primary focus on urban metro rail transit. For road networks, key contributors such as engine noise, tyre–road interaction, heavy vehicles, acceleration, braking, and pavement irregularities are examined. For rail and metro systems, wheel–rail rolling contact, track discontinuities, curve squeal, propulsion units, and structural radiation are evaluated. The study outlines three tiers of impact assessment—Screening Procedure, General Assessment, and Detailed Analysis—alongside standard acoustic descriptors (L_{max}, SEL, L_{eq}, and L_{dn}). Finally, engineering mitigation strategies including acoustic barriers, resilient track systems, floating slab tracks, rail dampers, and regular maintenance are analyzed to promote sustainable urban transit infrastructure.

Keywords: Transportation Noise, Ground-Borne Vibration, Metro Rail, Acoustic Descriptors, Noise Barriers, Floating Slab Track, Environmental Impact, Mitigation Measures.

1. INTRODUCTION

Urbanization has accelerated the expansion of road and rail transit corridors, frequently placing transportation infrastructure in close proximity to densely populated residential and institutional zones. While vital for mobility, transit operations generate environmental noise and vibration that degrade urban livability. In metropolitan rail transit operations, environmental impacts fall into four primary categories:

1. Air-borne (radiated) noise outside the transit corridor.
2. Ground-borne vibration transmitted to neighboring buildings.
3. Ground-borne noise radiated inside adjacent structures.
4. Air-borne noise inside the transit vehicles.

While interior vehicle acoustics are typically addressed by rolling-stock manufacturers, external air-borne noise and ground-borne vibration require rigorous civil and environmental engineering assessments during project planning and design. Although routine transit vibrations rarely cause structural damage to well-maintained buildings designed to standard codes, they can disrupt human sleep, interfere with speech, damage heritage structures, and impair precision instruments in hospitals and laboratories.

2. LITERATURE REVIEW AND RESEARCH GAP

Previous studies have established transportation as a dominant contributor to urban environmental noise. Road traffic research highlights the strong correlation between acoustic emissions and traffic volume, vehicle speed, heavy-vehicle share, and pavement surface roughness. Similarly, railway studies emphasize wheel–rail surface interaction, axle loads, train speed, and soil–structure vibration propagation. Researchers have developed empirical, analytical, and numerical models to predict noise levels and evaluate mitigation tools such as roadside noise barriers and resilient track fasteners.

Research Gap: Most existing studies evaluate air-borne noise and ground-borne vibration independently. An integrated dynamic assessment framework that evaluates both phenomena simultaneously across varying operational conditions, track structures, and receiver sensitivities requires further structured investigation.

3. METHODOLOGY AND ASSESSMENT FRAMEWORK

To systematically evaluate transportation noise and vibration, this study adopts a structured workflow progressing from baseline data collection to mitigation design, as illustrated in Fig. 1.




Fig. 1: Dynamic Noise and Vibration Study Methodology Framework

3.1 Three-Tier Project Assessment Levels

Depending on project scale, development phase, and proximity to sensitive land uses, environmental evaluations follow three progressive tiers summarized in Table 1.

Table 1: Comparison of Environmental Assessment Tiers

Assessment Tier	Project Phase	Scope & Analytical Techniques
Screening Procedure	Initial Planning / Categorical Exclusion	Rapid proximity check using standard lookup distances to identify sensitive receivers (hospitals, schools, homes).
General Assessment	Alternatives Analysis	Quantitative comparison of transit modes and alignments using empirical prediction curves and baseline noise levels.
Detailed Analysis	Preliminary & Final Design	Site-specific field monitoring, geotechnical soil boring, numerical modeling, and FFT frequency response to size barriers and floating slabs.

4. FUNDAMENTALS AND SOURCES OF TRANSIT NOISE

Environmental noise studies rely on the Source–Path–Receiver framework (Fig. 2). Noise is unwanted sound resulting from atmospheric pressure fluctuations, characterized by amplitude (decibels, dB), frequency (Hertz, Hz), and time variation. Human hearing spans 20 Hz to 20,000 Hz, with peak sensitivity in the mid-frequency range. Consequently, A-weighted decibels (dBA) are adopted as the standard unit to approximate human auditory response.



Fig. 2: Source–Path–Receiver Framework and Barrier Diffraction Mechanism

4.1 Major Noise Sources & Frequency Spectrum

In rail and metro corridors, steel wheels running on steel rails generate three distinct acoustic signatures across the frequency spectrum (Fig. 3): low-frequency *Rumble* (<250 Hz, peaking near 80–100 Hz), mid-frequency *Rolling Roar* (250–2,000 Hz), and high-frequency *Curve Squeal* (>2,000 Hz, peaking around 4 kHz on tight curves). Road vehicles additionally generate engine exhaust, aerodynamic, and tyre–pavement interaction noise.




Fig. 3: One-Third Octave Band Noise Spectrum of Transit Train on Curved Elevated Structure

4.2 Typical Source Levels, Speed & Attenuation

As shown in Fig. 4, typical A-weighted pass-by levels at 15.2 m (50 ft) range from 65 dBA for stationary trains in stations to 96 dBA for trains traversing older steel elevated structures at 50 mph. Sound energy attenuates along the path via geometric divergence (6 dB per doubling of distance for point sources; 3 dB for line sources), ground absorption (up to 5 dB over vegetated terrain), and solid noise barrier shielding (5 to 15 dB).




Fig. 4: Comparison of Typical Transit Source Noise Levels at 15.2 m (50 ft)

5. NOISE DESCRIPTORS AND RECEIVER RESPONSE

Electric-powered transit trains exhibit steep acoustic dependence on speed because wheel–rail rolling noise dominates, whereas diesel locomotives are engine-dominated at low speeds (Fig. 5a). Community annoyance increases non-linearly with cumulative exposure, rising from 10% highly annoyed at 60 dBA to 70% at 85 dBA (Fig. 5b). Table 2 defines the four standardized descriptors used to evaluate these impacts.




Fig. 5: (a) Propulsion Speed Dependence and (b) EPA Community High Annoyance Dose–Response Curve

Table 2: Standard Acoustic Descriptors for Transit Noise Assessment

Metric	Full Name	Mathematical Formulation & Land-Use Application
L_{max}	Maximum Sound Level	Peak A-weighted level during a single pass-by (Fast/Slow meter response); used for vehicle compliance testing.
SEL	Sound Exposure Level	Single-event cumulative energy normalized to 1 s: SEL = $10 \log_{10}$[Total Sound Energy].
$L_{eq}(h)$	Hourly Equivalent Level	$L_{eq}(h) = 10 \log_{10}[\Sigma 10^{SEL/10}] - 35.6$. Evaluates daytime speech interference in schools, offices, and parks.
L_{dn}	Day-Night Sound Level	$L_{dn} = 10 \log_{10}$[24-hr Energy] − 49.4 (with +10 dB penalty from 10 PM–7 AM). Evaluates residential sleep disturbance.

6. CASE STUDY: URBAN METRO RAIL SYSTEMS

Urban metro rail corridors operate at high headways across elevated viaducts, at-grade alignments, and underground tunnels in densely built environments. Case evaluations of urban metro networks demonstrate that elevated steel and concrete structures experience amplified wheel–rail rolling noise and structural vibration radiation, particularly along sharp-radius curves.

Field assessments confirm that transitioning from conventional ballasted tracks to ballastless track systems integrated with floating slab track (FST) technology substantially decouples dynamic wheel–rail forces from the supporting viaduct or tunnel invert. Combined with absorptive acoustic parapets on elevated decks, these interventions prevent ground-borne vibration from exceeding threshold limits in adjacent residential and medical buildings.

7. RESULTS, DISCUSSION, AND MITIGATION MATRIX

The dynamic analysis confirms that transportation-induced noise and vibration are governed by vehicle speed, axle load, wheel/rail surface roughness, and propagation path characteristics. Unmitigated transit operations cause sleep disturbance, speech interference, reduced workplace productivity, community annoyance, and malfunction of sensitive hospital or laboratory equipment. Table 3 summarizes the engineering mitigation matrix across the Source–Path–Receiver chain.

Table 3: Engineering Mitigation Strategies and Performance Effectiveness

Control Domain	Mitigation Technique	Mechanism & Expected Reduction
Source Control	Regular Rail Grinding & Wheel Truing	Eliminates surface corrugations and flats; reduces rolling noise by 3–6 dBA and prevents curve squeal.
Track Isolation	Resilient Fasteners & Rail Dampers	Elastomeric pads absorb high-frequency wheel–rail shocks and attenuate rail vibration radiation.
Substructure Isolation	Floating Slab Track (FST)	Concrete track slab mounted on elastomeric bearings or springs; isolates ground-borne vibration by 10–20 dB.
Propagation Path	Absorptive Acoustic Noise Barriers	Blocks direct line-of-sight and forces diffraction; reduces air-borne receiver noise by 5–15 dBA.
Receiver / Buffer	Green Belts & Building Insulation	Dense vegetation provides secondary ground absorption (up to 5 dB); double-glazed facades protect interiors.

8. CONCLUSION AND FUTURE SCOPE

8.1 Conclusion

This study presented a comprehensive evaluation of the dynamic mechanisms, measurement descriptors, environmental impacts, and mitigation strategies for noise and vibration in transportation systems. Effective control requires integrating acoustic and vibration criteria early in corridor planning, applying appropriate screening and detailed analysis tiers, and deploying resilient track designs alongside routine wheel–rail maintenance. Proper infrastructure design and barrier shielding significantly enhance environmental sustainability, structural protection, and community comfort.

8.2 Future Scope

Future research in transportation acoustics and structural dynamics should focus on:

- Developing Artificial Intelligence (AI) and machine-learning models for real-time noise and vibration prediction.
- Deploying IoT-enabled smart vibration monitoring sensors along urban metro viaducts.
- Engineering sustainable, low-noise composite track materials and advanced rail damping systems.

REFERENCES

1. Federal Transit Administration (FTA), *Transit Noise and Vibration Impact Assessment Manual*, U.S. Department of Transportation.
2. Ministry of Railways, *Indian Railways Standards and Guidelines for Noise and Vibration Control in Metro Rail Corridors*, Government of India.
3. S. S. Rao, *Mechanical Vibrations*, Pearson Education.
4. L. L. Beranek and I. L. Vér, *Noise and Vibration Control Engineering: Principles and Applications*, John Wiley & Sons.
5. World Health Organization (WHO), *Guidelines for Community Noise*, Geneva.
6. U.S. Environmental Protection Agency (EPA), *Information on Levels of Environmental Noise Requisite to Protect Public Health and Welfare with an Adequate Margin of Safety*.