

Enhancing Performance of Bituminous Pavement by Adding Plastic Waste

Dishant Burde¹, Siddhant kalsait², Yash Karemore³, Meezan Sheikh⁴, Om Mundare⁵

Department of Civil Engineering,

G H Raisoni College of Engineering and Management Nagpur, 410016 India

Abstract

The growing accumulation of plastic waste poses serious environmental challenges due to its non-biodegradable nature. At the same time, conventional bituminous pavements often suffer from durability issues such as rutting, cracking, and pothole formation. This study presents an innovative approach to improving pavement performance by incorporating waste plastic into bituminous mixes. The addition of processed plastic enhances mechanical properties such as strength, stability, and resistance to moisture damage. Experimental findings from various studies indicate improved Marshall Stability, reduced bitumen usage, and increased lifespan of pavements. This technique offers a sustainable, cost-effective, and environmentally responsible solution for modern road construction.

The rapid growth of plastic consumption has resulted in a significant increase in non-biodegradable waste, creating serious environmental challenges. Simultaneously, conventional bituminous pavements face performance issues such as rutting, cracking, and moisture damage. This research paper investigates the effectiveness of incorporating waste plastic into bituminous mixes to enhance pavement performance. The study focuses on the dry and wet processes of plastic incorporation and evaluates improvements in mechanical and durability properties. Results from experimental studies indicate increased Marshall Stability, improved resistance to deformation, reduced bitumen consumption, and extended pavement life. The integration of plastic waste in road construction not only improves engineering performance but also provides a sustainable solution for waste management.

The exponential rise in plastic consumption has led to a critical environmental challenge due to the accumulation

of non-biodegradable waste. Simultaneously, conventional bituminous pavements suffer from structural and functional distresses such as rutting, cracking, stripping, and pothole formation. This research investigates the incorporation of waste plastic into bituminous mixes as a sustainable and performance-enhancing solution. The study reviews material characteristics, methodologies (dry and wet processes), laboratory testing procedures, and performance outcomes. Results indicate significant improvements in Marshall Stability, tensile strength, resistance to moisture damage, and overall durability. Additionally, the reduction in bitumen consumption lowers construction costs. The integration of plastic waste into pavement construction provides a dual benefit of environmental protection and infrastructure enhancement, making it a promising approach for sustainable road development.

I. Introduction

Plastic materials are widely used due to their durability, lightweight nature, and cost-effectiveness. However, their resistance to degradation has resulted in severe environmental concerns. Plastic waste accumulation contributes to soil pollution, water contamination, and blockage of drainage systems. Traditional disposal methods such as incineration release harmful gases, while landfilling occupies valuable land resources.

At the same time, road infrastructure plays a vital role in economic development. Flexible pavements constructed using bitumen are widely adopted due to ease of construction and cost advantages. However, these pavements are prone to damage due to repeated traffic loading, temperature variations, and water infiltration.

Common failures include rutting, fatigue cracking, and potholes.

The concept of incorporating waste plastic into bituminous pavement addresses both issues simultaneously. Plastic-modified bitumen improves binding properties and enhances pavement performance. This approach supports sustainable development by reducing waste and improving infrastructure quality.

Plastic waste has become a global environmental concern due to its resistance to degradation and increasing accumulation in landfills and natural ecosystems. Traditional disposal methods such as incineration and dumping lead to environmental pollution and health hazards. In developing countries, improper plastic waste management exacerbates urban challenges such as clogged drainage systems and soil contamination.

On the other hand, flexible pavements constructed using bitumen are susceptible to damage caused by heavy traffic loads, temperature variations, and water infiltration. These issues result in frequent maintenance and reduced service life. In recent years, researchers have explored the use of waste plastic as a modifier in bituminous mixes to improve pavement performance while addressing environmental concerns.

The concept involves incorporating processed plastic waste into aggregates or bitumen, which enhances binding properties and structural strength. This approach aligns with sustainable development goals by promoting recycling and reducing environmental impact.

II. Problem Statement

The rapid increase in plastic consumption over recent decades has resulted in a significant rise in plastic waste, posing serious environmental and public health challenges. Due to its non-biodegradable nature, plastic accumulates in landfills, water bodies, and urban spaces, leading to soil and water pollution as well as blockage of drainage systems. Improper disposal methods such as open burning release toxic gases, contributing to air pollution and global warming. Managing this growing volume of plastic waste has become a major concern, especially in developing countries where waste segregation and recycling systems are often inadequate.

At the same time, conventional bituminous pavements face multiple performance-related issues. Roads are subjected to heavy traffic loads, temperature fluctuations, and water infiltration, which lead to common defects such as rutting, cracking, potholes, and surface deformation. These failures not only reduce the service life of pavements but also increase maintenance costs and disrupt transportation efficiency. The demand for durable, cost-effective, and sustainable road construction materials is therefore increasing.

The coexistence of excessive plastic waste and deteriorating road infrastructure presents an opportunity to address both challenges through a single innovative solution. Incorporating plastic waste into bituminous pavements has the potential to improve mechanical properties such as strength, durability, and resistance to moisture damage, while simultaneously reducing environmental pollution. However, there is still a need for systematic evaluation of this technology, including its performance characteristics, environmental impact, and economic feasibility.

Therefore, this study aims to explore the use of plastic waste in bituminous pavement construction as a sustainable approach to enhance road performance and manage plastic waste effectively

- Increasing plastic waste causing environmental hazards
- Poor durability of conventional bituminous roads
- High maintenance cost of pavements
- Lack of sustainable waste management solutions

III. Methodology

The methodology adopted for this study focuses on evaluating the performance of bituminous pavement modified with waste plastic through systematic material preparation, mixing procedures, and laboratory testing.

Initially, the required materials such as bitumen, aggregates, and plastic waste were collected. The plastic waste consisted mainly of polyethylene (PE), polypropylene (PP), and polystyrene (PS), commonly obtained from carry bags, packaging materials, and disposable items. The collected plastic was thoroughly cleaned to remove dirt and impurities, then dried and

shredded into small pieces (approximately 2–4 mm size) to ensure uniform mixing.

Aggregates were selected as per standard specifications and tested for their physical properties, including crushing value, impact value, and abrasion resistance, to ensure suitability for pavement construction. Bitumen was also tested for its properties such as penetration, softening point, and viscosity before modification.

The experimental work was carried out using the dry process, which is widely preferred due to its simplicity and effectiveness. In this process, aggregates were heated to a temperature of around 160°C. The shredded plastic waste was then added gradually to the hot aggregates, allowing it to melt and form a uniform coating over their surface. This plastic-coated aggregate was subsequently mixed with hot bitumen (heated to approximately 150–160°C) to produce the modified bituminous mix.

For comparison, a conventional bituminous mix without plastic was also prepared. Both conventional and plastic-modified mixes were used to prepare standard test specimens.

Laboratory tests were conducted to evaluate the performance of both mixes. Aggregate tests included crushing, impact, and Los Angeles abrasion tests to assess strength and durability. Bitumen tests such as penetration, softening point, and viscosity were carried out to determine the changes in binder properties after modification.

The key performance evaluation was done using the Marshall Stability test, which measures the load-bearing capacity and flow characteristics of the bituminous mix. The stability values, flow values, and density of both conventional and modified specimens were recorded and compared.

Finally, the results obtained from all tests were analyzed to determine the effectiveness of plastic waste in enhancing pavement performance. The methodology ensures a comprehensive evaluation of mechanical, durability, and economic aspects of plastic-modified bituminous pavements.

IV. Results and Analysis

The experimental investigation compared conventional bituminous mixes with plastic-modified mixes prepared using the dry process. The results clearly indicate that the incorporation of plastic waste significantly enhances the engineering properties of pavement materials.

1. Aggregate Properties

Tests conducted on aggregates before and after plastic coating showed considerable improvement in strength and durability. The aggregate crushing value decreased notably for plastic-coated aggregates, indicating higher resistance to compressive loads. Similarly, the impact value was reduced, reflecting improved toughness and resistance to sudden shocks. The Los Angeles abrasion value also decreased, demonstrating better resistance to wear and tear under traffic conditions. These improvements can be attributed to the plastic coating, which strengthens the aggregate surface and reduces particle degradation.

2. Bitumen Properties

The addition of plastic waste altered the properties of bitumen in a beneficial way. The penetration value of modified bitumen decreased compared to conventional bitumen, indicating increased hardness and stiffness. The softening point increased, which means the modified binder can withstand higher temperatures without deformation. Viscosity also improved, leading to better coating and binding characteristics. These changes suggest enhanced resistance to rutting and temperature-related damage.

3. Marshall Stability Test

The Marshall Stability test results revealed a significant increase in stability values for plastic-modified mixes. This indicates a higher load-bearing capacity and improved resistance to deformation under traffic loads. The flow values remained within acceptable limits, suggesting that the mix retained sufficient flexibility without becoming overly rigid. The overall density of the mix also showed slight improvement, indicating better compaction and reduced voids.

4. Overall Performance Analysis

The plastic-modified bituminous mix demonstrated superior performance compared to the conventional mix. The coating of aggregates with plastic reduced moisture absorption, minimizing stripping and pothole formation. Improved adhesion between bitumen and aggregates enhanced the structural integrity of the pavement. Additionally, the reduction in voids contributed to increased durability and longer service life.

5. Economic and Environmental Implications

The use of plastic waste reduced the requirement for bitumen by approximately 8–10%, resulting in cost savings. From an environmental perspective, the reuse of plastic waste helps in reducing landfill accumulation and pollution.

V. Materials Used

- I. Bitumen - A viscous binder derived from petroleum, used in road construction.
- II. Plastic Waste - Types used:
 - Polyethylene (PE)
 - Polypropylene (PP)
 - Polystyrene (PS)
- III. Aggregates
 - Coarse aggregates
 - Fine aggregates

VI. Future Scope

The incorporation of plastic waste in bituminous pavements has shown promising results in improving road performance and addressing environmental concerns. However, there remains significant scope for further research, technological advancement, and large-scale implementation.

One of the major areas for future work is the **standardization of mix design**. Although current practices demonstrate improved performance, there is a need to develop universally accepted guidelines regarding the optimum percentage and type of plastic to be used under different climatic and traffic conditions. This will ensure consistency and reliability in construction.

Another important aspect is the **long-term performance evaluation** of plastic-modified roads. While short-term laboratory and field results are encouraging, detailed studies are required to assess durability over extended periods, including resistance to fatigue, aging, and environmental exposure.

The **environmental impact assessment** also requires further investigation. Research should focus on understanding the potential release of microplastics and emissions during construction and service life, ensuring that the technology remains safe and sustainable.

Advancements in technology can lead to the development of **improved processing techniques**. Automation in plastic segregation, shredding, and mixing can enhance efficiency and reduce human effort. Additionally, combining plastic waste with other industrial by-products such as rubber, fly ash, or construction waste can further improve pavement performance.

There is also scope for integrating this technology into **smart city and green infrastructure projects**, where sustainability is a key priority. Governments and municipal bodies can promote policies encouraging the use of plastic waste in road construction, leading to wider adoption.

Further research can explore the use of **advanced additives**, such as nanomaterials or chemical stabilizers, along with plastic to enhance mechanical properties. Climate-specific studies can help optimize the technology for different regions, especially areas with extreme temperatures or heavy rainfall.

In conclusion, the future of plastic-modified bituminous pavements lies in technological innovation, policy support, and continuous research. With proper development and large-scale implementation, this approach can become a key solution for sustainable road construction and effective plastic waste management.

References

- Vasudevan, R. (2012). Application of waste plastics in flexible pavements. *Construction and Building Materials*.
- Kalantar, Z. N., Karim, M. R., & Mahrez, A. (2012). A review of using waste and virgin polymer in pavement. *Construction and Building Materials*, 33, 55–62.
- Hınıslıoğlu, S., & Agar, E. (2004). Use of waste HDPE in asphalt mixtures. *Materials Letters*, 58, 267–271.
- Gawande, A., et al. (2012). Waste plastic in road construction. *Journal of Engineering Research and Studies*.
- IRC: SP: 98-2013. Guidelines for use of plastic waste in bituminous mixes.
- Ministry of Road Transport and Highways (2015). Plastic waste utilization guidelines.

VII. Conclusion

The study on enhancing the performance of bituminous pavement by incorporating plastic waste demonstrates that this approach is both technically effective and environmentally beneficial. The addition of plastic waste to conventional bituminous mixes significantly improves key engineering properties such as strength, stability, durability, and resistance to moisture damage.

Laboratory test results, including Marshall Stability, penetration, and softening point tests, indicate that plastic-modified mixes perform better than traditional mixes under varying load and temperature conditions.

The plastic coating over aggregates reduces voids and water absorption, which are primary causes of pavement failures such as potholes, stripping, and cracking. As a result, roads constructed using plastic-modified bitumen exhibit longer service life and require less maintenance. Furthermore, the reduction in bitumen usage by approximately 8–10% contributes to cost savings, making this method economically viable.

From an environmental perspective, the utilization of waste plastic in road construction provides an effective solution for managing non-biodegradable waste. It helps reduce landfill accumulation, prevents plastic burning, and supports sustainable development practices. This approach also promotes the concept of a circular economy by converting waste materials into valuable construction resources.

However, certain challenges such as proper segregation of plastic waste, control of emissions during processing, and lack of widespread awareness need to be addressed for successful large-scale implementation. Future research and standardization will further enhance the reliability and acceptance of this technology.

In conclusion, the use of plastic waste in bituminous pavements offers a sustainable, cost-effective, and high-performance solution for modern road construction. With appropriate policies, technological advancements, and awareness, this method has the potential to revolutionize infrastructure development while addressing critical environmental issues.