

Environmental and Occupational Health Risks Associated with Hazardous Construction Waste

Rajiv Singh Gautam¹, Prof. Vishal Tiwari²

¹Research Scholar, Department of Fire Technology & Safety Engineering,

School of Engineering and Technology Vikrant University, Gwalior, (M.P.), India

²M.Tech Guide, Department of Fire Technology & Safety Engineering,

School of Engineering and Technology Vikrant University, Gwalior, (M.P.), India

Abstract

Construction and demolition activities generate substantial quantities of waste, some of which may contain hazardous substances capable of adversely affecting workers, surrounding communities, and the environment. Hazardous construction waste may include asbestos-containing materials, lead-containing paints, contaminated soil, solvents, adhesives, oils, chemical containers, treated materials, and dust containing respirable crystalline silica. During construction, renovation, and demolition, inappropriate identification, handling, storage, transportation, and disposal of these materials can increase exposure risks.

This research paper examines the **environmental and occupational health risks associated with hazardous construction waste** and proposes a systematic framework for identifying, assessing, and controlling these risks. Particular attention is given to exposure pathways, worker health effects, environmental contamination, waste segregation, storage, personal protective equipment, engineering controls, training, and monitoring. OSHA identifies asbestos, lead, silica, and other chemicals or heavy metals as potential hazards that may be hidden within existing structures, particularly during demolition. OSHA Respirable crystalline silica generated from concrete, brick, stone, mortar, and similar materials is associated with serious diseases including silicosis, lung cancer, COPD, and kidney disease. OSHA+1 The paper proposes integrating hazardous-waste management with Hazard Identification and Risk Assessment (HIRA) to improve construction-site safety and environmental performance.

Keywords: Hazardous construction waste, occupational health, environmental risk, HIRA, construction safety, asbestos, lead, silica, waste management, worker exposure.

Introduction

The construction industry is essential to economic and infrastructure development but generates significant quantities of construction and demolition waste. While a considerable proportion of construction waste consists of relatively inert materials such as concrete, bricks and metals, certain waste streams can contain hazardous substances.

Hazardous construction waste presents a dual challenge: **protecting workers from occupational exposure and preventing environmental contamination.**

During renovation and demolition, hazardous substances may be concealed within walls, floors, insulation, coatings, pipes and other building components. OSHA specifically identifies materials such as lead, asbestos, silica, chemicals and heavy metals as hazards that may be hidden within structures. OSHA

Improper handling can result in:

- Airborne dust and hazardous particulate exposure.
- Soil contamination.
- Surface-water and groundwater contamination.
- Chemical exposure.
- Occupational injuries and illnesses.
- Improper disposal and secondary exposure.
- Long-term environmental pollution.

Problem Statement

Construction workers may handle, disturb, transport, or dispose of hazardous materials without knowing their composition. This is particularly important during renovation and demolition, when previously concealed materials become exposed.

For example, cutting, grinding, drilling or crushing concrete, brick and mortar can generate respirable crystalline silica. OSHA identifies respirable silica exposure as a serious occupational health hazard and requires covered construction employers to implement measures to control worker exposure. OSHA+1

Similarly, demolition or renovation of structures containing lead-based materials can expose workers to lead. OSHA's construction lead standard specifically covers demolition, salvage, renovation, repair and removal activities involving lead-containing materials. OSHA

Aim of the Study

The primary aim of this research is:

To assess the environmental and occupational health risks associated with hazardous construction waste and develop an effective framework for managing these risks at construction sites.

Objectives

The study has the following objectives:

1. To identify major types and sources of hazardous construction waste.
2. To identify occupational health hazards associated with handling hazardous construction waste.
3. To examine potential environmental impacts of improper hazardous-waste management.
4. To assess the risks associated with hazardous waste generation, handling, storage and disposal.
5. To develop a practical HIRA framework for hazardous construction waste.

Research Questions

The study may address the following research questions:

1. What hazardous wastes are commonly generated during construction, renovation and demolition?
2. What are the principal occupational health risks associated with these wastes?
3. What environmental impacts can result from improper disposal?
4. Which construction activities create the greatest exposure potential?

5. How effective are existing waste-management and control measures?

Types of Hazardous Construction Waste

Hazardous waste generated on construction sites can vary according to the project, building age, construction materials and activities.

Waste/material	Potential hazard	Possible exposure
Asbestos-containing materials	Fibrous carcinogenic material	Inhalation
Lead-based paint/coatings	Toxic heavy metal	Inhalation/ingestion
Silica-containing dust	Respiratory hazard	Inhalation
Solvents	Toxic/flammable	Inhalation/skin contact
Paint residues	Chemical toxicity	Skin/inhalation
Adhesives	Chemical exposure	Inhalation/skin
Waste oils	Chemical/environmental contamination	Skin/soil/water
Contaminated soil	Chemical/biological exposure	Skin/inhalation
Chemical containers	Residual chemical exposure	Skin/inhalation
Batteries/electrical waste	Heavy metals/electrolytes	Contact/soil contamination
Treated wood	Chemical exposure	Dust/skin contact
Contaminated PPE/filters	Secondary exposure	Inhalation/contact

The exact classification of waste should be determined according to applicable national and local regulations rather than assuming that every construction waste stream is hazardous.

Occupational Health Risks

Silica exposure

Silica is present in materials including concrete, stone, brick and mortar. Activities such as cutting, drilling, grinding, crushing and demolition can generate respirable crystalline silica. OSHA

Health effects associated with respirable crystalline silica include:

- Silicosis.
- Lung cancer.
- Chronic obstructive pulmonary disease.
- Kidney disease.

OSHA+1

Engineering and work-practice controls are therefore important. OSHA identifies measures such as water suppression and appropriate exposure-control procedures for construction activities generating silica dust. OSHA

Asbestos exposure

Asbestos-containing materials may be encountered during renovation and demolition of older structures.

Potential sources include:

- Insulation.
- Roofing materials.
- Cement products.
- Floor tiles.
- Pipe insulation.
- Certain fire-resistant materials.

The major occupational concern is inhalation of airborne asbestos fibers when asbestos-containing materials are disturbed.

Therefore, suspected asbestos-containing materials should be assessed before disturbance, and removal should be conducted by appropriately trained and qualified personnel under applicable regulations. OSHA specifically advises identification and appropriate management of asbestos-containing materials before demolition. OSHA

Lead exposure

Lead may be present in old paints, coatings, pipes and other construction materials.

Potential exposure can occur during:

- Scraping.
- Sanding.
- Grinding.
- Burning.
- Cutting.
- Demolition.
- Removal of lead-containing materials.

Lead exposure can cause significant health effects, making identification and exposure control important during construction and demolition activities.

Chemical exposure

Construction sites may contain:

- Paints.
- Thinners.
- Adhesives.
- Cleaning chemicals.
- Solvents.
- Sealants.

- Resins.
- Fuels.
- Lubricants.

Exposure may occur through inhalation, skin contact, eye contact or accidental ingestion.

Controls should include appropriate labeling, Safety Data Sheets, ventilation, safe storage, worker training and suitable PPE.

Environmental Risks

Improper management of hazardous construction waste can affect multiple environmental pathways.

Air pollution

Dust generated during demolition, cutting and handling can become airborne. Silica-containing dust is of particular occupational concern. OSHA notes that demolition and heavy-equipment activities can generate respirable silica dust. OSHA

Soil contamination

Improper disposal of:

- Waste oils.
- Paint residues.
- Solvents.
- Chemicals.
- Contaminated soil.
- Batteries.

can introduce contaminants into the soil.

Water contamination

Rainwater moving through improperly stored waste can potentially transport contaminants into:

- Stormwater drains.
- Surface water.
- Groundwater.

Therefore, hazardous materials should be stored in controlled areas with appropriate containment.

Waste accumulation

Poor segregation can cause hazardous materials to mix with general construction waste, increasing handling and disposal risks and potentially making recycling or recovery more difficult.

Hazard Identification and Risk Assessment

A HIRA approach can be used to evaluate hazardous construction-waste activities.

A simple risk equation is:

$$\text{Risk} = \text{Likelihood} \times \text{Severity}$$

A five-level scale can be used for both likelihood and severity.

Likelihood

Score Description

- | | |
|---|----------------|
| 1 | Rare |
| 2 | Unlikely |
| 3 | Possible |
| 4 | Likely |
| 5 | Almost certain |

Severity

Score Description

- | | |
|---|------------------------------|
| 1 | Insignificant |
| 2 | Minor injury/impact |
| 3 | Moderate |
| 4 | Major |
| 5 | Fatality/catastrophic impact |

The resulting score can be categorized according to the organization's approved risk matrix.

Risk-Control Measures

Elimination

Where practicable, hazardous materials should be eliminated from the work process.

For example, materials containing hazardous substances can sometimes be replaced with safer alternatives during new construction.

Substitution

Replace hazardous products with less hazardous alternatives where technically feasible.

Engineering controls

Examples include:

- Local exhaust ventilation.
- Wet cutting.
- Dust suppression.
- Enclosures.
- Containment systems.
- Closed waste containers.
- Bunded chemical-storage areas.

OSHA specifically identifies water application and other engineering/work-practice controls as methods for reducing silica exposure during construction activities. OSHA

Administrative controls

These include:

- Hazardous-waste management plans.
- Permit-to-work systems.
- Restricted access.
- Worker training.
- Warning signs.
- Waste inventories.
- Inspection schedules.
- Emergency procedures.
- Exposure monitoring.
- Safe operating procedures.

Personal protective equipment

Depending on the hazard assessment:

- Safety helmet.
- Safety glasses/goggles.
- Chemical-resistant gloves.
- Protective clothing.
- Safety footwear.
- Hearing protection.
- Respiratory protection.

PPE should be treated as one component of a broader control strategy rather than the sole method of controlling hazardous exposure.

Role of Worker Training

Worker awareness is a critical component of hazardous-waste management.

Training should cover:

- Hazard recognition.
- Waste identification.
- Chemical labeling.
- SDS interpretation.
- Waste segregation.
- Safe handling.
- PPE.
- Emergency response.
- Spill response.
- Exposure reporting.
- Incident and near-miss reporting.

For silica-generating work, OSHA requires covered construction employers to provide workers with information and training concerning silica exposure and protective measures. OSHA

Research Methodology

A suitable methodology for an academic research project is a **mixed-method approach**.

Study design

The study can combine:

- Literature review.
- Site observation.
- Worker questionnaire.
- Interviews with safety personnel.
- HIRA.
- Waste-generation assessment.
- Review of existing waste-management procedures.

Data collection

Primary data can be collected through:

Questionnaire

Questions may address:

- Worker awareness.
- Waste segregation practices.
- PPE use.
- Training frequency.
- Hazard reporting.
- Storage practices.
- Emergency preparedness.

Site observation

Observe:

- Waste collection.
- Segregation.
- Storage.
- Labeling.
- Transportation.
- PPE use.
- Dust-generating activities.
- Chemical handling.

Interviews

Interview:

- Site managers. before work begins, when waste streams are mixed, or when hazardous materials are improperly stored, transported or disposed of. Silica exposure from construction and demolition activities is a well-established occupational health concern, while asbestos and lead can
- Safety officers.
- Environmental officers.
- Supervisors.
- Waste-handling workers.

Proposed Data Analysis

Questionnaire responses can be analyzed using:

- Frequency.
- Percentage.
- Mean.
- Standard deviation.
- Risk score.
- Cross-tabulation.

For example:

Safety Awareness Index = Number of positive responses / Total responses × 100

A similar index can be developed for:

- PPE compliance.
- Waste segregation.
- Training effectiveness.
- Hazard reporting.
- Emergency preparedness.

If sufficient data are available, statistical tests such as **chi-square, correlation, or regression analysis** can be used to investigate relationships between worker training, safety practices and hazardous-waste management performance.

Expected Findings

The study is expected to identify several areas requiring attention, potentially including:

1. Inadequate segregation of hazardous and non-hazardous waste.
2. Insufficient identification of hazardous materials before demolition.
3. Inconsistent use of appropriate PPE.
4. Inadequate labeling and storage.
5. Limited worker awareness.
6. Inadequate documentation and waste tracking.
7. Exposure to dust during demolition and material handling.
8. Potential environmental contamination from improper storage or disposal.

These should be treated as **research hypotheses/areas for investigation**, not predetermined findings. Actual results should be based on field data.

Discussion

The evidence demonstrates that hazardous construction waste cannot be managed solely as a conventional solid-waste issue. Its management is closely connected with occupational exposure and environmental protection.

Demolition presents particular challenges because hazardous materials can be hidden within existing structures. OSHA therefore emphasizes planning and hazard identification before demolition begins. OSHA

Silica provides a clear example of the connection between waste generation and occupational health. Concrete, brick, stone and mortar can generate respirable silica when mechanically disturbed, while uncontrolled dust can expose both workers performing the task and other people in the surrounding work area. OSHA+1

The management strategy should therefore move beyond simply removing waste from the construction site. A stronger system incorporates **source identification, segregation, exposure assessment, engineering controls, safe storage, authorized transportation, appropriate disposal, worker training and continuous monitoring**.

Conclusion

Hazardous construction waste represents an important occupational and environmental health challenge. Materials such as asbestos, lead-containing products, silica-containing materials, solvents, paints, oils and contaminated materials can create exposure risks during construction, renovation and demolition.

The risks are particularly significant when hazardous materials are not identified before work begins, when waste streams are mixed, or when hazardous materials are improperly stored, transported or disposed of. Silica exposure from construction and demolition activities is a well-established occupational health concern, while asbestos and lead can also create serious hazards when hazardous building materials are disturbed. OSHA+2

An effective management system should therefore integrate **hazard identification, risk assessment, waste characterization, segregation, engineering controls, worker training, PPE, emergency preparedness and environmental monitoring**.

The proposed HIRA-based framework provides a practical method for identifying hazardous construction-waste risks and prioritizing control measures. Its implementation can contribute to safer working conditions, improved environmental protection and more systematic construction-site waste management.

References

1. Occupational Safety and Health Administration (OSHA). **Demolition – Overview**. U.S. Department of Labor. OSHA
2. Occupational Safety and Health Administration (OSHA). **Silica, Crystalline – Construction**. U.S. Department of Labor. OSHA
3. Occupational Safety and Health Administration (OSHA). **Silica, Crystalline – Overview**. U.S. Department of Labor. OSHA
4. Occupational Safety and Health Administration (OSHA). **Respirable Crystalline Silica, 29 CFR 1926.1153**. OSHA
5. Occupational Safety and Health Administration (OSHA). **Lead, 29 CFR 1926.62**. OSHA
6. Occupational Safety and Health Administration (OSHA). **Control of Silica Dust in Construction: Heavy Equipment and Utility Vehicles Used During Demolition Activities**. OSHA
7. World Health Organization. **Throwing away our health: the impact of solid waste on human health – evidence, knowledge gaps, and health sector responses**. 2025. World Health Organization