International Journal of Scientific Research in Engineering and Management (IJSREM)
Volume: 10 Issue: 11 | Nov - 2026 SJIF Rating: 8.659 ISSN: 2582-3930

Experimental Plasma Confinement in Thermonuclear Fusion Reactors

A Comparative Analysis of Tokamak, Stellarator, and Inertial Confinement Paradigms

Dhruv, M.Sc.
P. G. Department of Physics
Swami Swatantranand Memorial College Dinanagar

ABSTRACT
Achieving controlled thermonuclear fusion represents one of the most significant engineering and physics challenges of the 21 st century. Replicating stellar power mechanisms on Earth requires confining deuterium-tritium plasma at temperatures exceeding 100 million °C while satisfying the Lawson Criterion (Lawson, 1957; Godes & Shablov, 2023). This paper examines the primary experimental paradigms of plasma confinement—specifically Magnetic Confinement Fusion (MCF) via tokamaks and stellarators, alongside Inertial Confinement Fusion (ICF). We analyze magnetohydrodynamic (MHD) instabilities, turbulent transport phenomena, and plasma-wall interaction constraints. Furthermore, we review milestones from flagship facilities including ITER, the National Ignition Facility (NIF), and Wendelstein 7-X (IPB Editors et al., 1999; Abu-Shawareb et al., 2024; Klinger et al., 2019), evaluating pathways toward steady-state net energy generation.

1. INTRODUCTION

The global transition toward carbon-free baseload energy requires revolutionary technological solutions. Controlled nuclear fusion offers an abundant alternative to fossil fuels and fission, producing no long-lived high-level radioactive waste. The predominant terrestrial fusion reaction relies on deuterium-tritium (D-T) fuel:

$$ {}^{2}_{1}H + {}^{3}_{1}H \rightarrow {}^{4}_{2}He\ (3.5\ MeV) + n\ (14.1\ MeV) $$

Overcoming the electrostatic Coulomb repulsion between fuel ions requires kinetic energies corresponding to ion temperatures (T_i) between 10 and 20 keV (≈ 100 to 200 million °C). At these conditions, matter exists entirely in the plasma state.

1.1 The Lawson Criterion & Confinement Requirements

Because physical wall contact quenches thermal energy and causes catastrophic ablation, plasma must be trapped using magnetic or inertial fields. Net energy gain requires satisfying the triple-product form of the **Lawson Criterion** (Lawson, 1957):

$$ n \cdot \tau_E \cdot T \geq 3 \times 10^{21}\ m^{-3} \cdot s \cdot keV $$

where n is plasma density, τ_E is energy confinement time, and T is temperature. Achieving this balance requires suppressing micro-turbulent transport and macroscopic fluid instabilities (Godes & Shablov, 2023).

2 MAGNETIC CONFINEMENT ARCHITECTURE

Magnetic Confinement Fusion (MCF) utilizes Lorentz forces ($\boldsymbol{F} = q(\boldsymbol{E} + \boldsymbol{v} \times \boldsymbol{B})$) to pin charged particles to field lines. A simple toroidal magnetic field creates gradient and curvature drifts ($\boldsymbol{v}_{\nabla B+R}$) that cause charge separation and rapid radial expansion. Restoring equilibrium requires twisting field lines helically around the torus.

2.1 Tokamak Physics and Stability Metrics

Tokamaks generate a helical field by combining an external toroidal field (B_ϕ) with an internal poloidal field (B_θ) induced by driving a large plasma current (I_p) via central transformer action (IPB Editors et al., 1999). The safety factor (q) parameterizes this pitch:

$$ q(r) \approx (r \cdot B_\phi) / (R_0 \cdot B_\theta(r)) $$

Rational values ($q = m/n$) can trigger tearing modes and magnetic islands. Incorporating positive or negative magnetic shear ($s = (r/q)(dq/dr)$) mitigates turbulence and promotes Internal Transport Barriers (ITBs).

2.2 Optimized Stellarators

Stellarators bypass internal current requirements by shaping complex 3D non-planar modular coils to provide magnetic twist externally (Klinger et al., 2019). This eliminates current-driven plasma disruptions and enables continuous steady-state operation.

3. INSTABILITIES & DIAGNOSTIC SYSTEMS

Confinement performance is governed by macroscopic MHD modes and sub-millimeter micro-turbulence:

- **Sawtooth Instabilities (m=1, n=1):** Periodic core temperature crashes occurring when core safety factor $q(0) < 1$.
- **Edge Localized Modes (ELMs):** Violent heat bursts at the edge pedestal during H-mode, requiring control via Resonant Magnetic Perturbations.
- **Thomson Scattering Diagnostics:** Incoherent Nd:YAG laser scattering measures localized n_e and broadens spectrally to yield T_e (where $\Delta\lambda^2 \propto T_e$).

4. COMPARATIVE FACILITY ANALYSIS

FACILITY	CONFINEMENT TYPE	PRIMARY TARGET	OPERATIONAL HORIZON
ITER (France)	Tokamak (Magnetic)	Q ≥ 1 0 Burning Plasma (500 MW)	Long Pulse (400–600 s)
NIF (USA)	Laser Inertial (ICF)	Target Fusion Ignition (Q > 1)	Pulsed Shots (Nanoseconds)
Wendelstein 7-X (Germany)	Optimized Stellarator	Disruption-Free Confinement Validation	Steady-State (> 30 Minutes)

5. CONCLUSION & OUTLOOK

Laboratory fusion has achieved landmark physics milestones, including laser ignition at NIF (Abu-Shawareb et al., 2024; Danson & Gizzi, 2023) and steady-state optimization at W7-X (Klinger et al., 2019). Realizing commercial fusion power requires advancing tungsten wall survival under 14.1 MeV neutron bombardment, establishing tritium breeding self-sufficiency, and scaling high-temperature superconducting (HTS) magnets.

REFERENCES

1 Abu-Shawareb, H., Acree, R., Adams, P., et al. (2024). Achievement oftarget gain larger than unity in an inertial confinement fusion experiment. *Physical Review Letters*, 132(6), 065102.

2 Danson, C. N., & Gizzi, L. A. (2023). Inertial confinement fusion ignition achieved at the National Ignition Facility – an editorial. *High Power Laser Science and Engineering*, 11 , e38.

3 Godes, A. I., & Shablov, V. L. (2023). Lawson criterion for different scenarios ofusing D-3He fuel in fusion reactors. *Nuclear Energy and Technology*, 9(3), 207–214.

4 IPB Editors, ITER Physics Expert Groups, & ITER Joint Central Team. (1999). Chapter 1 : Overview and summary ofthe ITER Physics Basis. *Nuclear Fusion*, 39(12), 2137–2174.

5 Klinger, T., Alonso, A., Bohenkov, S., et al. (2019). Performance and properties ofthe first plasmas ofWendelstein 7-X. *Plasma Physics and Controlled Fusion*, 59(1), 014018.

6 Lawson, J. D. (1957). Some criteria for a power producing thermonuclear reactor. *Proceedings ofthe Physical Society. Section B*, 70(1), 6–10.