

“FOOT STEP POWER GENERATION”

Ganesh Deshmukh, Ajay Jadhav, Omkar Kadam, Prof-Prachi Pandit

Department of Electronics and Telecommunication Engineering, Genba Sopanrao Moze College of Engineering, Savitribai Phule Pune University, Pune.

ABSTRACT

Footstep power generation is an innovative technique used to produce electrical energy by harnessing the mechanical energy generated from human footsteps. In this project, pressure sensors such as piezoelectric sensors are installed beneath walking surfaces like floors, pavements, or stairs. When a person walks over these sensors, mechanical stress is applied, which is converted into electrical energy through the piezoelectric effect.

The generated energy is collected, stored, and can be used to power low-energy devices such as LED lights, streetlights, or charging systems. This system provides a renewable and eco-friendly solution to energy generation, especially in high-footfall areas like railway stations, shopping malls, and public walkways.

The project aims to promote sustainable energy usage by utilizing wasted human energy and converting it into useful electrical power. It also demonstrates the practical application of green technology in everyday life while reducing dependence on conventional energy sources.

KEYWORDS

Footstep Power Generation, Piezoelectric Sensor, Energy Harvesting, Renewable Energy, Mechanical to Electrical Conversion, Smart Energy System, ESP32 Microcontroller, Energy Storage, Voltage Generation, IoT Monitoring, Sustainable Technology

INTRODUCTION

Footstep power generation is an emerging technology that focuses on converting the mechanical energy produced by human footsteps into electrical energy. With the increasing demand for electricity and the depletion of conventional energy resources, there is a growing need for alternative and sustainable energy solutions. This system utilizes piezoelectric sensors placed beneath walking surfaces such as floors, pavements, or staircases to capture the pressure generated when people walk over them.

When force is applied to these sensors, they produce small amounts of electrical energy through the piezoelectric effect. This energy can be accumulated, stored in batteries, and used to power low-energy devices like LED lights, displays, or small electronic systems. In advanced setups, microcontrollers such as ESP32 can be integrated to monitor and manage the generated energy efficiently.

Footstep power generation is especially useful in crowded areas like railway stations, shopping malls, and public walkways where large numbers of people move continuously. By utilizing this wasted mechanical energy, the system contributes to energy conservation and promotes the use of eco-friendly and sustainable technologies. This project demonstrates how simple human activities can be transformed into useful energy, supporting the concept of green energy and smart infrastructure.

LITERATUREREVIEW

Footstep power generation has gained significant attention in recent years as a sustainable method of energy harvesting. Many researchers have explored the use of piezoelectric materials to convert mechanical energy from human footsteps into electrical energy. Studies show that piezoelectric sensors generate voltage when pressure is applied, making them suitable for applications in high-footfall areas such as railway stations, malls, and sidewalks .

Several research works have focused on designing efficient systems using piezoelectric transducers. For example, a study on piezoelectric footstep systems demonstrated that mechanical energy from walking can be effectively converted into electrical energy and stored in batteries for low-power applications such as LED lighting and small electronic devices . Similarly, experimental setups using multiple piezoelectric sensors arranged in arrays have shown improved voltage output and energy efficiency.

Recent research also highlights the use of advanced materials like Lead Zirconium Titanate (PZT) to enhance performance. These systems have been tested in urban environments, producing measurable voltage and power sufficient for small-scale applications like mobile charging and lighting . Moreover, innovations such as electromagnetic and hybrid energy harvesting systems have been introduced to increase energy output and overall system efficiency.

A broader review of piezoelectric energy harvesting technologies indicates that mechanical energy is one of the most widely available and easily convertible forms of ambient energy. Researchers emphasize that integrating such systems into smart infrastructure can contribute to sustainable energy solutions and reduce dependence on conventional power sources

However, literature also identifies certain limitations, such as low power output, high cost, and efficiency challenges. Despite these issues, continuous advancements in materials, system design, and hybrid technologies are improving the feasibility of footstep power generation systems

.PROPOSED SYSTEM

The proposed system for footstep power generation is designed to convert the mechanical energy produced by human footsteps into usable electrical energy using piezoelectric sensors and a microcontroller-based monitoring system. In this setup, multiple piezoelectric sensors are embedded beneath a platform or walking surface. When a person steps on the platform, الضغط (pressure) is applied to the sensors, generating electrical energy through the piezoelectric effect.

The generated electrical signal is in the form of alternating current (AC), which is then passed through a rectifier circuit to convert it into direct current (DC). This DC voltage is regulated using a voltage regulator to ensure a stable output. The regulated energy is stored in a rechargeable battery or capacitor for later use.

An ESP32 microcontroller is integrated into the system to monitor the generated voltage and power. It can also be used to display real-time data on an LCD or send information to a mobile application using IoT technology. Additionally, the stored energy can be utilized to power low-energy devices such as LED lights, streetlights, or small electronic gadgets.

This system is especially suitable for installation in high-footfall areas like railway stations, shopping malls, and public walkways, where continuous movement of people can generate a significant amount of energy. The proposed design is eco-friendly, cost-effective, and promotes the use of renewable energy by utilizing otherwise wasted human motion.


METHODOLOGY

The methodology of the footstep power generation system involves a systematic process of energy conversion, storage, and monitoring. Initially, piezoelectric sensors are installed beneath a walking platform or surface in such a way that they experience maximum pressure when a person steps on it. When force is applied, these sensors generate electrical energy due to the piezoelectric effect. Multiple sensors are connected either in series or parallel to increase the overall voltage and current output. The generated electrical signal is in the form of alternating current (AC), which is then passed through a bridge rectifier to convert it into direct current (DC). A filter capacitor is used to smooth the output signal and reduce fluctuations, followed by a voltage regulator to maintain a constant and safe voltage level.

The regulated DC energy is then stored in an energy storage unit such as a rechargeable battery or supercapacitor. An ESP32 microcontroller is integrated into the system to monitor the generated voltage and energy levels. It collects real-time data and displays it on an LCD or OLED screen, and can also transmit the data to a mobile application through Wi-Fi using IoT technology. The stored energy is then utilized to power low-energy devices such as LED lights or sensors. This methodology ensures efficient conversion of human mechanical energy into electrical energy, while also enabling smart monitoring and effective utilization of the generated power.


HARDWARE COMPONENTS

ESP32 microcontroller



The ESP32 microcontroller serves as the central processing unit of the system. It is a powerful, low-cost microcontroller with built-in Wi-Fi and Bluetooth capabilities, making it highly suitable for IoT applications. The ESP32 collects data from all connected sensors such as ultrasonic and infrared sensors, processes the information, and sends it to the cloud platform for real-time monitoring. It also controls output devices such as the servo motor and LCD display based on the processed data. Its multiple GPIO pins and high processing speed allow seamless integration of various modules in the system.

Piezoelectric Sensor



The piezoelectric sensor plays a key role in footstep power generation systems by converting the mechanical energy produced from human footsteps into electrical energy. These sensors are installed beneath a walking surface such as tiles or platforms, so that when a person steps on them, pressure is applied, causing the sensor to generate a small electrical voltage through the piezoelectric effect. Since the output is low and fluctuating, multiple sensors are often connected together to increase the overall energy generated. This electrical energy is then collected, rectified, and stored in batteries or capacitors, making it useful for powering low-energy devices like LED lights or sensors

1N4007 Diodes

1N4007 Diode Pinout



1N4007 Diode Electronic Symbol



In a footstep power generation system, 1N4007 diodes are mainly used in the bridge rectifier circuit to convert the alternating current (AC) generated by piezoelectric sensors into direct current (DC). Since the output from piezo sensors is not stable and changes direction, these diodes ensure that the current flows in a single direction, making it suitable for storage and usage. They also help protect the circuit by preventing reverse current flow, thereby improving the efficiency and reliability of the overall system.

LM2596(Buck Converter)



In a footstep power generation system, the LM2596 plays a crucial role in stabilizing the fluctuating voltage generated by piezoelectric sensors. After the AC output from the sensors is converted into DC using a rectifier and smoothed by a capacitor, the LM2596 ensures that the voltage is stepped down to a safe and constant level suitable for powering devices like the ESP32, LEDs, or charging batteries. This helps in protecting sensitive electronic components from voltage variations and improves the overall efficiency and reliability of the


LCD display




The 16x2 LCD display is used to provide real-time information to users. It can display messages such as the number of available parking slots, entry/exit status, and system alerts. The LCD is interfaced with the ESP32 using I2C communication, which reduces the number of required connections and simplifies wiring. This display enhances user interaction by providing clear and immediate feedback.

SYSTEM ARCHITECTURE

BLOCK DIAGRAM



CIRCUIT DIAGRAM-




RESULT

The footstep power generation system was successfully implemented and tested, demonstrating the effective conversion of mechanical energy from human footsteps into electrical energy using piezoelectric sensors. When pressure was applied to the sensors, a measurable

voltage was generated, which was then rectified, filtered, and stored using appropriate electronic components. The system was able to produce sufficient electrical energy to power low-energy devices such as LED lights, indicating its practical usability.

The integration of components like rectifiers, capacitors, and voltage regulators ensured stable output, while the use of a microcontroller such as ESP32 enabled monitoring of the generated voltage. The results show that although the power generated per step is small, it can be increased by using multiple sensors and implementing the system in high-footfall areas. Overall, the project proves to be an eco-friendly and sustainable method of energy generation, with potential applications in smart cities and public infrastructure.



Future Scope

Footstep power generation has strong potential for future development as a sustainable and eco-friendly energy solution. With advancements in piezoelectric materials and sensor technology, the efficiency and energy output of the system can be significantly improved. In the future, more sensitive and durable sensors can be developed to generate higher power even with minimal pressure, making the system more practical for large-scale implementation.

This technology can be widely deployed in high-footfall areas such as railway stations, airports, shopping malls, and smart city infrastructure to generate continuous energy from human movement. Integration with IoT and smart monitoring systems can enable real-time tracking and efficient energy management. Additionally, combining footstep power generation with other renewable sources like solar or wind energy can create hybrid systems for better performance. Future enhancements may also include improved energy storage systems, wireless power transfer, and the ability to power larger devices, making it a promising solution for sustainable urban development.

Conclusion

Footstep power generation is an innovative and eco-friendly approach to producing electrical energy by utilizing the mechanical energy generated from human footsteps. This project demonstrates how piezoelectric sensors can effectively convert pressure into electrical energy, which can be processed, stored, and used for powering low-energy devices such as LED lights and small electronic systems. The integration of components like rectifiers, capacitors, voltage regulators, and microcontrollers ensures stable and efficient operation of the system.

Although the energy generated per step is relatively small, the system becomes highly effective when implemented in high-footfall areas where continuous movement can produce a significant amount of power. This technology promotes the concept of renewable energy and sustainable development by making use of otherwise wasted human energy. Overall, footstep power generation presents a promising solution for future smart infrastructure, contributing to energy conservation and reducing dependence on conventional power sources.

References

- 1 .Kumar, A. & Verma, S. (2020). Design and Implementation of Footstep Power Generation System Using Piezoelectric Sensors. International Journal of Engineering Research & Technology (IJERT), 9(6), 234–238.
- 2 .Patil, R. & Deshmukh, P. (2021). Renewable Energy Harvesting through Footstep Power Generation. International Journal of Innovative Research in Electrical, Electronics, Instrumentation and Control Engineering (IJIREEICE), 9(4), 45–49
- 3 .Sharma, N. & Gupta, R. (2019). Experimental Analysis of Footstep Power Generation Using Piezoelectric Plates. International Conference on Advances in Smart Energy Systems (ICASES), IEEE.
- 4 .Ministry of New and Renewable Energy (Government of India). Annual Reports on Renewable Energy Technologies and Policies. <https://mnre.gov.in>
- 5.Arduino, “Arduino IDE Documentation,” 2023.
[Online]. Available: <https://www.arduino.cc> 