

IOT BASED MONITORING OF QUALITY IN WATER

Nehal K Das¹, Nijuval B², Jishon Jacob³, Khadeeja Shabeer ⁴, Anjana Ashokan⁵,

¹Bachelor of Technology in CSE, NCERC

²Bachelor of Technology in CSE, NCERC

³Bachelor of Technology in CSE, NCERC

⁴Bachelor of Technology in CSE, NCERC

⁵Assistant Professor, Department of CSE, NCERC

Abstract - This paper presents an Internet of Things (IoT)-based system for monitoring water quality in real time. Traditional water testing methods are slow, costly, and do not provide continuous monitoring. The proposed system uses sensors to measure parameters such as pH, turbidity, temperature, and water level. An ESP32 microcontroller collects and processes the data and transmits it to the cloud using Wi-Fi. The system allows users to monitor water quality remotely through a web interface. It provides a low-cost, reliable, and efficient solution, reducing manual effort and enabling instant detection of unsafe water conditions.

Key Words: IoT, Water Quality, ESP32, pH Sensor, Turbidity, Real-time Monitoring.

1.INTRODUCTION

Water is one of the most essential resources for human survival, industrial activities, and environmental sustainability, making the monitoring of water quality a critical requirement. Poor water quality can lead to serious health issues, environmental degradation, and economic losses. Traditional methods of water quality assessment involve manual sampling and laboratory analysis, which are time-consuming, labor-intensive, and incapable of providing real-time information. These limitations make it difficult to detect sudden changes in water conditions and respond promptly to potential contamination. With the rapid advancement of technology, the Internet of Things (IoT) has emerged as an effective solution for real-time monitoring and automation in various domains. In this context, IoT enables continuous observation of water quality parameters using interconnected sensors and smart devices. The proposed system utilizes sensors to measure important parameters such as pH, turbidity, temperature, and water level, which are crucial indicators of water quality. An ESP32 microcontroller is used to collect and process the sensor data, which is then transmitted to a cloud platform through Wi-Fi communication. The data can be accessed remotely via a web-based interface, allowing users to monitor water conditions anytime and from anywhere. This approach not only improves efficiency but also reduces manual effort and operational

costs. The system is designed to be low-cost, reliable, and easy to implement, making it suitable for a wide range of applications including domestic, industrial, agricultural, and environmental monitoring. By providing continuous and real-time insights, the proposed IoT-based solution enhances decision-making and contributes to the effective management of water resources.

2. Body of Paper

2.1 System Overview

The proposed system is an Internet of Things (IoT)-based solution designed for continuous and real-time monitoring of water quality parameters. It integrates multiple sensors with a microcontroller and cloud platform to enable automated data collection, processing, and remote visualization. The system architecture ensures efficient data acquisition and transmission, making it suitable for both domestic and industrial applications.

2.2 Hardware Components

The system is built using several hardware components that work together to measure and monitor water quality parameters effectively.

The ESP32 microcontroller serves as the central processing unit of the system. It is responsible for interfacing with sensors, processing the acquired data, and transmitting it to the cloud using built-in Wi-Fi capabilities. Its low power consumption and high processing efficiency make it ideal for IoT applications.

The ultrasonic sensor (HC-SR04) is used to measure the water level. It operates by transmitting ultrasonic waves and calculating the distance based on the time delay of the reflected signal. This enables accurate detection of water levels in tanks and reservoirs.

The turbidity sensor measures the clarity of water by detecting the amount of light scattered due to suspended particles. Higher turbidity values indicate increased contamination levels, which may affect water usability.

The pH sensor is used to determine the acidity or alkalinity of water. The pH scale ranges from 0 to 14,

where neutral water has a value of 7. Monitoring pH is critical for assessing water suitability for drinking and other purposes.

The DS18B20 temperature sensor measures the water temperature with high accuracy. Temperature is an important parameter that influences chemical reactions and biological activities in water systems.

2.3 Data Acquisition and Transmission

The sensors continuously collect data related to water quality parameters. The ESP32 reads these values at regular intervals and performs basic processing before transmitting the data to a cloud server via Wi-Fi.

The use of wireless communication eliminates the need for complex wiring and allows flexible deployment. The data transmission process is reliable and ensures minimal delay, enabling real-time monitoring.

2.4 Cloud Integration and User Interface

The collected data is sent to a cloud platform where it is stored and processed. A web-based user interface is used to display the data in real time. Users can access this interface through smartphones, tablets, or computers.

The interface provides a clear visualization of parameters such as water level, pH, turbidity, and temperature. This enables users to monitor water quality remotely and take necessary actions when required.

2.5 Alert Mechanism

The system includes an alert mechanism to notify users when any parameter exceeds predefined safe limits. For instance, abnormal pH levels, high turbidity, or unsafe temperature conditions trigger alerts.

These alerts help in early detection of contamination and enable timely corrective measures, thereby improving safety and reliability.

2.6 Performance and Advantages

The proposed system demonstrates efficient performance in real-time monitoring of water quality parameters. It reduces dependency on manual testing methods and provides faster and more accurate results.

Compared to conventional systems, it offers several advantages such as low cost, ease of installation, reduced maintenance, and remote accessibility. The use of IoT technology enhances scalability and adaptability for various applications.

2.7 Applications

The proposed IoT-based water quality monitoring system can be effectively used in domestic environments to ensure safe drinking water. It allows households to continuously monitor parameters such as pH, turbidity, and temperature, helping users detect contamination at an early stage. This reduces health risks and eliminates the need for frequent manual testing.

In industrial applications, the system plays a crucial role in monitoring water used in manufacturing processes. Industries require strict control over water quality to maintain product standards and comply with environmental regulations. The system enables real-time monitoring and immediate detection of abnormal conditions, thereby improving operational efficiency and reducing potential losses.

The system is also highly useful in agricultural applications, where water quality directly affects crop growth and soil health. By monitoring parameters such as pH and temperature, farmers can ensure that the water used for irrigation is suitable. This leads to better crop yield and efficient water resource management.

In environmental monitoring, the system can be deployed in natural water bodies such as rivers, lakes, and reservoirs. It helps in tracking pollution levels and detecting changes in water conditions over time. This is useful for environmental agencies and researchers in maintaining ecological balance and ensuring sustainable water management.

Table -1: Sample Table format

Parameter	Measured value	Safe range	Status
PH Level	3.23	6.5 - 8.5	DANGER
Turbidity (clarity)	96 NTU	<100 NTU	CLEAR
Temperature	31.0 C	10 – 30 C	WARM
Water Level	2 cm	>=10 cm	EMPTY





Fig -1: Figure

Charts



3. CONCLUSIONS

The proposed Internet of Things (IoT)-based water quality monitoring system provides an efficient and reliable solution for continuous monitoring of essential water parameters such as pH, turbidity, temperature, and water level. Unlike traditional methods that rely on manual sampling and laboratory analysis, the system enables real-time data collection and remote monitoring, significantly reducing time, cost, and human effort.

The integration of multiple sensors with the ESP32 microcontroller ensures accurate data acquisition and efficient processing. The use of Wi-Fi connectivity allows seamless transmission of data to a cloud platform, where it can be accessed and visualized through a user-friendly web interface. This enhances the accessibility of

information and enables users to monitor water conditions from any location.

Directions,' ACM Transactions on Sensor Networks, 13(1), pp. 1–41.

The implementation of an alert mechanism further improves the effectiveness of the system by providing timely notifications when water quality parameters exceed safe limits. This helps in early detection of contamination and supports quick decision-making to prevent potential health and environmental risks.

Overall, the system demonstrates the practical application of IoT in environmental monitoring and highlights its potential in improving water quality management. Its low cost, scalability, and ease of implementation make it suitable for a wide range of applications, including domestic, industrial, agricultural, and environmental monitoring systems. The proposed solution contributes toward ensuring safe and sustainable water resources for future use.

ACKNOWLEDGEMENT

We would like to express our sincere gratitude to our mentor, Ms. Anjana Ashokan, for her invaluable guidance, encouragement, and continuous support throughout the development of this project. Her expertise and insightful feedback greatly contributed to enhancing our understanding and improving the quality of this work. We also extend our sincere thanks to Nehru College of Engineering and Research Centre, Thiruvilwamala, for providing the necessary resources and a supportive learning environment that enabled us to successfully complete this project.

REFERENCES

1. Rasin, Z. and Abdullah, M.R. (2009) 'Water Quality Monitoring System Using Zigbee Based Wireless Sensor Network,' International Journal of Engineering & Technology, 9(10), pp. 14–18.
2. Lambrou, T.P., Anastasiou, C.C., Panayiotou, C.G. and Polycarpou, M.M. (2014) 'A Low-Cost Sensor Network for Real-Time Monitoring and Contamination Detection in Drinking Water Distribution Systems,' IEEE Sensors Journal, 14(8), pp. 2765–2772.
3. Vijayakumar, N. and Ramya, R. (2015) 'The Real Time Monitoring of Water Quality in IoT Environment,' International Conference on Innovations in Information, Embedded and Communication Systems (ICIIECS), pp. 1–5.
4. Adu-Manu, K.S., Tapparello, C., Heinzelman, W., Katsriku, F.A. and Abdulai, J.D. (2017) 'Water Quality Monitoring Using Wireless Sensor Networks: Current Trends and Future Research