International Journal of Scientific Research in Engineering and Management (IJSREM)
Volume: 10 Issue: 10 | Oct - 2026 SJIF Rating: 8.659 ISSN: 2582-3930

IOT-Based Smart Soldier Safety System

Ms. Shinde P. S E&TC Dept. (JSPM's BSP)
Ms. Shinde P. S E&TC Dept. (JSPM's BSP)
Ms. Badhe T. D E&TC Dept. (JSPM's BSP)
Ms. Shendge S. B E&TC Dept. (JSPM's BSP)
Mr. Waghmode M. N E&TC Dept. (JSPM's BSP)

Abstract:

The Smart Soldier Safety Suit and Helmet are an IoT-based wearable safety system developed to improve the protection and monitoring of soldiers during field operations. This setup integrates multiple sensors into a smart suit and helmet to track vital signs like body temperature and heart rate, as well as soldier movement and ambient environmental factors. A microcontroller collects and processes the sensor data continuously. When an abnormal condition, fall, or hazardous situation is detected, the system generates an emergency alert and can transmit the soldier's status and location to a remote monitoring unit using wireless communication.

The system delivers instant monitoring capabilities, enabling quicker reaction times when critical events occur. We engineered this prototype to be lightweight, budget-friendly, and highly adaptable. This opens up clear paths for scaling the design, such as embedding AI-driven health diagnostics, upgrading to next-generation wireless modules, or integrating specialized safety sensors. Ultimately, this technology serves as a reliable asset to elevate situational awareness and protect personnel operating in unpredictable operational zones.

Key Words: "Smart Soldier, Smart Safety Suit, Smart Helmet, IoT, Wearable Technology, Soldier Safety, Health Monitoring, Environmental Monitoring, Emergency Alert, Wireless Communication, GPS, Sensor-based System".

1. INTRODUCTION

Soldiers are frequently required to work in challenging and unpredictable environments where physical safety, health status, and communication are important concerns. During field operations, soldiers may be exposed to extreme temperatures, physical stress, accidental falls, hazardous gases, and other environmental risks. In such situations, continuous monitoring can help identify abnormal conditions at an early stage and support timely action.

Traditional military protective equipment is mainly designed to provide physical protection against external threats. The development of wearable electronics and Internet of Things (IoT) technologies provides opportunities to integrate sensing and communication capabilities into protective equipment.

The Smart Soldier Safety Suit and Helmet are proposed as a wearable safety system that combines a protective suit and helmet with multiple sensors. Depending on the selected prototype configuration, sensors can be used to monitor parameters such as body temperature, heart rate, movement, fall conditions, and environmental factors. The collected information is processed by a microcontroller to determine the current status of the soldier.

Wireless communication can be used to transfer important sensor information from the wearable system to a remote monitoring unit. When a predefined abnormal condition is detected, the system can generate an emergency alert. A location module such as GPS can also be integrated to provide the approximate location of the soldier when location data is available, which may assist the monitoring team during an emergency.

By integrating sensing, processing, communication, and alert mechanisms into wearable equipment, the system can reduce the need for multiple independent monitoring devices. The design can also be adapted according to the requirements of different field conditions and available hardware components.

The Smart Soldier Safety Suit and Helmet provide a foundation for future development of intelligent soldier-monitoring systems. Future enhancements may include artificial intelligence for abnormal-condition analysis, improved wireless communication, additional environmental sensors, energy-efficient hardware, and advanced monitoring interfaces. Such developments can improve situational awareness and provide additional support for soldier safety in challenging environments.

2. Body of Paper

The proposed Smart Soldier Safety Suit and Helmet is an IoT-based wearable safety system designed to monitor the soldier's health, movement, location, and surrounding conditions. The MPU6050 sensor is used to detect sudden movement, impact, and changes in orientation, while the MAX30102 sensor monitors heart rate and SpO_2 (Peripheral Capillary Oxygen Saturation). A temperature sensor such as DHT11 or DS18B20 is used for temperature monitoring.

For location tracking, the NEO-6M GPS module provides the soldier's location information. A LoRa module is used to transmit sensor data wirelessly from the wearable unit to the base station. A panic button allows the soldier to manually trigger an emergency alert. A buzzer and LEDs provide local warning and system status indications. The complete system is powered using a rechargeable battery with a charging module.

The ESP32 continuously receives data from the connected sensors and processes the collected information. When a predefined abnormal condition, sudden impact, or emergency event is detected, the system can activate the local alert mechanism and transmit relevant information to the monitoring unit. The proposed architecture combines health monitoring,

motion detection, location tracking, wireless communication, and emergency indication in a single wearable platform.

2.1. Hardware Description

The hardware of the Smart Soldier Safety Suit and Helmet is developed to continuously monitor the soldier's health, movement, location, and environmental conditions. The system primarily consists of an ESP32 microcontroller, MPU6050 motion sensor, NEO-6M GPS module, LoRa, MAX30102 heart-rate and SpO_2 sensor, temperature sensor, panic button, buzzer, LEDs, and a rechargeable battery with charging module. These components work together to collect sensor data, process the information, and provide an emergency alert when an abnormal condition is detected.

1. ESP32 Microcontroller




Fig. 1: ESP32 Microcontroller

The ESP32 microcontroller acts as the central control unit of the Smart Soldier Safety Suit and Helmet. It is responsible for collecting inputs from the connected sensors, processing the soldier's health and safety parameters, controlling the alert devices, and managing wireless communication. The ESP32 is selected because of its built-in Wi-Fi and Bluetooth capabilities, low-power operation, sufficient GPIO pins, and processing capability, making it suitable for IoT-based wearable safety applications.

The ESP32 continuously receives data from sensors such as the MPU6050, MAX30102, temperature sensor, and panic button. Based on the sensor readings, it processes the soldier's movement, heart rate, SpO_2, temperature, and emergency status. When a predefined abnormal condition or emergency event is detected, the ESP32 activates the buzzer and LEDs and can transmit the relevant information through LoRa.

2. MPU6050 Module




Fig. 2: MPU6050 Module

The MPU6050 acts as a motion and orientation sensing unit in the Smart Soldier Safety Suit and Helmet. It combines a 3-axis accelerometer and a 3-axis gyroscope to measure the soldier's movement, acceleration, and orientation. The sensor provides motion data to the ESP32 through the I^2C communication interface, allowing the controller to continuously monitor changes in the soldier's movement.

The MPU6050 is mainly used to detect sudden movement, impact, abnormal orientation, and possible fall conditions. The ESP32 processes the sensor readings and compares them with predefined conditions. If a significant movement or possible fall is detected, the system can activate the buzzer/LED alert and transmit the emergency status through the wireless communication module. This feature helps improve the safety monitoring capability of the proposed wearable system.

3. NEO-6M GPS




Fig. 3: NEO-6M GPS

The NEO-6M GPS module is used as the location-tracking unit in the Smart Soldier Safety Suit and Helmet. It receives signals from GPS satellites and provides geographical location information such as latitude and longitude. The module communicates with the ESP32 through a serial interface, allowing the controller to receive and process the location data. In this project, the NEO-6M continuously provides the soldier's location information when a valid GPS signal is available. During an emergency condition, such as a detected fall, sudden impact, or activation of the panic button, the ESP32 can use the GPS coordinates along with the emergency status and transmit them through the LoRa to the monitoring or base station. This helps the monitoring team identify the approximate location of the soldier and supports faster emergency response.

4. DHT11 Temperature Sensor




Fig. 4: DHT11 Temperature Sensor

The DHT11 temperature sensor is used to monitor temperature conditions in the Smart Soldier Safety Suit and Helmet. It measures the surrounding temperature and provides the temperature data to the ESP32 microcontroller through a digital signal. The DHT11 is selected because it is simple to interface, low-cost, and suitable for prototype-level monitoring applications.

The DHT11 continuously provides temperature readings to the ESP32. The controller processes the measured value and compares it with a predefined threshold. If the temperature exceeds the specified limit, the system can activate the buzzer and LED alert and transmit the warning through the wireless communication module. This feature helps in monitoring temperature-related conditions and enhances the overall safety-monitoring capability of the proposed system.

5. LoRa (Long Range)




Fig. 5: LoRa (Long Range)

The LoRa (Long Range) communication module is used for wireless communication in the Smart Soldier Safety Suit and Helmet. It provides long-range, low-power data transmission between the soldier's wearable system and a remote monitoring or base station. The LoRa module is connected to the ESP32 microcontroller, which sends important sensor information through the wireless link.

The LoRa module can transmit the soldier's health status, motion/fall alert, temperature information, and GPS location to the monitoring unit. When an emergency condition is detected, the ESP32 sends the relevant data through LoRa so that the monitoring team can receive the alert and take appropriate action. This makes LoRa suitable for applications where long-range and low-power communication is required.

6. MAX30102




Fig 6: MAX30102

The MAX30102 is a biosensor module used for monitoring the soldier's heart rate and blood oxygen saturation (SpO_2) in the Smart Soldier Safety Suit and Helmet. It uses integrated red and infrared LEDs along with a photodetector to measure changes in blood flow. The sensor communicates with the ESP32 microcontroller through the I^2C interface, allowing the collected physiological data to be processed.

The MAX30102 continuously measures the soldier's heart rate and SpO_2 level. The ESP32 processes the sensor readings and checks them against predefined conditions. If an abnormal reading is detected, the system can activate the buzzer and LED alert and transmit the health status through the LoRa communication module. This provides an additional health-monitoring feature for the proposed wearable safety system.

7. Buzzer



Fig. 7: Buzzer

The buzzer is used as an audible alert device in the Smart Soldier Safety Suit and Helmet. It is controlled by the ESP32 microcontroller and provides an immediate warning when an abnormal or emergency condition is detected.

The buzzer can be activated when conditions such as a possible fall, abnormal health parameter, high temperature, or panic button activation are detected. The ESP32 sends a control signal to the buzzer, which produces an audible warning to notify the soldier and nearby personnel. The buzzer therefore provides a simple and effective local emergency indication and complements the wireless alert system.

8. LED (Light Emitting Diode)



Fig. 8: LED

The LED (Light Emitting Diode) is used as a visual status and alert indicator in the Smart Soldier Safety Suit and Helmet. It is controlled by the ESP32 microcontroller and provides a simple visual indication of the current system condition.

In this project, the LED can indicate different conditions such as normal operation, emergency status, sensor detection, or panic activation. When an abnormal condition is detected, the ESP32 activates the LED along with the buzzer to provide a visual warning. This helps the soldier and nearby personnel quickly identify the system status and emergency conditions.

3. CONCLUSION

The Smart Soldier Safety Suit and Helmet are a wearable safety system designed to monitor the soldier's health, movement, temperature, and location in real time. The system uses sensors and an ESP32 microcontroller to collect and process important information. In emergency situations, it can provide local alerts and transmit relevant information through wireless communication. The integration of health monitoring, motion detection, GPS tracking, and emergency alerts can improve soldier safety and support faster response. The system can be further enhanced with solar-assisted charging, AI-based monitoring, advanced sensors, and improved wireless communication for future applications.

4. ACKNOWLEDGEMENT

We would like to express our sincere gratitude to our respected Principal, Head of Department, and Project Guide for their valuable guidance, support, and encouragement during the preparation of this review paper. We are thankful to our department and college for providing the necessary academic resources and facilities.
We also acknowledge the valuable information obtained from research papers, journals, and other academic sources related to smart wearable technology, IoT, and soldier safety systems. Finally, we thank our teachers, classmates, and family members for their support and encouragement throughout the preparation of this review paper.

5. REFERENCES

1. Patel, V., Yeware, N., Thombre, B., Chopde, A.: Soldiers Health Monitoring and Position Tracking System. In: 2024 IEEE International Students' Conference on Electrical, Electronics and Computer Science (SCEECS). IEEE (2024) 1–4

2. Sabarimuthu, M., Krishna, R.: IoT Based Soldier Status Monitoring Using Sensors and SOS Switch. In: 2022 Second International Conference on Computer Science, Engineering and Applications (ICCSEA). IEEE (2022) 1479–1484

3. Anand, R., Swaroop, S.: A review on smart wearable devices for soldier safety during battlefield using WSN technology. In: Materials Today: Proceedings. Vol. 33(8), Elsevier (2020) 360–365

4. Patil, N., Iyer, B.: Arduino-based Soldier Location and Health Tracking System. In: International Journal of Innovative Science and Research Technology. Vol. 7(11), IJISRT (2022) 910–915

5. Singh, J., Kumar, R., Sharma, P.: Health Monitoring and Soldier Tracking System using IOT. In: International Journal of Engineering Research & Technology. Vol. 8(14), IJERT (2019) 1–6

6. Sabarimuthu, M., Krishna, R.: IoT Based Soldier Status Monitoring Using Sensors and SOS Switch. In: 2022 Second International Conference on Computer Science, Engineering and Applications (ICCSEA). IEEE (2022) 1479–1484

7. Haramkar, V.S., Mane, O.P., Shinde, A.A., Patil, K.S., Kadam, M.: Development of Lora Sensor-based safety system for soldiers. In: International Journal of Engineering Development and Research. Vol. 14(2), MDPI (2026) 70–74

8. S. K. Saidu Babu, G. Ravi Kumar, and R. Begum, "Soldier healthcare parameters monitoring system using Internet of Things," International Journal of Scientific Research in Science, Engineering and Technology (IJSRSET), 2023

9. Maruti, V.G., Kodge, P., Krupa, Y.K., Yuvaraj, M.: Soldier Health Monitoring System Using Esp 32 Microcontroller. In: International Journal of Advanced Research in Journal of Science, Engineering and Technology. Vol. 13(1), IARJSET (2026) 118–123

10. Kumar, A., Vignesh, S., Karthik, R.: Soldier Monitoring and Tracking System using ESP-NOW and Cloud Networks. In: 2024 International Conference on Tactile Internet and Edge Computing (IC-TIEC). IEEE (2024) 1–6

11. Jethwa, P., Panchasara, H.: Realtime Wireless Embedded Electronics for Soldier Security Systems using ESP32-CAM Platforms. In: Journal of Academic Research and Advanced Frameworks. Vol. 4(4), RJWave (2026) 653-659

12. Sabarimuthu, M., Krishna, R.: IoT Based Soldier Status Monitoring Using Sensors and SOS Switch. In: 2022 Second International Conference on Computer Science, Engineering and Applications (ICCSEA). IEEE (2022) 1479–1484

13. Kumar, A., Vignesh, S., Karthik, R.: Soldier Monitoring and Tracking System using ESP-NOW and Cloud Networks. In: 2024 International Conference on Tactile Internet and Edge Computing (IC-TIEC). IEEE (2024) 1–6

14. Vikas, D., Kumar, P., Kumar, S.: Soldier Health Monitoring and Position Tracking with LoRa Transmissions. In: Proceedings of the Tactical Micro-Electronics Forum. Zenodo (2025) 41–48

BIOGRAPHIES



Ms. Prajakta S. Shinde
Student (E&TC Dept.)
JSPM'S BSP, Wagholi, Pune



Ms. Pranjal S. Shinde
Student (E&TC Dept.)
JSPM'S BSP, Wagholi, Pune



Ms. Tanvi D. Badhe
Student (E&TC Dept.)
JSPM's BSP, Wagholi, Pune



Ms. Shashwati B. Shendge
Student (E&TC Dept.)
JSPM's BSP, Wagholi, Pune



Mr. Mahesh N. Waghmode
Lecturer (E&TC Dept.)
JSPM's BSP, Wagholi, Pune