International Journal of Scientific Research in Engineering and Management (IJSREM)
Volume: 10 Issue: 10 | Oct - 2026 SJIF Rating: 8.659 ISSN: 2582-3930

IOT Server Simulation for Device Monitoring and Control using Cisco Packet Tracer

Dr. Hemavathi[1], Sharanya R[2], Ujwal M[3], Tharun S[4]

[1]Department of Electronics and Communication Engineering, B.M.S. College of Engineering, Bengaluru, India
[2,3,4]PG-DC students, Department of Electronics and Communication Engineering, B.M.S. College of Engineering, Bengaluru

---

Abstract - The Internet of Things (IoT) has become one of the most rapidly growing technologies for connecting physical devices through communication networks, enabling remote monitoring, automation, and intelligent control. This work presents the design and implementation of a smart home automation system using Cisco Packet Tracer. The proposed system employs a Home Gateway acting as the IoT server to provide wireless connectivity, Dynamic Host Configuration Protocol (DHCP), and centralized device management. Smart devices including a Smart Lamp, Smart Door, Smart Window, Smart Fan, and IoT Appliance are connected through Wi-Fi and registered with the Home Gateway. A Personal Computer accesses the IoT dashboard through a web browser, allowing users to remotely monitor and control connected devices in real time. The proposed framework demonstrates wireless communication, centralized IoT device management, DHCP configuration, and smart home automation in a virtual environment. The implementation validates the effectiveness of Cisco Packet Tracer as an educational platform for understanding IoT architecture, communication protocols, and remote device control without requiring physical hardware.

Key Words: Internet of Things (IoT), Cisco Packet Tracer, Smart Home Automation, Home Gateway, Wireless Communication, DHCP, IoT Server, Remote Monitoring, Smart Devices, Network Simulation.

1.INTRODUCTION

The Internet of Things (IoT) has emerged as one of the most transformative technologies of the modern digital era, enabling billions of physical devices to communicate, exchange data, and perform intelligent operations over communication networks with minimal or no human intervention. IoT integrates embedded systems, sensors, actuators, wireless communication technologies, cloud computing, and data analytics to create interconnected environments capable of real-time monitoring, automation, and decision-making. The rapid growth of IoT has revolutionized numerous sectors, including smart homes, healthcare, industrial automation, transportation, agriculture, environmental monitoring, and smart city infrastructure. By allowing devices to collect, process, and transmit information efficiently, IoT enhances operational efficiency, reduces manual effort, improves resource utilization, and provides greater convenience, safety, and reliability in everyday applications.

Among the various applications of IoT, smart home automation has become one of the most widely adopted and rapidly expanding domains. In a smart home environment, interconnected devices such as lighting systems, doors, windows, fans, security systems, and household appliances communicate through a centralized controller or gateway. Users can remotely monitor and control these devices using computers, smartphones, or tablets through a web interface or dedicated application. Smart home automation not only improves user comfort and security but also contributes to energy conservation by enabling intelligent control of electrical appliances based on user preferences or environmental conditions. The integration of wireless networking technologies such as Wi-Fi further simplifies device connectivity and enhances system flexibility by eliminating extensive cabling requirements.

Cisco Packet Tracer, developed by Cisco Systems, is a comprehensive network simulation platform that provides students, researchers, and networking professionals with a virtual environment for designing, configuring, testing, and analyzing computer networks and IoT applications without requiring expensive physical hardware. In addition to traditional networking devices such as routers, switches, and servers, Cisco Packet Tracer supports a wide variety of IoT-enabled sensors, actuators, smart appliances, and embedded devices. The software provides an intuitive graphical interface for creating realistic smart home and industrial IoT topologies, configuring wireless communication, implementing Dynamic Host Configuration Protocol (DHCP), registering IoT devices, and monitoring network operations in real time. This makes it an effective educational and research tool for understanding IoT architecture, communication protocols, and device management before deploying systems in real-world environments.

In this work, a smart home automation system is designed and implemented using Cisco Packet Tracer to demonstrate the practical concepts of IoT communication and centralized device management. The proposed system consists of a Home Gateway that functions as the IoT server, wireless access point, and DHCP server, providing seamless connectivity to multiple smart devices such as a Smart Fan, Smart Light, Smart Garage Door, Smart Window, and IoT Appliance. These devices are connected wirelessly, automatically assigned IP addresses, and registered with the Home Gateway for centralized monitoring and control. A Personal Computer is used to access the IoT dashboard through a web browser, enabling users to remotely monitor device status and perform control operations such as switching appliances on or off and operating smart devices in real time.

The proposed implementation demonstrates reliable wireless communication, centralized IoT management, remote accessibility, and practical smart home automation while providing valuable hands-on experience in IoT network design, device configuration, and system operation. The developed simulation serves as an effective learning platform for understanding the principles of IoT networking and highlights

the potential of smart technologies in building intelligent, scalable, and energy-efficient automation systems.

2. Proposed Methodology

The proposed system presents an Internet of Things (IoT)-based smart home automation framework developed using Cisco Packet Tracer to demonstrate centralized device management, wireless communication, and remote monitoring in a simulated environment. The primary objective of the proposed design is to create an intelligent network where multiple smart devices communicate with a central IoT server through a reliable wireless infrastructure, allowing users to monitor and control household appliances remotely. The proposed architecture closely resembles a real-world smart home implementation while providing a cost-effective and hardware-independent platform for learning IoT concepts and networking technologies.

The system architecture consists of several networking and IoT components, including an Access Point, Network Switch, IoT Server, Personal Computer (PC), and multiple IoT-enabled devices such as a Smart Fan, Smart Light, Smart Garage Door, Smart Window, and a generic IoT Appliance. The Access Point serves as the wireless communication hub, enabling all smart devices to connect to the network through Wi-Fi. It acts as a bridge between the wireless IoT devices and the wired network infrastructure. The Network Switch provides Layer-2 connectivity and facilitates communication between the Access Point, IoT Server, and Personal Computer by forwarding data packets efficiently across the network.

The IoT Server functions as the central management unit of the proposed system. It is responsible for registering IoT devices, maintaining device information, processing user requests, and hosting web-based IoT services. Each smart device is configured to connect to the wireless network using the predefined Service Set Identifier (SSID) and authentication credentials. Once connected, the devices automatically obtain IP addresses using the Dynamic Host Configuration Protocol (DHCP), eliminating the need for manual network configuration. After successful network association, every IoT device registers with the IoT Server, allowing it to appear on the centralized dashboard for monitoring and control. This automated registration process ensures efficient management of multiple devices while simplifying network administration.

The Personal Computer acts as the client device through which users interact with the IoT system. By entering the server's IP address into a web browser and providing valid login credentials, users can access the IoT dashboard. The dashboard displays the operational status of all registered devices and provides individual controls for each appliance. Users can remotely switch the Smart Fan and Smart Light ON or OFF, open and close the Smart Garage Door, and operate other IoT appliances in real time. Whenever a user issues a command, the IoT Server processes the request and forwards it through the Network Switch and Access Point to the corresponding IoT device, which immediately performs the desired operation. This communication process demonstrates centralized control and real-time interaction between users and connected smart devices.

The implementation methodology begins with placing all required networking devices within the Cisco Packet Tracer workspace, followed by establishing wired connections between the Access Point, Switch, Server, and Personal Computer using copper straight-through cables. Smart IoT devices are then configured to communicate wirelessly with the Access Point. After configuring wireless settings, DHCP services, and IoT server functionality, all devices are registered with the server to enable centralized monitoring and remote control. Finally, communication between devices is verified by performing multiple control operations through the web interface, confirming successful network connectivity and system functionality.




Fig -1: System Architecture

The proposed system architecture is designed to implement an Internet of Things (IoT)-based smart home automation network using Cisco Packet Tracer. The architecture integrates both wired and wireless communication technologies to establish seamless connectivity between users and smart devices through a centralized IoT server. The primary objective of the architecture is to enable real-time monitoring, remote control, and efficient management of multiple smart appliances within a secure and scalable network environment. By utilizing a centralized architecture, the system ensures reliable communication, simplified device management, and efficient resource utilization while providing users with convenient access to connected devices from a single interface.

The architecture consists of several essential networking components, including an Access Point, Network Switch, IoT Server, Personal Computer (PC), and various IoT-enabled appliances such as a Smart Fan, Smart Light, Smart Garage Door, Smart Window, and a generic IoT Appliance. Each component performs a specific function that contributes to the overall operation of the smart home network. The Access Point serves as the wireless communication hub by broadcasting a Wi-Fi network that enables all IoT devices to connect wirelessly. It acts as a bridge between the wireless devices and the wired network infrastructure, ensuring uninterrupted communication throughout the system.

The Network Switch functions as the central wired networking device responsible for forwarding data packets between connected devices. It establishes communication between the Access Point, IoT Server, and Personal Computer using Ethernet connections. By efficiently directing network traffic, the switch ensures that control commands and device status information are delivered accurately and without delay. This centralized wired backbone improves network stability

and supports reliable communication between all network components.

Network Configuration

The network devices were configured according to the following procedure.




Fig -2: Configuring the Access point

Step 1: Placing the Devices: The Access Point, Switch, Server, PC, IoT Appliance, Smart Fan, Smart Garage Door, and Smart Light were placed in the Cisco Packet Tracer workspace.

Step 2: Connecting the Network:

The Access Point was connected to the Switch using a Copper Straight-Through cable. The Server and PC were also connected to the Switch using Copper Straight-Through cables. All IoT appliances were connected wirelessly to the Access Point.

Step 3: Configuring the Server:

The Server was configured to provide IoT services. The IoT service was enabled so that smart devices could register themselves with the server. The server also maintained the device database and accepted remote control requests from the client.

Step 4: Configuring the Access Point

The Access Point was configured with the required wireless network settings. The SSID was assigned, allowing all IoT devices to connect to the same wireless network.

Step 5: Connecting IoT Devices

Each IoT appliance was configured to connect to the wireless network. After entering the SSID and authentication details, the devices successfully joined the network.

The connected devices include:

- IoT Appliance
- Smart Fan
- Smart Garage Door
- Smart Light

Step 6: Registering the Devices

After establishing wireless connectivity, each IoT device was registered with the IoT Server. Once registered, the server displayed all connected devices on the dashboard.

Step 7: Accessing the IoT Server

The Personal Computer was used to access the IoT Server using a web browser. The user entered the server IP address and logged in using the configured username and password. After successful authentication, the IoT dashboard displayed all registered devices.

Step 8: Controlling the Devices:

The IoT dashboard provides individual controls for each appliance.

The following operations were performed:

- Switching the Smart Fan ON and OFF.
- Opening and Closing the Garage Door.
- Turning the Smart Light ON and OFF.
- Operating the IoT Appliance remotely.

The corresponding status changes were observed immediately in the simulation workspace.

3. Results and Discussion

This section describes the implementation of the IoT-based smart home network using Cisco Packet Tracer. The experiment involves configuring the network devices, connecting the IoT appliances to the wireless network, registering the appliances with the IoT server, and verifying their operation through a web browser. The successful execution of these steps demonstrates remote monitoring and control of smart devices over a network.

Experimental Setup

The experimental setup consists of the following devices:

- One Access Point
- One Switch
- One Server
- One Personal Computer (PC)
- One IoT Appliance
- One Smart Fan
- One Smart Garage Door
- One Smart Light

All IoT devices communicate wirelessly with the Access Point. The Access Point is connected to the Switch using a copper straight-through cable. The Server and PC are also connected to the Switch. The Server hosts the IoT services, while the PC is used to access the server through a web browser.

The performance of the network was verified by connecting all IoT appliances to the Access Point, registering them with the IoT Server, and remotely controlling them through the Personal Computer (PC). The observations confirm that the designed network successfully supports wireless communication, centralized device management, and remote operation of IoT appliances.

The IoT smart home network was successfully designed and implemented using Cisco Packet Tracer. All IoT appliances established wireless communication with the Access Point and were successfully registered with the IoT Server. The Personal Computer accessed the server through a web browser, allowing remote monitoring and control of all connected appliances. The Smart Fan, Smart Garage Door, Smart Light, and IoT Appliance responded correctly to user commands. The successful operation of all devices verified the proper functioning of the proposed IoT-based smart home automation system. The following observations were recorded during the execution of the experiment.

Table -1: Experimental observation table

Sl. No.	IoT Device	Operation Performed	Observed Result	Status
1	IoT Appliance	ON/OFF	Device responded correctly to control commands	Successful
2	Smart Fan	ON/OFF	Fan switched ON and OFF successfully	Successful
3	Smart Garage Door	Open/Close	Garage door opened and closed correctly	Successful
4	Smart Light	ON/OFF	Light switched ON and OFF successfully	Successful
5	Access Point	Wireless Communication	All IoT devices connected successfully	Successful
6	Server	Device Registration	All IoT devices registered successfully	Successful
7	Personal Computer	Browser Access	IoT dashboard displayed all connected devices	Successful

The IoT Server acts as the core management unit of the entire architecture. It hosts IoT services, maintains a database of registered devices, processes user requests, and provides a web-based interface for remote monitoring and control. Every smart device must register with the IoT Server before it can participate in the network. The server authenticates devices, stores their operational status, and continuously updates the dashboard to reflect real-time device information. This centralized management approach simplifies administration and enables efficient monitoring of all connected appliances through a single platform.

4. CONCLUSIONS

The IoT-based smart home automation system was successfully implemented and tested using Cisco Packet Tracer. The Access Point provided wireless connectivity to all IoT appliances, while the Server managed device registration and communication. The Personal Computer successfully accessed the IoT dashboard through a web browser and remotely controlled the connected appliances. The experiment demonstrated the practical application of IoT technology in smart home automation and provided a clear understanding of wireless networking, centralized device management, and remote monitoring.

REFERENCES

1. A. Bahga and V. Madisetti, Internet of Things: A Hands-on Approach. Hyderabad, India: Universities Press, 2015.
2. R. Kamal, Internet of Things: Architecture and Design Principles, 2nd ed. New Delhi, India: McGraw-Hill Education, 2017.
3. L. Da Xu, W. He, and S. Li, "Internet of Things in industries: A survey," IEEE Transactions on Industrial Informatics, vol. 10, no. 4, pp. 2233–2243, Nov. 2014.
4. A. Al-Fuqaha, M. Guizani, M. Mohammadi, M. Aledhari, and M. Ayyash, "Internet of Things: A survey on enabling technologies, protocols, and applications," IEEE Communications Surveys & Tutorials, vol. 17, no. 4, pp. 2347–2376, Fourth Quarter 2015.
5. S. Li, L. Da Xu, and S. Zhao, "The Internet of Things: A survey," Information Systems Frontiers, vol. 17, no. 2, pp. 243–259, Apr. 2015.
6. M. A. Khan and K. Salah, "IoT security: Review, blockchain solutions, and open challenges," Future Generation Computer Systems, vol. 82, pp. 395–411, May 2018.
7. F. Restuccia, S. D'Oro, and T. Melodia, "Securing the Internet of Things in the age of machine learning and software-defined networking," IEEE Internet of Things Journal, vol. 8, no. 16, pp. 12918–12940, Aug. 2021.
8. Y. Liu, M. Peng, G. Shou, Y. Chen, and S. Chen, "Toward edge intelligence: Multi-access edge computing for 5G and Internet of Things," IEEE Internet of Things Journal, vol. 7, no. 8, pp. 6722–6747, Aug. 2020.
9. M. Aazam and E.-N. Huh, "Fog computing and smart gateway based communication for cloud of things," in Proc. IEEE 2nd Int. Conf. Future Internet of Things and Cloud (FiCloud), Barcelona, Spain, Aug. 2014, pp. 464–470.
10. P. P. Ray, "A survey on Internet of Things architectures," Journal of King Saud University – Computer and Information Sciences, vol. 30, no. 3, pp. 291–319, Jul. 2018.
11. M. Sethi and R. Sarangi, "Internet of Things: Architectures, protocols, and applications," Journal of Electrical and Computer Engineering, vol. 2017, Art. no. 9324035, pp. 1–25, 2017.
12. H. Ning and H. Liu, "Cyber-Physical-Social Thinking Space for Internet of Things," IEEE Internet of Things Journal, vol. 2, no. 2, pp. 127–143, Apr. 2015.
13. C. Perera, C. H. Liu, and S. Jayawardena, "The emerging Internet of Things marketplace from an industrial perspective: A survey," IEEE Transactions on Emerging Topics in Computing, vol. 3, no. 4, pp. 585–598, Dec. 2015.
14. D. Evans, "The Internet of Things: How the Next Evolution of the Internet Is Changing Everything," Cisco Internet Business Solutions Group (IBSG), White Paper, Apr. 2011.
15. O. Vermesan and P. Friess, Eds., Internet of Things – From Research and Innovation to Market Deployment. Aalborg, Denmark: River Publishers, 2014.
16. K. Ashton, "That 'Internet of Things' Thing," RFID Journal, vol. 22, no. 7, pp. 97–114, Jun. 2009.