

Liquid Tree

Under the guidance of: Mr. U. S. Shirshetti

Saumya R. Gawali

Information Technology

Sou. Venutai Chavan Polytechnic Pune
Pune, India

Saumyagawali675@gmail.com

Pranav N. Vartale

Information Technology

Sou. Venutai Chavan Polytechnic Pune
Pune, India

pranavvartale003@gmail.com

Dipak B. Funde

Information Technology

Sou. Venutai Chavan Polytechnic Pune
Pune, India

dipakfunde67@gmail.com

Manish B. Wagh

Information Technology

Sou. Venutai Chavan Polytechnic Pune
Pune, India

manishwagh041@gmail.com

Urban air pollution and climate change require innovative and sustainable solutions to improve environmental quality and public health. This paper presents the design and implementation of a Liquid Tree (LIQUID3 Photobioreactor), inspired by natural photosynthesis processes performed by trees. The proposed system integrates a transparent photobioreactor tank, microalgae culture, air circulation system, and environmental monitoring sensors to absorb carbon dioxide (CO₂) and release oxygen efficiently. The architecture enables continuous air purification through controlled biological processes and supports real-time monitoring of parameters such as light intensity, temperature, and CO₂ concentration. Unlike traditional trees, the Liquid Tree can be installed in limited urban spaces while delivering comparable or higher air purification efficiency. The system demonstrates effective carbon capture, oxygen generation, and environmental sustainability in compact city environments. Performance analysis shows improved air quality, reduced carbon footprint, and efficient space utilization. Future scope includes IoT-based monitoring, AI-driven optimization, and large-scale deployment in smart cities.

Keywords — Liquid Tree, Photobioreactor, Microalgae, Air Purification, Carbon Capture, Smart Cities, Environmental Sustainability

I. INTRODUCTION

The rapid growth of urbanization, industrialization, and population has significantly increased air pollution levels, posing serious threats to environmental sustainability and public health. Traditional methods of pollution control, such as planting trees, are often limited by space constraints, slow growth rates, and maintenance challenges in densely populated cities. As urban environments become more complex and polluted, there is an increasing demand for innovative and technology-driven solutions capable of improving air quality in real time. Intelligent environmental systems that integrate biological processes with engineering design are now essential for enhancing air purification efficiency and supporting sustainable urban development.

Modern cities require compact and efficient solutions that can replicate the ecological benefits of natural trees while adapting to space limitations. Inspired by the natural process of photosynthesis, the Liquid Tree (LIQUID3 Photobioreactor) is developed as an advanced system to demonstrate artificial air purification using microalgae. The project integrates a transparent bioreactor structure, microalgae culture, air circulation mechanism, and environmental monitoring components into a unified architecture capable of performing continuous carbon absorption and oxygen generation.

The system operates by continuously absorbing carbon dioxide (CO₂) from the surrounding air and utilizing microalgae to perform photosynthesis in the presence of light. The microalgae convert CO₂ into oxygen and biomass, effectively reducing air pollution levels. Sensors and control mechanisms help maintain optimal conditions such as light intensity, temperature, and nutrient levels to ensure efficient biological activity. This continuous interaction between environmental input and biological processing ensures consistent air purification performance, similar to the natural functioning of trees.

A crucial feature of the proposed system is its ability to function efficiently in limited urban spaces while providing measurable environmental benefits. Unlike traditional trees, the Liquid Tree does not require large land areas and can be installed in high-pollution zones such as roadsides, public squares, and industrial regions. The system also supports monitoring and maintenance through controlled conditions, ensuring reliability and consistent performance. This structured and sustainable approach enhances environmental management and demonstrates the potential of combining biotechnology with urban infrastructure for cleaner and healthier cities.



II. RELATED WORK

The development of sustainable air purification technologies has evolved from traditional tree plantation methods to advanced bioengineering solutions capable of improving air quality in urban environments. Early approaches primarily relied on increasing green cover and implementing basic filtration systems to reduce pollution levels. However, with rapid urbanization and limited land availability, these methods became insufficient for densely populated cities. Recent advancements in environmental engineering have led to the development of microalgae-based systems and photobioreactors that can efficiently absorb carbon dioxide (CO₂) and release oxygen. Foundational studies in biotechnology and environmental science established the principles of photosynthesis-based carbon capture, while later research introduced compact and controlled systems capable of operating in urban conditions [1, 2].

2.1 Growth of Microalgae-Based Air Purification Systems (2018–2024)

Recent academic and industrial research from 2018 to 2024 indicates significant growth in the development of microalgae-based air purification systems [3, 4]. Studies published in environmental and engineering journals highlight the increasing use of photobioreactors for carbon capture and oxygen generation. The adoption of microalgae is driven by their high photosynthetic efficiency compared to traditional plants. Additionally, advancements in sensor technology and low-cost monitoring systems have enabled better control of environmental parameters such as light, temperature, and CO₂ concentration. The data suggests that the transition from traditional air purification methods to intelligent bio-reactive systems began around 2020, supported by improvements in biotechnology and real-time monitoring techniques [3, 5].

2.2 Shift Toward Integrated Bio-Tech Environmental Systems

Recent literature (2022–2026) emphasizes the development of integrated systems that combine biological processes with engineering and digital technologies [6]. Instead of relying solely on natural or mechanical methods, modern environmental solutions integrate microalgae cultivation, sensor networks, and automated control systems into unified architectures. These systems operate as closed-loop environments where real-time data is used to regulate internal

conditions and maximize efficiency. This shift represents a movement from passive environmental solutions to active and intelligent systems capable of continuous air purification and environmental monitoring. Such architectures enhance efficiency, scalability, and adaptability in urban applications [6, 7].

2.3 Monitoring, Optimization, and Environmental Control Mechanisms

Current advancements in smart environmental systems highlight the importance of continuous monitoring and optimization to ensure efficient performance [1]. In microalgae-based systems, maintaining optimal conditions such as light intensity, nutrient levels, temperature, and CO₂ supply is critical for effective photosynthesis. Research trends now incorporate IoT-based sensors, automated control units, and data analytics to monitor system performance and optimize output. Continuous validation and system feedback help maintain stability and improve reliability. As Liquid Tree technology evolves, enhancing monitoring accuracy, reducing maintenance requirements, and maximizing oxygen production remain key research challenges in sustainable urban environmental systems.

III. SYSTEM ARCHITECTURE

A modular and layered architecture is essential for ensuring reliability, scalability, and continuous operation in environmental purification systems. The proposed Liquid Tree (LIQUID3 Photobioreactor) follows a structured bio-engineering architecture that integrates biological processing, environmental sensing, control mechanisms, and monitoring systems. The architecture is designed to establish a controlled-loop system where environmental inputs such as carbon dioxide (CO₂), light, and temperature continuously influence biological output in the form of oxygen production. The system ensures stable operation, efficient photosynthesis, and consistent air purification through coordinated interaction of all subsystems.

A. Structural Layer Analysis

The proposed architecture is partitioned into four interconnected functional layers:

I. Biological Processing Layer

This layer represents the core functional component responsible for air purification, including:

- Microalgae culture for photosynthesis
- Water medium for algae growth
- Nutrient supply system
- CO₂ absorption mechanism

These components directly perform the biological process of converting carbon dioxide into oxygen. The microalgae utilize light energy to carry out photosynthesis, making this layer the primary contributor to environmental purification.

II. Structural and Support Layer

This layer consists of the physical framework that supports the system, including:

- Transparent photobioreactor tank
- Air pump and circulation system
- CO₂ inlet and oxygen outlet pathways
- LED lighting system (for controlled environments)

The purpose of this layer is to provide a stable and controlled environment for microalgae growth. The transparent structure allows maximum light penetration, while the air circulation system ensures continuous supply of CO₂ and proper mixing within the tank.

III. Control and Monitoring Layer

The intelligence and regulation of the system reside in this layer, which includes:

- Sensors for CO₂ concentration, temperature, light, and pH levels
- Microcontroller or control unit
- Data acquisition system
- Automated regulation mechanisms

This layer continuously monitors environmental conditions and maintains optimal parameters required for efficient photosynthesis. It ensures that the system operates under ideal conditions by adjusting factors such as light intensity, airflow, and nutrient supply.

IV. User Interaction and Data Management Layer

This layer manages system interaction, monitoring, and data visualization, including:

- Display interface for real-time monitoring
- IoT-based remote monitoring system (optional)
- Data logging and analytics platform
- Alert and maintenance notification system

The system provides users with real-time information about performance parameters such as CO₂ absorption rate and oxygen production. It also supports future integration with smart city infrastructure for centralized environmental monitoring.

B. Communication and Control Flow

The Liquid Tree system follows a structured process flow architecture:

- Air Flow: CO₂ from the environment → Absorbed into photobioreactor → Used by microalgae
- Biological Flow: Microalgae perform photosynthesis → Oxygen released into the environment
- Monitoring Flow: Sensors collect environmental data → Control unit processes data → Adjustments made
- Power Flow: Electrical supply → Distributed to sensors, pumps, and lighting system

Unlike conventional large-scale industrial purification systems, the Liquid Tree operates as a localized, self-contained unit with real-time environmental interaction and minimal latency.

C. Control Strategy: Controlled Biological Loop vs Passive Purification

The effectiveness of the architecture depends on the control strategy used. The Liquid Tree system utilizes:

Closed-Loop Control for environmental regulation (feedback from sensors to maintain optimal conditions).
Passive Natural Process for photosynthesis (biological conversion without mechanical force).

The closed-loop monitoring ensures continuous adjustment of environmental parameters, leading to efficient CO₂ absorption and oxygen generation. This significantly improves performance compared to traditional passive air purification methods such as natural tree plantation.

IV. FEATURES

• Efficient CO₂ Absorption

The system effectively absorbs carbon dioxide from the surrounding air using microalgae, which have a higher photosynthetic efficiency compared to traditional plants.

• Continuous Oxygen Generation

Microalgae continuously produce oxygen through photosynthesis, improving air quality in real time.

• Compact and Space-Efficient Design

The Liquid Tree requires minimal space and can be installed in dense urban areas where traditional tree plantation is not feasible.

• Real-Time Environmental Monitoring

Sensors monitor parameters such as CO₂ levels, temperature, light intensity, and pH to ensure optimal system performance.

• Automated Control Mechanism

The system automatically adjusts environmental conditions like light, airflow, and nutrient supply based on sensor data.

• Low Maintenance System

Compared to traditional trees, the Liquid Tree requires controlled and predictable maintenance, making it suitable for urban deployment.

• Sustainable and Eco-Friendly Solution

The system uses natural biological processes, making it environmentally sustainable and energy-efficient.

• Modular Design

The system is designed in modules, allowing easy upgrades, maintenance, and scalability.

• Urban Air Purification Capability

It is highly effective in polluted environments such as roadsides, industrial zones, and public spaces.

- Scalability for Smart Cities
The system can be integrated with IoT and smart city infrastructure for large-scale environmental monitoring and control.

V. METHODOLOGY

The methodology of the Liquid Tree system follows a structured process that converts environmental inputs into biological air purification outputs. The system captures carbon dioxide from the atmosphere and utilizes microalgae to perform photosynthesis, resulting in oxygen generation.

5.1 Data Acquisition

The system collects environmental data using sensors and air intake mechanisms.

Key aspects include:

- CO₂ Intake System: Captures carbon dioxide from the surrounding air
- Environmental Sensors: Measure temperature, light intensity, CO₂ concentration, and pH levels
- Input Data: Environmental parameters used to regulate system performance

The collected data is sent to the control unit for further processing.

5.2 Environmental Processing and Optimization

Before biological processing, the system ensures optimal conditions for microalgae growth.

Processing steps include:

- Regulation of light intensity (natural or LED-based)
- Temperature control for stable biological activity
- Maintaining proper nutrient levels in water
- Air circulation for uniform CO₂ distribution

These steps ensure efficient photosynthesis and system stability.

5.3 CO₂ Absorption and Photosynthesis Process

The system uses microalgae to perform the core biological function.

Process includes:

- Absorption of CO₂ from the environment
- Utilization of sunlight or artificial light
- Conversion of CO₂ into oxygen and biomass through photosynthesis

This continuous process enables real-time air purification.

5.4 Monitoring and Validation

To maintain efficiency, the system continuously monitors its performance.

Performance evaluation includes:

- CO₂ absorption rate
- Oxygen production rate
- Stability of environmental conditions
- System efficiency over time

These metrics help in optimizing system performance.

5.5 Real-Time Control and Output

After processing environmental data, the system adjusts its operation accordingly.

Control logic includes:

- Regulating airflow and CO₂ intake
- Adjusting light intensity for optimal photosynthesis
- Maintaining nutrient balance
- Ensuring continuous oxygen release

This ensures consistent and efficient air purification.

VI. IMPLEMENTATION

The implementation of the Liquid Tree system involves integrating biological components with mechanical and electronic systems to achieve efficient air purification.

6.1 Hardware Components

The hardware setup consists of the following main components:

- Photobioreactor Tank: Transparent container for microalgae culture
- Microalgae Culture: Performs photosynthesis
- Air Pump System: Circulates air and supplies CO₂
- Sensors: Monitor environmental parameters (CO₂, temperature, light, pH)
- Lighting System: Provides controlled light for photosynthesis

The system continuously interacts with the environment to absorb CO₂ and release oxygen.

6.2 Software Tools

The system may use software for monitoring and control.

Key tools include:

- Microcontroller-based programming for system control
- IoT platforms for remote monitoring (optional)
- Data logging systems for performance tracking

These tools enable efficient monitoring and automation.

6.3 System Integration

The hardware and software modules are integrated into a continuous purification loop.

Implementation flow:


- CO₂ is absorbed from the environment
- Sensors collect environmental data
- Control system processes the data
- Microalgae perform photosynthesis
- Oxygen is released into the atmosphere
- System parameters are continuously adjusted

This integrated architecture enables automated and continuous air purification.

6.4 Prototype Development

A prototype of the Liquid Tree system is developed using a transparent tank, microalgae culture, and monitoring sensors.

The system is tested in controlled conditions to evaluate its efficiency in reducing CO₂ levels and improving air quality.



VII. PERFORMANCE ANALYSIS

The performance of the Liquid Tree system is evaluated by comparing it with traditional air purification methods such as tree plantation.

A. CO₂ Absorption Efficiency

The system uses microalgae, which have higher photosynthetic efficiency compared to natural trees.

Experimental observations show that the system can absorb significant amounts of CO₂ in a shorter time, improving air quality effectively.

B. Oxygen Generation Performance

The microalgae continuously produce oxygen as a by-product of photosynthesis.

Results indicate that:

- Oxygen production is consistent and continuous
- Efficiency is higher than traditional plants in limited space
- Suitable for urban pollution control

C. Response Time

The system operates continuously, with real-time environmental interaction.

Unlike traditional trees, the Liquid Tree responds faster to increased CO₂ levels due to controlled conditions, ensuring efficient purification.

D. System Reliability

The integrated biological and mechanical system demonstrates stable performance over long durations.


However, performance may be affected by:

- Insufficient light availability
- Improper maintenance
- Environmental fluctuations

E. Overall Performance Impact

Overall, the Liquid Tree system significantly improves air quality in urban environments. It reduces carbon emissions, increases oxygen levels, and provides a compact alternative to traditional trees.

These advantages demonstrate its effectiveness as a sustainable solution for smart cities and environmental management systems.



VIII. CONCLUSION

The Liquid Tree (LIQUID3 Photobioreactor) demonstrates an effective and innovative approach for improving urban air quality using biological processes. The system integrates a photobioreactor tank, microalgae culture, environmental sensors, and control mechanisms to absorb carbon dioxide (CO₂) and generate oxygen in real time.

By utilizing the natural process of photosynthesis, the proposed system successfully captures CO₂ from the surrounding environment and converts it into oxygen, contributing to pollution reduction and environmental

sustainability. Experimental observations show improved air purification efficiency, faster response to environmental changes, and better space utilization compared to traditional tree plantation methods.

The results indicate that the system can operate efficiently under controlled environmental conditions and can continuously purify air with minimal delay. Although performance may be affected by factors such as insufficient light, improper maintenance, or environmental fluctuations, the prototype proves the feasibility of a compact and efficient air purification system.

Overall, the Liquid Tree provides a reliable and sustainable solution for urban pollution control, smart city development, and environmental management. Future improvements may include IoT-based monitoring systems, AI-driven optimization, and large-scale deployment to enhance efficiency, automation, and scalability.

IX. REFERENCES

[1] Borowitzka, M. A., "Microalgae for CO₂ Capture and Climate Change Mitigation," *Journal of Applied Phycology*, 2013.

(Reference for microalgae-based carbon capture systems.)

[2] Richmond, A., *Handbook of Microalgal Culture: Applied Phycology and Biotechnology*, Wiley, 2004.
(Provides theoretical concepts related to microalgae cultivation and applications.)

[3] Chisti, Y., "Biodiesel from Microalgae," *Biotechnology Advances*, 2007.
(Useful for understanding microalgae efficiency and biological processes.)

[4] Ugwu, C. U., Aoyagi, H., and Uchiyama, H., "Photobioreactors for Mass Cultivation of Algae," *Bioresource Technology*, 2008.
(Important research on photobioreactor design and operation.)

[5] Singh, J., and Gu, S., "Commercialization Potential of Microalgae for Biofuels Production," *Renewable and Sustainable Energy Reviews*, 2010.
(Reference for large-scale applications of microalgae systems.)

[6] Brennan, L., and Owende, P., "Biofuels from Microalgae—A Review of Technologies for Production," *Renewable and Sustainable Energy Reviews*, 2010.
(Reference for system efficiency and sustainability.)

[7] Wang, B., Li, Y., Wu, N., and Lan, C. Q., "CO₂ Bio-Mitigation Using Microalgae," *Applied Microbiology and Biotechnology*, 2008.

[8] Posten, C., "Design Principles of Photo-Bioreactors for Cultivation of Microalgae," *Engineering in Life Sciences*, 2009.