

“Long Range IoT Emergency Support System for Hilly and Remote Areas”

Aniket Kakade, Yash Chakor Ramkishn Chole, Prof Kolape Snehal

JSPM's Bhivrabhai Sawant Institute of Technology and Research
Wagholi. Pune. 412207 (Electronics and Telecommunication)

ABSTRACT

In many remote and rural regions, access to immediate emergency assistance remains a major challenge due to the lack of reliable communication infrastructure and limited network connectivity. This project, titled “Long Range Emergency Support System for Remote Areas,” aims to design and develop a robust and efficient solution to address this critical issue.

The system utilizes Lo-Ra (Long Range Communication) technology to enable long-distance data transmission without requiring continuous internet connectivity. It is integrated with an ESP32 microcontroller, GPS module for real-time location tracking, and emergency push buttons for user interaction. In emergency situations, the user can activate an alert that transmits location details and distress information to a central monitoring station or nearby receiver units.

Additionally, the system supports dual communication methods using Wi-Fi or GSM, where available, to improve reliability and ensure successful message delivery. The received information can be displayed on a mobile application or web-based monitoring dashboard, enabling authorities, rescue teams, or family members to respond quickly and effectively.

Keywords: Lo-Ra Communication, Emergency Alert System, GPS Tracking, IoT, Remote Area Connectivity, ESP.

1. INTRODUCTION

In today's world, safety and emergency response systems are becoming increasingly important, especially in remote and rural areas where communication infrastructure is limited. Existing emergency systems mainly rely on technologies such as mobile networks, internet connectivity, and centralized control systems. Most emergency support solutions depend on smartphones and applications that use GPS and internet services to send alerts. These systems work effectively in urban areas where network coverage is strong. However, in remote or isolated regions, these systems face major challenges due to poor or unavailable network connectivity.

Existing systems such as emergency helplines, mobile safety applications, and GPS tracking devices require continuous internet or cellular network availability. In areas such as forests, mountains, rural villages, or disaster-affected zones, network signals are often weak or completely unavailable. As a result,

users may fail to send distress signals during emergency situations.

Another limitation of current systems is their dependency on high-power devices and complex communication infrastructure. Many existing solutions are not designed for long-range communication without internet support. Additionally, these systems may not provide reliable real-time communication over long distances without depending on telecom networks.

Due to these limitations, there is a strong need for a reliable, low-power, and long-range communication system that can operate independently of traditional network infrastructure. This gap in existing emergency systems highlights the importance of developing an improved solution that ensures safety and communication even in remote and inaccessible areas.

2. Literature Survey

1] Baldan, N., et al. (2023)

Lo-Ra Based IoT System for Emergency Assistance and Safety in Mountaineering.

This paper presents an IoT and Lo-Ra-based emergency communication system designed for mountainous and remote areas. The proposed system enables users to send emergency alerts along with GPS location details without depending on cellular networks. The authors highlight the advantages of long-range communication and low power consumption, which make the system suitable for outdoor and rescue applications.

2] Sutopo, H., et al. (2024)

Lo-Ra Mesh-Based IoT GPS Tracking System for Mountain Climbers

This study proposes a Lo-Ra mesh network for tracking mountain climbers in difficult terrains. The system allows multiple nodes to communicate with each other, extending communication coverage and improving reliability. The mesh-based approach ensures continuous tracking and communication even if one node becomes unavailable, making it useful for trekking and rescue operations.

3] Kumar, A., & Singh, R. (2024)

Lo-Ra WAN and IoT-Based Landslide Early Warning System

This research introduces a Lo-Ra WAN-based IoT system for monitoring landslide conditions in remote areas. Different environmental sensors are used to collect real-time data, and warning alerts are generated whenever abnormal conditions are detected. The system improves disaster management by providing early warning communication in locations where conventional networks are limited.

4] Rahman, M., et al. (2024)

Design and Feasibility Analysis of Lo-Ra-Based Communication

This paper analyzes the performance and practicality of LoRa based communication systems for disaster management applications. The study evaluates communication range, energy efficiency, and implementation cost. The results show that LoRa technology is highly suitable for emergency communication in rural and disaster-prone regions because of its long-range capability and low power requirements. The paper also discusses limitations such as scalability and signal interference.

3. METHODOLOGY

The methodology for developing the proposed Long-Range IoT Emergency Support System focuses on creating a reliable and energy-efficient communication solution for remote and hilly regions where traditional network connectivity is limited. The system is designed using IoT and LoRa communication technology to provide long-distance emergency communication during critical situations.

Initially, the major communication problems and safety challenges faced in remote areas are identified. Based on these requirements, suitable technologies such as LoRa communication, GPS tracking, and ESP32 microcontroller integration are selected to ensure efficient data transmission over long distances with low power consumption.

The proposed system architecture consists of a GPS module, ESP32 controller, LoRa communication module, emergency push button, buzzer, and a mobile or web-based monitoring platform. During operation, the GPS module continuously collects location data, which is processed by the ESP32 microcontroller. When an emergency situation occurs, the user activates the emergency button, and the system immediately generates a local alert through the buzzer while transmitting the distress signal and location details using the LoRa module.

The transmitted information is received at the monitoring station or mobile application, where real-time alerts and location details are displayed for quick emergency response. The methodology also includes hardware interfacing, software programming using Arduino IDE and Embedded C, data processing, and implementation of real-time communication protocols to ensure reliable operation in remote environments.




Fig Block Diagram of system

Explanations the block diagram:

The system consists of a GPS Module that provides real-time location data to the **ESP32 Wi-Fi Module**, which acts as the main controller. Upon receiving the data, the ESP32 processes it and triggers a Buzzer for local alerts while simultaneously sending the information to the LoRa SX1278 Module for wireless transmission. The transmitted data is then received and displayed on a Mobile Application, enabling users to monitor emergency situations in real time.

4. REQUIREMENTS

1. Lo-Ra Module




The **LoRa SX1278 Module** is a low-power, long-range wireless communication device based on the Semtech SX1278 chip, widely used in IoT applications for remote monitoring and safety systems. It operates in license-free ISM bands (433/868/915 MHz) and supports communication ranges up to 5–10 km in line-of-sight conditions. Using LoRa spread spectrum modulation, it ensures reliable data transmission with low data rates (0.018–37.5 kbps) and high interference immunity. The module operates at 3.3V, features low power consumption, and communicates with microcontrollers via SPI interface, making it suitable for energy-efficient and long-distance communication systems.

GPS Module (Neo-6M) The **Neo-6M GPS Module** is a



The Neo-6M GPS Module compact device used for real-time location tracking by providing latitude, longitude, and altitude data with good accuracy. It communicates with microcontrollers via UART (TX/RX) and operates on 3.3V–5V. With features like an inbuilt antenna, backup battery, and fast signal acquisition, it is widely used in navigation, emergency alert, and IoT tracking systems.

2. LED



The **LED (Light Emitting Diode)** is a low-power component used for visual indication in electronic systems. It operates at 2V–3.3V with about 20mA current and emits light when forward biased. In the Smart Farm D-E-fence system, it indicates system status such as power ON/OFF, alerts, and communication activity, often working with a buzzer for audio-visual alerts.

3. ESP32



The **NodeMCU ESP32** is a powerful microcontroller widely used in IoT applications due to its high performance and built-in connectivity. It is based on a dual-core processor running up to 240 MHz and operates at 3.3V. The board supports Wi-Fi and Bluetooth communication, making it ideal for wireless projects. It offers multiple GPIO pins, analog inputs, PWM channels, and communication interfaces like UART, SPI, and I2C. With features such as low power modes and sufficient flash memory, it provides an efficient and flexible platform for developing smart and connected systems.

4. Buzzer



The **Buzzer** is an output component used to generate sound signals in electronic systems. It can be either active (produces sound with a direct DC supply) or passive (requires a microcontroller signal to generate tones). Typically operating between 3.3V and 12V, it can produce sound levels of around 85–100 dB. It works by converting electrical energy into sound through vibrations of a piezoelectric element or internal coil, making it useful for alerts and notifications in embedded systems.

5. Lithium Battery



The **Lithium Battery** is a lightweight and high-performance power source widely used in IoT and portable systems. It typically operates at a nominal voltage of 3.7V with a charging voltage of 4.2V and offers capacities ranging from 500 mAh to over 5000 mAh. Known for its high energy density, low self-discharge rate, and long life cycle (300–1000 recharge cycles), it provides efficient and reliable power. Due to these features, it is highly suitable for applications like emergency support systems where continuous and dependable power supply is essential.

2. Overall System & Result



Fig Result



Fig Overall Setup

5. Key Features & Advantages

1. **Real-Time Tracking:** To enable real-time GPS tracking of individuals in remote mountainous regions.
2. **Long-Range Communication:** To establish long-range, low-power communication using LoRa technology.
3. **Comprehensive Alert System:** To design an emergency alert system with a buzzer for local alerts and a mobile dashboard for remote monitoring.
4. **Low Power Consumption:** To ensure the device has low power consumption suitable for prolonged field usage.
5. **Enhanced Safety:** To improve safety and enable faster rescue operations during emergencies.

6. Conclusion:

The proposed IoT-based emergency support system provides an effective and reliable solution for communication in remote and hilly areas. By utilizing LoRa technology, the system enables long-range data transmission without relying on GSM or internet networks. It ensures real-time location tracking and instant emergency alerts, improving response time and safety. The system is cost-effective, energy-efficient, and suitable for applications such as trekking, disaster management, and rural safety. Future enhancements may include integration of health monitoring sensors, renewable energy sources, and advanced communication technologies to further improve system performance.

7. REFERENCES

1. Baldan, N., et al. (2023). LoRa-Based IoT System for Emergency Assistance and Safety in Mountaineering. *International Journal of Safety and Security Engineering*.Sutopo, H., et al. (2024).
2. LoRa Mesh-Based IoT GPS Tracking System for Mountain Climbers. *International Journal of Safety and Security Engineering*.Kumar, A. & Singh, R. (2024).
3. LoRaWAN and IoT-Based Landslide Early Warning System. *IEEE Conference on IoT in Disaster Management*.Rahman, M., et al. (2024).
4. Design and Feasibility Analysis of LoRa-Based Communication System for Disaster Management. *International Journal of Communication Systems*.Fernandez, J., et al. (2024).
5. Alaa, M., et al. (2019). "A Comparative Study of Low-Power Microcontrollers for IoT Applications," *IEEE Access*, Vol. 7, pp. 110234-110255.
6. Azzawi, M. A., et al. (2020). "Energy Efficient IoT: Battery Management and EnergyHarvesting Techniques," *Journal of Low Power Electronics and Applications*, Vol. 10,Issue 2.
7. Goursac, A., & El-Hoiydi, A. (2018). "A Comparative Analysis of LoRa, Sigfox, and
8. NB-IoT for IoT Applications," *Proceedings of the IEEE International Conference on Wireless and Mobile Computing, Networking and Communications (WiMob)*.
9. Kumar, S., et al. (2022). "IoT-Based Safety System for Trekkers using Arduino and GPS," *International Journal of Advanced Research in Computer and Communication Engineering*, Vol. 11, Issue 4.
10. Li,Y. & Zhang, W. (2021). "LoRaWAN for Remote Sensing Environmental Applications," *IEEE Sensors Journal*, Vol. 21, Issue 10, pp. 11785-11794.
11. Patel, R. & Singh, K. (2021). "Real-Time Tracking System for Hikers using GSM and Cloud," *2nd International Conference on Computation, Automation and Knowledge*
12. Sharma, et al. (2020). "IoT-Based Disaster Management System using GSM," *Proceedings of the 4th International Conference on Electronics, Communication and Engineering*.