

Modified-Leach: A Modified Cluster Based Routing Protocol for Wireless Sensor Network

¹Vijay Kumar, ²Shafi Jindal

¹Research Scholar, Department of Electrical Engg, JCDDM College of Engg, Sirsa, Haryana, India-125056

²Assistant Professor, Department of Electrical Engg, JCDDM College of Engg, Sirsa, Haryana, India-125056

ABSTRACT

Wireless detector network consists of enormous range of detector nodes that are willy-nilly deployed in AN unattended surroundings. Wireless detector networks are self-configurable and infrastructure less. The detector nodes in WSN are energy forced, as a result of their battery operated. Energy conservation and long time period of the network are major challenges during a detector network. Electronic communication consumes lots of WSN energy. There are several protocols are projected for power-efficient communication during a wireless detector network. The cluster based mostly routing protocols are best famed for increasing energy potency, stability and network time period of WSNs. Due to restrictions in WSNs, wherever the resources are restricted, several factors might have an effect on its performance and functioning. These factors are also system output, delay, and energy. During this paper, a bunch protocol has proposed to extend system output and system delay, and increase energy saving. During this paper, we have a tendency to propose a brand new routing technique known as changed - LEACH that may be applied to static detector networks to provide high performance.

Keywords: *Communication, Modified -LEACH, Routing, Sensor, WSN*

1. INTRODUCTION

Wireless detector Networks (WSNs) carries with it several detector nodes. The standard configuration of such a detector node during a WSN includes single or multiple sensing components, an information processor, human action elements and an influence supply. Normally, the sensing components perform measurements associated with the conditions existing at its close surroundings [1]. These measurements are reworked into corresponding electrical signals and are processed by the information processor. A sensor node makes use of its human action elements so as to transmit the information, over a wireless channel, to a base station (a sink node). By exploitation such a configuration, detector nodes in such WSNs have resource constraints like restricted energy, low storage capability, and weak computing ability [2]. What is more, because of unsafe operating surroundings, resources particularly the energy of detector nodes, wouldn't get replaced or recharged. Thus, associate degree economical energy saving

protocol is needed to prolong the network life. During this paper, we tend to propose associate degree energy-saving routing protocol that supported cluster technique. It follows the subsequent 2 considerations: firstly- maximizes the life of the network. Secondly- maximizes the quantity of knowledge message received by the sink node. Rather than imposing transmission energy constraints on each individual node, the whole energy consumption of the network ought to be thought-about [4]. The cluster head node collects knowledge from its neighbor nodes, then combination and sends that knowledge to the bottom station. this text devises a brand new technique to pick out the best nodes as cluster heads and alter the spherical time in each spherical. We tend to use the minimum spanning tree to send knowledge messages to the bottom station. That the nodes' die rate can decrease and eventually the network life time can increase.

LEACH ALGORITHM

LEACH (Low Energy adaptational bunch Hierarchy) is initial planned by Wendi B. Heinzelman of Massachusetts Institute of Technology [5]. This protocol provides a conception of spherical. LEACH protocol runs with several rounds. Every spherical contains 2 sections: cluster setup section and steady phase. Within the setup section, every node decides whether or not or to not become a cluster head for current spherical. The choice depends on call created by the node by selecting a random variety between zero and one. If the amount is a smaller amount than the brink $T(n)$ [6], the node becomes a cluster head for the present spherical. The brink is about as:

$$T(n) = \begin{cases} \frac{p}{1-p^{(r \bmod (1/p))}} & \text{if } n \in G; \\ 0 & \text{else} \end{cases}$$

Where p is that the chance of the node being elect as a cluster-head node, r is that the variety of rounds passed, and G is that the set of nodes that haven't been cluster-heads within the last $1/p$ rounds, $\bmod$ denotes modulo operator. Nodes that ar cluster heads

in spherical r shall not be elect within the next $1/p$ rounds.




Fig 1. Architecture of Leach

Fig.1 depicts a wireless device network protocol supported LEACH that is split into 3 clusters, the black circle in every cluster represents the cluster head, and therefore the remainder of the white circles indicate non-cluster head nodes. Every cluster encompasses a cluster head node. The protocol willy-nilly selects cluster head node circularly, the energy of the complete network load is equally distributed to every device node which may reach lower energy consumption and improve the network life.

II.RELATED WORK

2.1 Energy and output Analysis of stratified Routing Protocol (LEACH) for Wireless detector Network is projected by Rajesh Patel Sunil Pariyani Vijay Ukani in 2011 [8], Wireless detector networks (WSNs) have gained increasing attention from each the analysis community and actual users. The economical utilization of energy supply in a very detector node is extremely necessary criteria to prolong the life time of wireless detector network. Wireless detector networks have explored to several new protocols specifically designed for detector networks wherever energy thought is extremely crucial.

Most of importance, given to stratify routing protocols supported clump has higher measurability. There are a unit many energy economical stratified routing protocols among this LEACH is known protocol, authors have simulated LEACH in NS2 and analyzed performance of LEACH in terms of energy, output and lifelong.

2.2 Hierarchic routing protocol in wireless detector network is projected by Harneet Kour in a pair of 012 [5], Due to recent advancement and changes in

wireless detector network, numerous routing protocols have emerged.

Hierarchical-based routing may be a cluster based mostly routing during which high energy nodes square measure at random elite for process and causing knowledge whereas low energy nodes square measure used for sensing and send data to the cluster heads. This property of hierarchical-based routing contributes greatly to the network measurability, life and minimum energy. During this paper, we are going to discuss numerous hierarchic routing protocols in wireless detector networks.

DISADVANTAGES OF THE LEACH PROTOCOL

Although LEACH protocol prolongs the network lifespan in distinction to plane multi-hop routing and static routing, it still has issues. The cluster heads square measure elective at random, that the best variety and distribution of cluster heads cannot be ensured. The nodes with low remnant energy have an equivalent priority to be a cluster head because the node with high remnant energy.

Therefore, those nodes with less remaining energy could also be chosen because the cluster heads which is able to result that these nodes might die initial. The cluster heads communicate with the bottom station in single-hop mode that makes LEACH cannot be utilized in large-scale wireless detector networks for the limit effective communication vary of the detector nodes.[2]

III.THE PROPOSED PROTOCOL

Modified-LEACH is employed to get the optimum Cluster Head, maximize the network life time & schedulability bounds conjointly derived. [7]. Here the Cluster Head is no appointive supported most residual energy. Once every spherical, energy consumption of CH and regular nodes are calculated. From this calculated worth, those nodes contain higher residual energy are designated as CH. Cluster formation is analogous to LEACH. Modified-LEACH rule is predicated on residual energy, at completely different rounds nodes have most energy are designated as CH. that the drain rate of the nodes are linear and packet delivery rate is accrued.

At the top of every spherical, utilization of energy is healthier and therefore network time period is prolonged in higher level compared to alternative algorithms.

It conjointly supports for derivation life time bounds for playacting schedulability check to confirm

certainty of the nodes. This prediction is extremely abundant useful for real time WSN Fig.2 depicts.




Figure 2: Modified-LEACH of maximize the network life time.

The random choice rule for LEACH simply results in the imbalance of the keep energy of device nodes, thereby; the consumption of system energy is inflated. To make sure that the energy load is uniformly distributed throughout the network, the extra parameters together with the residual energy and also the consumed energy for transmittal information are applied to optimize the method of cluster head choice. The most plan of the improved cluster head choice rule is to avoid the lower residual energy nodes and better consumed energy nodes to be cluster-head. A brand new $T(n)$ is outlined as follow:

$$T_{new}(n) = \begin{cases} \frac{P_{head}}{1 - P_{head}^{(r \cdot \text{mod}(1/P_{head}))}} \cdot \frac{E_{current}}{E_{initial}}, & \text{if } n \in G; \\ 0, & \text{else} \end{cases}$$

Where the $E_{current}$ is that the residual energy of nodes at the r spherical, $E_{initial}$ is that the initial energy of nodes. By victimisation $T_{new}(n)$, {risk|the likelihood|the chance} for low residual energy nodes being cluster head is greatly reduced and also the possibility for top residual energy nodes being cluster head is enhanced.

$$P_{head} = \sqrt{\frac{N}{2\pi}} \sqrt{\frac{E_{fs}}{E_{mp}}} \frac{M}{d_{toBS}^2 \times N}$$

In the Modified-LEACH, the worth of p_{head} is dynamically calculated consistent with the formula (3). Then, detector node is arbitrarily appointed

variety between zero and one, if price of the quantity is a smaller amount than $T_{new}(n)$, the detector node is chosen because the cluster-head at the present spherical. In the Modified-LEACH protocol, the spherical time $T_{current}$ is outlined at the start of the spherical $R_{current}$. It depends on the best cluster size, instead of employing a constant spherical time T for each spherical within the network life. Then we are able to outline the present spherical time $T_{current}$ as follows:

$$T_{current} = NF_{avg} \cdot (M_{min} \cdot \sigma + \lambda)$$

Where, NF_{avg} is that the average range of frames for a cluster with size $1/p_{head}$. $M_{min} \cdot \sigma + \lambda$ is that the frame time of a cluster that has the minimum size (the minimum range of nodes M_{min}). When process the spherical time $T_{current}$ for the present spherical, the bottom station sends the cluster info and therefore the changed $T_{current}$ to all or any nodes within the network, so every node will verify its cluster and its time interval within the TDMA schedule.

IV. SIMULATION RESULTS

In this area, we primarily utilize reproductions to break down and assess the execution of the calculation. This paper utilizes the MATLAB to recreate the strategy. To check the enhanced calculation proposed, we will contrast the outcomes and LEACH.

A. Simulation Setup

The essential reenactment parameters for our model are said in Table I. The investigation is completed by utilizing a similar vitality source whose underlying vitality is 0.5J. The combination coefficient is 0.5. Each hub transmits a k bits information parcel per round to its group head. The span of a control parcel L_{ctrl} is 100 bits.

Table 1: Transmission line parameter

Description	Symbol	Value
Number of nodes	N	100
The initial node energy	$E_{initial}$	0.5J
Energy consumed by the amplifier to transmit at a short distance	E_{fs}	10pJ/bit/m ²
Energy consumed by the amplifier to transmit at a longer distance	E_{mp}	0.0013pJ/bit/m ⁴
Energy consumed in the electronics circuit to transmit or receive the signal	E_{elec}	50pJ/bit
Data packet	k	4000 bits
Control packet	L_{ctrl}	100 bits
Data aggregation energy	E_{da}	5pJ/bit/report
The cluster probability of LEACH	p	0.05
The Sensing area	$M \times M$	100m×100m




Fig 4: Alive Nodes (1700 98% dead)

V.SIMULATIONS AND ANALYSIS

A hundred sensing element nodes are organized every which way within the field of 100m×100m sq. meters. As shown in Fig.3, the sink node is found at position (50, 140) and every one node is not any longer mobile as long as they're placed. In WSNs, there are lots of parameters to judge a bunch of formulas. During this paper, the typical remaining energy of all nodes and therefore the variety of nodes alive are chosen to match the performance of the improved formula with LEACH. While not considering alternative external factors, if a node's energy is a smaller amount than zero, we tend to outline it as a dead node. Once all nodes within the network are dead, we tend to outline it as network failure. [6]




Fig 5 Previous dead node output (1756 all dead)




Fig 3: Dead Nodes




Fig 6 Previous live nodes




Fig7 : Cui new dead nodes (2061 all dead)

square measure less or their distances to base station square measure aloof from the nodes, as a result of the significant energy burden the cluster head can before long die and life time of network reduced. The future directions for routing in WSN vary from network structure to, application sorts to application demands. Completely different completely different} applications have different sensitivity factors. Completely different completely different} network styles have different constraints with relevancy variable challenges. There square measure completely different problems at style level of WSN, like node preparation, nonuniformity, localization and synchronization that has to be explored additional. There square measure varied protocols already developed for WSNs got to be compared with relevancy WSNs application categories.




Fig 8: New live nodes

VI.CONCLUSION AND FUTURE SCOPE

Proposed protocol describe Associate in Nursing energy-efficient multi-hop routing protocol mistreatment leveling in device node network for the aim of maximization of the life time of wireless device network and for the minimize energy consumption of device network. It chooses cluster head haphazardly within the levels of the info transmission within the network. The amount of the info transmission within the network has been defines by mistreatment the bottom station messages at the beginning of the wireless device networks. The cluster head choice technique at the amount is comparable to it of LEACH protocol that causes that the present energy of some cluster heads of cluster

References

- [1] R. Ahlswede , N. Cai , R. Li and R. W. Yeung "Network info flow", IEEE dealings on scientific theory, vol. 46, pp. 1204 -1216, 2011.
- [2] J. Saltzer , D. Reed and D. Clark "End-to-end arguments in system design", ACM dealings on computing system, vol. 2, no. 4, pp. 277 - 288, 2012
- [3] H. Balakrishnan , V. Padmanabhan , S. Seshan and R. Katz "A comparison of mechanisms for rising communications protocol performance over wireless links", IEEE/ACM Transactions on Networking (TON), vol. 5, no. 6, pp. 756 -769, 2013.
- [4] W. R. Heinzelman, J. Kulik, and H. Balakrishnan. "Adaptive protocols for info dissemination in wireless sensing element networks". In Proceedings of MobiCom'99, Seattle, WA, Aug. 2012.
- [5] G. Khanna, S. Bagchi, and Y. Wu. "Fault tolerant energy aware knowledge dissemination, protocol in sensing element networks". In Proceedings of DSN'04, June 2014.
- [6] J. Kulik, W. R. Heinzelman, and H. Balakrishnan. "Negotiation-based protocols for disseminative info in wireless sensing element networks". Wireless Networks, vol. 8, pp. 169-185, 2012.
- [7] W. B. Heinzelman, A. P. Chandrakasan, and H. Balakrishnan, "An Application-Specific Protocol design for Wireless Microsensor Networks", IEEE Transactions on Wireless Communications, vol. 1, pp. 660-670, Oct, 2012.
- [8] F. M. Omer, D. A. Basit, and S. G. Asadullah, "Multi-hop Routing with Low Energy adaptative cluster Hierarchy," Proc. International Conference on detector Technologies and Applications (SENSORCOMM 10), IEEE Press, , pp. 262-268, July, 2010.
- [9] Y. Zhang, K. Partridge and J. Reich, "Localizing tags exploitation mobile infrastructure". In Proceedings of the third International conference on location and context awareness (LoCA). Lecture notes in computing (LNCS 4718). Springer, pp. 279-296, Sep 20-21 2013