International Journal of Scientific Research in Engineering and Management (IJSREM)
Volume: 10 Issue: 10 | Oct - 2026 SJIF Rating: 8.659 ISSN: 2582-3930

Multi Robot Coordination for Swarm Robotics

Patil Bhavesh[1], Pawar Nakul[2], Sodanwar Paras[3], Pande Vighnesh[4], Deshmukh Y.V.[5]

[1]Student,E&TC & JSPM's Bhivrabai Sawant Polytechnic
[2]Student,E&TC & JSPM's Bhivrabai Sawant Polytechnic
[3]Student,E&TC & JSPM's Bhivrabai Sawant Polytechnic
[4]Student,E&TC & JSPM's Bhivrabai Sawant Polytechnic
[5]Lecture,E&TC & JSPM's Bhivrabai Sawant Polytechnic

Abstract - Swarm robotics leverages the collective behavior of decentralized, self-organized systems to perform tasks that are too complex or time-consuming for a single autonomous agent. This project presents a framework for multi-robot coordination utilizing a robust master-slave architecture to ensure synchronized movement and task execution. At the core of each robotic unit is a PIC microcontroller, selected for its efficient processing capabilities, real-time control, and seamless integration with peripheral hardware.

To achieve dynamic collaboration, the system relies on Radio Frequency (RF) communication to establish a reliable, low-latency network between the master controller and the slave robots. The master robot is responsible for processing high-level objectives and broadcasting precise navigational commands via RF modules. The slave robots receive these signals and drive their DC motors accordingly to maintain formation and execute localized movements.

The embedded control logic and communication protocols are developed using C programming within the MPLAB environment, ensuring highly optimized, hardware-level execution. This coordinated approach demonstrates a scalable and fault-tolerant method for robotic collaboration, offering significant potential for real-world applications such as automated environmental exploration, search and rescue operations in hazardous environments, and decentralized industrial automation.

Key Words: Multi-Robot Coordination, Swarm Robotics, Cooperative Control, Distributed Algorithms, Multi-Agent Systems, Autonomous Navigation, Task Allocation, Collision Avoidance, and Swarm Intelligence.

1.INTRODUCTION

Swarm robotics is an emerging field of robotics that focuses on the coordination and cooperation of multiple robots to perform tasks efficiently. It is inspired by the collective behavior of natural systems, such as ants, bees, birds, and fish, which work together to achieve common goals. Instead of relying on a single complex robot, swarm robotics uses several simple autonomous robots that communicate and cooperate with one another to complete tasks.

Multi-robot coordination is an important part of swarm robotics. It allows multiple robots to share information, divide tasks, avoid collisions, plan paths, and work together in a coordinated manner. Each robot can use sensors, communication modules, and control algorithms to understand its surroundings and make decisions. By following predefined rules and exchanging information, the robots can achieve collective behavior without requiring a central controller for every decision.

The main objective of multi-robot coordination is to improve the efficiency, reliability, flexibility, and performance of robotic systems. If one robot fails, other robots may continue performing the assigned task. This makes swarm robotics suitable for applications where a single robot may be insufficient, expensive, or inefficient.

Swarm robotics has applications in various fields, including agriculture, industrial automation, warehouse management, disaster rescue operations, environmental monitoring, military surveillance, space exploration, and search-and-rescue missions. For example, multiple robots can search a disaster-affected area simultaneously, while coordinating their movements to cover a larger region in less time.

The development of artificial intelligence, machine learning, wireless communication, and advanced sensors has improved the capabilities of multi-robot systems. Technologies such as the Robot Operating System (ROS), Bluetooth, Wi-Fi, and Zigbee can support robot communication and coordination, depending on the system requirements.

However, several challenges remain in swarm robotics, including communication delays, limited battery life, obstacle avoidance, task distribution, localization errors, and maintaining coordination when individual robots fail.

Effective coordination algorithms are required to overcome these challenges and ensure safe and efficient operation.

Therefore, the project **Multi Robot Coordination for Swarm Robotics** focuses on understanding how multiple robots can communicate, cooperate, and coordinate their movements to accomplish a common objective.

The system aims to demonstrate the principles of collective intelligence, autonomous decision-making, task allocation, and cooperative navigation. This project provides a foundation for developing intelligent robotic systems capable of performing complex tasks with improved efficiency, scalability, and reliability.

2. Body of Paper

2.1 Overview of Solar Tracking Systems

Multi Robot Coordination for Swarm Robotics is a robotic system in which multiple robots work together to perform a common task. The system is inspired by the collective behavior of social insects, such as ants and bees, where individual members follow simple rules to achieve complex goals as a group.

In swarm robotics, each robot operates as an individual unit with its own sensors, controller, actuators, and communication

capabilities. The robots exchange information with one another or respond to their surroundings to coordinate their actions. Depending on the system design, coordination can be achieved through centralized control, decentralized control, or distributed algorithms.

2.2 Working Principle of Dual Axis Solar Tracking System

The working principle of Multi Robot Coordination for Swarm Robotics is based on the cooperation and coordination of multiple autonomous robots to achieve a common objective. Each robot is equipped with sensors, a microcontroller, motors, a power supply, and a wireless communication module. Initially, the robots sense their surrounding environment and collect information about obstacles, nearby robots, and their positions. This information is processed by the control system using predefined algorithms to determine the appropriate actions. The robots communicate with one another to share information, allocate tasks, coordinate movements, and avoid collisions. Depending on the application, the robots may follow a leader or make decisions independently using a decentralized control approach.

They work simultaneously to complete tasks such as searching an area, transporting materials, monitoring the environment, or navigating through obstacles. If an obstacle is detected or a robot fails, the coordination algorithm can adjust the movement or redistribute tasks among the remaining robots. Thus, multi-robot coordination enables a group of robots to perform complex tasks efficiently, reliably, and cooperatively with minimal human intervention.




Fig: Block Diagram

2.3 Major Components of the System

2.3.1 PIC Microcontrollers

A PIC (Peripheral Interface Controller) microcontroller is a programmable integrated circuit developed by Microchip Technology. It is used to control electronic devices and embedded systems by processing input signals, executing programmed instructions, and generating output signals. PIC microcontrollers are widely used in automation, robotics, industrial control, sensor systems, and communication applications.



Fig: PIC Microcontrollers

2.3.2 DC Motors

A DC motor (Direct Current Motor) is an electromechanical device that converts direct-current electrical energy into mechanical energy. It produces rotational motion that can be used to move robotic wheels, conveyor belts, and other mechanical systems. In swarm robotics, DC motors are essential components because they enable individual robots to move, turn, and coordinate their movements with other robots.



Fig: DC Motor

2.3.3 RF Transmitter

A RF (Radio Frequency) Transmitter is an electronic device that transmits data wirelessly using radio waves. It is used in communication systems to send information from one device to another without requiring a physical connection. In multi-robot coordination for swarm robotics, an RF transmitter can send commands, status information, sensor readings, and coordination messages between robots or from a central controller to individual robots.



Fig: RF Transmitter

2.3.4 RF Receiver

A RF (Radio Frequency) Receiver is an electronic device that receives wireless signals transmitted by an RF transmitter and converts them into usable data. It is commonly used in wireless communication, remote-control systems, automation, and robotics. In multi-robot coordination for swarm robotics, an RF receiver enables a robot to receive movement commands, task assignments, and status information from a central controller or another robot.



Fig: RF Transmitter

2.3.5 Coil Antennas

A coil antenna is a type of antenna made by winding a conductive wire into a coil shape. It is used to transmit or receive electromagnetic signals in wireless communication systems. Coil antennas are commonly used in radio-frequency (RF) circuits, RFID systems, remote controls, and compact electronic devices. In multi-robot coordination for swarm robotics, a suitable coil antenna can support wireless signal transmission and reception, depending on its design and operating frequency.



Fig: Coil Antennas

2.4 System Architecture and Control Algorithm of Multi Robot Coordination for Swarm Robotics describes the arrangement of hardware and software components that enable multiple robots to communicate, coordinate, and perform tasks collectively. The system consists of PIC microcontrollers, sensors, DC motors, motor driver circuits, RF transmitters, RF receivers, and coil antennas. Each robot operates as an individual unit and exchanges information with other robots or a central controller through wireless communication.

The PIC microcontroller acts as the main control unit of each robot. It receives input signals from sensors and wireless communication modules, processes the information according to the programmed control algorithm, and generates output signals for controlling the motors. RF transmitters and receivers provide wireless data exchange, while compatible antennas support signal transmission and reception. Sensors help robots detect obstacles and understand their surroundings. The motor driver supplies the current required to operate the DC motors, allowing the robots to move forward, reverse, turn, and stop. By combining sensing, communication, and motion control, the system enables multiple robots to perform cooperative tasks.




Fig: Flowchart

The basic control algorithm follows these steps:

1. Initialize the PIC microcontroller, sensor inputs, RF transmitter and receiver, and DC motor control system.
2. Read the sensor values to detect obstacles and collect information about the surrounding environment.
3. Receive wireless data and coordination messages from other robots or the central controller.
4. Process the sensor readings and received messages to determine the robot's current status and assigned task.
5. Compare the sensor readings with predefined threshold values to identify obstacles or changes in the environment.
6. Adjust the motor speed and direction when an obstacle is detected or a movement correction is required.
7. Coordinate robot movements and task execution by exchanging information with other robots.
8. Transmit the robot's status and task information when required.
9. Repeat the process continuously while ensuring safe movement, obstacle avoidance, and compliance with the robot's movement limits.

This feedback-based method enables the system to respond to changes in sunlight direction. However, sensor calibration, suitable tolerance settings, motor response time, and mechanical accuracy influence the overall tracking performance.

2.5 Performance Evaluation

The performance of a multi-robot coordination system for swarm robotics can be evaluated by analyzing the efficiency of multiple robots working together and comparing their performance with individual robot operation under similar conditions. Important parameters include task completion time,

task success rate, communication reliability, coordination efficiency, obstacle avoidance accuracy, movement accuracy, and power consumption.

The task completion time is the total time required for the robots to complete an assigned task. The task success rate can be calculated using:

$$\text{Task Success Rate} = \frac{N_s}{N_t} \times 100$$

Where,

- N_s = Number of successfully completed tasks
- N_t = Total number of assigned tasks

The communication reliability of the system can be measured by comparing the number of successfully received messages with the total number of messages transmitted.

$$\text{Communication Reliability} = \frac{M_r}{M_t} \times 100$$

Where:

- M_r = Number of messages successfully received
- M_t= Total number of messages transmitted

The improvement in task completion time can be calculated by comparing the time required by a single robot with the time required by the coordinated robot swarm.

$$\text{Time Improvement} = \frac{T_s - T_m}{T_s} \times 100$$

Where:

- T_s= Task completion time for a single robot
- T_m = Task completion time for multiple coordinated robots

For practical testing, the robots should perform the same or comparable tasks under similar environmental conditions. Measurements should be repeated several times to account for variations in obstacle placement, communication interference, sensor readings, and battery voltage. The system should also be tested with different numbers of robots to evaluate scalability and coordination performance.

The overall benefit of multi-robot coordination should account for the time saved, successful task execution, communication overhead, and additional energy consumed by the robots. The results can be used to determine whether cooperation improves system performance compared with individual robot operation. Actual experimental measurements are necessary to validate the effectiveness of the proposed swarm robotics system.

2.6 Advantages and Limitations

The major advantage of a multi-robot coordination system is its ability to use multiple autonomous robots to perform tasks cooperatively, potentially improving efficiency and reducing task completion time compared with a single robot. Each robot can collect sensor data, communicate through RF modules, and execute commands using a PIC microcontroller and motor driver. The system also provides practical experience in embedded systems, wireless communication, sensor interfacing, motor control, and autonomous navigation. Such systems are useful for educational demonstrations, industrial automation, warehouse operations, environmental monitoring, and search-and-rescue research.

However, multi-robot coordination systems have certain limitations. They require additional hardware, communication modules, sensors, batteries, and maintenance for each robot. Wireless communication can be affected by signal interference, obstacles, and limited transmission range. Coordinating multiple robots also increases the complexity of control algorithms and collision avoidance. Sensor errors, motor variations, and battery limitations may affect overall performance. Therefore, reliable communication protocols, efficient task allocation, suitable sensor calibration, collision-avoidance algorithms, and effective power management are important for reliable operation.

Parameter	Single Robot	Centralized Multi-Robot System	Decentralized Swarm Robotics
Number of robots	One	Multiple	Multiple
Movement	Individual control	Coordinated by a central controller	Coordinated through local rules and communication
Task execution	Sequential or individual	Tasks assigned centrally	Tasks distributed among robots
System complexity	Low	Moderate to high	Moderate to high
Initial cost	Relatively low	High	Depends on robot count and hardware
Control system	One controller	Central controller and robot controllers	Individual robot controllers
Communication	May not be required	Centralized communication	Robot-to-robot or local communication
Collision avoidance	Between robot and obstacles	Managed through central planning and local sensing	Managed through local sensing and coordination rules
Scalability	Limited by one robot's capabilities	Depends on central controller capacity	Can be expanded, subject to communication and coordination limits

Typical applications	Inspection and simple automation	Warehouse fleets and coordinated manufacturing	Search-and-rescue, exploration, and distributed monitoring

Table 1. Comparison of Fixed, Single-Axis, and Dual-Axis Solar Tracking Systems

Parameter	**Centralized Coordination**	**Decentralized Coordination**	**Distributed Coordination**
Working principle	A central controller manages robot movements and task assignments	Each robot makes decisions using local sensor data and available messages.	Robots share computational and coordination tasks to achieve a common objective.
Main components	Central controller, robot controllers, sensors, RF modules, motors	PIC microcontrollers, sensors, RF modules, motor drivers	Multiple robot controllers, sensors, communication modules, coordination algorithms
Decision-making	Performed mainly by the central controller	Performed independently by individual robots	Shared among robots according to the algorithm
Communication	Robots communicate with the central controller	controller Robots exchange local information when required	Robots exchange information to support collective decisions
System complexity	Moderate to high	Moderate	Moderate to high
Response time	Depends on the central controller and communication delays	Can respond quickly to local environmental changes	Depends on the coordination algorithm and information exchange
Scalability	May be limited by central controller capacity	Can expand with suitable local control rules	Can scale with suitable communication and coordination methods
Reliability	Central controller failure may affect the entire system	May tolerate individual robot failures, depending on system design	May tolerate individual robot failures, depending on system design
Initial cost	Moderate to high	Depends on the number of robots and hardware	Depends on communication, processing, and robot requirements
Main limitation	Dependence on the central controller	Limited local information may reduce global coordination	Communication overhead and coordination complexity
Suitability	Warehouse management and coordinated manufacturing	Autonomous navigation and local obstacle avoidance	Swarm robotics, distributed exploration, and cooperative search

Table 2. Comparison of Centralized, Decentralized, and Distributed Multi-Robot Coordination Methods

2.7 Applications and Future Scope

Multi-robot coordination in swarm robotics can be used in industrial automation, warehouse management, agriculture, search and rescue operations, environmental monitoring, and educational research laboratories. The system can be further improved by incorporating AI-based decision-making, IoT-based monitoring, wireless data transmission, real-time status tracking, and remote performance analysis. Additional improvements may include advanced sensors, efficient communication protocols, intelligent task allocation, collision-avoidance algorithms, and energy-efficient motor control. Future developments should focus on balancing coordination accuracy, communication reliability, energy consumption, system cost, and robot performance. This balance is essential for making multi-robot coordination a practical, reliable, and economically suitable solution for different swarm robotics applications.

3. CONCLUSIONS

Multi-robot coordination in swarm robotics is a promising technique for improving the efficiency of multiple robots working together to perform complex tasks. A PIC microcontroller-based system using sensors, RF transmitter and receiver modules, motor drivers, and DC motors provides a practical platform for demonstrating cooperative robot movement and wireless communication. Its performance must be verified through controlled experiments measuring task completion rate, communication reliability, response time,

collision avoidance, and power consumption. Further improvements in coordination algorithms, sensor accuracy, wireless communication, and energy management can enhance the reliability, scalability, and practical usefulness of the swarm robotics system.

ACKNOWLEDGEMENT

We would like to express our sincere gratitude to our **SPI Coordinator, Mr. M. N. Waghmode**, for his valuable guidance, encouragement, and support throughout the preparation of this review paper on *"Multi Robot Coordination For Swarm Robotics"*

We would also like to express our sincere gratitude to our **Project Coordinator, Mr. M. N. Waghmode**, for his valuable guidance, continuous encouragement, and technical support throughout the preparation of this review paper.

We are also thankful to **Mr. N. E. Bhutekar, Head of the Electronics and Telecommunication (E&TC) Department**, for his valuable suggestions, academic guidance, and support.

We extend our sincere thanks to our respected Principal, **Dr. P. T. Kale**, Vice Principal, **Dr. M. S. Yadav**, and Academic Dean, **Dr. V. S. Dabhade**, for their encouragement and academic support.

We are grateful to all faculty members of the E&TC Department for their cooperation, technical assistance, and constructive suggestions. Finally, we thank **JSPM Bhivrabai Sawant Polytechnic, Wagholi, Pune**, for providing the necessary facilities and a supportive learning environment to complete this review paper successfully.

REFERENCES

[1] Brambilla, M., Ferrante, E., Birattari, M., Dorigo, M.: Swarm robotics: a review from the swarm engineering perspective. Swarm Intelligence 7 (2013) 1–41. https://doi.org/10.1007/s11721-012-0075-2

[2] Şahin, E.: Swarm robotics: From sources of inspiration to domains of application. In: Swarm Robotics, Lecture Notes in Computer Science, vol. 3342 (2005) 10–20. https://doi.org/10.1007/978-3-540-30552-1_2

[3] Dorigo, M., Birattari, M., Brambilla, M.: Swarm robotics. Scholarpedia 9(1) (2014) 1463. https://doi.org/10.4249/scholarpedia.1463

[4] Bayındır, L.: A review of swarm robotics tasks. Neurocomputing 172 (2016) 292–321. https://doi.org/10.1016/j.neucom.2015.05.116

[5] Sahin, E., Spears, W.M. (eds.): Swarm Robotics: SAB 2004 International Workshop. Lecture Notes in Computer Science, vol. 3342. Springer, Berlin (2005). https://doi.org/10.1007/978-3-540-30552-1

[6] Şahin, E., Winfield, A.F.T. (eds.): Special Issue on Swarm Robotics. Swarm Intelligence 2 (2008).

[7] Parker, L.E.: Multiple mobile robot systems. In: Siciliano, B., Khatib, O. (eds.) Springer Handbook of Robotics. Springer, Berlin (2008) 921–941. https://doi.org/10.1007/978-3-540-30301-5_40

[8] Cao, Y.U., Fukunaga, A.S., Kahng, A.B.: Cooperative mobile robotics: Antecedents and directions. Autonomous Robots 4 (1997) 7–27. https://doi.org/10.1023/A:1008855018923

[9] Gerkey, B.P., Matarić, M.J.: A formal analysis and taxonomy of task allocation in multi-robot systems. The International Journal of Robotics Research 23(9) (2004) 939–954. https://doi.org/10.1177/0278364904045564

[10] Matarić, M.J.: The Robotics Primer. MIT Press, Cambridge, MA (2007).

[11] Şahin, E., Spears, W.M., Winfield, A.F.T.: Swarm robotics. In: Swarm Robotics: SAB 2004 International Workshop. Lecture Notes in Computer Science, vol. 3342. Springer, Berlin (2005) 3–4.

[12] Winfield, A.F.T.: Foraging Robots. In: Swarm Robotics: SAB 2004 International Workshop. Lecture Notes in Computer Science, vol. 3342. Springer, Berlin (2005) 25–42.

[13] Dorigo, M., Birattari, M., Trianni, V., et al.: Evolving self-organizing behaviors for a swarm-bot. Autonomous Robots 17 (2004) 223–245.

[14] Couzin, I.D., Krause, J., Franks, N.R., Levin, S.A.: Effective leadership and decision-making in animal groups on the move. Nature 433 (2005) 513–516. https://doi.org/10.1038/nature03236

[15] Reynolds, C.W.: Flocks, herds and schools: A distributed behavioral model. Computer Graphics 21(4) (1987) 25–34. https://doi.org/10.1145/37402.37406

[16] Arkin, R.C.: Behavior-Based Robotics. MIT Press, Cambridge, MA (1998).

[17] Siegwart, R., Nourbakhsh, I.R., Scaramuzza, D.: Introduction to Autonomous Mobile Robots. 2nd edn. MIT Press, Cambridge, MA (2011).

[18] Corke, P.: Robotics, Vision and Control: Fundamental Algorithms in MATLAB. 2nd edn. Springer, Cham (2017).

[19] Microchip Technology Inc.: PIC16F877A Data Sheet: 28/40/44-Pin Enhanced Flash Microcontrollers. Microchip Technology Inc.

[20] Microchip Technology Inc.: PIC Microcontroller Technical Documentation and Application Notes. Microchip Technology Inc. https://www.microchip.com/

BIOGRAPHIES

	Patil Bhavesh Student, JSPM's BSP bhavesh2008patil@gmail.com
	Pawar Nakul Student, JSPM's BSP pawarnakul32@gmail.com
	Sodanwar Paras Student, JSPM's BSP parassodanwar47@gmail.com
	Pande Vighnesh Student, JSPM's BSP vighneshpande28@gmail.com
	Mr. Deshmukh Y.V. Lecturer, JSPM's BSP ydeshmukh_entc@jspmbspoly.edu.in