

NeuroFusion: Multimodal Emotion Recognition using EEG and Deep Learning

Hasini Chowdary G¹, Yaseen Sutar², Kushal Surath³, Vikas S⁴, Vegi Fernando⁵

¹Student, Department of CSE (AIML), Dayananda Sagar University, Bengaluru, India

²Student, Department of CSE (AIML), Dayananda Sagar University, Bengaluru, India

³Student, Department of CSE (AIML), Dayananda Sagar University, Bengaluru, India

⁴Student, Department of CSE (AIML), Dayananda Sagar University, Bengaluru, India

⁵Associate Professor, Department of CSE (AIML), Dayananda Sagar University, Bengaluru, India

Abstract - The identification of emotions based on electroencephalogram signal patterns has attracted considerable interest in the brain computer interface domain owing to its various uses in the health sector, human-computer interaction, and monitoring of mental states. This work introduces NeuroFusion, a multi-modal deep learning model aimed at increasing emotion classification accuracy by incorporating EEG signal characteristics together with deep neural networks. The system carries out the preprocessing, feature extraction, and classification steps of the input EEG signals using deep learning algorithms that exploit both temporal and spatial brain patterns. The experimental results reveal that the developed technique outperforms conventional machine learning methods in terms of accuracy. The design of the method allows for efficient scalability, making it ideal for real-time applications. The source code used in developing the algorithm is available through an open-source platform.

Key Words: EEG, Emotion Recognition, Deep Learning, BCI, Multimodal Learning

1. INTRODUCTION

Recognition of emotions has been one of the areas of focus for researchers studying brain computer interfaces and artificial intelligence due to the varied applications that it may offer in the healthcare industry, human-computer interaction, and mental well-being evaluation. Since EEG signals reflect brain activity directly, their usage in emotion recognition can be very effective. On the other hand, they tend to be very complex and thus not easy to classify using traditional machine learning algorithms.

The recent advances in deep learning have offered promising ways of obtaining information from complex biological signals. The utilization of neural networks helps extract both spatial and temporal characteristics of complex datasets. There are, however, some problems that need to be addressed, including high error rate, inability to generalize and poor feature extraction.

In this paper, we introduce NeuroFusion, a multimodal deep learning approach intended to increase emotion recognition by EEG signals. Our proposed method involves using efficient preprocessing, feature extraction, and deep learning models to classify emotions more accurately. This framework is tested using benchmark data sets and its results are compared to other methods.

Our contributions in this study include the creation of a novel multimodal learning model, efficient feature representation of EEG signals, and improved classification results by applying deep learning methods. Our framework will be made publicly available using a repository link for future studies and experiments.

1.1 Problem Statement

Recognizing emotions from EEG signals poses a difficult challenge due to the complexity and noise present in the brain signals. Classical machine learning algorithms have not been successful in capturing the spatio-temporal dynamics of the EEG signals, which results in reduced classification accuracy. Subject variation and weak feature representation make the problem even more difficult. Hence, there exists a need for an efficient and accurate system for classifying EEG signals for emotion recognition.

1.2 Proposed Solution

To overcome these difficulties, NeuroFusion, a deep learning-based multimodal framework for emotion recognition from EEG signals, is proposed in this paper. The NeuroFusion framework involves signal pre-processing, feature extraction, and deep learning models for effective analysis of EEG signals for emotion recognition purposes. By employing neural networks, the system can model complex patterns within the EEG signals for improved predictions.

2. METHODOLOGY

The proposed NeuroFusion system is designed to perform emotion recognition using EEG signals through a structured pipeline consisting of preprocessing, feature extraction, and classification using deep learning models. The overall workflow of the system is illustrated in Fig. 1.




Fig -1: Proposed NeuroFusion System Architecture

Firstly, EEG signals are recorded and processed by applying certain filters to eliminate the noises and artifacts in the signal. This helps ensure that the signal is clean and ready to be analyzed. Following the processing stage, the next step is to extract appropriate features from the EEG signal that will capture the patterns related to emotions.

After feature extraction, the process continues by applying deep learning algorithms where the signal's temporal and spatial representations can be learned. This involves training the model to recognize the emotional state of the user.

2.1 Data Preprocessing

The EEG signal is very susceptible to interference from the external environment, including eye movement, muscle activation, and noise.

In the proposed method, the following preprocessing steps will be taken:

1. Noise reduction through filtering techniques such as band-pass filters
2. Normalizing the EEG signal to ensure consistency among different data samples
3. Artifacts removal due to eye blinks and muscle activity

This will enable the machine learning algorithm to extract relevant information from brain activities without being affected by external factors.

2.2 Feature Extraction

Feature extraction is vital when it comes to translating raw EEG signal data into useful forms for proper classification. For this study, statistical and frequency domain features will be extracted to analyze unique traits associated with brain activities.

The statistical features like mean, variance, and standard deviation are extracted from the signal. On the other hand, frequency features are extracted from the data using fast Fourier transform. This method is important since it helps in understanding the signal across various frequency bands, which are related to emotions. These features help in

providing an informative yet simplified form of EEG signals to facilitate emotion classification.

2.3 Classification using Deep Learning

The feature extraction results in extracted features that become input to the deep learning algorithm for classifying emotions.

Deep learning algorithms are known for their effectiveness in EEG analysis since they are able to find complicated patterns not easily extractable with other approaches.

Classification consists of the following actions:

- Feature input to the neural network model
- Model training on labeled EEG data
- Optimization of model parameters

A simple architecture of the deep learning algorithm utilized in this study is depicted in Fig 2.




Fig -2: Deep Learning Model for Emotion Classification

3. RESULTS AND DISCUSSION

Performance evaluation of the proposed NeuroFusion model on EEG datasets was carried out to determine its efficacy in emotion classification. To measure the efficiency in terms of improvement in accuracy and performance, various machine learning models were compared with NeuroFusion.

Table -1: Accuracy Comparison of Different Models

Model	Accuracy(%)
SVM	72
Random Forest	78
KNN	75
CNN	85
NeuroFusion Model	91

Table 1 shows that the suggested NeuroFusion model exhibits the highest accuracy compared to other models under

consideration. Conventional ML methods such as SVM, KNN, and Random Forest have been shown to yield relatively poor results due to the inability to detect complex patterns in EEG data. On the contrary, deep learning models yield better performance due to higher accuracy levels.

Accuracy of Various ML Models



Fig -3: Accuracy Comparison of Different Models

It can be observed from Fig 3 that the NeuroFusion model outperforms other models with an appreciable margin. The bar chart indicates the superiority of deep learning algorithms in dealing with EEG signals, thus yielding improved performance levels.




Fig -4: Confusion Matrix of NeuroFusion Model

Fig 4 gives an indication of the stability of the NeuroFusion model when predicting emotional states. It shows how accurate the algorithm performs when making predictions across different categories.

3.1 Performance Analysis

The enhanced performance achieved by the NeuroFusion model is due to several important reasons:

- Preprocessing of the EEG data to eliminate noises and other types of artifacts

- Feature extraction process based on both time-domain and frequency-domain techniques
- Capability of deep learning algorithms to recognize complex patterns
- Combining different processing stages into one architecture

The combination of these reasons leads to better performance and accuracy than that obtained through other methods.

3.2 Discussion

Despite the good performance metrics obtained with the developed approach, some issues have been identified. First, individual EEG signals are characterized by variability, which can impact their recognition. Second, deep learning algorithms tend to be computationally complex when compared to other methods.

At the same time, it should be noted that the benefits offered by the system outweigh potential shortcomings. Improved accuracy and advanced feature recognition make this approach valuable for emotion recognition using EEG signals.

3.3 Limitations and Future Work

Despite the enhanced accuracy obtained by the proposed NeuroFusion model in the recognition of emotions based on EEG signals, some limitations remain. One of the major problems of EEG signals is their high complexity that varies for each individual. This could hinder the performance of the model in terms of generalizability across different datasets.

Moreover, the effectiveness of the proposed model strongly depends on the preprocessing quality and the amount of available labeled samples. In turn, the other challenge to overcome is related to the computational complexity of deep learning models, which can complicate their deployment in real-time conditions.

Nonetheless, the proposed system has shown excellent performance in various tests. Future research might consider increasing the size of the dataset for improving the generalizability of the model, reducing computational complexity through optimization, and utilizing hybrid approaches, among others.

4. CONCLUSIONS

The proposed NeuroFusion system presents an effective approach for emotion recognition using EEG signals by leveraging deep learning techniques. The integration of preprocessing, feature extraction, and classification enables the model to capture complex patterns in brain activity and achieve higher accuracy compared to traditional methods.

The experimental results demonstrate that the proposed model outperforms conventional machine learning algorithms in terms of classification performance. The use of deep learning allows the system to learn both temporal and spatial features, resulting in improved prediction accuracy.

Although the model shows promising results, challenges such as variability in EEG signals and computational complexity still exist. Future work can focus on optimizing the model for

real-time applications and improving generalization across different datasets.

The implementation of the proposed system is made publicly available to support reproducibility and further research in the field of emotion recognition.

The implementation and source code of the proposed system are available at:

<https://github.com/apex-parzival/NeuroFusion.git>

ACKNOWLEDGEMENT

It is a pleasure to thank **Dr. Vegi Fernando A, Associate Professor in the Computer Science and Engineering (AIML) Program at Dayananda Sagar University**, for her valuable guidance, constant encouragement, and support which made this project possible in its current form. The valuable advice and inputs provided by her have been of great help in taking this project to its present state.

It is our pleasure to thank the faculty and the institute for giving us an appropriate environment to carry out our study. Lastly, we are thankful to those who, directly or indirectly, helped us in completing this project.

REFERENCES

- [1] J. A. Miranda-Correa, M. K. Abadi, N. Sebe, and I. Patras, "AMIGOS: a dataset for affect, personality and mood research on individuals and groups," *IEEE Transactions on Affective Computing*, vol. 12, no. 2, pp. 479–493, Nov. 2018, doi: 10.1109/taffc.2018.2884461.
- [2] P. Zhong, D. Wang, and C. Miao, "EEG-Based emotion recognition using regularized graph neural networks," *IEEE Transactions on Affective Computing*, vol. 13, no. 3, pp. 1290–1301, May 2020, doi: 10.1109/taffc.2020.2994159.
- [3] M. P. Kalashami, M. M. Pedram, and H. Sadr, "EEG feature extraction and data augmentation in emotion recognition," *Computational Intelligence and Neuroscience*, vol. 2022, pp. 1–16, Mar. 2022, doi: 10.1155/2022/7028517.
- [4] D. Saraswat *et al.*, "Explainable AI for Healthcare 5.0: Opportunities and Challenges," *IEEE Access*, vol. 10, pp. 84486–84517, Jan. 2022, doi: 10.1109/access.2022.3197671.
- [5] J. Xie *et al.*, "A Transformer-Based approach combining deep learning network and Spatial-Temporal information for raw EEG classification," *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, vol. 30, pp. 2126–2136, Jan. 2022, doi: 10.1109/tnsre.2022.3194600.
- [6] T. N. Alotaiby, S. A. Alshebeili, F. M. Alotaibi, and S. R. Alrshoud, "Epileptic seizure prediction using CSP and LDA for scalp EEG signals," *Computational Intelligence and Neuroscience*, vol. 2017, pp. 1–11, Jan. 2017, doi: 10.1155/2017/1240323.
- [7] S. Sakhavi, C. Guan, and S. Yan, "Learning temporal information for Brain-Computer interface using convolutional neural networks," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 29, no. 11, pp. 5619–5629, Mar. 2018, doi: 10.1109/tnnls.2018.2789927.
- [8] R. W. Picard, "Affective Computing," MIT Press, 1997.

- [9] S. Koelstra *et al.*, "DEAP Dataset for Emotion Analysis," *IEEE Transactions*, 2012.

BIOGRAPHIES



Hasini Chowdary G is a student in the Department of CSE (AIML) at DSU, Bengaluru. Her areas of interest include artificial intelligence, machine learning, and brain-computer interface systems. She is particularly interested in applying deep learning techniques to real-world problems. She has worked on projects related to emotion recognition and intelligent systems.



Yaseen Sutar is a student in the Department of CSE (AIML) at DSU, Bengaluru. His interests include data science, machine learning, and software development. He has contributed to projects involving data analysis and intelligent systems. He is passionate about building scalable and efficient solutions.



Kushal Surath is a student in the Department of CSE (AIML) at DSU, Bengaluru. His areas of interest include deep learning, neural networks, and artificial intelligence. He has experience working on projects related to predictive modeling and data-driven applications.



Vikas S is a student in the Department of Computer Science and Engineering (AIML) at Dayananda Sagar University, Bengaluru. His interests include machine learning, computer vision, and intelligent systems. He has been involved in developing projects that focus on real-world applications of AI and data analysis.

Dr. Vegi Fernando A is currently an Associate professor in CSE (AIML) Program at DSU. She has Completed her UG at Manonmaniam Sundaranar University, Tirunelveli, PG from Anna University and her Doctorate of Philosophy (PhD) in the field of Deep Learning at Anna University, Chennai. She has around 17 years of teaching experience in various domains. She has been a resource person at various FDP's, Speaker at various International and National conferences / workshops. Her areas of interest include Deep Learning, Cloud Computing, Programming and analysis of algorithms.