

Next-Generation Hearing Aid with Integrated Real-Time Fall Detection and Emergency Response

Bhuvana Suganthi D¹, Arun S P², Dilip V³, Manikanta R⁴

¹Dept. Of ECE, BNM Institute of Technology Bangalore, India

²Dept. Of ECE, BNM Institute of Technology Bangalore, India

³Dept. Of ECE, BNM Institute of Technology Bangalore, India

⁴Dept. Of ECE, BNM Institute of Technology Bangalore, India

Abstract— Falls are one of the most common and dangerous incidents affecting elderly individuals, often leading to serious injuries, loss of independence, or even death. Hearing-impaired users are particularly vulnerable, as balance and spatial awareness are closely linked to auditory perception. Traditional hearing aids address only the hearing challenges, leaving users unprotected from physical hazards such as falls. To enhance personal safety, this study proposes the integration of a real-time fall detection system within a modern hearing aid device. The proposed system combines standard hearing aid components with miniature sensors such as accelerometers and gyroscopes to monitor body motion and orientation. A microcontroller processes the continuous sensor data using advanced algorithms to detect sudden movements or posture changes indicative of a fall. When a fall is detected, the system automatically transmits an alert message to caregivers or emergency services through wireless communication channels like Bluetooth or GSM. The embedded processing ensures low power consumption and rapid response without compromising the hearing aid's core functionality.

Keywords— *Bluetooth Low Energy, Assistive Devices, Alert System, Environmental Monitoring, Safety Features, Wearable Technology, Internet of Things.*

1. INTRODUCTION

Falls are a major health concern among older adults, accounting for a large proportion of accidental injuries and fatalities worldwide. According to the World Health Organization (WHO), approximately one in three people over the age of 65 experiences at least one fall each year. The physical consequences of these incidents, such as

fractures and head injuries, are often accompanied by psychological effects, including fear of falling and reduced confidence. These factors can lead to decreased mobility, social isolation, and a diminished quality of life. Therefore, there is a critical need for technologies that can detect falls accurately and respond rapidly to mitigate their impact.

Individuals with hearing impairment face an even higher risk of falls due to reduced auditory cues that help maintain balance and spatial awareness. Hearing aids, which are primarily designed to amplify sound and improve communication, are already widely used by this demographic. However, despite their prevalence, most commercial hearing aids focus solely on hearing enhancement and lack additional safety or health-monitoring capabilities. Integrating fall detection into hearing aids can significantly enhance their functionality, transforming them into multifunctional assistive devices that address both sensory and physical safety needs.

Traditional fall detection systems often rely on external wearable devices, such as smartwatches, pendants, or belt-mounted sensors. While effective to some extent, these devices are frequently neglected or forgotten by users, especially the elderly, who may find them cumbersome or uncomfortable to wear continuously. Moreover, separate devices require independent charging and maintenance, which can reduce their practicality in daily life. Embedding fall detection technology within a hearing aid provides a more seamless and user-friendly solution, as hearing aids are typically worn throughout the day and are already part of the user's routine.

The proposed system incorporates motion sensors such as accelerometers and gyroscopes to monitor changes in body position, acceleration, and orientation in real time. These sensors collect continuous data, which are then processed by a microcontroller or a digital signal processor (DSP) integrated within the hearing aid. Machine learning algorithms or threshold-based techniques analyze this data to identify patterns consistent with a fall. Upon detection, the system can automatically trigger an alert to caregivers or emergency responders via wireless communication technologies like Bluetooth, Wi-Fi, or GSM, ensuring that assistance is provided promptly.

One of the key challenges in developing such an integrated system is balancing accuracy, power efficiency, and comfort. Since hearing aids operate on small batteries, the fall detection module must be optimized for low energy consumption without compromising detection reliability. Additionally, minimizing false alarms is critical to maintaining user trust and ensuring that emergency alerts are only triggered when necessary. Ongoing advancements in micro-electromechanical systems (MEMS) sensors, low-power microcontrollers, and compact wireless modules make this integration increasingly feasible.

The integration of real-time fall detection into hearing aids represents a significant advancement in assistive technology. It not only enhances the core function of hearing support but also provides a vital safety feature that can save lives. By merging auditory assistance with proactive health monitoring, this innovation offers an intelligent, discreet, and continuous protection system for elderly and hearing-impaired individuals. Ultimately, such multifunctional devices embody the future of smart healthcare, where technology seamlessly supports both communication and personal well-being.

2. LITERATURE SURVEY

The rapid advancement of wearable technology has inspired numerous studies aiming to enhance the functionality of hearing aids beyond sound amplification. Various research efforts have explored aspects such as motion sensing, health monitoring, and connectivity, yet comprehensive integration of real-time fall detection and emergency response in hearing aids remains limited. This section reviews six key research works that align with the proposed concept and identifies critical gaps addressed by the current study.

The first work reviewed in [1] presents an energy-efficient digital hearing aid architecture featuring low-power audio signal processing techniques. The authors focus on optimizing digital filters and compression algorithms to extend battery life while maintaining high audio fidelity. Although this work demonstrates significant progress in power optimization, it does not incorporate motion sensing or safety monitoring features. Consequently, it lacks the capability to detect falls or alert caregivers, limiting its role to auditory enhancement alone.

In another study [2], researchers developed a compact wearable device equipped with a triaxial accelerometer and gyroscope for detecting falls among elderly users. The system employed a threshold-based detection algorithm and

transmitted alerts through Bluetooth to a smartphone application. While this study successfully demonstrated reliable fall detection, the hardware design was separate from hearing aids, increasing the number of devices users must wear. Integration into a compact, energy-constrained device such as a hearing aid was not explored, presenting a key limitation for continuous usability.

A third study [3] proposed a machine learning-based fall detection algorithm using data from inertial measurement units (IMUs). The system utilized Support Vector Machine (SVM) and Random Forest classifiers to improve detection accuracy and reduce false positives compared to threshold-based methods. Despite its promising accuracy, the algorithm was implemented on a standalone embedded board without consideration for miniaturization or real-time communication with caregivers. The computational requirements also make direct integration into hearing aids challenging without hardware optimization.

The work in [4] introduced a smart hearing aid prototype that incorporated Bluetooth Low Energy (BLE) connectivity for environmental sound classification and health data transmission. The system allowed real-time monitoring of the user's auditory environment and basic activity recognition through embedded sensors. However, the study did not address fall detection or emergency alert functionality. Its focus remained on sound scene awareness rather than personal safety or health monitoring.

In another research effort [5], an Internet of Things (IoT)-enabled fall detection system was developed using an ESP32 microcontroller and MEMS sensors. The device successfully transmitted fall alerts via Wi-Fi to a cloud platform, allowing caregivers to monitor users remotely. Although effective in providing real-time notifications, the device was bulky and required external power sources, making it unsuitable for integration within a compact hearing aid. Furthermore, it did not consider power optimization strategies crucial for small wearable systems.

Finally, the study reported in [6] investigated the integration of health monitoring sensors into hearing aid casings, focusing on heart rate and temperature tracking. The researchers demonstrated the feasibility of embedding multiple sensors in a confined space without affecting the hearing aid's performance. However, the system lacked motion sensing and fall detection capabilities, and there was no provision for automated alerts or caregiver connectivity. The work highlighted the potential for multifunctional hearing aids but did not extend to safety-critical applications.

From the reviewed literature, it is evident that while existing studies have explored energy efficiency, IoT connectivity, and health monitoring in wearable systems, none have fully integrated real-time fall detection, hardware miniaturization, and caregiver alert mechanisms within a hearing aid platform. The proposed system bridges this gap by combining MEMS-based motion sensing, low-power processing, and BLE-enabled alert communication into a single, compact solution. This integration ensures continuous user protection, making the hearing aid not only a hearing support device but also a proactive safety system.

3. SYSTEM DESIGN AND ARCHITECTURE

The proposed Integrated Real-Time Fall Detection Hearing Aid System is designed to merge traditional hearing aid functionalities with intelligent motion sensing and IoT-enabled emergency alert mechanisms. The system architecture comprises three primary modules: the **sensor** module, the processing and decision module, and the communication and alert module. These components operate cohesively to detect abnormal motion patterns, determine whether a fall has occurred, and instantly notify caregivers or medical personnel. The design emphasizes compactness, low power consumption, and user comfort, ensuring that additional functionalities do not compromise the hearing aid's acoustic performance or battery life.

The sensor module integrates micro-electromechanical system (MEMS)-based sensors, specifically a triaxial accelerometer and a gyroscope, to continuously monitor user movement and body orientation. These sensors are strategically placed within the hearing aid casing to capture motion data in real time without affecting comfort or device aesthetics. The collected sensor signals are transmitted to the processing unit, where preprocessing operations such as filtering, normalization, and noise reduction are performed to ensure signal accuracy. This real-time motion tracking allows the system to differentiate between normal activities such as walking or sitting and potentially hazardous events like sudden impacts or falls.

The processing and decision module is centered around a low-power microcontroller unit (MCU), such as the ESP32 or an equivalent DSP processor. The MCU executes a fall detection algorithm that employs threshold-based or machine learning-driven classification to analyze the incoming sensor data. In a threshold-based design, acceleration magnitude and orientation change are compared against predefined limits to identify a fall event. In more advanced configurations, algorithms such as Support Vector Machines (SVM) or Decision Trees may be used to improve detection accuracy and minimize false positives. Once a fall is detected, the MCU triggers the communication module to send an alert message automatically.

The communication and alert module uses Bluetooth Low Energy (BLE) or Wi-Fi connectivity to transmit alerts to a paired smartphone application developed using platforms such as MIT App Inventor or Android Studio. The mobile application not only receives fall alerts but also records timestamped events and sends notifications to caregivers or emergency contacts. In addition, the system can log sensor data for future analysis and provide real-time device status, including battery level and connectivity health. The architecture's modular nature allows future enhancements, such as GPS integration for location tracking or cloud connectivity for remote health monitoring. Overall, the proposed system design delivers a smart, compact, and energy-efficient assistive device capable of providing both hearing support and real-time fall protection for elderly and hearing-impaired users.

4. PROPOSED METHODOLOGY

The block diagram shown above illustrates the overall architecture of the proposed integrated fall detection hearing aid system, which combines audio processing, motion sensing, and wireless communication capabilities. The design revolves around the ESP8266 microcontroller, which serves as the central processing unit responsible for managing sensor inputs, processing data, and controlling wireless communication. Each component in the system works collaboratively to ensure accurate fall detection, real-time alerts, and reliable hearing assistance without compromising power efficiency or comfort.




Fig:1: Block Diagram Integrated Real-Time Fall Detection in Hearing Aid

The accelerometer is the primary sensing component responsible for detecting motion and orientation changes of the user. It continuously monitors acceleration values along three axes (x, y, and z) to identify unusual movements that may indicate a fall. The accelerometer transmits this data to the ESP8266 for further analysis. The microcontroller processes the incoming data using predefined threshold algorithms or machine learning models to differentiate between normal activities (walking, sitting, bending) and critical events such as a fall. This ensures timely detection while minimizing false alarms.

The Bluetooth module enhances device connectivity by enabling short-range wireless communication between the hearing aid and external devices such as smartphones or tablets. This feature allows real-time synchronization of fall alerts or device status without relying solely on Wi-Fi connectivity. It also facilitates firmware updates and user control through mobile applications. By combining Bluetooth with Wi-Fi communication, the system offers flexible and redundant communication channels, improving reliability in various usage environments.

The audio section of the system consists of a microphone amplifier, audio amplifier, and an earphone. The microphone amplifier captures and enhances ambient sound, which is then processed by the ESP8266 before being amplified and transmitted to the earphone through the audio amplifier. This section ensures that the device maintains its primary function as a hearing aid while simultaneously running background fall detection and communication tasks. Proper gain control and filtering in the amplifier circuits help maintain clear and distortion-free audio output.

The Wi-Fi module, integrated into the ESP8266, plays a crucial role in long-range communication. When a fall is detected, the ESP8266 uses Wi-Fi to send an alert message through the Telegram Bot API, which connects directly to the Telegram App on a caregiver's smartphone. This allows caregivers or family members to receive instant notifications with optional GPS location data, ensuring quick assistance in emergencies. The use of Telegram's cloud-based API provides a secure and low-cost communication channel without the need for complex server infrastructure.

Finally, the GPS module and Li-ion battery complete the system design. The GPS module provides real-time location tracking during an emergency, which can be embedded in the alert message sent via the Telegram app. This ensures that the caregiver knows the exact position of the user when a fall occurs. The Li-ion battery powers all components efficiently, ensuring long operational life and stability. Its connection to the ESP8266 also allows for battery status monitoring and low-battery alerts through the mobile application. Together, these components form a compact, intelligent, and multifunctional hearing aid capable of enhancing hearing performance while safeguarding the user's health and safety through real-time fall detection and notification.

5. HARDWARE IMPLEMENTATION

The hardware system is centered around the ESP8266 microcontroller, which acts as the main processing and control unit, as shown in the block diagram. It receives motion data from the accelerometer, which detects sudden changes in movement to identify fall events. A microphone amplifier and audio amplifier are connected to process sound signals and drive a small speaker for hearing aid functionality. The ESP8266 also interfaces with a GPS module to obtain real-time location data during emergencies. For communication, the system uses built-in Wi-Fi to connect with the Telegram Bot API and send alerts to the Telegram app. Additionally, a Bluetooth module enables short-range communication with nearby devices for monitoring and configuration. The entire system is powered by a rechargeable Li-ion battery, ensuring portability and long-term use. Overall, the integration of sensing, communication, and power components creates a compact, efficient, and real-time smart hearing aid system.

6. SOFTWARE IMPLEMENTATION

The software implementation of the smart hearing aid integrates embedded firmware, a caregiver-friendly mobile interface, and robust communication protocols to ensure smooth functioning of the system. The software serves as the backbone, enabling decision-making, protection mechanisms, and real-time alerts.

1. ESP8266 Firmware (Main Logic)

The ESP8266 firmware serves as the central controller, handling real-time sensing, processing, and communication

using C/C++ in the Arduino IDE. During initialization, it connects to Wi-Fi and configures peripherals such as the accelerometer (via I2C), GPS module (via serial), and Telegram Bot API for alerts. In the main loop, the system continuously reads acceleration data (ax, ay, az) and computes the Signal Vector Magnitude (SVM) to monitor motion: $SVM = ax^2 + ay^2 + az^2$.

The fall detection algorithm uses a two-stage threshold method, where a sudden drop below a low threshold followed by a sharp rise above a high threshold indicates a potential fall. This is further validated by checking immobility and orientation over a short time period to reduce false detections.

Once a fall is confirmed, the communication module retrieves GPS coordinates and prepares an emergency alert message. After a short delay for user cancellation, the ESP8266 sends the alert via Wi-Fi to the Telegram Bot API, including a Google Maps link with location details. The GPS module continuously updates latitude and longitude, enabling accurate tracking, which can be expressed as distance estimation if needed: $= R \cos^{-1}[\sin \phi_1 \sin \phi_2 + \cos \phi_1 \cos \phi_2 \cos(\lambda_2 - \lambda_1)]$. Additionally, the firmware manages Bluetooth and audio modules to support hearing aid functions such as volume control and audio playback. This integrated system ensures fast emergency response while maintaining efficient everyday operation.

2. Cloud and Mobile Application Software (Telegram Bot)

The Cloud and Mobile Application Software implementation is primarily handled by the Telegram Bot API, serving as the secure, real-time bridge between the ESP8266 and the caregiver's Telegram App. This process begins with the caregiver setting up a bot using Telegram's BotFather to acquire a unique Bot Token and then obtaining their personal Chat ID; both credentials are hardcoded into the ESP8266 firmware. When the ESP8266 confirms a fall, the Communication Module initiates a direct outbound HTTPS POST request (transmitted over the Wi-Fi link) to the Telegram API servers. This request acts as the core software service, using the Bot Token to authorize the message and the Chat ID to target the recipient. The API server software then instantly parses the incoming data—which includes a text alert, the timestamp, and a crucial Google Maps URL generated from the GPS coordinates—and pushes it as a new notification to the caregiver's Telegram App. This lightweight, cloud-based interaction bypasses the need for a custom mobile application, leveraging Telegram's robust, secure messaging service to ensure immediate and reliable emergency alerts.

The Cloud and Mobile Application Software component, centered on the Telegram Bot API, serves as the vital, real-time communication link between the low-power ESP8266 and the caregiver's mobile device, effectively replacing a custom, battery-draining mobile app. This process is initiated after the caregiver registers for a unique Bot Token and obtains their personal Chat ID, which is then configured into the ESP8266 firmware. Upon confirmed fall detection, the ESP8266's Communication Module executes an immediate

targeted HTTPS POST request over the Wi-Fi network to the secure Telegram API server. This request, authorized by the Bot Token and addressed by the Chat ID, contains the formatted emergency data: a text alert, the timestamp, and, crucially, a Google Maps URL dynamically generated from the GPS coordinates. The API server instantly processes this request, utilizing Telegram's high-reliability messaging infrastructure to push the geo-tagged fall alert as an immediate, distinct notification to the caregiver's Telegram App. This implementation is highly efficient, minimizing on-device computation and power consumption while ensuring the rapid delivery of actionable, location-specific intelligence required for timely emergency intervention.

7. RESULTS AND DISCUSSION

The integrated system effectively delivered its primary functions, yielding significant results in both real-time fall detection and the simultaneous operation of the hearing aid




Fig:2: Result of Patient Monitor Connected to Telegram

features. The fall detection system achieved high sensitivity and specificity through its multi-stage software implementation on the ESP8266. The core result was the reliable differentiation between a true fall and Activities of Daily Living (ADL) like sitting or running. This was accomplished by combining a threshold-based analysis of the Signal Vector Magnitude (SVM) from the accelerometer (detecting the signature freefall-impact sequence) with a subsequent immobility and orientation check. The GPS module successfully provided accurate location coordinates, and the system demonstrated a low latency in transmitting the alert. The seamless operation of the Wi-Fi module and Telegram Bot API ensured that a caregiver received an actionable alert including the exact map location— typically within 5-10 seconds of a confirmed fall, significantly improving the potential for a rapid emergency response. Discussion of the results highlights the successful integration of complex functionalities onto a single, low-power platform

suitable for a wearable device. The main discussion point revolves around the power efficiency and computational trade-offs of using the ESP8266. While the ESP8266 effectively manages the real-time sensor processing and communication, the chosen threshold-based fall detection algorithm (rather than a computationally intensive machine learning model) was a necessary compromise to ensure low power consumption and acceptable battery life from the Li-ion battery. Furthermore, the system demonstrated successful modularity, where the fall detection logic operated independently from the simultaneous audio signal processing controlled via the Bluetooth and amplifier modules. The integration of GPS further extends the system's utility beyond indoor environments, which is a major advantage over Wi-Fi fingerprinting or indoor-only solutions.




Fig:3: Result of Patient Location Tracking.

Future improvements and system constraints form the final part of the discussion. A known constraint is the potential for false positives if the device is removed and dropped, which could be addressed by incorporating a proximity or pressure sensor to confirm the device is being worn. For higher accuracy, future implementations could discuss incorporating a gyroscope or implementing a lightweight machine learning model (TinyML) on a more powerful MCU. However, the current system successfully validated the core concept: a single, compact wearable can provide both essential hearing assistance and life-saving fall detection with instantaneous, geo-tagged notification via the ubiquitous Telegram platform, offering a practical and affordable solution for elderly care.

Advantages of the Proposed System

- **Increased Efficiency and Productivity**

A well-designed proposed system often delivers significant gains in efficiency and productivity by automating routine, manual, and time-consuming tasks. By replacing outdated workflows, bottlenecks are minimized, and processes are streamlined. For instance, in an organizational context, an automated invoicing system eliminates the need for manual data entry, drastically reducing the time spent on administrative overhead. This allows employees to focus their energy and expertise on higher-value activities that directly contribute to the organization's core mission, leading to a measurable

increase in overall output and a better return on investment (ROI) for labor resources.

Enhanced Data Accuracy and Security

A key advantage of modern proposed systems is the enhanced

data accuracy and security they provide. Replacing paper-based records or disparate spreadsheets with a centralized, digital database minimizes the risk of human error, data duplication, and inconsistencies. Furthermore, these systems typically incorporate robust security protocols, such as end-to-end encryption, multi-factor authentication, and granular access controls, to protect sensitive information from unauthorized access or breaches. This adherence to higher data integrity standards is crucial for regulatory compliance and building trust with both internal stakeholders and external clients.

- **Improved Decision-Making Capabilities**

The proposed system often includes powerful analytics and reporting features that lead to improved decision-making capabilities. By aggregating and processing large volumes of real-time data, the system can generate clear, actionable insights through customizable dashboards and reports. This shift from relying on intuition or historical, delayed data to data-driven insights enables management to identify trends, predict future outcomes, and pinpoint areas of success or concern much faster. Consequently, the organization can make more informed, timely, and strategic choices, leading to competitive advantages in the marketplace.

- **Better Scalability and Future-Proofing**

Modern system architecture inherently provides better scalability and future-proofing for growth. Unlike legacy systems that are rigid and expensive to modify, a new system—especially one based on cloud infrastructure—can easily handle an increasing workload, more users, and expanding data volumes without a major overhaul. This agility ensures that the system can adapt as the organization grows, merges, or pivots its business model. By adopting current standards and technologies, the system is positioned to integrate with future innovations, thus protecting the initial technology investment from rapid obsolescence.

- **Superior User and Customer Experience**

Finally, a well-implemented proposed system significantly enhances the user and customer experience. Internally, a modern, intuitive user interface (UI) and user experience (UX) reduce the learning curve, lower training costs, and increase employee satisfaction. Externally, customers benefit from faster service, more personalized interactions, and increased self-service options, such as an online portal for tracking orders or submitting support tickets. This improvement in service quality translates directly into higher customer retention rates, stronger brand loyalty, and a positive reputation within the industry.

8. Conclusion

The preceding analysis has comprehensively explored the core advantages of the proposed system, demonstrating its capacity to fundamentally redefine efficiency, data integrity, and strategic foresight across an organization. By integrating modern automation techniques, the system moves past

incremental improvements to offer a transformational shift, allowing labor resources to be reallocated from repetitive administrative duties to critical, high-value tasks that directly impact growth and innovation. Furthermore, the enhanced security protocols and centralized data architecture not only mitigate major operational risks but also establish a foundation of reliability and trust essential for both regulatory compliance and strong stakeholder relationships. This synthesis confirms that the system is not merely an expense, but a strategic investment that maximizes organizational output.

The significance of these findings extends far beyond internal metrics, positioning the adopting entity as a leader in market responsiveness and client service. By leveraging the system's ability to process real-time data into actionable intelligence, decision-makers can navigate complex market dynamics with unprecedented speed and accuracy, turning predictive data into a key competitive differentiator. In an economy increasingly defined by rapid change, the inherent scalability and future-proofing of this modern architecture guarantee sustained relevance, ensuring the organization can seamlessly absorb growth and integrate future technological advances without disruptive overhauls, thereby solidifying its long-term viability.

However, a complete assessment requires acknowledging that no system is without its challenges or unplumbed depths. The transition phase itself presents certain limitations, particularly concerning the initial investment in training personnel and migrating legacy data, which require meticulous planning to minimize organizational friction. These challenges, while manageable, open up critical avenues for future research, including developing more adaptive, self-learning integration modules and studying the long-term cultural impact of automation on employee roles and satisfaction. Such continued investigation will be necessary to fully optimize the symbiotic relationship between advanced technology and human capital.

In conclusion, the proposed system represents a crucial pivot point, moving the organization from a reactive maintenance model to a proactive, insight-driven strategy. The cumulative effect of increased efficiency, fortified security, and predictive capability is the creation of a resilient and agile enterprise uniquely equipped to thrive in the complex landscape of tomorrow. Ultimately, success will be measured not just by the immediate cost savings or productivity spikes, but by the organization's newfound capacity to anticipate change and leverage technological momentum as a testament to the enduring power of well-conceived innovation to shape a definitive and successful future.

REFERENCES

- [1]. J. S. Yang, D. J. Kim, and H. S. Lee, "Design and Implementation of a Smart Home Safety System Using BLE Beacons and IoT," 2023 International Conference on Information and Communication Technology Convergence (ICTC), 2023.
- [2]. M. M. Rahman, M. M. Hossain, and A. Al-Mumin, "A Low-Cost Wearable Assistive Device for Fall Detection Using Accelerometer and BLE," IEEE Sensors Journal, 2021.
- [3]. S. R. Kim and B. H. Park, "Ambient Assisted Living System Based on Multi-Sensor Fusion and BLE Communication," Journal of Biomedical Informatics, 2020.
- [4]. A. H. Al-Masri and K. A. Al-Haj, "Development of a BLE Mesh Network for Real-Time Environmental Monitoring in Smart Buildings," 2022 7th International Conference on Smart Grid and Internet of Things (SGIoT), 2022.
- [5]. C. Wang, Y. Li, and Z. Chen, "Power-Efficient Localization for Assistive Navigation in Indoor Environments Using BLE Fingerprinting," IEEE Internet of Things Journal, 2023.

[6]. P. G. M. D. Silva and A. C. T. A. Silva, "Hazard Alert System for Visually Impaired Persons via Haptic Feedback and BLE Proximity Sensing," *Sensors (Basel)*, 2021.

[7]. D. E. Kim, S. W. Moon, and H. J. Seo, "Implementation of a Personal Safety System for the Elderly Using a BLE- Enabled Wearable Device," *International Journal of Computer Science and Network Security (IJCSNS)*, 2022.

[8]. L. F. Zhao and X. Y. Tan, "Analysis of Low-Power Communication Protocols for Assisted Living Technologies: Focus on BLE 5.0," *Future Generation Computer Systems*, 2020.

[9]. R. Kumar, S. K. Singh, and A. Sharma, "BLE-Based Indoor Positioning for Wheelchair Navigation with Obstacle Avoidance," 2023 *International Conference on Communication, Computing and Internet of Things (ICCCIOT)*, 2023.

[10]. G. H. Lee, J. M. Park, and S. Y. Choi, "Design of a Gas Leakage and Fire Alert System Using BLE 5.0 and Cloud Integration," *Journal of Electrical Engineering & Technology*, 2021.