

Rail Surface Crack Identification and Obstacle Detection Using IOT

B. Vijay Kumar
dept. of CSE(AI&ML)

Assistant professor

Vignana Bharathi Institute of
Technology

Hyderabad, Telangana

banda.vijaykumar@vbithyd.ac.in

J. Nithin

dept. of CSE(AI&ML)

Vignana Bharathi Institute of
Technology

Hyderabad, Telangana

nithin.naikj4267@gmail.com

M. Prathyusha

dept. of CSE(AI&ML)

Vignana Bharathi Institute of
Technology

Hyderabad, Telangana

mekalapathyusha8@gmail.com

K. Sathwik Reddy

dept. of CSE(AI&ML)

Vignana Bharathi Institute of
Technology

Hyderabad, Telangana

sathwikreddykankanala@gmail.com

Abstract—Railway safety is a top priority due to ongoing accidents and security issues. This paper introduces the "RailTel Safety Solutions" project, which is an autonomous robotic system made to improve railway safety. The system creates an obstacle-avoiding robot that can detect and navigate around obstacles on its own. It uses ultrasonic sensors for real-time obstacle detection and can also find cracks in the railway tracks. When an issue is detected, the system logs the exact location using a GPS module and sends immediate alerts to a control station via a GSM communication module. This method allows for real-time monitoring, reduces accident risks, and improves maintenance efficiency.

Keywords—Railway Safety, Obstacle Detection, Crack Detection, Robotics, Ultrasonic Sensors, GPS, GSM

I. INTRODUCTION


In the fast-paced world of railway operations, safety and security are constant concerns. Despite ongoing efforts, accidents, security breaches, and emergencies still pose significant risks, making it necessary to find new ways to improve safety. Current safety systems often depend on a mix of physical infrastructure, manual safety procedures, and basic surveillance. However, these systems have many drawbacks. They often provide limited surveillance coverage, lack integration among various safety components, and rely too much on manual intervention. These issues can delay the detection and response to safety threats, affecting both passenger safety and operational efficiency. To overcome these challenges, this project presents an autonomous robotic system for monitoring railway tracks. The system is built to detect obstacles, such as debris or foreign objects, and can also identify structural issues like cracks on the tracks. By utilizing robotics, the system can offer continuous, real-time monitoring without the need for manual oversight. This literature survey is compiled exclusively from the works referenced and discussed within the two provided base papers: Railway Track Crack Detection and Obstacle Detection and Avoidance for Autonomous Electric Vehicle. Reference numbers correspond to the citations in the original base papers.

Existing research in crack detection for railways has focused on automating the process to eliminate slow and labour-

intensive manual examination. The literature presents several methods, including an LED-LDR sensor assembly [3], but this approach is limited by environmental requirements. Other researchers have used IR sensors with Bluetooth technology [4] and a mix of ultrasonic and PIR sensors [5] for fault detection. The idea of a specific, autonomous "Railway Track Crack Detection Vehicle" [2] has been investigated, along with "Railway Track Crack Detection and Data Analysis" [6]. Additionally, a separate method includes the use of image processing specifically for "Crack Detection in Railway Track" [1].

At the same time, research on autonomous vehicles emphasizes safety through effective obstacle detection and avoidance mechanisms that include both detection and control [2]. Comparisons of sensors [1] suggest that ultrasonic sensors are often better for obstacle detection than IR and LASER sensors [1], since IR sensors detect shorter distances than LASER [1]. Perception solutions also involve LiDAR for detailed 3D mapping [5]; however, sensor fusion is necessary because a single sensor is not enough [3]. Various avoidance techniques have been described, such as using fixed-mounted or rotating sonar sensors and laser scanners [2] or employing IR and PIR motion sensors [8]. Studies have explored the autonomous navigation of a micro-bus [7] and autonomous vehicles using a full mapping GPS system [9]. Simulation models in tools like MATLAB/Simulink validate autonomous electric vehicles and their control logic [6], supporting research aimed at creating an "Obstacle Avoiding Robot" [10] and the "Development of an Obstacle Avoiding Robot" [11].


II. SYSTEM ARCHITECTURE



III. METHODOLOGY

The system needs multiple essential components to operate properly. The hardware system consists of Ultrasonic sensors for obstacle detection, and a GPS module for real-time position tracking. A GSM communication module sends alerts, and a central microcontroller manages all operations on a mobile robotic unit. The microcontroller runs a control program which manages data processing software to analyze sensor readings and decision-making logic for navigation and hazard stopping, and communication protocol for alert formatting and GSM module transmission.

The system operates through five distinct modules, which the Control Module (microcontroller) supervises. The process starts with the Sensor Module (Ultrasonic and GPS) which gathers environmental and location information continuously. The Data Processing Module receives this raw data to identify anomalies and record GPS positions of detected obstacles and cracks. The Decision Making Module selects the robot's next action between autonomous navigation and stopping immediately for critical hazards. The Communication Module activates the GSM module to send an immediate alert with location information to the control station when an anomaly occurs.



IV. IMPLEMENTATION

The implementation phase included the physical construction of the robot prototype and the development of the software necessary to integrate and control the components. Based on

the system design, the system was realized by connecting sensors and communication modules with a central microcontroller.

1. Hardware Implementation

The robotic vehicle was constructed using a chassis equipped with DC motors, wheels and a power supply. The core of the system is an Arduino UNO microcontroller, which acts as the central processing unit. The following main components were integrated:

Control Module: An Arduino UNO board is the brains of the operation, responsible for running the main control loops, processing sensor data and triggering actions.

Mobility System: An L293D motor driver IC is used to communicate with the Arduino. This allows the microcontroller to control the speed and direction of the 5V DC motors, allowing the robot to move on tracks.

Obstacle detection: An HC-SR04 ultrasonic sensor is mounted on the front of the robot. Its TRIG and ECHO pins are connected to the digital pins of the Arduino to measure distance and detect physical obstacles in the robot's path.

Position Tracking: A GPS module is integrated to provide accurate, real-time geographic coordinates (latitude and longitude) of the robot's position. This is necessary to log the exact location of any detected anomalies.

Communication module: A GSM module is connected to the serial pin of the Arduino. This module has the option of a SIM card and is used to send automatic SMS (Short Message Service) notifications to a pre-configured mobile number (control station).

Power supply: The entire system is powered by a battery pack (as shown in Figure 8 of the report), making the robot autonomous

2. Software Implementation

The system's logic become evolved in C/C++ using the Arduino IDE. The software program is designed around a number one manipulate loop that executes the centre functionalities of the robotic.

The operational algorithm is as follows:

Initialization: Upon startup, the system initializes all components: the serial verbal exchange for the GSM and GPS modules, the pin modes for the Ultrasonic sensor (TRIG as output, ECHO as enter), and the pins for the L293D motor driving force.

Continuous Operation Loop: The robot enters an countless loop to carry out its inspection responsibilities:

Movement: The robot instructions the L293D driving force to move the cars ahead, propelling the unit alongside the track.

Obstacle Scanning: The device continuously triggers the Ultrasonic sensor to measure the space to the closest object.

Crack Scanning: Simultaneously, the system reads statistics from the crack detection sensor.

Decision Making: The software techniques the sensor information to make real-time decisions:

If an Obstacle is Detected (e.g., ultrasonic studying is below a hard and fast threshold):

The microcontroller at once sends a STOP command to the L293D motor driver, halting the robot to prevent a collision. It queries the GPS module for the current coordinates.

It commands the GSM module to ship an SMS alert (e.g., "Obstacle gift") alongside the GPS facts.

If a Crack is Detected:

The device queries the GPS module for the present day coordinates.

It commands the GSM module to ship an SMS alert (e.g., "CRACK DETECTED") with the right range and longitude, as shown in the output displays (Fig 10).

The robot maintains to move ahead to test the rest of the tune.

If No Anomalies are Found: The robotic keeps its ahead motion, and the loop repeats.

V. FUTURE SCOPE

The "Railtel Safety Solutions" project has established a basic robotic platform for improving railway safety through obstacle and crack detection using ultrasonic sensors, GPS location tracking, and GSM alerts. While the current system serves as a strong proof-of-concept for real-time monitoring, there are many opportunities for growth. This project can evolve from a detection tool into a predictive and autonomous railway management system.

One key area for improvement lies in sensor fusion and data processing. Future versions should combine more sensors to address the drawbacks of using a single sensor. Adding LiDAR would offer high-resolution 3D mapping for better obstacle classification.

Infrared and thermal cameras would improve detection capabilities in bad weather and darkness. These cameras could also spot overheated track components. The most important step forward will be using machine learning algorithms. Instead of just reporting detected cracks, an AI model could look at sensor data patterns to allow for predictive maintenance.

It could predict potential track failures before they become serious. AI-driven computer vision could also analyze video feeds to distinguish between harmless items, like a plastic bag, and dangerous ones, like a large rock, thus cutting down on false alarms. Additionally, the system's usefulness can increase by creating autonomous maintenance robots.

The current inspection bot design could be enhanced with robotic arms or repair tools to carry out minor repairs on-site, reducing the need for manual work and costly downtime. Finally, better integration with existing railway infrastructure is crucial. Rather than just sending an SMS alert, the system

should communicate directly with current signaling systems and track switches.

This would enable the automatic management of train traffic in affected areas, forming a truly integrated and smart safety network. It would also require the development of a secure, web-based dashboard for remote monitoring and control by railway operators.

VI. CONCLUSION

The creation of the railway track monitoring system is an important improvement in maintaining the safety and efficiency of railway transport. With the help of modern technologies like robotics, sensors, and communication systems, the system facilitates the detection of track anomalies and obstacles in advance. This decreases the chance of accidents and enhances the reliability of railway transport in general.

Through various project phases, including a feasibility study, system analysis, design, implementation, and testing, a strong and reliable system was successfully created to meet the specified requirements. The system's ability to detect and report track issues accurately, along with its real-time communication features, gives railway operators valuable information to maintain track safety and ensure smooth operations.

VII. REFERENCES

- [1] Adarsh, Kaleemuddin, Dinesh & Ramachandran. (2016). Performance Comparison of IR and Ultrasonic Sensor.
- [2] S. Modi. (2002). Robot Obstacle Avoidance.
- [3] Pavithra, S. S. S., & R. (2017). A survey on autonomous car and sensing technologies.
- [4] Jaycil & Randy. (2015). Autonomous Vehicle Navigation and Sensing Systems, Proceedings of the 2015 International Conference on Operations Excellence and Service Engineering 178.
- [5] Domínguez, E, J, J. & C. (2011). LIDAR based Perception Solution for Autonomous Vehicles, 2011 11th International Conference on Intelligent Systems Design and Applications 790.
- [6] Zhou, Chen, & Xiu. (2009). A Simulation Model to Evaluate and Verify Functions of autonomous vehicle based on simulink, Springer-Verlag Berlin Heidelberg, 10.1007/978-3-642-10817-4_64.
- [7] Fernández, Domínguez, Fernández-Llorca, Alonso, & sotelo. (2013). Autonomous Navigation and obstacle avoidance of a Micro-bus, International Journal of Advanced Robotic Systems, 10.5772/56125.
- [8] R, Z. & S. (2016). Obstacle-avoiding robot with IR and PIR motion sensors, IOP Conf. Series: Materials Science and Engineering, 10.1088/1757-899X/152/1/012064.

[9] Sakkhor, Zaman, & Sadi. Autonomous Car Using Full Mapping GPS System.

[10] Tabassum, Lopa, Tarek, & Ferdosi. (2017). Obstacle Avoiding Robot, Global Journal of Research in Engineering.

[11] Nasucha. (2015). Development Of an Obstacle Avoiding Robot, Jurnal Sistem Computer, ...