

Railway Management System Using IOT

**B. Nayana (3BR21EE009), Nagaveni K. N. (3BR21EE062), Nikath Banu N. (3BR21EE067),
Nijamuddin M. (3BR21EE068)**

Department of Electrical and Electronics Engineering
Ballari Institute of Technology and Management, Ballari, Karnataka, India

ABSTRACT

Railway safety requires continuous monitoring of tracks, platforms, and train compartments to reduce accidents caused by track defects, obstacles, fire, and improper platform management. This paper presents an IoT-based Railway Management System designed to provide automated monitoring and rapid response to hazardous railway conditions. The proposed system employs an Arduino Uno as the main controller along with IR sensors, ultrasonic sensors, a fire sensor, NodeMCU, ZigBee communication, LCD display, relays, DC motors, and a water-sprinkling mechanism. IR and ultrasonic sensors are employed for track and obstacle monitoring, while IR sensors at the station are used to determine platform availability. A fire sensor continuously monitors fire conditions and initiates safety actions such as water sprinkling and compartment/engine detachment when a fire is detected.

The IoT communication facility enables detected events to be transmitted to a mobile application over Wi-Fi, providing real-time information regarding railway conditions. Experimental implementation demonstrates the detection of right-side and left-side track cracks and fire conditions, with corresponding warning messages transmitted to the mobile application. The developed system therefore combines track monitoring, platform availability detection, fire protection, and wireless communication in an integrated railway safety framework.

Keywords— Internet of Things (IoT), Railway Management, Arduino Uno, Track Crack Detection, IR Sensor, Ultrasonic Sensor, Fire Detection, NodeMCU, ZigBee, Railway Safety.

INTRODUCTION

Railway transportation plays an important role in passenger and commercial transportation, but railway accidents can result in severe loss of life, property, and disruption of transportation services. Track cracks, structural abnormalities, obstacles, level-crossing incidents, and fire accidents are some of the important factors affecting railway safety. Conventional manual inspection methods require considerable manpower and time and may not provide continuous monitoring of railway infrastructure. Therefore, automated monitoring and early detection of hazardous conditions are important for improving railway operational safety.

The proposed Railway Management System using IoT integrates sensing, processing, communication, and control technologies to address these safety concerns. The system detects track cracks and obstacles using IR and ultrasonic sensors and monitors fire conditions using a fire sensor. Platform availability is also monitored so that information can be communicated to an approaching train. Arduino Uno controllers process sensor signals, while NodeMCU and ZigBee provide communication between different parts of the system. Through IoT-based communication, safety-related information can also be transmitted to a mobile application, enabling real-time monitoring and faster corrective action.

LITERATURE SURVEY

Several researchers have proposed different techniques for railway track monitoring and crack detection. Aliza Raza Rizvi and Rauf Khan [1] introduced an image-processing-based method for identifying cracks in railway tracks, aiming to improve the speed and scalability of inspection while reducing human intervention. However, the approach requires large datasets and high-performance computing resources for improved accuracy. Rizvi, Khan, and Ahmad [2] proposed a vision-based railway track crack detection system to automate inspection and reduce manual effort, but the method has limitations in detecting very small cracks. Zhicong Liang *et al.* [3] applied deep convolutional neural networks for rail-surface defect detection using the SegNet architecture, demonstrating the potential of deep learning for automated defect identification.

Scarlett Liu, Quandong Wang, and Yiping Luo [4] reviewed visual inspection technologies based on image processing for railway maintenance and discussed their applications and future development; however, false-positive detection can reduce reliability. R. Thendral *et al.* [5] developed a computer-vision-based railway crack detection method using deep learning and Gabor image features, but environmental conditions and poor image quality may increase the detection error. Rahman Shafique, Hafeez-Ur-Rehman Siddiqui, and Furquan Rustam [6] proposed an acoustic-analysis-based technique for railway track fault detection to improve automation and reliability, although the approach may face difficulties in distinguishing normal track variations from abnormal conditions. These studies indicate the need for a simple, reliable, and real-time monitoring system integrating multiple sensors and IoT communication for improved railway safety.

PROBLEM STATEMENT

Railway tracks are continuously subjected to environmental and operational stresses that can produce cracks and other defects. Failure to identify these defects at an early stage can lead to accidents, service interruption, increased maintenance costs, and risks to passengers. In addition, fire accidents and improper platform management further increase operational risks. Hence, a real-time automated system is required for continuous railway monitoring and timely safety action.

OBJECTIVES

The two main objectives of the proposed work are:

1. To develop an IoT-based railway safety system capable of detecting track cracks, obstacles, fire conditions, and platform availability using appropriate sensors and Arduino-based control.
2. To provide real-time communication and automatic safety response through NodeMCU/ZigBee communication, mobile alerts, water sprinkling, and control mechanisms.

PROPOSED SYSTEM

The proposed Railway Management System consists mainly of **station and train modules**. The station module incorporates an Arduino Uno, IR sensors, LCD display, ZigBee communication module, and regulated power supply. Multiple IR sensors monitor platform occupancy and provide information regarding platform availability. The Arduino processes the sensor signals and communicates the corresponding platform information through the wireless communication system. The station-module block diagram provided in the project illustrates the integration of three IR sensors, Arduino Uno, LCD, ZigBee, and the power-supply unit.

The train module integrates track-monitoring sensors, Arduino-based processing, wireless communication, DC motor control, relay-based operation, and fire-protection mechanisms. Track abnormalities and obstacles are monitored through IR and ultrasonic sensing, while the fire sensor detects hazardous fire conditions. When a hazardous condition is identified, the controller initiates the required safety operation and communicates the detected condition through the IoT interface. The overall arrangement is therefore designed to combine railway-track inspection, platform monitoring, train movement, fire protection, and wireless data transmission into a single automated system.

BLOCK DIAGRAM

Fig. 1 shows the block diagram of the IoT-based Railway Management System, integrating the Arduino Uno with IR, ultrasonic, and fire sensors for continuous railway safety monitoring. The controller processes the sensor inputs and operates the LCD, ZigBee communication, DC motor, relay, water sprinkler, and alarm to provide automatic detection and response to hazardous conditions.




Fig 1 block diagram

CIRCUIT DIAGRAM

Fig. 2 shows the integrated circuit diagram of the IoT-based Railway Management System, where the Arduino Uno receives inputs from IR, ultrasonic, and fire sensors for track, obstacle, and fire monitoring. The controller operates the LCD, ZigBee communication, DC motor, water sprinkler, and buzzer through the motor-driver and relay circuits to provide automatic monitoring and emergency response.




Fig 2 circuit diagram

METHODOLOGY

The proposed methodology begins with continuous acquisition of information from the sensors installed in the station and train modules. IR sensors monitor the railway track and platform conditions, while the ultrasonic sensor determines the distance between the system and detected obstacles. The Arduino Uno receives these sensor outputs and compares them with the programmed operating conditions. During normal operation, the controller allows the system to continue its regular operation. When a track crack, obstacle, or unavailable platform condition is detected, the corresponding information is processed and transmitted to the required subsystem.

Fire monitoring is performed continuously using the fire sensor. When a fire condition is identified, the controller activates the required emergency mechanism, including water sprinkling and the specified detachment mechanism. NodeMCU provides IoT connectivity for transmitting safety information to the mobile application, while ZigBee supports communication between the station and train modules. Thus, sensing, decision-making, wireless communication, and physical control are combined to achieve real-time railway safety monitoring.

RESULTS AND DISCUSSION

The **Fig. 3 and Fig. 4** show the developed Railway Management System implemented using separate station and train hardware modules. Experimental testing demonstrated successful detection of railway-track abnormalities and fire conditions, generating notifications such as “RIGHT SIDE CRACK DETECTED,” “LEFT SIDE CRACK DETECTED,” and “FIRE DETECTED.” These alerts were transmitted through Wi-Fi and displayed on the mobile TCP client application, demonstrating the real-time IoT communication capability of the developed prototype..

The platform-monitoring arrangement further enables the system to determine platform availability using IR sensors and communicate this information to an approaching train. Integration of the different subsystems demonstrates the

feasibility of combining track crack detection, fire detection, platform monitoring, and wireless communication in a single prototype. The system reduces dependence on manual track inspection and enables faster identification and communication of potentially unsafe railway conditions.

Station Module:




Fig. 3 Hardware Setup of Station Module

Train Module:



Fig.4 Hardware Setup of Train Module

CONCLUSION

An **IoT-based Railway Management System** has been developed to improve railway safety through automated monitoring and communication. The system integrates IR and ultrasonic sensors for track and obstacle monitoring, fire sensing for emergency detection, platform availability monitoring, Arduino-based control, and IoT communication. Automatic monitoring can reduce the risk associated with railway-track cracks and fire incidents while reducing the requirement for manual track inspection.

The implemented prototype demonstrates track-crack detection, fire detection, platform monitoring, and transmission of warning information through wireless communication. Future development can incorporate predictive maintenance, 5G-based communication, additional environmental sensors, smart-city integration, and large-scale implementation in railway and metro networks.

REFERENCES

- [1] Kalpanansharma, Jagdish Kumawat, Saurabh Maheshwari, and Neeti Jain, “Railway Security System Based on Wireless Sensor Networks—State of the Art,” 2014.
- [2] Diksha Nagdevte, Mohammad Zakir, Anand Muley, and A. H. Shelar, “Detection of Crack in Rail Road Using Ultrasonic and PIR Sensor,” 2014.
- [3] J. C. Priyanka, A. Saranya, L. C. Shanmathi, and S. Baranikumar, “Automatic Level Crossing Gate with Database Collection,” 2015.
- [4] Jun Zhang and Guiyun Tian, “An Evolution of RFID Grids for Crack Detection,” 2017.
- [5] Sumit Pandey, Abhishek Mishra, Pankaj Gaur, Amrindra Pal, and Sandeep Sharma, “Automatic Fire Initiated Braking and Alert System for Trains,” 2016.
- [6] Victoria J. Hodge, Simon O’Keefe, Michael Weeks, and Anthony Moulds, “Wireless Sensor Networks for Condition Monitoring in the Railway Industry: A Survey,” *IEEE Transactions on Intelligent Transportation Systems*, 2015.
- [7] Bo Ai *et al.*, “Challenges Toward Wireless Communications for High-Speed Railway,” *IEEE Transactions on Intelligent Transportation Systems*, 2014.
- [8] Ch. Muneendra Rao and B. R. Bala Jaswanth, “Crack Sensing Scheme in Rail Tracking System,” *International Journal of Engineering Research and Application*, 2014.