

Real Time Road Condition Detection

Paras Bhatt
Computer Science department
Chandigarh University
India
22bcs15683@cuchd.in

Prince Tanwar
Computer Science department
Chandigarh University
India
22bcs16057@cuchd.in

Devensh Yadav
Computer Science department
Chandigarh University
India
22bcs16082@cuchd.in

Amanpreet Singh
Computer Science department
Chandigarh University
India
aman.e9618@cumail.in

Abstract— Real-time road condition detection has recently become an important research topic because of the growing needs of intelligent transportation systems, autonomous vehicles, and smart infrastructure. Road conditions have a direct impact on traffic safety, vehicle dynamics, fuel economy, and overall transportation reliability. Conventional road condition monitoring methods are mostly dependent on manual road inspection, interval road surveys, or fixed roadside sensors, which are often expensive, outdated, and geographically restricted. Real-time road condition detection systems, on the other hand, have the objective of continuously monitoring road surface conditions like potholes, cracks, wetness, ice formation, rough surfaces, and debris accumulation using automated and computer-driven methods. The real-time nature of the detection system is also significant because road conditions can change very rapidly because of weather, road construction, and traffic-related deterioration. Real-time road condition detection systems are increasingly able to handle large-scale road condition monitoring with high accuracy because of the rapid development of sensing technology, edge computing, and machine learning. This research area is at the nexus of transportation engineering, computer vision, signal processing, and artificial intelligence, which makes it both technically complex and highly relevant to society.

Keywords— policy monitoring, AI, NLP, digital governance, policy analytics, AI for support

I. INTRODUCTION

Real-time detection of road conditions is a crucial factor in improving transportation safety and efficiency. Poor road conditions are one of the primary causes of vehicle damage, traffic congestion, and road accidents around the world. Potholes, road deformations, and slippery roads are some of the road hazards that can increase the braking distance of vehicles and affect stability, especially during adverse weather conditions. Real-time road condition detection helps provide warnings to drivers and systems to adjust their speed, route, or driving accordingly. In the case of connected and autonomous vehicles, real-time road condition detection is even more important because autonomous driving systems require accurate perception of the environment to make safe decisions. Moreover, transportation departments can also benefit from real-time data because they can focus on the most

critical road maintenance based on priority rather than conducting regular maintenance checks. As the number of urban residents and traffic density continues to rise, the need for continuous monitoring of road conditions will continue to increase, and real-time road condition detection systems will be the backbone of future mobility infrastructure [3].

Conventional road condition monitoring systems are mainly based on manual road surveys, visual checks, and road inspection vehicles equipped with costly sensors. Although these systems can offer high-precision data, they have a number of natural drawbacks. Manual road surveys are time-consuming, laborious, and error-prone, and thus not suitable for frequent or large-scale road condition monitoring. Road inspection vehicles, although accurate, are expensive to maintain and operate, and thus can only be used for major highways or periodic road condition monitoring. Fixed roadside sensors have limited spatial coverage and cannot detect sudden changes in road conditions. Moreover, conventional road condition monitoring systems are often not real-time, leading to delayed identification of potential hazards that could have been mitigated in advance. Real-time road condition detection systems seek to address these limitations by using widely available sensors, mobile platforms, and intelligent algorithms to offer timely and comprehensive road condition information.




Figure 1
(bar chart of integrity & access)

Contemporary real-time systems for road condition detection utilize a broad spectrum of sensors to record physical properties of the road. The most widely used sensors for this purpose are cameras, accelerometers, gyroscopes, LiDAR, radar, and environmental sensors such as temperature and humidity sensors. Camera-based systems allow for visual inspection of the road surface, making them ideal for detecting cracks, potholes, water accumulation, and changes in road surface texture. Inertial sensors, especially accelerometers, are useful for detecting vibrations and shocks caused by road irregularities or potholes. LiDAR and radar sensors are capable of depth and surface profile measurement, enabling accurate detection of deformations and obstacles. Environmental sensors provide additional information that can be used to detect conditions such as icing or wetness on the road surface. The selection of sensors to be used depends on several factors, including cost, accuracy, durability, and the target platform for deployment. Multiple sensor modalities are often used together to improve the reliability of road condition detection by overcoming the limitations of individual sensors, especially in adverse environmental conditions such as low light or rain.

Vehicles themselves have emerged as robust platforms for the real-time collection of road condition data. Modern vehicles are increasingly equipped with sophisticated sensor systems, computing capabilities, and connectivity solutions. By leveraging the sensors already installed in vehicles, such as accelerometers, cameras, and wheel speed sensors, road condition detection can be achieved without incurring additional infrastructure costs. Crowdsourcing data from a large number of vehicles enables broad spatial coverage and frequent updates, allowing for the monitoring of road networks at the city or national level. Vehicle-based systems enjoy natural exposure to a wide range of road conditions, offering a rich source of data that captures real-world usage patterns. However, differences in vehicle make, suspension systems, and sensor calibrations pose challenges that must be mitigated by normalization and algorithm design. In spite of these challenges, vehicle-based platforms are one of the most scalable and cost-effective solutions for real-time road condition detection.

I. LITERATURE REVIEW

A. Evolution of Decision and Analytics Models

Smartphones have proven to be a viable and widely available platform for road condition detection because of their sensor capabilities and connectivity. The accelerometers, gyroscopes, GPS, and cameras present in smartphones are capable of detecting motion patterns, location information, and images that are useful for road surface analysis. The smartphone-based system allows for the collection of data on a large scale using the crowdsourcing concept, which uses millions of people without requiring any additional hardware. Smartphone-based systems are very appealing in areas where the budget for infrastructure development is limited. The smartphone-based system also faces some difficulties in terms of orientation, mounting location, user activity, and sensor quality. Advanced signal processing and machine learning algorithms are required to eliminate noise and extract useful information. Despite the difficulties, smartphone-based systems have shown great promise for real-time pothole, rough road, and road anomaly detection.[7]

Computer vision is a key component of real-time road condition detection, especially for visual inspection of road surfaces. Images and videos taken by cameras mounted on vehicles or installed along roads are processed to detect surface irregularities like cracks, potholes, ruts, and debris. Approaches vary from traditional image processing techniques like edge detection and texture analysis to modern deep learning-based object detection and segmentation algorithms. Deep convolutional neural networks have demonstrated outstanding ability to learn complex visual patterns related to road damage in varying lighting and weather conditions. However, real-time processing requirements impose strict efficiency demands on model design and hardware support to facilitate timely detection. Though computer vision-based systems provide highly informative context, their performance can be adversely affected in low visibility conditions, requiring additional sensing modalities for robust operation.




Figure 2 (pie chart of distribution)

B. Weaknesses in Traditional Indicator Choice Techniques

Vibration-based road condition detection involves the analysis of signals obtained from accelerometers and gyroscopes to determine road surface irregularities. As a vehicle moves over irregular sections of the road, specific patterns of vibration are created, which can be analyzed to detect irregularities. Filtering, spectral analysis, and time-domain analysis of signals are employed to identify road-induced vibrations independent of vehicle dynamics and driver input. Real-time analysis of signals allows for immediate detection of potholes and rough road surfaces. The challenge in vibration-based road condition detection is the effect of vehicle-specific parameters, such as suspension hardness and speed. Effective models must therefore address these factors to provide consistent results across different vehicles. Vibration-based road condition detection is computationally efficient and suitable for real-time analysis [10].

Machine learning has emerged as an integral part of real-time road condition detection systems because of its capability to analyze complex patterns and noisy data. Supervised learning algorithms are widely employed to classify road conditions based on labeled sensor data, while unsupervised learning algorithms are capable of

detecting anomalies in the data without any labeling. Machine learning models are trained on features extracted from visual data, vibration patterns, and environmental factors to differentiate between normal and deteriorated road conditions. Machine learning models are capable of adapting to different road conditions and learning from increasing amounts of data. Nonetheless, data quality and generalization of machine learning models are still major challenges [12][13].

feature-level fusion, or decision-level fusion, with trade-offs between computational complexity and robustness. In real-time applications, feature-level fusion and decision-level fusion are generally favored because of efficiency considerations. For example, vibration-based pothole detection can be validated through visual information to eliminate false alarms triggered by vehicle dynamics. Robust fusion approaches are important for enhancing system robustness in adverse weather conditions, varying traffic patterns, and diverse sensing infrastructures [16].

II. METHODOLOGY

A. Architectural Design

The real-time detection systems also have to meet very rigorous latency requirements such that the detected real-time hazards are acted upon effectively. In other words, delayed detection of the hazards considerably reduces the usefulness of the systems. The systems may include several stages of detection, including the acquisition of raw data from the various involved sensors, followed by preprocessing, feature detection, and communication. It is therefore crucial that each of the stages is well engineered to minimize the cost of the computations while ensuring efficiency is maintained. In this regard, several methods are used, such as the systems using the sliding window approach. Another key factor is the challenges that are experienced in urban centers, particularly because of the population density. The urban centers are normally more challenging and are therefore a crucial part of the automation systems. Consequently, real-time is not regarded as a technical objective but an intrinsic part of the systems.[17].

Edge computing has emerged as an essential facilitator of the process of real-time road condition detection due to its capability of processing the data in proximity to the source of data generation. This removes the end-to-end latency experienced in the transmission of raw data to central processing systems. This process allows for an instantaneous detection of hazards, which is of critical importance in real-time processes. Edge computing also helps in reducing bandwidth utilization in large systems, thus enhancing scalability. However, the processing capabilities of these devices are limited, thus requiring the optimization of algorithm processing. This is achieved by employing certain suitable techniques in the design of these systems. Edge computing is therefore an optimal solution in achieving an appropriate balance between the requirements of the process [18].

B. Five Ranking Methods and Iterative Thresholding

Even though immediate detection is made possible through edge computing, the role played by cloud computing platforms in aggregating the data and conducting historical analysis and strategic planning cannot be ignored. The data collected from the distributed edge nodes can be sent to the centralized cloud computing systems, which will be useful for long-term storage and analysis. Analysis of the stored data will enable identifying trends and conducting predictive maintenance and performance analysis on the infrastructure. Aggregated data relating to the conditions of the roads can be analyzed to determine the best course of action regarding the repair of the road. Therefore, the use of the cloud computing platforms allows the system to be updated, with the detectors being updated with new data whenever it is available. The




Figure 3 (Scatter chart representing accuracy)

C. The Role of Data Quality and Context in Decision-Making

Deep learning has made substantial progress in the state of the art for visual road damage detection. Convolutional neural networks are able to learn hierarchical features that represent fine-grained visual patterns of surface degradation. Object detection and semantic segmentation models are able to jointly detect multiple damage types. For real-time deployment, pruning, quantization, and edge inference are needed. Deep learning-based systems have achieved high accuracy on a wide range of road conditions and are a crucial part of contemporary road monitoring systems.[14].

D. Research Gaps

Multimodal sensor fusion is an important facilitator of reliable real-time road condition detection because no single sensing modality is capable of effectively capturing all the variations of road surface conditions under different environmental and operational settings. Vision sensors are rich in spatial and contextual information but are extremely vulnerable to lighting conditions, shadows, rain, fog, and occlusions. Inertial sensors, such as accelerometers and gyroscopes, are robust to visual degradation but lack accurate localization and semantic interpretation of surface damage. Multimodal fusion of complementary data sources can improve the accuracy of detection and minimize uncertainties. Fusion approaches can be performed at different levels, such as raw data fusion,

approach of using a combination of edge computing and cloud computing is ideal and thus widely recommended for use in intelligent transportation systems.

C. Iterative Thresholding for Consensus Indicator Selection

The integration of real-time road condition detection with a geographic information system significantly enhances spatial awareness and decision-making capabilities. GIS platforms organize mapped data for detected anomalies on specific road segments, enabling the visualization of spatial patterns and the severity distribution. It was this spatial context that was pivotal for interpreting detection results and planning focused maintenance interventions. GIS integration also enables route optimization and navigation services with dynamic updates based on prevailing road conditions. For instance, detected potholes or flooded segments can be communicated to navigation systems to reroute traffic proactively. In addition, spatial analysis tools allow authorities to identify high-risk zones, recurring locations of damage, and even correlations between road conditions with environmental factors. Embedding real-time detection in a geographic context, GIS integration transforms raw sensor data into actionable infrastructure intelligence.

III. EXPERIMENTAL SETUP

A. Datasets

Weather and environmental conditions have a major impact on the road conditions and the performance of the detection process. For example, rain, snow, ice, and other extreme weather conditions can change the road conditions suddenly. Thus, it is necessary to take into account the weather while implementing real-time detection methods and while dealing with the classification outcomes. Change in weather can affect the road conditions significantly. Hence, while implementing real-time detection techniques, it is necessary to take into account the change in weather. Therefore, while implementing real-time techniques, it is necessary to take into account the impact of such change in weather while implementing the actual classification process. Handling the impact of the environment is a major requirement while implementing the real-time road condition detection process.

B. Advanced AI-Driven Mechanism

Quality of data forms a critical component, as accurate detection of road conditions is impossible in a real-time scenario. However, it is challenging to achieve high-quality data, as no matter how hard we try, there is always a possibility of getting noisy signals from sensors. Sensor signals are prone to different types of noises, and their quality may degrade due to different types of distortion. These types of noises may include those caused by sensors, vehicles, traffic, and even environmental factors. Filtering, normalization, and removal of outliers are critical preprocessing steps that are necessary for extracting meaningful insights from raw data. Hence, managing these types of noises is critical, especially when dealing with crowdsourced data, as managing data quality is a critical aspect that can get affected by a variety of factors.

IV. RESULTS & DISCUSSION


A. Raw Indicator Score Analysis

The issue of privacy and security is a major concern with crowdsourced approaches to detecting road conditions. There is a likelihood of inadvertently collecting and disclosing sensitive information regarding the routes and itineraries of individuals who participate in such projects, particularly if data is collected from sources such as cars and smartphones. The issue of ensuring privacy is critical with regard to urban planning and the regulation of crowdsourced approaches to collecting data on the conditions of roads and other infrastructure. Therefore, the privacy of individuals must be respected and ensured with such approaches. There is a need to balance the issue of scalability with the issue of data quality with regards to ensuring privacy within the urban setting.

B. Correlation Structure of Numeric Indicators

The evaluation process of real-time road condition detection systems can be measured by various parameters. The accuracy of road condition detection is very important, but on the other hand, the performance of the system can also play a significant role in the overall detection process. The traditional parameters, like classification accuracy, precision, and recall, need to be supplemented with other parameters concerning the detection process itself, as detection in these cases is more important than accuracy, as qualitative parameters can be more important than quantitative parameters in the long run. There are many ways to evaluate these systems, which can also be validated during the real-world implementation of these systems.

For urban and rural road networks, various challenges may occur for real-time road condition detection. An urban road network may be thought of as an environment with dense traffic, complex scenes, and dynamic infrastructure. On the other hand, rural road networks may involve instances of limited connectivity, limited data availability, and varied road nature. Therefore, the detection system has to cater well to these contrasting conditions through flexible strategies. Challenges related to deployment involve considerations of environmental, infrastructural, and operational factors. The concept of successful detection systems has integrated robust properties.



Flowchart

CONCLUSION

Real-time detection of road conditions is an essential component of an intelligent transportation system, which allows for dynamic and effective management of traffic on the roads while ensuring proper safety services are provided. Through integration with other services, road conditions can be utilized in an effective manner while providing accident prevention services and dynamic congestion management services. Furthermore, integration can also ensure that data sharing is achieved among interested players in transportation, which will eventually help create effective response strategies as transportation systems become more intelligent with time and its integration with road condition detection systems becomes a necessity.

Precise and timely road condition information is crucial for the safe operation of autonomous and connected vehicles. Road surface anomalies directly influence vehicle control, braking, and path planning. The output of real-time detection systems is a key input to onboard decision-making algorithms, which increases situational awareness well beyond that achievable with onboard sensors. Shared knowledge of road conditions amongst the connected vehicle fleet enhances collective safety. As higher levels of automation are reached, the reliability of road condition detection will become increasingly important, making it one of the key enablers of autonomous mobility.

The application of real-time road condition detection system is beneficial in various ways and has considerable economic and social implications. Not only does it cut the long-run cost of repair, but it can also prolong the lifespan of the roads and other infrastructures. Furthermore, it can improve road safety, reducing the cost and enhancing the social benefits of the residents and the public. Other social benefits include reduced traffic congestion, lower vehicle maintenance costs, as well as providing equity in transport.

Future research directions in real-time road condition detection will be oriented toward achieving greater precision, scalability, and flexibility. Emerging trends such as improvements in sensor technology, ML, and edge computing will provide the momentum for future research directions. The challenges to be addressed in the future will be the handling of extreme conditions, generalization, and interpretability. This will be achieved through multidisciplinary research.

Therefore, real-time road condition detection is seen as a revolutionary innovation in transportation systems, enhancing road safety, efficiency, and resiliency. Among its many applications, this technology would be beneficial in providing critical knowledge related to road conditions. Recent and future studies in overcoming road condition challenges would be necessary to take this innovation to its next level. As road transportation systems become smarter and more connected, real-time road condition detection is expected to feature in redefining its future.

REFERENCES

[1] S. S. Yoon, K. Lee, and J. Kim, "Real-time road surface condition monitoring using vehicle-mounted sensors," *IEEE*

Transactions on Intelligent Transportation Systems, vol. 20, no. 10, pp. 3620–3631, 2019.

[2] E. Eriksson, L. Girod, B. Hull, R. Newton, S. Madden, and H. Balakrishnan, "The pothole patrol: Using a mobile sensor network for road surface monitoring," *Proceedings of the 6th International Conference on Mobile Systems, Applications, and Services*, pp. 29–39, 2008.

[3] R. Mednis, G. Strazdins, R. Zviedris, G. Kanonirs, and L. Selavo, "Real time pothole detection using Android smartphones with accelerometers," *International Conference on Distributed Computing in Sensor Systems*, pp. 1–6, 2011.

[4] J. Lin and S. Chen, "Road anomaly detection using smartphone-based accelerometer data," *Sensors*, vol. 18, no. 3, pp. 1–19, 2018.

[5] Y. Maeda, H. Sekimoto, T. Seto, T. Kashiwayama, and H. Omata, "Road damage detection using deep neural networks with images captured through a smartphone," *Computer-Aided Civil and Infrastructure Engineering*, vol. 33, no. 12, pp. 1127–1141, 2018.

[6] A. Mohan, V. N. Padmanabhan, and R. Ramjee, "Nericell: Rich monitoring of road and traffic conditions using mobile smartphones," *Proceedings of the 6th ACM Conference on Embedded Network Sensor Systems*, pp. 323–336, 2008.

[7] H. Tsai, Y. Chiang, and C. Chu, "Road surface roughness detection based on vehicle vibration analysis," *Journal of Transportation Engineering*, vol. 138, no. 8, pp. 1045–1052, 2012.

[8] M. Douangphachanh and H. Oneyama, "Estimation of road roughness condition from smartphones under realistic settings," *Engineering Geology*, vol. 181, pp. 82–92, 2014.

[9] J. Fan, Y. Yu, and Y. Zhang, "Vision-based road crack detection using deep convolutional neural networks," *IEEE Access*, vol. 7, pp. 105456–105465, 2019.

[10] Z. Zhang, Q. Zou, Q. Li, and Q. Wang, "Deep learning-based road crack detection using adaptive image segmentation," *IEEE Transactions on Intelligent Transportation Systems*, vol. 20, no. 10, pp. 3704–3716, 2019.

- [11] P. R. De Lima, P. L. Rossetti, and R. M. Silva, "A survey on automatic road condition monitoring systems," *IEEE Intelligent Transportation Systems Magazine*, vol. 13, no. 2, pp. 35–54, 2021.
- [12] C. Koch and I. Brilakis, "Pothole detection in asphalt pavement images," *Advanced Engineering Informatics*, vol. 25, no. 3, pp. 507–515, 2011.
- [13] Y. Hou, H. Li, and M. Bergasa, "Road surface condition recognition based on convolutional neural networks," *Sensors*, vol. 19, no. 2, pp. 1–18, 2019.
- [14] M. Aly, "Real-time detection of lane markers in urban streets," *IEEE Intelligent Vehicles Symposium*, pp. 7–12, 2008.
- [15] J. Guerrero-Ibáñez, S. Zeadally, and J. Contreras-Castillo, "Sensor technologies for intelligent transportation systems," *Sensors*, vol. 18, no. 4, pp. 1–23, 2018.
- [16] T. Miura, M. Okada, and S. Noda, "Road surface condition detection using in-vehicle cameras and edge computing," *IEEE Transactions on Vehicular Technology*, vol. 69, no. 11, pp. 13314–13325, 2020.
- [17] A. Vittorio, V. Rosolino, I. Teresa, and G. Marco, "Automated pothole detection using machine learning techniques," *Automation in Construction*, vol. 100, pp. 53–59, 2019.
- [18] S. Mandal, S. S. Bhowmik, and S. S. Roy, "Multisensor fusion-based road condition monitoring system," *IEEE Sensors Journal*, vol. 21, no. 5, pp. 6374–6385, 2021.
- [19] P. Casas, J. Mazel, and P. Owezarski, "Data-driven traffic analysis and anomaly detection," *Computer Networks*, vol. 57, no. 2, pp. 330–343, 2013.