

## Real Time Safe Black Box System

Varsha Shetty<sup>1</sup>, Ananya Shetty<sup>2</sup>, Shahu Thakur<sup>3</sup>, Yash Tatkare<sup>4</sup>

<sup>1</sup>Department of Electronics and Telecommunication Engineering, Atharva College of Engineering

<sup>2</sup>Department of Electronics and Telecommunication Engineering, Atharva College of Engineering

<sup>3</sup>Department of Electronics and Telecommunication Engineering, Atharva College of Engineering

<sup>4</sup>Department of Electronics and Telecommunication Engineering, Atharva College of Engineering

\*\*\*

**Abstract** - This paper presents the design and implementation of a Real-Time Safe Black Box System (R-Safe) for enhancing vehicle safety and accident response. The system integrates multiple sensors with an ESP32 microcontroller to monitor critical parameters such as acceleration, temperature, alcohol presence, and environmental conditions. A GPS (Global Positioning System) module enables real-time location tracking, while sensor data is processed to detect abnormal events such as collisions, fire hazards, or driver impairment. Upon detection, the system generates immediate audio-visual alerts and transmits essential information, including location and event data, for rapid emergency response. Data is also stored locally for post-accident analysis. The prototype is implemented on a mobile platform to demonstrate real-time functionality under dynamic conditions. Experimental results show that the system effectively identifies hazardous situations and provides timely alerts, improving response time and safety awareness. The proposed system offers a low-cost, scalable solution for intelligent vehicle monitoring and can be extended with cloud integration and predictive analytics for enhanced performance.

**Key Words:** IoT (Internet of Things), vehicle safety, black box system, ESP32, real-time monitoring, accident detection

### 1. INTRODUCTION (Size 11, Times New roman)

Road accidents are a major global concern, resulting in significant loss of life and property every year. According to recent reports, a large number of accidents are caused by factors such as over speeding, driver fatigue, alcohol consumption, and vehicle malfunctions. Traditional vehicle safety systems and black box recorders primarily focus on post-accident data collection, offering limited support for real-time prevention and immediate emergency response. This highlights the need for an intelligent system that not only records data but also actively monitors and prevents hazardous situations.

With the advancement of embedded systems and the Internet of Things (IoT), it is now possible to design smart vehicle monitoring solutions that operate in real time. By integrating multiple sensors with microcontrollers, continuous tracking of vehicle and driver parameters can be achieved. Such systems can detect abnormal conditions and provide instant alerts, thereby reducing the probability of accidents and improving overall road safety.

This paper proposes a Real-Time Safe Black Box System (R-Safe), which combines sensor-based monitoring, real-time data

processing, and communication capabilities into a unified platform. The system utilizes an ESP32 microcontroller along with sensors such as accelerometers, gas detectors, and temperature sensors to detect critical events. A GPS module is incorporated for location tracking, enabling quick emergency response in case of accidents.

The proposed system not only records data for post-accident analysis but also functions as a preventive safety mechanism by issuing real-time alerts. Furthermore, its modular and cost-effective design makes it suitable for integration into a wide range of vehicles. This work aims to contribute towards the development of intelligent transportation systems that enhance safety, reduce accident rates, and enable faster emergency assistance.

## 2. Body of Paper

### 2.1 System Overview

The proposed Real-Time Safe Black Box System (R-Safe) is an embedded and Internet of Things (IoT)-based solution designed to enhance vehicle safety through continuous monitoring and real-time alert generation. The system integrates multiple sensors with a central microcontroller unit to collect, process, and transmit data related to vehicle and driver conditions. The primary objective is to detect abnormal situations such as collisions, fire hazards, and driver impairment, and respond instantly through alerts and communication mechanisms.

The architecture consists of sensing, processing, storage, and communication layers. Sensor data is acquired and processed by the microcontroller, and relevant outputs are generated in the form of alerts or stored logs. The system also supports location tracking using a Global Positioning System (GPS) module.

### 2.2 Hardware Components

The hardware implementation of the system is centered around the ESP32 microcontroller, which acts as the main processing unit. It is selected due to its low power consumption, built-in Wi-Fi capability, and sufficient processing power for real-time applications.

The system incorporates several sensors, including an Inertial Measurement Unit (IMU) for motion detection, gas sensors for detecting smoke and alcohol presence, and temperature sensors for monitoring environmental conditions. The IMU provides acceleration and orientation data, which is critical for detecting sudden impacts or collisions.

A GPS module is used to obtain real-time location data, enabling the system to transmit coordinates during emergency situations. Additionally, an SD card module is used for local data storage, ensuring that all critical information is preserved even in the event of system failure.

## 2.3 Software Implementation

The software component of the system is developed using embedded C programming in the Arduino Integrated Development Environment (IDE). The microcontroller continuously reads sensor data and processes it using predefined threshold-based logic.

When sensor values exceed specified limits, the system identifies it as an abnormal event. For example, a sudden spike in acceleration may indicate a collision, while the presence of alcohol above a threshold level indicates driver impairment. In such cases, the system triggers audio-visual alerts and logs the event data.

The system also supports communication with external platforms for real-time monitoring. Data can be transmitted to a cloud server or dashboard using wireless connectivity, enabling remote access and analysis.

## 2.4 Working Principle

The working of the system is based on continuous sensing, processing, and response. As described in Sec. 2.1, the system collects real-time data from multiple sensors. This data is processed by the ESP32 microcontroller, which applies decision logic to determine whether the conditions are normal or hazardous.

In the event of abnormal conditions, such as high acceleration, detection of smoke, or alcohol presence, the system activates warning mechanisms including buzzers and LEDs. Simultaneously, the GPS module retrieves the current location, and the data is stored locally and transmitted for further use.

This real-time response mechanism ensures that potential hazards are addressed promptly, thereby reducing the risk of accidents and improving safety outcomes.

## 2.5 Advantages of the Proposed System

The proposed system offers several advantages over traditional vehicle monitoring solutions. Unlike conventional black box systems, it provides real-time alerts in addition to post-accident data logging. The integration of multiple sensors improves detection accuracy and reliability.


Furthermore, the system is cost-effective and scalable, making it suitable for a wide range of vehicles. Its modular design allows for easy integration of additional features such as

machine learning-based prediction models and mobile application interfaces.

## 2.6 Limitations

Despite its advantages, the system has certain limitations. The accuracy of detection depends on sensor calibration and environmental conditions. Additionally, real-time communication features are dependent on network availability, which may not always be reliable.

Future improvements can focus on enhancing sensor accuracy, incorporating artificial intelligence for predictive analysis, and improving communication reliability.



**Fig -1:** Block Diagram

## 3. CONCLUSIONS

This paper presented a Real-Time Safe Black Box System (R-Safe) for vehicle safety and accident monitoring. The system integrates multiple sensors with an embedded microcontroller to detect abnormal conditions such as collisions, fire hazards, and driver impairment. Real-time alerts and GPS-based location tracking enable faster emergency response and improved safety.

The proposed system demonstrates a cost-effective and scalable approach for intelligent vehicle monitoring. Experimental observations indicate that the system can successfully detect hazardous situations and provide timely alerts. Future work includes integration of cloud-based analytics and machine learning techniques for predictive accident detection and enhanced decision-making.

## ACKNOWLEDGEMENT

The authors would like to express their sincere gratitude to Atharva College of Engineering for providing the necessary facilities and support to carry out this work. The authors also extend their heartfelt thanks to Prof. Gauri Vaidya for her valuable guidance, encouragement, and continuous support throughout the development of this project.

**REFERENCES**

- [1] A. A. Alsahlawi and M. A. Mangoud, "IoT-Based Vehicle Black Box for Enhanced Safety Standards," *Smart Computing Systems (SCS)*, 2022.
- [2] A. F. T. Winfield, A. van Maris, P. Salvini, and M. Jirotko, "An Ethical Black Box for Social Robots: A Draft Open Standard," 2022.
- [3] P. Josephin, R. Hegde, and B. Veerasamy, "Accident Detection Using Automotive Smart Black Box Based Monitoring System," *ScienceDirect*, 2023.
- [4] H. K., S. M., and D. K., "Lightweight Vehicle Black Box System with Automatic Emergency Assistance," *International Journal for Research in Applied Science and Engineering Technology (IJRASET)*, 2013.
- [5] S. Rekha and D. Dasharath, "Intelligent Vehicle Black Box System Using IoT," 2023.
- [6] S. Sethuraman and S. Santhanalakshmi, "Implementing Vehicle Black Box System by IoT-Based Approach," 2020.
- [7] A. Rahman, "IoT-Based Smart Vehicle Monitoring and Tracking System," 2024.
- [8] P. A. Khayum and P. Bhargavi, "Vehicle Black Box System for Accident Analysis Using IoT," 2025.