International Journal of Scientific Research in Engineering and Management (IJSREM)
Volume: 10 Issue: 10 | Oct - 2026 SJIF Rating: 8.659 ISSN: 2582-3930

Relaying and Delivery Assurance in Long-Range Radio Alerting for Remote Areas: A Review with a Preliminary Bench Observation

Dr. Mrs. G. P. Halde, Abhay Bhanarkar, Atharva Hete, Kabir Wasnik, Avesh Bhoyar
Department of Electronics and Communication Engineering
Priyadarshini College of Engineering, Nagpur, India
{abhaybhanarkar2005@gmail.com, atharvahete@gmail.com, kabirwsnk@gmail.com}

***Abstract*—Emergency alerting outside cellular coverage is a natural use for long-range, low-power radio, yet most published work on such radios concerns fixed gateways and periodic sensor data rather than a person who needs to be sure that a call for help has been heard. This paper reviews what the literature says about the range, capacity and delivery limits of LoRa-based networks, discusses the main ways in which relaying and acknowledgement can be combined, and identifies the open questions that matter for wearable alerting devices. A single short bench observation, in which a message relayed through one intermediate node was acknowledged to its sender, is included only as an indication that the approach is practical. No quantitative performance results are claimed.**

***Index Terms*—LPWAN, LoRa, emergency alerting, relaying, delivery assurance**

I. Introduction

Search-and-rescue work in forests, mountains and flood-hit districts depends on the first alert reaching someone who can act. Cellular networks are often thinnest exactly where accidents are most likely, and satellite services, though available, add cost and weight that limit their use for casual or low-income users. Low-power wide-area network (LPWAN) technologies offer a different compromise: very small messages, sent slowly, over long distances, using little energy [1], [2].

Among these technologies LoRa has received the most attention, and its radio layer is documented by the chipset manufacturer [3]. Its usual network layer, LoRaWAN, arranges end devices around gateways in a star [4]. That arrangement works well when gateways are installed in advance. It works less well for an alert originating wherever a person happens to be.

This paper makes three points. First, it summarises evidence on how far LoRa links reach and how they scale. Second, it sets out the design choices that arise when a message must be relayed and its delivery confirmed, without committing to one implementation. Third, it lists open problems specific to devices worn by people. A brief bench observation is added at the end to show that the combination is feasible on inexpensive hardware.

TABLE I
Summary of Cited Approaches

Ref.	Focus	Relevance to alerting
[5], [7]	Range and link behaviour	Shows feasibility; fixed devices
[6], [9]	Scaling with device count	Warns of collisions
[10]	Protocol limits	Delivery guarantee is weak
[13]	Mesh relaying	Workable; not person-worn
[14]	On-demand routing	Control overhead is costly

II. What the Literature Establishes

A. Range

Field studies have looked at LoRa coverage for remote health and wellbeing monitoring [5] and at the factors that limit range and the effect of interference on real links [7]. Application-oriented evaluations in distributed measurement settings point the same way [8]. The overall message is that long links are possible, but that terrain, antenna placement and the chosen radio parameters strongly influence what is achieved. Most of these trials use devices at fixed, favourable positions.

B. Capacity and Reliability

When many devices share the channel, collisions become a limiting factor, and analytical and simulation studies have examined how quickly performance falls [6], [9]. Discussion of LoRaWAN's practical constraints, including duty cycle, capacity and reliability, appears in [10], and broader surveys compile the same concerns [11], [12]. For alerting, the most relevant point is that the standard model gives little guarantee about whether any one message was received.

C. Multi-Hop Operation

Relaying removes the need for every device to reach a gateway directly. A synchronous LoRa mesh used for monitoring in underground infrastructure shows that this can work over the same radio technology [13]. General-purpose ad-hoc routing methods exist [14], but they rely on route discovery traffic, which is expensive when the channel is slow and shared. Table I summarises the approaches discussed above.




Fig. 1. Qualitative view of how added assurance raises channel and energy cost. The positions are illustrative and not measured.

III. Design Considerations

A. Where to Confirm Delivery

A confirmation can be generated at different points. In a *per-link* scheme, each receiver acknowledges to the node that sent the packet to it, which keeps retransmissions local and short. In an *end-to-end* scheme, only the final destination confirms, which tells the origin what it most needs to know but gives intermediate nodes no basis for deciding whether to retry. Many practical designs combine the two. The choice affects how much channel time an alert consumes and how quickly the origin learns the outcome. Fig. 1 shows the trade in simplified form.

B. Limiting Forwarding

Without a limit, a relayed message can circulate indefinitely, and repeated copies waste airtime. A cap on the number of forwarding steps is a simple control. In very small networks, a fixed cap is easier to reason about than a discovered route, and it avoids the control overhead noted earlier.

C. Handling Repeats

Retransmission and relaying can each deliver the same message more than once. The destination therefore needs a way to recognise a message it has already accepted. This also raises a question about what the destination should do when a repeat arrives: ignoring it silently could leave the sender uncertain, so the destination may need to repeat its confirmation without treating the message as new.

D. Channel Time

Because the channel is slow, the time a transmission occupies depends strongly on the radio parameters chosen [3]. Higher spreading factors extend range but lengthen each transmission, which in turn increases the chance of collision and the energy spent per message [6]. Any scheme that adds confirmations and retries should be judged against this cost rather than against delivery alone.

IV. Issues Specific to Wearable Devices

A. Energy

A device worn for days must idle cheaply and still be ready to transmit. Relaying for others adds to the load of whoever happens to be nearest, so the energy burden is not shared evenly.

B. Mobility and Position

Neighbouring devices move, so a relay that was in range a minute ago may not be now. A person may also be unconscious or unable to touch the device, which makes the quality of the alert contents and the certainty of delivery more important than for a fixed sensor.

C. Body and Terrain Effects

The wearer's body absorbs and blocks signals, and trees, slopes and rock reduce range further. Results from fixed outdoor placements, such as those cited above, should therefore be treated as optimistic for this use.

D. Trust in the Alert

Operators who receive many alerts must decide which to act on first, and false alarms waste effort. This is a separate problem from transport and is not discussed further here.

V. Preliminary Bench Observation

To check that relaying and confirmation can be combined on inexpensive hardware, we arranged two wearable-style nodes and a receiver so that the first node could reach the receiver only through the second. A message raised on the first node arrived at the receiver, and the first node was informed of the outcome. A message sent twice was not recorded twice. This was a functional check on a bench. We did not count packets, time the exchange or measure distance, and we draw no performance conclusions from it.

VI. Open Questions

The review points to several questions that bench work cannot answer.

- How does delivery ratio change with each added relay in realistic terrain?
- How much extra channel time and energy does confirmation cost compared with unconfirmed sending?
- How should a node behave when the return path fails but the message was in fact received?
- How many simultaneous senders can a small relay network support before collisions dominate?

Answering them will need repeated outdoor trials with logged results.

VII. Conclusion

The literature shows that LoRa links are long and that relaying is feasible, but it says little about wearable alerting devices in which the sender must know the outcome. We outlined the main choices for confirmation and forwarding, listed issues particular to worn devices, and reported a single bench observation consistent with feasibility. Quantitative evaluation in the field remains to be done.

REFERENCES

[1] U. Raza, P. Kulkarni, and M. Sooriyabandara, "Low power wide area networks: An overview," *IEEE Commun. Surveys Tuts.*, vol. 19, no. 2, pp. 855–873, 2017.
[2] M. Centenaro, L. Vangelista, A. Zanella, and M. Zorzi, "Long-range communications in unlicensed bands: The rising stars in the IoT and smart city scenarios," *IEEE Wireless Commun.*, vol. 23, no. 5, pp. 60–67, 2016.
[3] Semtech, "SX1276/77/78/79 datasheet," Semtech Corp., Camarillo, CA, USA, Rev. 6, 2020.
[4] LoRa Alliance, "LoRaWAN L2 1.0.4 specification (TS001-1.0.4)," 2020.
[5] J. Peta¨ja¨ja¨rvi, K. Mikhaylov, M. Ha¨ma¨la¨inen, and J. Iinatti, "Evaluation of LoRa LPWAN technology for remote health and wellbeing monitoring," in *Proc. 10th Int. Symp. Med. Inf. Commun. Technol. (ISMICT)*, 2016, pp. 1–5.
[6] M. C. Bor, U. Roedig, T. Voigt, and J. M. Alonso, "Do LoRa low-power wide-area networks scale?" in *Proc. 19th ACM Int. Conf. Model., Anal. Simul. Wireless Mobile Syst. (MSWiM)*, 2016, pp. 59–67.
[7] J. C. Liando, A. Gamage, A. W. Tengourtius, and M. Li, "Known and unknown facts of LoRa: Experiences from a large-scale measurement study," *ACM Trans. Sensor Netw.*, vol. 15, no. 2, Art. 16, 2019.
[8] M. Rizzi, P. Ferrari, A. Flammini, and E. Sisinni, "Evaluation of the IoT LoRaWAN solution for distributed measurement applications," *IEEE Trans. Instrum. Meas.*, vol. 66, no. 12, pp. 3340–3349, 2017.
[9] O. Georgiou and U. Raza, "Low power wide area network analysis: Can LoRa scale?" *IEEE Wireless Commun. Lett.*, vol. 6, no. 2, pp. 162–165, 2017.
[10] F. Adelantado, X. Vilajosana, P. Tuset-Peiro, B. Martinez, J. Melia`-Segu´ı, and T. Watteyne, "Understanding the limits of LoRaWAN," *IEEE Commun. Mag.*, vol. 55, no. 9, pp. 34–40, 2017.
[11] J. Haxhibeqiri, E. De Poorter, I. Moerman, and J. Hoebeke, "A survey of LoRaWAN for IoT: From technology to application," *Sensors*, vol. 18, no. 11, Art. 3995, 2018.
[12] A. Lavric and V. Popa, "Internet of Things and LoRa low-power wide-area networks: A survey," in *Proc. Int. Symp. Signals, Circuits Syst. (ISSCS)*, 2017, pp. 1–5.
[13] C. Ebi, F. Schaltegger, A. Ru¨st, and F. Blumensaat, "Synchronous LoRa mesh network to monitor processes in underground infrastructure," *IEEE Access*, vol. 7, pp. 57663–57677, 2019.
[14] C. Perkins, E. Belding-Royer, and S. Das, "Ad hoc on-demand distance vector (AODV) routing," IETF RFC 3561, Jul. 2003.