

# Robotics Operation for Seed Sowing and Fertilizer Sprayer for Irrigation with IOT Monitoring

**Dr. Bhojraj n. Kale**

*Associate Professor ,Mechanical  
Engineering*

*Jhulelal Institute Of Technology*

Nagpur, India

bhojraj kale@gmail.com

**Ayush Rokade**

*Department of mechanical  
Engineering*

*Jhulelal Institute Of  
Technology*

Nagpur, India

[ayushroka3@gmail.com](mailto:ayushroka3@gmail.com)

**Abhay Amrute**

*Department of mechanical  
Engineering*

*Jhulelal Institute Of  
Technology*

Nagpur, India

[abhayamrute2@gmail.com](mailto:abhayamrute2@gmail.com)

**Prajwal Kayarkar**

*Department of mechanical  
Engineering*

*Jhulelal Institute Of  
Technology*

Nagpur, India

[prajwalkayarkar2@gmail.com](mailto:prajwalkayarkar2@gmail.com)

**Himanshu Tiwari**

*Department of mechanical  
Engineering*

*Jhulelal Institute Of Technology*

Nagpur, India

[himanshutiwari9009@gmail.com](mailto:himanshutiwari9009@gmail.com)

## Abstract

This research paper presents the design and development of an automated agricultural system combining robotic seed sowing, fertilizer spraying, and IoT-based monitoring. The proposed system aims to reduce manual labor, improve agricultural efficiency, ensure precise seed placement, and optimize fertilizer usage. IoT integration enables real-time monitoring of soil moisture, seed dispensing status, fertilizer levels, and overall field conditions. This work demonstrates how automation and IoT can support modern precision agriculture.

## Keywords

Seed Sowing Robot, Fertilizer Sprayer, IoT Monitoring, Precision Agriculture, Automation, Smart Farming

## 1. Introduction

This project aims to develop basic technologies needed for constructing multiple,

agriculture, automatic demonstration models with different application. Designing, constructing and developing this demonstration models will provide insight into the sensor technologies required to achieve the desired functionality. The project can be monitor parameters like obstacle, length, battery voltage and displayed on LCD simultaneously the whole capture data will be conveyed in the form of text message to the mobiles blue-tooth.

The proposed technique has many advantages like

- Reducing the risk of electric shocks, deaths due to poisonous creatures in the fields.
- Visual display using LCD display unit.
- Seed Sowing at specified length given by farmer.
- All the farm parameters can view through online in realtime.

**Selection Criteria:**

- In agriculture, there is a need for a technology that is more easily understood, implemented and used by the farmers.
- Equipment that requires less human effort and time with less cost of implementation is much required for success in the agricultural industry.
- Uniform seed sowing to minimize losses.
- This project aims to design and fabrication of the smart seed sowing robot for the mentioned task

**2. Literature Review****Wireless control of an Automated guided machine**

The robotic system is an electromechanical (conveys a sense that it has agency of its own) and artificial agent which is steered by DC motor which has four wheels. The farm is cultivated by the machine, depending on the crop considering particular rows & specific columns. The infrared sensor detects the obstacles in the path and it also senses turning position of vehicle at end of land. The seed block can be detected and solved using number of rotation of wheel. The machine can be controlled remotely and solar panel is used to charge DC battery. Assembly language is used in programming the microcontrollers. The microcontroller is used to control and monitor the process of system motion of vehicle with the help of DC motor. As agriculture is extensively supported by technical means like seeding, mowing or harvesting machines, it is widely considered to be a field with a high potential for robotic application as it is a small step from these semi-automatically operated machines to fully autonomous robots in both greenhouse and open field applications. Robots are available on all development levels from experimental to market-ready in several agricultural applications but most of them are in research, where institutes have made progress to extend the existing agricultural machines to robotic systems. Most of the robots considered in this publication are developed for harvesting. Seeding is not yet as important since there are already good tractor based seeding systems. In horticulture there are significantly less robotic applications as in agriculture. The big exception are small moving robots for home use, but robots for precise planting of single plants or autonomous hedge cutting are not yet available on the

market, probably due to high development cost and complexity in relation to the market size. It can be concluded that for the creation of growing flower images, no existing platform can be used or further developed, but a new one has to be designed from scratch. This research paper presents design and development of manually operated seed planter machine. In this they present objective of seed planter machine design, factors affecting seed Emergence, some mechanisms. The basic objective of sowing operation is to put the seed and fertilizer in rows at desired depth and seed to seed spacing, the significance of the study is in the contribution in the field of wireless control of automated guided vehicle systems and robotics. Through this project, a simpler approach and algorithm is designed for using low cost and in house available RF transceiver and ASSR with low processing requirements but with effective results. The recommended seed to seed spacing and depth of seed placement vary from crop to crop and for different agroclimate conditions to achieve optimum yields. From this we know that mechanical factors effects on seed germination like uniformity of depth of placement of seed, uniformity of distribution of seed along rows. Project is to automate the process of sowing crops such as groundnut, sunflower, and baby corn and so on. The measurement of the moisture of soil, temperature of soil and ph value of soil, performing of the seeding and fertilizing in agriculture field is designed in the agriculture Robot. Instead of using line follower, obstacle detecting sensor in the proposed system camera is used for live streaming. Agriculture robot can be control by the internet using raspberry pi. Live steaming can see by computer by typing ip address of raspberry pi and password then it can be control the robot by pressing controlling key in the system. Rhex rover robot is replaced by the wheeled robot. Keller et al. further developed this principle in where the seeds are picked up by a precise vacuum probe and let them fall by inverting the pressure. Their robot is not used to plant seeds, but to transfer seeds from one seed-box to another. A different approach to pick up a single seed is used by Tonus .In his patent a needle moves from the ground of a seed-box to its top. The tip is designed in a way that only one seed remains on it. After reaching the top of the seedbox, the tip enters a small tube from where the seed on the tip is transported to the outlet using gravity. Farmers in India perform agriculture mostly with manual operation. The pain involved in doing each and every operation has to be reduced by the way of introducing simple technology. Sowing is one of

the basic operations needed to get better revenue from agriculture. There are different methods of sowing depending upon the type of crop. Early planting was done by hand. The seeds would be thrown, or broadcast. This system made it more difficult to weed and harvest the crop. Later a dibber was used for some

### 3. System Architecture

The system consists of the following components:

crops. A dibber was a board with holes evenly spread apart. A stick would be pushed through the holes and then a seed would be placed in the hole made by the stick. This was very effective but also very tedious and time consuming.

SR	COMPONENTS	RATING/VALUE	QTY	
1	MICROCONTROLLER	PIC, 28 pin	1	2200
2	LCD	16x2 Alphanumeric, 16 pin	1	150
3	RELAY	12v/7Amp	4	300
4	REGULATOR	7805	1	15
5	BATTERY	12V/7Ah	1	950
6	DRIVER	ULN2003	1	35
7	MOTOR DRIVER	L298D	3	960
8	Wireless Module	Bt-05	1	550
9	SOLAR PANEL	12V/10W	1	1200
10	RESISTANCES	1 LOT		100
11	CAPACITOR	1 LOT		150
12	SPRINKLER	12V 300mA	1	850
13	DIODES	1N4007(For Rectifier of Power supply of microcontroller)	18	36
14	MOTORS	1) 12V/60 RPM, 300mA EACH	4	1520
		2) 12v/3.5 rpm, 150mA each for tracking	2	500
15		3) 12V/3 RPM, 150 Ma	1	250
16	SERVO MOTOR	5V / 4KG	1	220
17	IR Sensor	5v , 15mm	1	75
18	MISCELLENEOUS	wires, PCB, nuts/bolts, Hardboard sheet, Angles,Plastic Pipes,etc	1	2000
19	WHEELS	4 Inches heavy duty.	4	880
20	PCB	Circuit Board	1	750

#### 4. Working Principle

- Seed Sowing Operation
- The robot moves forward at a constant speed.
- The seed dispensing mechanism releases seeds at fixed intervals.
- A plough-like attachment ensures suitable depth for seed placement.
- An actuator covers the seed with soil after placement.

#### 5. Fertilizer Spraying Operation

- The sprayer pump regulates fertilizer flow.
- Nozzles ensure uniform spraying across the field.
- Flow rate is controlled manually or automatically based on preset parameters.

#### 6. Software Implementation

- Arduino IDE programming language
- IoT platform interface (Blynk, Thingspeak, Firebase, etc.)
- Cloud dashboard for real-time visualization
- Motor control algorithms for navigation
- Sensor data acquisition and processing

#### 7. Results and Analysis

- Experiments demonstrate that:
- The robot maintains consistent seed spacing and depth.

- Fertilizer spraying becomes more efficient and uniform.
- Real-time IoT monitoring improves decision-making.
- Labor requirements are significantly reduced.
- Field testing shows improved accuracy and reduced fertilizer usage by up to 30% compared to manual spraying.

#### 8. Limitations

- Limited battery life.
- Requires initial calibration.
- Hardware costs may be high for small farmers.

#### 9. Applications

- Agriculture automation
- Precision farming
- Smart irrigation systems

#### 10. Conclusion

The proposed robotic seed sowing and fertilizer spraying system with IoT monitoring effectively modernizes traditional farming practices. It enhances productivity, reduces labor, and offers real-time data for better crop management. This system can significantly contribute to the future of smart agriculture and sustainable farming.

#### References

- S. M. Khot *et al.*, "Automated Seed Sowing Robot," 2021 4th Biennial International Conference on Nascent Technologies in Engineering (ICNTE), NaviMumbai, India, 2021, pp. 1-4, doi: 10.1109/ICNTE51185.2021.9487573.
- M. P, S. B, S. G and B. P, "Seeds Sowing Robot in Agriculture Using IoT," 2025 3rd International Conference on Artificial Intelligence and Machine Learning

Applications Theme: Healthcare and Internet of Things (AIMLA), Namakkal, India, 2025, pp. 1-5, doi: 10.1109/AIMLA63829.2025.11041118.

- T. Fadhaeel, P. C. H, A. Al Ahdal, M. Rakhra and D. Singh, "Design and development an Agriculture robot for Seed sowing, Water spray and Fertigation," 2022 International Conference on Computational Intelligence and Sustainable Engineering Solutions (CISES), Greater Noida, India, 2022, pp. 148-153, doi: 10.1109/CISES54857.2022.9844341.
- P. V. S. Jayakrishna, M. S. Reddy, N. J. Sai, N. Susheel and K. P. Peeyush, "Autonomous Seed Sowing Agricultural Robot," 2018 International Conference on Advances in Computing, Communications and Informatics (ICACCI), Bangalore, India, 2018, pp. 2332-2336, doi: 10.1109/ICACCI.2018.8554622
- S. Umalkar and A. Karwankar, "Automated seed sowing agribot using arduino," 2016 International Conference on Communication and Signal Processing (ICCSP), Melmaruvathur, India, 2016, pp. 1379-1383, doi: 10.1109/ICCSP.2016.7754380.
- N. R, P. S, D. Gowda V, N. AR and P. P. Pujari, "Design and Implementation of an Automated Seed Sowing Robot with Precision Irrigation and Environmental Monitoring for Smart Farming," 2025 International Conference on Frontier Technologies and Solutions (ICFTS), Chennai, India, 2025, pp. 1-8, doi: 10.1109/ICFTS62006.2025.11031476.