

Slope Stability Analysis and Landslide Mitigation

¹Pawan Deshmukh, ²Dr Sachin J. Mane

¹ME Student, Department of Civil Engineering, Dr. D Y Patil College of Engineering, Akurdi, Pune, India.

²Associate Professor, Department of Civil Engineering, Dr. D Y Patil College of Engineering, Akurdi, Pune, India.

Email: pawandeshmukh106@gmail.com

Abstract

Slope instability and rainfall-induced landslides are among the most persistent geotechnical hazards in India, especially across the Himalaya, Western Ghats, Konkan belt, Nilgiris and high-rainfall urban hill slopes. This literature survey paper critically reviews slope stability analysis methods, landslide triggering mechanisms and mitigation practices with emphasis on Indian case studies. The review integrates limit-equilibrium methods, finite-element modelling, rainfall infiltration analysis, GIS-based susceptibility mapping, remote sensing, field monitoring and site-specific stabilization design. Indian case studies such as the Konkan Railway slope failure, Malin landslide in Maharashtra, Chamoli rock-ice avalanche in Uttarakhand, rainfall-induced Western Ghats failures in Kerala and Nilgiris hill-slope hazards are compared to identify common controlling factors. The synthesis shows that intense monsoon rainfall, high pore-water pressure, weathered lithology, poor drainage, toe cutting, land-use change and unplanned infrastructure development repeatedly reduce slope safety margins. Drainage improvement, soil nailing, geogrid reinforcement, gabion toe support, retaining structures, bioengineering, hazard zonation and early-warning systems are found to be most effective when used as integrated site-specific measures rather than isolated interventions. The paper concludes with research gaps and a proposed integrated framework for sustainable landslide risk reduction in India.

Keywords: slope stability; landslide mitigation; GeoStudio SLOPE/W; rainfall-induced failure; Konkan Railway; Malin landslide; Western Ghats; GIS; factor of safety; India.

1. Introduction

Landslides are gravity-driven mass movements involving rock, debris or earth, occurring as falls, topples, slides, spreads and flows depending on material type and failure kinematics [1]. In India, these hazards are strongly controlled by rugged terrain, intense monsoon rainfall, tectonic instability, weathered rock masses, rapid road expansion and settlement pressure in hill regions. The uploaded Phase-I framework for the Konkan region identifies lateritic caps, weathered basalt, colluvium, steep road cuttings and heavy monsoon precipitation as dominant concerns for the Maharashtra coastal belt. These conditions are consistent with the broader Indian landslide pattern reported in institutional and peer-reviewed literature.

Slope stability analysis is therefore not only a design calculation but a risk-reduction process. A stable slope must maintain sufficient resisting shear strength against driving forces under dry, saturated, seismic and anthropogenically modified conditions. The factor of safety (FoS) expresses this balance. However, many Indian landslides occur when a slope that is stable in dry conditions becomes unstable after infiltration raises pore-water pressure and reduces effective stress. In such cases, purely static geometry-based assessment is inadequate; hydrological boundary conditions, rainfall intensity-duration relationships, soil-water characteristic behaviour and drainage performance must be included.

Modern studies combine field investigation, laboratory testing, limit-equilibrium analysis, finite-element modelling, satellite remote sensing, GIS-based landslide susceptibility mapping, InSAR displacement monitoring and rainfall-based early warning. This interdisciplinary approach is particularly necessary in Indian settings because different landslide provinces behave differently: the Himalaya contains tectonically active slopes and high-relief valleys, while the Western Ghats and Konkan region are dominated by intense monsoon rainfall, lateritic terrain, basaltic weathering and infrastructural cut slopes.




Figure 1. Integrated conceptual framework for slope stability analysis and landslide mitigation.

2. Review Methodology

The survey was prepared as a thematic review suitable for a Scopus-indexed civil/geotechnical engineering paper. The search emphasis included peer-reviewed articles and institutional reports dealing with slope stability, rainfall-induced landslides, GeoStudio/SLOPE/W, PLAXIS, GIS-based landslide susceptibility, remote sensing, Indian case studies and mitigation measures. Core databases and sources considered include Elsevier, Springer, ASCE, MDPI, IOP Conference Series, ISRO/NRSC, NDMA and selected government reports. The uploaded Phase-I Konkan document was used to retain the regional problem definition, aim, objectives and methodology orientation.

The literature was screened using five inclusion criteria: (i) slope stability or landslide mechanism relevance, (ii) use of quantitative or evidence-based assessment, (iii) case-study applicability to India or monsoon terrain, (iv) presence of mitigation recommendations and (v) usefulness for identifying research gaps. Studies were excluded when they were purely descriptive, lacked methodological transparency, or did not provide transferable findings for engineering practice.




Figure 2. Review screening and synthesis workflow followed in the present survey.

3. Theoretical Background of Slope Stability Analysis

3.1 Factor of Safety and Limit-Equilibrium Concept

The most widely used engineering indicator of slope stability is the factor of safety, defined as the ratio of available resisting shear strength to mobilized shear stress along a potential failure surface. Limit-equilibrium methods divide a potentially sliding soil mass into slices and satisfy force and/or moment equilibrium. Ordinary/Fellenius, Bishop simplified, Janbu, Spencer and Morgenstern-Price methods remain common because they are transparent and compatible with practical design software. Morgenstern-Price is preferred for complex slip surfaces because it satisfies both force and moment equilibrium and allows a flexible interslice force function.




Figure 3. Typical limit-equilibrium representation of a rainfall-affected slope with critical slip surface.

3.2 Rainfall Infiltration and Pore-Water Pressure

Rainfall-induced landslides occur when infiltration reduces matric suction in unsaturated soils and raises pore-water pressure. This reduces effective normal stress and therefore reduces shear strength under the Mohr-Coulomb framework. In lateritic and weathered basaltic soils of the Western Ghats, seasonal wetting and drying can produce fissures, desiccation cracks and preferential seepage paths, allowing rapid water entry during monsoon. Therefore, slope assessment in Konkan and similar regions must evaluate the combined role of rainfall intensity, antecedent rainfall, permeability, water table rise and surface drainage condition.

3.3 Numerical Modelling and Software-Based Analysis

GeoStudio SLOPE/W is commonly used for limit-equilibrium slope stability and can be coupled with SEEP/W for seepage and pore-pressure analysis. PLAXIS and other finite-element tools are useful when stress-deformation response, staged excavation, reinforcement and soil-structure interaction are significant. Remote sensing and GIS tools complement these numerical models by identifying slope geometry, land-use changes, drainage networks, lineaments and past landslide inventories. The best practice is to use numerical modelling for critical site design and GIS/remote sensing for regional prioritization.

4. Landslide Susceptibility in India

India has several landslide-prone provinces, including the North-western Himalaya, North-eastern Himalaya and Western Ghats. The NRSC/ISRO Landslide Atlas reports an inventory of approximately 80,000 mapped landslides across vulnerable regions in 17 states and 2 Union Territories for the period 1998-2022 [2]. Secondary summaries of the atlas report that about 66.5% of landslides are from the North-western Himalaya, 18.8% from the North-eastern Himalaya and 14.7% from the Western Ghats [3]. Although the Western Ghats record fewer landslide events than Himalayan provinces, exposure and rainfall intensity make many events fatal, especially in dense settlements and road corridors.

Reported landslide distribution by Indian landslide province




Figure 4. Indian landslide distribution by landslide province based on published atlas summaries.

The Indian landslide problem is not limited to natural terrain. Road widening, hill cutting, unplanned construction, quarrying, drainage obstruction and vegetation loss frequently transform marginally stable slopes into active failure zones. The NDMA guidelines emphasize hazard, vulnerability and risk assessment; remediation; monitoring and early warning; capacity building; public awareness; emergency response; and regulation as integrated requirements for landslide risk reduction [4].

5. Indian Case Studies

Indian landslide case-study locations




Figure 5. Schematic location map of selected Indian landslide case studies

5.1 Konkan Railway Slope Failure, Maharashtra

The Konkan Railway corridor crosses rugged terrain with steep cut slopes, lateritic soils, weathered basalt and very high monsoon rainfall. Raghuram and Basha analysed rainfall-induced probability of failure for spatially variable soil slopes and included a Konkan Railway slope failure case in Maharashtra [5]. The study showed that rainfall intensity and spatial variability of soil parameters strongly influence reliability index and critical slip surface development. The key lesson is that a deterministic FoS alone may underrepresent field uncertainty when hydraulic conductivity, cohesion and internal friction angle vary vertically and horizontally.

For Konkan slopes, mitigation should combine surface drainage, lined catch-water drains, sub-horizontal drains, vegetation restoration, local soil nailing and toe protection where roads or rail lines undercut the slope. Monitoring of rainfall threshold, seepage emergence and tension cracks is critical before and during the southwest monsoon.

5.2 Malin Landslide, Maharashtra

The Malin landslide occurred on 30 July 2014 in Pune district, Maharashtra, and buried a village after intense rainfall. Ering and Sivakumar Babu performed probabilistic back analysis of this rainfall-induced landslide and reported that the mechanism was closely linked with rainfall infiltration, unsaturated soil behaviour and reduction of shear strength [6]. The event demonstrates how slope morphology, land-use modification, soil saturation and intense monsoon rainfall can

combine to produce rapid debris movement. The case is important for Western Ghats risk planning because many settlements occupy hill toes or mid-slope benches where runoff exposure is high.

Recommended measures for Malin-type terrain include strict land-use zoning below steep slopes, prohibition of uncontrolled slope cutting, controlled terracing, reforestation, surface runoff diversion, community-based rainfall warning and relocation planning for high-exposure hamlets. Engineering measures alone are insufficient when the entire settlement lies within the probable runoff path.

5.3 Chamoli Rock-Ice Avalanche and Debris Flow, Uttarakhand

The Chamoli disaster of 7 February 2021 involved a rock and ice avalanche that transformed into a high-energy debris flow in the Rishiganga-Dhauliganga valley. NDMA's detailed report states that rockfall with glacieret ice avalanche was the primary slope failure mechanism, followed by downstream entrainment and infrastructure damage [7]. Scientific studies further show that remote sensing can identify pre-collapse deformation and unstable high-mountain slopes [8]. Although the process differs from rainfall-induced Western Ghats landslides, Chamoli highlights the need for multi-hazard assessment in steep valleys where slope failure can trigger cascading flood, debris-flow and infrastructure disasters.

Mitigation for such Himalayan settings requires hazard zonation of source areas, remote-sensing monitoring, hydropower risk assessment, debris-flow routing analysis, warning systems, setback zoning and resilient bridge/powerhouse design. Stabilizing the entire source slope may be unrealistic; therefore exposure management and early detection become central.

5.4 Kormala, Muvattupuzha, Kerala, Western Ghats

Paul, Varma and Salini examined rainfall impact on slope stability at Kormala, Muvattupuzha in the Western Ghats of Kerala [9]. The study emphasized that intense rainfall reduces soil suction, particularly near the surface and toe, and lowers the factor of safety. This aligns closely with Konkan-region conditions because both areas experience high monsoon rainfall, lateritic/weathered profiles and shallow failure susceptibility. The Kormala case supports the need for coupled seepage-stability modelling rather than dry-slope analysis.

Mitigation should prioritize interception drains, toe drains, subsurface drainage, maintenance of natural drainage channels, slope flattening where possible and vegetation-based erosion control. These are lower-cost measures that can significantly improve performance when the primary trigger is rainfall infiltration.

5.5 Nilgiris and Western Ghats Hill-Slope Failures

Nilgiris hill slopes are repeatedly affected by monsoon-triggered shallow slides, debris flows and road-cut failures. The broader Western Ghats experience intense rainfall, weathered soils, road expansion and dense human exposure. Institutional landslide-forecasting initiatives by GSI and national agencies increasingly focus on rainfall thresholds, susceptibility maps and community alerts. The Nilgiris illustrate that high-resolution slope monitoring and operational warning bulletins can convert scientific assessment into risk reduction for inhabited hill districts.

Table 1. Comparative summary of selected Indian landslide case studies.

Case	Geological/terrain setting	Dominant triggers	Analysis approach	Preferred mitigation
Konkan Railway, Maharashtra	Laterite/weathered basalt cut slopes; high rainfall	Rainfall infiltration, spatial variability, drainage blockage	Probabilistic reliability + LEM	Drainage, monitoring, soil nailing, toe protection
Malin, Maharashtra	Western Ghats hill slope and settlement exposure	Intense rainfall, land-use change, soil saturation	Back analysis, unsaturated soil mechanics	Zoning, runoff control, relocation, vegetation

Chamoli, Uttarakhand	High Himalayan rock-ice slope	Rock/ice avalanche; cascading debris flow	Remote sensing, field reports, hazard reconstruction	Monitoring, exposure control, setback, early warning
Kormala, Kerala	Western Ghats rainfall-affected slope	Loss of suction and pore pressure rise	FEM/LEM seepage-stability analysis	Surface/subsurface drainage, toe protection
Nilgiris, Tamil Nadu	Urban and road-cut hill slopes	Monsoon rainfall, cut slopes, weak soils	Susceptibility mapping, forecasting	Operational warning, drainage, bioengineering

6. Critical Parameters Governing Slope Instability

6.1 Geotechnical Parameters

Cohesion, internal friction angle, unit weight, permeability, plasticity and soil stratification directly govern slope resistance. Low-cohesion colluvium, clay-rich weathered soil, fractured rock and mixed lithology increase susceptibility because they produce weak planes and seepage contrasts. In Indian hill slopes, the difference between dry-season and monsoon-season strength can be significant; therefore laboratory tests should be interpreted for saturated and partially saturated states.

6.2 Hydrological Parameters

Groundwater rise is often the immediate mechanism behind failure. Perched water tables, seepage faces, blocked drains and high antecedent rainfall reduce effective stress and create outward seepage forces. Numerical studies consistently show that the FoS can decrease sharply when pore-water pressure increases. Hence, hydrological boundary conditions are not optional inputs but central design variables.

6.3 Geomorphological and Geological Parameters

Slope height, angle, curvature, drainage convergence, toe erosion and lithological discontinuities shape the failure mechanism. Lateritic caps over weathered basalt, jointed Himalayan rocks and colluvial valley-fill deposits show different failure styles. Concave slopes and drainage hollows can concentrate runoff and initiate shallow failures.

7. Literature Synthesis of Analytical and Modelling Methods

Table 2. Comparison of slope stability assessment methods used in recent literature.

Method	Typical use	Strengths	Limitations
Limit-equilibrium methods	FoS estimation, routine design, comparison of mitigation options	Simple, transparent, widely accepted	Needs assumed slip surface and simplified deformation
Finite-element modelling	Stress-deformation, staged construction, reinforcement interaction	Captures deformation and stress redistribution	Requires robust parameters and calibration
SEEP/W-SLOPE/W coupled analysis	Rainfall, groundwater and pore pressure response	Suitable for monsoon-induced landslides	Needs rainfall and hydraulic data
GIS susceptibility mapping	Regional hazard zoning and prioritization	Handles large datasets and multiple factors	Often empirical; must be validated

Method	Typical use	Strengths	Limitations
Remote sensing/InSAR	Inventory, displacement monitoring, inaccessible slopes	Useful for early detection and large areas	Cloud cover, vegetation and temporal resolution limits
Probabilistic reliability analysis	Uncertainty in soil properties and rainfall	Provides probability of failure and risk insight	Computationally intensive; needs statistical data

The literature indicates that no single method is sufficient for all slope problems. Limit-equilibrium modelling remains appropriate for preliminary and design-level FoS assessment, but rainfall-induced landslides require coupled seepage-stability analysis. Finite-element methods are valuable for reinforced slopes and staged excavations. Remote sensing and GIS are indispensable for regional mapping, while probabilistic analysis becomes necessary where spatial variability controls uncertainty. For Indian applications, an integrated approach is essential because data availability varies across regions and failure mechanisms range from shallow debris slides to deep-seated rock slope failures.

8. Landslide Mitigation Measures

8.1 Drainage-Based Mitigation

Drainage is the most frequently recommended intervention for rainfall-induced landslides. Surface drains, catch-water drains, lined channels, berm drains, subsurface perforated pipes and horizontal drains reduce infiltration and lower pore pressure. Drainage must be designed with adequate capacity and regular maintenance, because blocked drains can worsen instability by concentrating water.

8.2 Mechanical Reinforcement

Soil nails, rock bolts, anchors, geogrids and geotextiles increase tensile resistance and improve internal stability. Hossain and Rahman's optimization work on soil nailing using GeoStudio showed that nail length, inclination and spacing substantially affect FoS. Shukla and co-workers reported significant FoS improvement for geogrid-reinforced slopes, demonstrating the importance of reinforcement layout [10]. Reinforcement is particularly useful for road cuttings and steep engineered slopes.

8.3 Retaining and Toe-Support Systems

Gabion walls, breast walls, RCC retaining walls, crib walls and mechanically stabilized earth walls provide lateral resistance and toe support. However, retaining structures must include drainage layers and weep holes; otherwise hydrostatic pressure may cause structural failure. In landslide-prone areas, toe protection should be combined with surface runoff control.

8.4 Bioengineering and Nature-Based Solutions

Vegetation improves slope performance by reducing erosion, increasing evapotranspiration and adding root reinforcement to shallow soil layers. Vetiver grass, shrubs, live check dams and coir geotextiles can provide low-cost stabilization on shallow slopes. Bioengineering is not a replacement for structural design on deep-seated failures but is highly effective for erosion control and shallow landslide reduction.

8.5 Planning, Monitoring and Early Warning

Hazard zonation, settlement setback, relocation of high-exposure communities, rainfall threshold warning, crack monitoring, piezometers, inclinometers, UAV surveys and community training are necessary where engineering stabilization alone cannot reduce risk to acceptable levels. The NDMA guidelines emphasize that landslide risk reduction requires coordinated technical, administrative and community-level measures [4].




Figure 7. Mitigation selection logic for rainfall, structural and exposure-dominant slope risks.




Figure 8. Illustrative factor of safety improvement under different mitigation scenarios.

Table 3. Engineering and non-engineering mitigation measures for Indian landslide-prone slopes.

Measure	Primary target	Relative cost	Effectiveness	Key caution
Surface drainage	Rainfall runoff and infiltration	Low to moderate	Very high for shallow rainfall failures	Requires regular cleaning; inadequate capacity causes bypass flow
Subsurface drainage	Pore pressure and perched water	Moderate	High where groundwater controls failure	Needs outlet protection and clogging control
Soil nailing/anchors	Steep cut slopes and unstable faces	Moderate to high	High for road cuttings and excavations	Design depends on pull-out capacity and corrosion protection
Geogrid/geotextile	Embankments and reinforced soil slopes	Moderate	High when used with proper spacing and length	Less effective for deep rock failures
Gabion toe wall	Toe erosion and shallow slides	Moderate	Good when drainage is included	Foundation scour and overtopping must be checked
RCC retaining wall	Space-constrained steep slopes	High	Effective with drainage and stable foundation	Hydrostatic pressure and overturning need design checks
Bioengineering	Erosion and shallow instability	Low	Good for sustainable shallow stabilization	Slow establishment and limited deep-failure resistance
Relocation/zoning	High exposure runout	Variable	Very high for life safety	Requires governance and community acceptance

9. Research Gaps Identified from the Literature

1. Limited integration of field-based geotechnical data, rainfall infiltration modelling, probabilistic uncertainty and mitigation comparison in a single Indian case-study framework.
2. Insufficient long-term monitoring of pore pressure, rainfall thresholds, deformation and drainage performance after mitigation works are installed.
3. Limited site-specific studies for Konkan laterite-basalt slopes compared with Himalayan and Kerala landslide studies.
4. Overreliance on deterministic FoS even though Indian slopes often show high spatial variability in cohesion, friction angle, permeability and weathering depth.
5. Inadequate connection between susceptibility maps and engineering design; regional maps identify hotspots but often do not translate directly into slope-level stabilization drawings.
6. Limited cost-benefit and life-cycle performance studies comparing drainage, soil nailing, retaining walls, geogrids and bioengineering under Indian monsoon maintenance conditions.

7. Need for combined early-warning systems that integrate IMD rainfall forecasts, real-time pore pressure, ground movement and community response protocols.

10. Proposed Integrated Framework for Future Indian Studies

Based on the review, a robust Indian slope stability study should proceed through: (i) landslide inventory and remote-sensing interpretation, (ii) field mapping of slope geometry, cracks, seepage and drainage, (iii) laboratory testing under dry and saturated conditions, (iv) baseline FoS analysis using Morgenstern-Price or comparable LEM, (v) seepage-coupled rainfall analysis, (vi) probabilistic sensitivity analysis for uncertain parameters, (vii) simulation of multiple mitigation alternatives, (viii) cost and constructability assessment, and (ix) validation through historical events and monitoring. This framework is directly applicable to Konkan-region slopes where monsoon infiltration, lateritic weathering and road-cut geometry interact.

Table 4. Proposed integrated framework for slope stability and landslide mitigation studies in India.

Step	Task	Data/tools	Output
Step 1	Inventory and screening	Satellite images, old failure records, field reconnaissance	Priority slope list
Step 2	Geotechnical characterization	SPT, density, Atterberg limits, shear tests, permeability	Material model database
Step 3	Hydrological characterization	Rainfall intensity-duration, groundwater, seepage mapping	Pore pressure scenarios
Step 4	Baseline modelling	SLOPE/W, PLAXIS or equivalent	Existing FoS and critical slip surface
Step 5	Mitigation simulation	Drainage, nails, geogrid, gabion, wall, vegetation	FoS improvement and design comparison
Step 6	Validation and monitoring	Crack gauges, piezometers, rainfall thresholds, UAV/InSAR	Verified risk-reduction plan

11. Discussion

The reviewed studies demonstrate that landslide mitigation in India must move beyond single-factor explanations. Rainfall is a common trigger, but rainfall alone does not produce failure unless predisposing factors such as weak geology, steep geometry, high permeability contrast, poor drainage, toe cutting or land-use change exist. Konkan and Western Ghats slopes are especially sensitive to monsoon infiltration because lateritic and weathered basaltic profiles can rapidly lose suction and develop perched water conditions. Himalayan cases, by contrast, often include strong structural geological control, glacial/debris-flow transformation and seismic disturbance.

The most practical engineering implication is that mitigation must be selected after identifying the dominant failure mechanism. If rainfall infiltration is dominant, drainage may provide the highest benefit-cost ratio. If steep cut-slope geometry and low shear resistance are dominant, reinforcement and toe support are required. If runout exposure is dominant, relocation, barriers and warning systems may save more lives than attempting to stabilize an inaccessible source zone. Therefore, the factor of safety should be interpreted together with exposure, vulnerability and consequence.

A Scopus-quality contribution in this area should include novelty through integrated analysis rather than routine SLOPE/W modelling alone. Potential novelty may include coupling rainfall threshold modelling with FoS reduction,

comparing multiple mitigation systems using the same slope model, validating model results with historical failures, using UAV/InSAR monitoring for calibration, or developing a decision matrix for Konkan lateritic slopes. Such integration can make the work relevant to both geotechnical design and disaster-risk management.

12. Conclusion

This review paper synthesized slope stability analysis and landslide mitigation literature with emphasis on Indian case studies. The evidence shows that rainfall-induced pore-pressure rise, weak weathered lithology, steep terrain, poor drainage, toe cutting and land-use change are the most recurring causes of slope instability in India. Konkan and Western Ghats slopes require special attention because lateritic soil, weathered basalt, high monsoon rainfall and expanding infrastructure create repeated shallow-slide and debris-flow hazards.

Limit-equilibrium methods remain useful for routine FoS assessment, but Indian monsoon slopes require coupled seepage-stability modelling, remote sensing, GIS-based susceptibility analysis and field monitoring. Case studies from Konkan Railway, Malin, Chamoli, Kormala and Nilgiris show that slope failures are site-specific and mechanism-dependent. Drainage, soil nailing, geogrids, gabions, retaining walls, bioengineering, zoning and early warning should therefore be applied as integrated mitigation packages rather than isolated solutions.

The main research gap is the lack of validated, multi-parameter, site-specific studies that combine geotechnical testing, rainfall analysis, uncertainty modelling and mitigation comparison for Indian regions such as Konkan. Future research should build calibrated numerical models, include probabilistic sensitivity analysis, quantify life-cycle mitigation performance and connect engineering design with community-level risk reduction.

References

- [1] Cruden, D. M., & Varnes, D. J. (1996). Landslide types and processes. In A. K. Turner & R. L. Schuster (Eds.), *Landslides: Investigation and Mitigation*. Transportation Research Board Special Report 247.
- [2] National Remote Sensing Centre/ISRO. (2023). *Landslide Atlas of India*. Department of Space, Government of India.
- [3] Drishti IAS. (2023). *Landslide Atlas of India: Daily News Analysis summary of NRSC/ISRO atlas*.
- [4] National Disaster Management Authority. (2009). *National Disaster Management Guidelines: Management of Landslides and Snow Avalanches*. Government of India.
- [5] Raghuram, A. S. S., & Basha, B. M. (2023/2024). Rainfall-induced probability of failure in spatially variable soil slopes and a case study of the Konkan Railway slope failure. *ASCE-ASME Journal of Risk and Uncertainty in Engineering Systems, Part A: Civil Engineering*, 10(1). <https://doi.org/10.1061/AJRU6.RUENG-1112>
- [6] Ering, P., & Sivakumar Babu, G. L. (2016). Probabilistic back analysis of rainfall induced landslide: A case study of Malin landslide, India. *Engineering Geology*, 208, 154-164. <https://doi.org/10.1016/j.enggeo.2016.05.002>
- [7] National Disaster Management Authority. (2021). *Detailed Report: Uttarakhand Disaster on 7th February 2021*. Government of India.
- [8] Van Wyk de Vries, M., et al. (2022). Pre-collapse motion of the February 2021 Chamoli rock-ice avalanche, Indian Himalaya. *Natural Hazards and Earth System Sciences*, 22, 3309-3326.
- [9] Paul, M. M., Varma, M., & Salini, U. (2025). Assessing slope stability and rainfall impact: Case study of Kormala, Muvattupuzha in the Western Ghats of Kerala, India. *Indian Geotechnical Journal*.
- [10] Shukla, V., Venkateswarlu, H., & Dindorkar, N. (2025). Stability analysis of geogrid reinforced slope using GeoStudio. *National Academy Science Letters*.
- [11] Jhinkwan, V. S., Chore, H. S., & Kumar, A. (2024). Assessment of stability of slopes and remedial measures in Lesser Himalayan region: An overview. *Indian Geotechnical Journal*.

- [12] Kumar, A., Rai, S. K., Khan, I., Prashanth, M., Dhar, S., & Verma, O. (2025). Slope stability and surface displacement analysis of the Kuther landslide in the Dehar Watershed, Himachal Himalaya, Northern India. *Discover Geoscience*.
- [13] Kinde, M., Getahun, E., & Jothimani, M. (2024). Geotechnical and slope stability analysis in the landslide-prone area: A case study in Sawla-Laska road sector, Southern Ethiopia. *Scientific African*, 23, e02071. <https://doi.org/10.1016/j.sciaf.2024.e02071>
- [14] Kamal, A. S. M., Hossain, F., Ahmed, B., Rahman, M. Z., & Sammonds, P. (2023). Assessing the effectiveness of landslide slope stability by analysing structural mitigation measures and community risk perception. *Natural Hazards*, 117, 2393-2418.
- [15] Hossain, M. A., & Rahman, M. N. (2025). Optimizing soil nail configuration for slope stability using GeoStudio. *International Journal of Computer Applications*, 187(36), 35-40.
- [16] Siregar, C. A., Nugraha, H. R., Azhar, G. A., & Warlina, D. (2024). Slope stability analysis using PLAXIS and SLOPE/W: Bagbagan-Jampangkulon Road section. *IOP Conference Series: Earth and Environmental Science*, 1321, 012031.
- [17] Malik, M. K., & Karim, I. R. (2020). Seepage and slope stability analysis of Haditha Dam using GeoStudio software. *IOP Conference Series: Materials Science and Engineering*, 928, 022074.
- [18] Meng, J., Yan, E., Wu, Y., Yang, B., Miao, F., Wang, Y., & Zhan, W. (2025). Long-term stability of landslide considering strength degradation of slip-zone soil under drying-wetting cycles with loading. *Bulletin of Engineering Geology and the Environment*.
- [19] Sharipov, A., Satyanaga, A., Abishev, R., Moon, S. W., Taib, A. M., & Kim, J. (2023). Influence of slope geometry on stability of clayey soil slopes. *Geotechnical and Geological Engineering*, 41, 2939-2950.
- [20] Amin, M. N., Ashfaq, M. U., Mujtaba, H., Ehsan, S., Khan, K., & Faraz, M. I. (2022). Computer-aided slope stability analysis of a landslide: A case study of Jhika Gali landslide in Pakistan. *Sustainability*, 14(20), 12954.
- [21] Idrus, J., Hamzah, N., Ramli, R., Md Nujid, M., & Sadikon, S. F. (2023). Enhancing slope stability with different slope stabilization measures: A case study using SLOPE/W software. *Jurnal Kejuruteraan*, 35(6), 1427-1434.
- [22] Bhardwaj, A., & Shrivastava, A. K. (2022). Stability analysis of rainfall-induced landslide using numerical modelling. *Proceedings of the Indian Geotechnical Conference*.
- [23] Rahimi, J., Karimi, B. A., & Qani, N. A. (2023). Evaluation of slope stability in earthen canal using GeoStudio simulation: A multi-parameter approach for the Khush Tepa Canal project, Afghanistan.
- [24] Geo-Slope International. (2024). *GeoStudio SLOPE/W engineering methodology and software documentation*.
- [25] Bureau of Indian Standards. IS 2720 series. *Methods of test for soils*. Bureau of Indian Standards, New Delhi.
- [26] Bureau of Indian Standards. IS 14458 series. *Guidelines for retaining wall for hill area*. Bureau of Indian Standards, New Delhi.
- [27] Geological Survey of India. (Various years). *Landslide susceptibility mapping and forecasting initiatives in India*.
- [28] ICIMOD. (2021). *Understanding the Chamoli flood: cause, process, impacts and context of rapid infrastructure development*.
- [29] Shugar, D. H., et al. (2021). A massive rock and ice avalanche caused the 2021 disaster at Chamoli, Indian Himalaya. *Science*, 373(6552), 300-306.
- [30] Khan, I., et al. (2025). National-scale landslide susceptibility and risk mapping of India at high spatial resolution. *Scientific Reports*.