

Smart Helmet: An Intelligent Solution for Rider Safety

Authors: Prof. R. Wani, Aaditya Jadhav, Shreyash Mundhe, Prashant Pawar.

Department of Electrical Engineering AISSMS College of Engineering, Pune, Maharashtra, India

Abstract —

Road safety is a critical concern worldwide, with a significant number of accidents caused by human negligence such as drunk driving and failure to wear protective gear. This paper presents the design and implementation of a Smart Helmet System that integrates Internet of Things (IoT) technology to enhance rider safety and reduce accident risks. The proposed system incorporates an alcohol detection sensor to monitor the rider's breath and prevent the motorcycle from starting if alcohol consumption is detected beyond a safe threshold. Additionally, a helmet detection mechanism ensures that the bike ignition system is enabled only when the rider is wearing the helmet properly.

Furthermore, the system includes an accident detection module, which utilizes sensors such as accelerometers to identify sudden impacts or abnormal motion patterns. In the event of an accident, the system automatically sends the rider's real-time GPS location to predefined emergency contacts, enabling faster response and medical assistance. The integration of wireless communication modules ensures seamless data transmission and system reliability.

By combining safety enforcement and emergency response features, the proposed smart helmet provides an automated and efficient solution to minimize road accidents and enhance rider protection. This IoT-based approach demonstrates significant potential for improving transportation safety and promoting responsible riding behavior.

Keywords — Smart Helmet, Internet of Things (IoT), Alcohol Detection System, Helmet Detection, Accident Detection, GPS Tracking, Rider Safety, Vehicle Ignition Control, Emergency Alert System, Wireless Communication

I. INTRODUCTION

In Road accidents are a major cause of fatalities worldwide, especially among motorcycle riders, often due to not wearing helmets and driving under the influence of alcohol. Despite existing safety regulations, lack of enforcement and human negligence continue to increase risks on the road. To address these issues, this paper proposes a **Smart Helmet system** based on Internet of Things (IoT) technology, aimed at improving rider safety through automation. The system integrates an **IR sensor** to detect helmet usage and an **MQ-3 alcohol sensor** to monitor alcohol levels. A **NodeMCU (ESP32)** controller processes this data and ensures that the motorcycle starts only when safety conditions are met.

Additionally, the system includes an **MPU6050 sensor** for accident detection and a **GPS module** for sending real-time location alerts to emergency contacts via GSM or wireless communication.

Overall, the proposed system provides a smart, efficient, and cost-effective solution to enhance rider safety and enable quick emergency response using IoT automation.

II. LITERATURE REVIEW

Smart helmet systems have gained significant attention in recent years as an effective approach to improving motorcycle rider safety through IoT and automation.

Choi and Kim (2021) conducted a comprehensive review of over 100 studies and found that most systems focus on core safety functions such as helmet detection, alcohol sensing, and accident alert mechanisms. Their study emphasizes the importance of integrating sensors, microcontrollers, and communication technologies into a unified framework.

Lee et al. (2022) and related works highlight the advancement of smart helmets using **multimodal sensing and artificial intelligence**, where machine learning models such as CNN are used to detect hazardous conditions with high accuracy. These systems also employ cloud platforms for real-time monitoring, demonstrating the growing importance of AI-enabled IoT solutions.

Pearkao et al. (2025) proposed an **AI-integrated smart helmet** using cameras and YOLO-based object detection to identify surrounding vehicles and alert riders through voice messages. Their system achieved up to 85% accuracy and showed improved situational awareness, though performance slightly decreased at higher speeds.

The smart helmet system integrates safety and accident-prevention features using sensors and microcontroller-based automation. It ensures the bike starts only when the rider wears the helmet properly, is free from alcohol, and the side stand is lifted, using IR, MQ-3, and position sensors connected to an Arduino Uno. A gyroscopic sensor detects crashes by monitoring bike tilt, and a GSM module sends automatic alerts to emergency contacts during accidents. The system effectively enhances rider safety and enforces responsible riding. Future improvements can include IoT-based real-time monitoring, GPS for location tracking, ESP8266 or Raspberry Pi integration for wireless communication, and advanced features like health tracking and image-based road sign detection for a more comprehensive safety solution.

The proposed smart helmet system enhances road safety by integrating helmet detection and alcohol monitoring using sensors and automation. It employs a helmet sensor to verify if the rider is wearing the helmet and a gas sensor to detect alcohol levels, both connected to an Arduino-based control unit. If the helmet is not worn or alcohol is detected, the system locks the vehicle ignition and keeps the lights off, preventing the rider from starting the bike. Additionally, if alcohol is sensed after unlocking, a GSM alert is sent to the rider's family, adding a layer of accountability. The system effectively prevents drunk and unsafe riding through automated checks and real-time alerts.

Future improvements could include IoT-based data logging, GPS integration for location tracking, use of ESP8266 or Raspberry Pi for wireless connectivity, and app-based interfaces for emergency alerts and rider monitoring to make the system more intelligent and user-friendly.

The smart helmet for bike riders integrates multiple technologies to enhance rider safety and accident response. It uses an MQ-3 alcohol sensor to detect intoxication, a vibration sensor to identify impacts or falls, and a GSM-GPS module to send automatic SMS alerts with the rider's location to emergency contacts. An ESP32-CAM module enables live video streaming and real-time monitoring, offering visual data during incidents. The system operates on a microcontroller (ESP32/NodeMCU) with rechargeable battery support, providing immediate alerts through buzzer and LED indicators. Testing confirmed accurate alcohol detection, vibration response, and quick communication via GSM. This helmet promotes responsible riding and ensures rapid emergency response. Future improvements can include AI-based accident prediction, biometric health tracking, augmented reality heads-up displays, IoT-based data storage, and seamless integration with smart wearables for a fully connected safety ecosystem.

The IoT-based Smart Motorcycle Helmet ensures rider safety by integrating multiple smart sensors and modules. It uses an MQ-3 alcohol sensor to detect intoxication and an IR switch to verify if the rider is wearing the helmet—only when both conditions are satisfied does the bike ignition activate. Additional modules such as GPS, GSM, and accelerometer detect accidents, track location, and send emergency alerts to registered contacts. Ultrasonic sensors alert riders of nearby vehicles, while a camera and night-vision system enhance visibility. Controlled by an Arduino Uno, the system prevents drunk and helmetless riding, reducing accidents effectively. Future improvements could include IoT cloud connectivity, AI-based accident prediction, and compact hardware integration for better performance and user convenience.

The IoT-based Smart Helmet aims to enhance rider safety by preventing accidents and enabling timely emergency response. It uses sensors such as MQ-3 for alcohol detection, vibration and MEMS sensors for accident identification, and IR sensors for helmet detection. The system, built on Arduino with GSM and GPS modules, prevents ignition if the rider is intoxicated or not wearing the helmet and sends real-time accident alerts with location details to emergency contacts via cloud connectivity. Experimental results show high accuracy in detecting crashes and alcohol levels. Future improvements may include AI-driven accident prediction, live video streaming, biometric monitoring, and integration with smart wearables for a more advanced and connected safety system.

The Smart Helmet Ignition System works using two modules—one inside the helmet and one on the bike. Sensors in the helmet detect whether it is worn and send this information wirelessly to the bike module. The bike module verifies the signal and allows ignition only if the helmet is properly worn; otherwise, the relay keeps the engine off, ensuring that the bike starts only when safety conditions are met.

The IoT-based smart helmet system uses NodeMCU microcontrollers embedded in the helmet and motorcycle to collect sensor data (helmet detection using switch belt + flex sensor, drowsiness using accelerometer/gyroscope, accident detection, and GPS location tracking). These data are sent in real-time to Firebase over Wi-Fi, and the Android app displays rider status and location; if helmet is not worn, the relay keeps the ignition off, and in case of drowsiness or accident, alerts and coordinates are shared automatically.

III. METHODOLOGY and SYSTEM ARCHITECTURE

1. System Overview

The system is divided into two main units:

Helmet Unit (Master NodeMCU) → Responsible for sensing and decision-making

Bike Unit (Slave NodeMCU) → Responsible for ignition control and emergency communication

Communication between the two units is established using **Bluetooth protocol**, where the helmet unit acts as the master and the bike unit acts as the slave.

2. Helmet Unit (Master NodeMCU)

The helmet unit integrates multiple sensors to monitor rider conditions in real time.

a) Helmet Detection (IR Sensor)

An **IR sensor** is placed inside the helmet to detect whether the rider is wearing the helmet. The sensor outputs a digital signal:

HIGH → Helmet worn

LOW → Helmet not worn

This condition is continuously monitored by the master NodeMCU.

b) Alcohol Detection (MQ-3 Sensor)

The **MQ-3 sensor** detects alcohol vapors from the rider's breath. The sensor provides an analog voltage proportional to alcohol concentration.

If alcohol level > threshold → Unsafe condition

If alcohol level < threshold → Safe condition

The NodeMCU processes this signal to determine whether the rider is fit to drive.

c) Accident Detection (MPU6050 Sensor)

(your important addition)

The **MPU6050 sensor**, which includes a 3-axis accelerometer and 3-axis gyroscope, continuously monitors:

Sudden acceleration

Tilt angle

Impact force

If the sensor values exceed predefined thresholds (e.g., high vibration or sudden tilt), the system identifies it as a **possible accident condition**.



Fig. 1

d) GPS Module (NEO-6M)

A **GPS module** is used to capture real-time coordinates (latitude and longitude) of the rider during emergencies.

e) Decision Logic (Master NodeMCU)

The master NodeMCU processes all sensor data and applies the following logic:

IF (Helmet worn = TRUE) AND (Alcohol detected = FALSE) → Send "START SIGNAL" via Bluetooth

ELSE

→ Do not send signal

Additionally, in case of accident detection: → Send "ACCIDENT SIGNAL + GPS DATA" to slave NodeMCU

3. Bike Unit (Slave NodeMCU)

The bike unit acts as an execution and communication system.



Fig.2

a) Bluetooth Receiver

The slave NodeMCU receives signals from the helmet (master) via Bluetooth.

b) Ignition System (Motor/Relay)

A **motor (prototype)** or **relay (real bike)** is connected to the slave NodeMCU:

If valid signal received → Motor ON (Bike starts)

If no signal → Motor OFF

This ensures that the bike cannot start unless safety conditions are satisfied.

c) GSM Module (On Slave – Your Actual Design) ✓

A **GSM module** is connected to the slave NodeMCU to send SMS alerts.

When the slave receives an **accident signal** from the master:

It extracts GPS coordinates

Sends SMS to emergency contacts

4. Communication Flow

Helmet NodeMCU (Master) checks:

Helmet condition

Alcohol condition

If safe: → Sends Bluetooth signal

Bike NodeMCU (Slave): → Receives signal
→ Activates ignition

During accident: → MPU6050 detects impact
→ GPS gets location
→ Data sent to slave
→ GSM sends alert

5. System Advantages of This Architecture

1. Separation of sensing and ignition improves safety.
2. Bluetooth-based communication reduces wiring complexity.
3. Helmet acts as intelligent controller (prevents misuse).
4. Fast emergency alert via GSM.
5. Modular design (easy future upgrades like AI, cloud).




Fig.3

IV. FUTURE SCOPE

The proposed system can be further enhanced by integrating **AI-based** helmet detection using computer vision, cloud-based monitoring for real-time data access, and advanced communication technologies such as IoT platforms. Additional features like **health monitoring sensors**, **voice-based SOS alerts**, and mobile application integration can further improve rider safety and system efficiency.

V. CONCLUSION

The proposed Smart Helmet system provides an effective and reliable solution for enhancing motorcycle rider safety through IoT-based automation. By implementing a **dual NodeMCU architecture with Bluetooth communication**, the system ensures that critical safety conditions are verified at the helmet level before enabling vehicle ignition.

The integration of an **IR sensor for helmet detection** and an **MQ-3 sensor for alcohol detection** successfully prevents unsafe riding practices such as riding without a helmet or under the influence of alcohol. The use of a **master-slave communication model** improves system modularity and ensures secure data transmission between the helmet and bike units.

Furthermore, the inclusion of an **MPU6050 sensor for accident detection** and a **GPS-GSM based alert system** enables real-time emergency response by sending the rider's location to predefined contacts. This significantly reduces response time during critical situations and increases the chances of timely medical assistance.

Overall, the system demonstrates a **cost-effective, scalable, and practical approach** to improving road safety and minimizing human errors. Future enhancements such as **AI-based monitoring**, **cloud integration**, and **advanced communication**

technologies can further improve system efficiency, accuracy, and real-world adaptability.

VI. REFERENCES

- [1] Choi, Yosoon, and Yeanjae Kim. "Applications of smart helmet in applied sciences: a systematic review." *Applied Sciences* 11, no. 11 (2021): 5039.
- [2] Lee, Peter, HeePyung Kim, M. Sami Zitouni, Ahsan Khandoker, Herbert F. Jelinek, Leontios Hadjileontiadis, Uichin Lee, and Yong Jeong. "Trends in smart helmets with multimodal sensing for health and safety: scoping review." *JMIR mHealth and uHealth* 10, no. 11 (2022): e40797.
- [3] Pearkao, Chatkhane, Puripong Suthisopapan, Arunnee Jaitieng, Sukuman Homvisetvongsa, and Lerkiat Wicharit. "Development of an AI-Integrated Smart Helmet for Motorcycle Accident Prevention: A Feasibility Study." *Journal of Multidisciplinary Healthcare* (2025): 957-968.
- [4] Mathavan, J. Joy, V. K. D. Wijesekara, N. Satheeskanth, W. M. U. J. Wanasinghe, M. Maathushan, and V. V. Wijenayake. "Smart helmet to start the motorbike and to prevent accidents." In IOP Conference Series: Materials Science and Engineering, vol. 1258, no. 1, p. 012051. IOP Publishing, 2022.
- [5] Rajarathnam, D. R. P., S. Manikandan, S. Gokul, G. Viknesh, and S. Ranjith. "Development of Smart Helmet Detection System for Motorcycle Rider." *International Research Journal on Advanced Electronics and Computer Technology (IRJAECT)* 1, no. 01 (2025): 34-38.
- [6] Kanase, Sandip S., Shivagond N. Teli, Sandhya D. Jadhav, Jaydeep S. Patil, Tanaji S. Kanase, and Ankur S. Pawar. "Design and development of Smart Helmet." *Journal of The Institution of Engineers (India): Series C* 104, no. 2 (2023): 253-259.
- [7] Shahare¹, Bhavesh, Shivani Chawde, Rakesh Gudafwar, Harshada Pal⁴, Purvi Bobade⁵, and Shyam Bawankar. "IoT Based smart motor cycle helmet." *Journal of Electronics* 3, no. 01 (2021): 15-22.
- [8] Vivekanandan, P., P. Radhika, A. Sivamani, P. Pradeesh, and D. Rakesh. "Accident Prevention Using IoT-Based Smart Helmet." *Nanosistemi, Nanomateriali, Nanotecnologii* 22, no. 3 (2024).
- [9] Pawar, Omkar, Sakshi Khanna, Dipali Walde, and Najib Ghatte. "Smart Helmet Ignition System: A Solution to Ensure Bike and Pillion Rider Safety." In *International Conference on Recent Advancements and Modernisations in Sustainable Intelligent Technologies and Applications (RAMSITA 2025)*, pp. 914-925. Atlantis Press, 2025.
- [10] Prasetyawan, Purwono, Slamet Samsugi, Agus Mulyanto, Muhammad Iqbal, and Rizky Prabowo. "A prototype of IoT-based smart system to support motorcyclists safety." In *Journal of Physics: Conference Series*, vol. 1810, no. 1, p. 012005. IOP Publishing, 2021.