

Smart Surveillance Restoration System: Frameworks, Challenges, and Future Directions

Chinta Yaswanth Varma

(160122771100)

Dept. of AI & DS

CBIT, Hyderabad, India

chintayaswanth99@gmail.com

Garlapati Lalithya

(160122771307)

Dept. of AI & DS

CBIT, Hyderabad, India

lalithya04122005@gmail.com

Seri Ratan Kumar

(160122771127)

Dept. of AI & DS

CBIT, Hyderabad, India

ratankumarseri23@gmail.com

Pallavi Yenigalla

Dept. of AI & DS

CBIT, Hyderabad, India

pallaviyenigalla_aids@cbit.ac.in

Abstract—Intelligent surveillance restoration platforms are important for recovering and improving video footage. They turn unprocessed surveillance footage into useful information in today's world of widespread video surveillance. The full evaluation shows that modern systems use intelligent processing pipelines to get the most out of degraded video footage by combining scene separation, quality improvement, and missing data recovery systems. The examination of twelve pivotal papers elucidates their methodologies for addressing prevalent visual disturbances such as darkness, motion artifacts, and occlusions via standard benchmark testing and practical application evaluations. Our evaluation indicates substantial progress in adaptive real-time input management, alongside persistent difficulties in cross-scenario robustness and resource demands. The research paper presents a methodology that offers comprehensive security system management by employing automated solutions to minimize human errors and enhance threat detection through improved security alert systems.

Index Terms—Smart Surveillance, Video Restoration, Dynamic Scene Processing, Quality Enhancement, Gap-Filling Techniques

I. INTRODUCTION

The digital surveillance networks have grown to the point where they are now used as the main source of information for security operations, investigations, and urban control systems [1], [3], [5], [7], [10]. It takes a lot of manual work to improve these streams because it means changing the brightness, fixing defects, and rebuilding segments, which uses up resources and makes the system less reliable [4], [6], [9], [12]. To make intelligent systems, we need to find the most important parts and improve video quality by repairing disruptions on their own. This is because the quality of the footage keeps getting worse because of environmental conditions, hardware problems, and compression artifacts. [2], [11], [13].

Their most recent research has shown that the problem is widespread. Studies from 2024 show that about 60–70% of urban surveillance video is useless because of bad lighting and camera movement, which makes the video blurry and hard to analyze for evidence and ongoing threats. The situation calls

for the quick creation of automated restoration systems that can use AI to quickly and accurately recover information from these data sets at edge locations.




Fig. 1. Breakdown of Common Degradation Types in Surveillance Footage (Based on 2024 Urban Monitoring Surveys)

Modern progress relies on the integration of machine learning systems that utilize temporal patterns and sensory information systems to develop innovative approaches for managing surveillance data [3], [5], [8], [10]. But legacy pipelines still depend a lot on expert advice, which can cause bottlenecks that slow down important workflows in high-stakes settings [9], [14]. The recent changes are all about making systems that are easier to use and can work in a variety of settings while still being flexible [11], [15], [16].

Generative architectures that use adversarial setups, progressive refiners, and attention-driven modules are great at fixing missing data problems, making continuous frame sequences, and supporting different types of analytical operations [1], [3], [7], [8], [12]. The Smart Restoration Core will work as an independent system that finds and fixes problems, comes up with solutions, checks results, and gets useful information with

little help from people [2], [6], [13], [17]. These tools are always having trouble with time-based transitions, handling system failures that aren't always predictable, and keeping data safe [5], [9], [15]. The primary challenge of live deployment systems arises from the quest for comprehensive performance data analysis, as system upgrades and diverse training methodologies fail to address the issue of protracted response times [14], [16], [18].

Integrated designs have gained popularity for addressing these challenges [2], [4], [11], [17]. These systems make operations run better by going through different steps, such as finding flaws, improving signals, and checking for coherence [6], [9], [13]. The examples demonstrate how components enhance their interactions via coordinated layers that manage intricate visibility scenarios and collaborative configurations that facilitate shared computing [10], [12], [15]. Still, a lot of users care more about how things look than about important things like system speed, energy efficiency, and following the law, which are all necessary for real integration [14], [18], [19].

The Smart Restoration Core's operational loop [1], [2], [5], [11], [16] combines artistic generation with controlled management and constant evaluation. Combining intuitive cues with layered dissemination and corrective cycles makes self-governing systems that work with trustworthiness and clear improvement processes [3], [7], [8], [12], [17]. The responsive loop has different modules that do different things, such as finding anomalies and checking accuracy [9], [13], [15]. The organization uses continuous monitoring, quantitative benchmarking, stakeholder validation, and audit trails as part of its evaluation process to make sure that restored footage meets operational, legal, and evidentiary standards.

The study combines well-established successes in cross-modal integration, creative automation, and flexible refinement systems [2], [6], [9], [11], [16]. Twelve important studies that demonstrate outcomes in adaptive scaling, flow-based mending, and unified processing are presented in the analysis. Through the creation of autonomous systems that facilitate improved insight recovery, the analysis demonstrates how intelligent automation revolutionizes surveillance intelligence operations. [1]–[13], [15]–[21].

II. RELATED WORKS

A. Robust Nonlinear Functions for Dim Scene Recovery [1]

The study compares the effectiveness of several approaches for mapping underlit visuals with more conventional techniques for interference reduction and boundary preservation. It achieves approximately 11% better signal-to-noise ratios in low-visibility sequences by optimizing fits across a variety of environments, making it appropriate for basic surveillance tasks. When dealing with extreme overexposure scenarios, the method performs poorly, demonstrating the necessity of combined assumption-based approaches. [1].

The potential applications of nonlinear functions in distributed surveillance networks are increased by the new edge

AI integration trends for 2025, which allow them to function in real-time on devices with limited resources.

B. Semantic Guidance for Obscured Region Revival [2]

By doing testing on stormy dusk video footage, the authors present a context-aware system that anticipates environmental indicators to improve hidden areas. The technique improves object visibility by reducing fringe effects by 17%. Simplified versions for on-device operation are required due to the system's increased processing power requirements [2].

C. Integrated Handling of Precipitation and Low Illumination [3]

The technique tests its performance on a combination of artificial and real-world datasets and employs two processing units to handle overlapping problems concurrently. Although the combined approaches improve structural metrics by 8dB, data source changes result in diminishing returns that require constant adjustment [3].

D. Light Reconstruction Using Virtual Probe Simulation [4]

To improve performance in unstable lighting conditions by 14%, the system uses virtual light sources to restore environments from partial information. According to the results of reference [4], the current system requires material-specific enhancements to handle reflective surfaces.

done

E. Adversarial Masking for Concealed Audio Retrieval [6]

The self guided competitive learning technique extracts voices among visual clutter and the quality of the output is improved by 21 percent feedback mechanism. The selective disclosure strategy proves in handy in the privacy preservation, but the system does not accommodate the various accents. This has been observed to render its use in a wider manner impossible.

F. Combined Noise Reduction and Scaling for Compact Devices [7]

The dual-path model is effective when linked sensors are involved to perform both the cleanup operation and the enlargement operation that results in reduction of 32 percent delay on simple hardware systems. The system is scalable although it has limited storage capacity that restricts its capacity of handling high definition contents.

G. Challenged Identity Archive for Detection Tuning [8]

Identification instruments of its database of modified low-resolution photos of faces are judged by the system 13 percent. Researchers have noted that more heterogeneous groups of participants should be hired since the dataset is not collected in a balanced way.

H. Statistical Filtering for Distortion in Packed Streams [9]

The first classification process means the removal of the abnormal data, which results in the increase of the latter activities by a 19 percent due to the special interventions. The system is user friendly but it does not detect emerging types of data perversion. [9].

done

I. Flow-Optimized Frame Enlargement [10]

This system provides bidirectional sequence synchronization via the sophisticated motion tracking that leads to 6dB signal enhancement of unsteady video images. The rapid movements still result in inconsistencies. [10].

J. Streamlined Modules for Sequential Scaling [11]

Vital part extraction in the system reduces the size of the system by 38 percent and preserves the quality of the original products. The research outlines threats that come about due to the use of small datasets when tuning. [11].

K. Simulated Flaw Generation for Broad Adaptation [12]

Creation of the artificial problem by the practical enhancer leads to a 9 percent improvement of the ordinary methods of dealing with new forms of flaws. The holes in imitating outliers are still an issue. Some topic sentences in the article are designed so that the reader can clearly grasp their intended significance. —human—; subheading Signal Disentanglement of Clear Origins [13]) The temporal splitter works to isolate elements that results to a 24 percent enhancement in the clarity of dialogues when working in a noisy environment. This issue of overlapping elements continues to happen with complex audio mixes as per research

III. COMPARATIVE ANALYSIS

The following section evaluates twelve selected contributions through multiple levels to develop a **Smart Restoration Core** blueprint. The evaluation system analyzes four main criteria which include quality markers (signal metrics and similarity), performance metrics (speed and operations), resilience (variation tolerance), and extensibility (volume handling). The research shows how generative tools and structures lead to better recovery and proxy modeling and fine-tuning methods in surveillance applications. The 2025 research focuses on edge computing integration to develop models which deliver both rapid processing and high-quality output restoration. The system enables privacy protection at device level which satisfies current privacy requirements while solving smart city deployment problems.

A. Overview of Examined Contributions: Approaches and Shortcomings

Table I summarizes key strategies and their limitations.

TABLE I
OVERVIEW OF EXAMINED CONTRIBUTIONS: APPROACHES AND SHORTCOMINGS

Authors	Approach	Shortcomings
Razafindratovolahy et al.	Curve-based dim recovery [1]	Overloads on peaks; needs assumptions [1]
Xiao et al.	Context hints for obscurations [2]	Resource-intensive; lighter versions required [2]
Lin et al.	Paired paths for wet/dim issues [3]	Origin mismatches weaken [3]
Zhu et al.	Simulated sources for brightness [4]	Reflections unhandled [4]
Wang et al.	Competitive veils for audio [6]	Accent constraints [6]
Ge et al.	Fused cleanup-scaling [7]	High-res storage hurdles [7]
Manchanda et al.	Altered archive for tuning [8]	Sampling skews [8]
Sathish et al.	Measure-based anomaly sorting [9]	Dynamic flaws escape [9]
Chan et al.	Motion-synced enlargement [10]	Rapid shifts falter [10]
Chan et al.	Vital part extraction [11]	Narrow data fits poorly [11]
Wang et al.	Artificial flaw building [12]	Outlier mismatches [12]
Defossez et al.	Temporal component split [13]	Mix complexities linger [13]

B. Quality-Focused Evaluation

Quality assessment depends on two main factors which include the accuracy of results and the evaluation of errors through signal-to-noise and similarity score analysis. The research studies [3], [5], [7], [9], [10] present measurement approaches that focus on particular application areas. Table II summarizes.

The evaluation system shows Paired Paths performs better than other systems when dealing with multiple types of degradation which surveillance footage typically experiences during weather and movement conditions.

C. Performance and Optimization Review

Performance is key for practical rollout. The research from [1], [4], [7], [11] demonstrates various approaches to decrease both system expenses and operational timeframes. Table III highlights differences.

The upcoming surveillance system of 5G technology in 2025 will make these enhancements necessary by enabling

TABLE II
QUALITY EVALUATION ACROSS KEY MODELS

Contribution / Model	Domain Focus	Key Quality Metric
Paired Paths [3]	Wet/Dim Combo	+8dB Similarity
Fused Cleanup [7]	Sensor Scaling	34.5 Signal-to-Noise
Motion-Synced [10]	Sequence Scaling	31.9 Signal-to-Noise
Practical Enhancer [12]	Varied Flaws	+9% Novel Hold
Structure-Guided [18]	Gap Mending	27.8 Similarity




Fig. 2. Visual Quality Evaluation Across Models

lower-latency, higher-bandwidth links that support edge-cloud hybrid deployments and allow restoration modules to run closer to where data is produced.

TABLE III
PERFORMANCE AND OPTIMIZATION REVIEW

Contribution / Model	Measure	Gain
Curve Mapping [1]	Operation Reduction	-23% Operations
Simulated Sources [4]	Processing Time	14% Faster
Fused Model [7]	Device Handling	32% Quicker
Vital Extraction [11]	Size Trim	-38% Parameters

D. Resilience and Consistency Measures

Resilience tests steady results under changes. [6], [8], [12], [18] explore repeated scenarios. Table IV aggregates.

Multiple factors in urban surveillance systems lead to testing resilience because they operate under changing light conditions and fluctuating numbers of people which demands training data with high quality.

E. Extensibility and Intuitive Handling Review

The main purpose of the core system depends on its ability to evaluate large-scale processing operations which operate independently. [7], [10], [11], [19] probe this. Table V emphasizes.

Smart cities require surveillance systems that can monitor extensive urban areas so restoration pipelines need to process




Fig. 3. Visual Performance and Optimization Review

TABLE IV
RESILIENCE AND CONSISTENCY MEASURES

Contribution / Model	Test Ground	Resilience Indicator
Competitive Veils [6]	Repeated Sharpness	21% Steady
Altered Archive [8]	Variation Tolerance	13% Reliable Precision
Practical Enhancer [12]	New Flaws	88% Quality Retention
Structure-Guided [18]	Fluid Completions	Expert-Level Match

large petabyte-scale archives while maintaining stable computational performance.

F. Broader Evaluation Takeaways

The research shows that recovery through creative methods continues to develop as a field of study. Leaders in quality/stability: Paired Paths, Practical Enhancer; in performance: Fused, Vital Extraction; in extensibility: Kernel-Adaptive, Loop Refiner. The independent cores unite natural quality with




Fig. 4. Visual Resilience and Consistency Measures

TABLE V
EXTENSIBILITY AND INTUITIVE HANDLING REVIEW

Contribution / System	Intuitive Range	Extensibility Result
Fused Model [7]	Sensor Cleanup-Scaling	Device-Flexible
Motion-Synced [10]	Sequence Sync	Batch Capacity
Kernel-Adaptive [19]	Shake Correction	Motion Extensible
Loop Refiner [20]	Stepwise Polish	Volume Iterative




Fig. 5. Visual Extensibility and Intuitive Handling Review

efficient flow and self-sufficient surveillance through modular design elements.

The perfect design demands a combination of sync (ref10), hints (ref2), and trimming (ref11) to achieve full restoration.

IV. GAPS IDENTIFIED

Deep architectures have made progress in recovery and handling tasks yet fundamental gaps continue to exist [1], [3], [5], [7], [10], [11]. Video inpainting for surveillance faces two major challenges that affect its performance: camera motion and static versus dynamic region separation which results in degraded restoration quality that undermines evidential integrity.

A. Constrained Flexibility and Adjustment

The existing frameworks tend to focus on specific defects or particular measurement scales [3], [4], [6], [9]. The development of new combinations needs additional work [7], [10], [12], [13] which restricts the ability to use versatile cores [11], [14], [15].

B. Weak Cross-Modal Teamwork

Division of labor exists but the integration of systems remains at a fundamental stage [2], [5], [8], [11]. The system requires both standardized hidden layers and adaptable connections to achieve complete visual-audio understanding [9], [13], [16], [17]

C. Shortfalls in Assessment Standards

The current ratings system bases its evaluations solely on signal scores which disregards important aspects such as operational value and system continuity and data tracking capabilities [3], [7], [9], [12]. The absence of unified surveillance standards creates an obstacle for performing accurate comparisons [10], [14], [18], [19].

D. Deficit in Clarity and Openness

The dark secrets keep the core functions shrouded in darkness that weakens faith in official use of the functionality of these core functions

Training loops and repeats block on-site execution [2], [6], [9], [11]. The current research shows that only a few methods exist for reducing or increasing weight [10], [14], [17], [19].

E. Hurdles in Merging with Current Flows

The research shows positive results yet the integration between security and learning chains operates independently [3], [5], [8], [12]. The current status of input validation standards remains underdeveloped according to research papers [9], [13], [15], [18]. The research fails to handle both synthetic data threats and bias issues which remain unaddressed throughout the process [4], [7], [9], [11]. The absence of proper verification procedures leads self-run results to produce erroneous conclusions according to [5], [10], [14], [17] especially when proof gaps occur [12], [15], [18], [20].

F. Sparse Real-Setting Tests and Rollouts

Research in different fields continues to advance but researchers have not yet established sufficient evidence from actual field tests. Studies about team dynamics and long-term survival rates have not been conducted extensively.

G. Missing Adaptive Growth

People do not assess their own errors or conduct self-assessments of their experimental work. The complete core structures of Looped evolution remain unstudied at this point.

H. Scattered Open Development

The drive for repeatability creates divisions between different kinds of resources and their corresponding interfaces. The system lacks both unified testing capabilities and additional add-on components.

I. Gap Roundup

The research continues to advance yet it fails to address essential aspects regarding system flexibility and openness and reach and self-rule capabilities. The gaps need core permanence through established norms and properly defined measurement systems and unambiguous construction methods. [8], [10], [15], [18], [20].




Fig. 6. Key Challenges in Video Inpainting for Surveillance Applications (Relative Impact Scores)




Fig. 7. Projected Advancements in AI-Driven Video Restoration for Surveillance (2025-2030)

V. FUTURE RESEARCH DIRECTIONS

Core evolution aims to achieve flexible operations through precise understanding and truthful interactions with customers [1], [2], [5], [11]. Top: broad builds address flaws without hands-on changes [3], [6], [9], [13]. The process of ongoing learning through oversight helps people develop abilities to handle new challenges that emerge in their environment [7], [10], [12], [15].

Evaluation of the restoration pipeline system for 2025 and beyond shows edge AI and cloud-hybrid architectures will revolutionize its operational capabilities. The system will allow predictive maintenance of footage quality and direct connection with IoT surveillance systems. The new system will provide real-time behavioral analysis during restoration to enhance threat detection capabilities.

The spread parts exchange ideas through systematic findings parsing which researchers demonstrated in their studies [2], [4], [8], [11]. The process of group echoing leads to the creation of new ideas [5], [9], [14], [16]. Standards now extend beyond scoring systems because they include elements that promote freshness and unity and allow for verification [6], [12], [18].

Openness builds assurance [3], [5], [11], [15]. Weave trackable bits explaining routes [7], [9], [12], [16]. Panels/levels open logic widely [10], [13], [18]. Power pushes slimming/lightening for eco scales [8], [14], [19].

Morals/sensitivity guide advances [2], [5], [9], [17]. Guard against fakes/skews [4], [10], [12], [15]. Checks/skew nets tune morals [6], [13], [18]. Shared setups enable teams to work together while keeping their work areas free from any accidental spills [7], [11], [16], [19].

Tests through extended fields [1], [3], [8], [14]. Live checks give bend data [9], [12], [17], [19]. Endgame: self-growing, error-fixing, honing across times [5], [10], [15], [20]. Rapid circular motion gives rise to strong, continuous cores. [2], [6], [11], [18], [20]–[24].

VI. CONCLUSION

The overview provides an in-depth analysis of Smart Restoration Cores which will revolutionize monitoring systems by using guided flaw detection and repair and creation and weaving techniques. Research of available sources indicates that deep builds have experienced sudden increases together with various adjustments and alternate methods for intuitive salvage. The situation continues to exist because of the ongoing breaches in organizational flexibility and candor and measurement practices and moral standards. The investigation proposes three essential elements which include standardized testing protocols, improved interoperability and system navigation methods, and clear, domain-aware evaluation criteria (for example, task-specific spatial/area metrics) to support robust comparison and deployment. The combination of oversight techniques with cost-effective designs produces genuine self-help tools which enhance field detection speed.

Future systems will achieve dual objectives of footage recovery and predictive capability enhancement through collaborative interpretable AI frameworks which will transform surveillance into an intelligent public safety guardian.

REFERENCES

- [1] A. Razafindratovolahy and Y. Rao, "A Simple Yet Robust Nonlinear Function for Low-Light Image Enhancement Task," *IEEE Signal Processing Letters*, vol. 32, pp. 3370–3374, 2025.
- [2] Q. Xiao, H. Jin, H. Su and R. Yan, "SELL: A Method for Low-Light Image Enhancement by Predicting Semantic Priors," *IEEE Signal Processing Letters*, vol. 32, pp. 1785–1789, 2025.
- [3] X. Lin, J. Yue, S. Ding, C. Ren, L. Qi and M.-H. Yang, "Dual Degradation Representation for Joint Deraining and Low-Light Enhancement in the Dark," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 35, no. 3, pp. 2461–2473, Mar. 2025.
- [4] Z. Zhu, X. Yang, R. Lu, T. Shen, T. Zhang and S. Wang, "Ghost Imaging in the Dark: A Multi-Illumination Estimation Network for Low-Light Image Enhancement," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 35, no. 2, pp. 1576–1590, Feb. 2025.
- [5] C. G. Willcocks et al., "Deep learning for digital pathology: A survey of the state of the art," *Medical Image Analysis*, 2023.

- [6] S.-S. Wang, J.-Y. Chen, B.-R. Bai, S.-H. Fang and Y. Tsao, "Unsupervised Face-Masked Speech Enhancement Using Generative Adversarial Networks With Human-in-the-Loop Assessment Metrics," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 32, pp. 3826–3837, 2024.
- [7] L. Ge, W. Bao, X. Sheng, D. Yuan, B. B. Zhou and Z. Wang, "Joint Video Denoising and Super-Resolution Network for IoT Cameras," *IEEE Internet of Things Journal*, vol. 11, no. 17, pp. 28526–28538, Sep. 1, 2024.
- [8] S. Manchanda, K. Bhagwatkar, K. Balutia, S. Agarwal, J. Chaudhary, M. Dosi, C. Chiranjeev, M. Vatsa and R. Singh, "D-LORD: DYSL-AI Database for Low-Resolution Disguised Face Recognition," *IEEE Transactions on Biometrics, Behavior, and Identity Science*, vol. 6, no. 2, pp. 147–157, Apr. 2024.
- [9] E. Sathish, S. Radha, and P. Florence, "Noise Classification and Removal in Compressively Sensed Surveillance Videos Using Statistical Measures," in *Proc. International Conference on Computer Communication and Informatics (ICCCI)*, Coimbatore, India, 2023, pp. 1–6.
- [10] K. C. K. Chan, X. Wang, K. Yu, C. Dong, C. C. Loy, "BasicVSR++: Improving Video Super-Resolution with Enhanced Propagation and Alignment," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 8260–8270.
- [11] K. C. K. Chan, X. Wang, K. Yu, C. Dong, C. C. Loy, "BasicVSR: The Search for Essential Components in Video Super-Resolution and Beyond," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2021, pp. 4947–4956.
- [12] X. Wang, L. Xie, C. Dong, Y. Shan, "Real-ESRGAN: Training Real-World Blind Super-Resolution with Pure Synthetic Data," in *Proc. IEEE/CVF Int. Conf. on Computer Vision Workshops (ICCVW)*, 2021, pp. 196–205.
- [13] A. Defossez, G. Synnaeve, and Y. Adi, "Real-Time Speech Enhancement in the Waveform Domain," *arXiv preprint arXiv:2006.12847*, 2020.
- [14] R. Zhang, P. Isola, A. A. Efros, E. Shechtman, and O. Wang, "The unreasonable effectiveness of deep features as a perceptual metric," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2018, pp. 5867–5876.
- [15] O. Kupyn, T. Martyniuk, J. Wu, Z. Wang, "DeblurGAN-v2: Deblurring (Orders-of-Magnitude) Faster and Better," in *Proc. IEEE/CVF Int. Conf. on Computer Vision (ICCV)*, 2019, pp. 8877–8886.
- [16] Y.-T. Chang et al., "Free-Form Video Inpainting with 3D Gated Convolution and Temporal PatchGAN," in *Proc. IEEE/CVF Int. Conf. on Computer Vision (ICCV)*, 2019, pp. 8837–8846.
- [17] D. Kim et al., "Deep Video Inpainting," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 5792–5801.
- [18] K. Nazeri, E. Ng, T. Joseph, F. Qureshi, M. Ebrahimi, "EdgeConnect: Structure-Guided Image Inpainting Using Edge Prediction," in *Proc. IEEE/CVF Int. Conf. on Computer Vision Workshop (ICCVW)*, 2019, pp. 3265–3274.
- [19] X. Wang, K. C. K. Chan, K. Yu, C. Dong, C. C. Loy, "EDVR: Video Restoration with Enhanced Deformable Convolutional Networks," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition Workshops (CVPRW)*, 2019, pp. 195–204.
- [20] M. Haris, G. Shakhnarovich, N. Ukita, "Recurrent Back-Projection Network for Video Super-Resolution (RBP)," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 3887–3896.
- [21] S. Kondratyuk et al., "AIM 2025 Low-light RAW Video Denoising Challenge: Dataset, Methods and Results," *arXiv preprint arXiv:2508.16830*, 2025.
- [22] A. Dehan and L. Kong, "Complete and Temporally Consistent Video Outpainting," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition Workshops (CVPRW)*, 2022, pp. 1240–1249.
- [23] J. Sun et al., "The Tenth NTIRE 2025 Image Denoising Challenge Report," in *Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition Workshops (CVPRW)*, 2025.
- [24] M. Gonzalez-Huici et al., "Efficient Recurrent Real Video Restoration," *Digital Signal Processing*, vol. 145, 2024.