

SMART TRASH COLLECTOR AN IOT BASED AUTOMATED WASTE COLLECTOR

Aarthi A¹, Brindha S², Shanmugi M³, Sneekha M⁴ and Shiyamala K⁵

^{1,2,3,4}UG Students, Department of Artificial Intelligence and Data Science, Bharathiyar Institute of Engineering for Women (Autonomous), Salem, Tamil Nadu, India.

⁵ Assistant Professor, Department of Artificial Intelligence and Data Science, Bharathiyar Institute of Engineering for Women (Autonomous), Salem, Tamil Nadu, India.

ABSTRACT

Rapid urbanization and population growth have led to a significant increase in the generation of solid waste in cities and public places. Efficient waste management has become one of the major challenges faced by municipal authorities and environmental agencies. Traditional waste collection systems usually operate on fixed schedules and rely on manual inspection of garbage bins. These conventional methods are often inefficient because waste bins may overflow before the scheduled collection time, leading to unhygienic conditions, foul odour, and the spread of diseases. In addition, unnecessary trips by waste collection vehicles to half-filled bins result in increased fuel consumption, higher operational costs, and inefficient use of manpower. To address these issues, this project proposes a Smart Trash Collector, an automated waste monitoring system that uses Internet of Things (IoT) concepts combined with GSM communication technology. The main objective of this system is to monitor the garbage level inside waste bins in real time and notify the waste management authorities when the bin becomes full. The system uses an Ultrasonic Sensor to measure the distance between the top of the bin and the garbage level. The measured data is processed using an 8051 Microcontroller, which

continuously analyzes the fill level of the bin. When the garbage level exceeds a predefined threshold value, the microcontroller automatically activates a GSM Module to send a Short Message Service (SMS) alert to the municipal authority or waste collection personnel. This alert system ensures that the garbage bin is emptied at the right time, preventing overflow and maintaining cleanliness in public areas. In addition, an LCD display is used to show the garbage status locally, and a buzzer provides an immediate alert signal when the bin reaches the maximum capacity. The proposed system helps improve the efficiency of waste management by enabling timely collection and reducing unnecessary monitoring efforts. It also minimizes environmental pollution, improves public hygiene, and reduces operational costs associated with manual waste management systems. The system is simple, cost-effective, and easy to implement using embedded system components. Due to its reliability and wide communication coverage through GSM technology, the system can be effectively used in both urban and rural areas.

Furthermore, the Smart Trash Collector can play an important role in the development of smart cities by introducing automation and real-time monitoring in waste management processes. The

system can be deployed in various locations such as railway stations, bus stands, hospitals, educational institutions, shopping malls, and residential areas. By ensuring efficient waste monitoring and collection, this system contributes to creating a cleaner, healthier, and more sustainable environment.

Keywords:

IoT, Smart Waste Management, Ultrasonic Sensor, 8051 Microcontroller, GSM Module, Garbage Monitoring System

I.INTRODUCTION

Waste management has become a major problem in many cities and urban areas due to rapid population growth and increasing consumption. Traditional garbage collection systems mostly follow fixed schedules, where waste collection vehicles visit bins at regular intervals without knowing whether the bins are full or empty. This often leads to inefficient waste collection, overflowing garbage bins, unpleasant odours, and unhygienic surroundings. Overflowing bins can also attract insects, animals, and harmful bacteria, which may cause serious health and environmental problems.

With the advancement of the Internet of Things (IoT), it is now possible to design smart systems that monitor and manage waste more efficiently. IoT enables devices and sensors to communicate with each other and share data through networks, making automation and real-time monitoring possible. By integrating sensors, microcontrollers, and communication modules, waste management systems can become more intelligent and responsive.

The Smart Trash Collector system is designed to improve the efficiency of waste collection using modern technology. In this system, an ultrasonic sensor

is used to measure the level of garbage inside the bin. The sensor continuously monitors the distance between the garbage surface and the top of the bin. When the garbage reaches a predefined threshold level, the sensor sends the data to the 8051 microcontroller, which acts as the main control unit of the system.

The microcontroller processes the sensor data and determines whether the bin is full or not. When the garbage bin reaches its maximum capacity, the system automatically sends a notification message to the waste management authority using a GSM module. This message alerts the authorities that the bin needs to be emptied. Additionally, an LCD display can show the current status of the bin, and a buzzer can provide a local alert when the bin is full.

This automated system helps municipal authorities monitor garbage bins remotely and collect waste only when necessary. As a result, it reduces unnecessary trips by garbage collection vehicles, saves fuel, and improves operational efficiency. Moreover, it helps maintain cleaner surroundings, reduces environmental pollution, and supports the development of smart cities.

The Smart Trash Collector system demonstrates how IoT technology can be used to solve real-world problems by making waste management systems smarter, more efficient, and environmentally friendly.

II.RELATED WORK

Several researchers have proposed smart waste management systems using IoT technologies to improve the efficiency of garbage collection and reduce environmental pollution. These systems mainly use sensors, microcontrollers, and communication modules to monitor garbage levels and send alerts when bins become full.

A study proposed an IoT-based smart garbage monitoring system where ultrasonic sensors are used to measure the level of waste in garbage bins. The sensor detects the distance between the garbage and the top of the bin, and when the waste reaches a predefined level, the system sends a notification to waste collection authorities. This approach helps prevent overflowing bins and maintains a cleaner environment.

Another research work developed a GSM-based intelligent garbage monitoring system that uses sensors and a microcontroller to detect garbage levels and send SMS alerts to the control room. The system ensures that waste is collected quickly when the bin becomes full and helps municipal authorities manage waste collection more efficiently.

Some researchers also proposed IoT-enabled waste management systems with GPS and web-based platforms. These systems allow authorities to monitor the status of multiple bins in real time and optimize garbage collection routes. Such systems improve operational efficiency and reduce fuel consumption by avoiding unnecessary collection trips.

Recent studies further enhanced smart waste management systems by integrating advanced technologies such as cloud platforms, mobile applications, and data analytics. These systems provide real-time monitoring, automated alerts, and improved decision-making for municipal waste management operations.

Although many existing systems focus on IoT-based monitoring using different microcontrollers and communication platforms, there is still a need for a simple, low-cost, and reliable system. Therefore, this project proposes a Smart Trash Collector using an ultrasonic sensor, 8051 microcontroller, and GSM module, which provides an efficient and cost-effective

solution for monitoring garbage levels and notifying authorities when bins are full.


III. PROPOSED SYSTEM

The proposed system introduces a Smart Trash Collector that uses IoT technology to monitor the level of garbage in waste bins and improve waste management efficiency. The system mainly consists of an ultrasonic sensor, an 8051 microcontroller, a GSM module, an LCD display, and a buzzer. The ultrasonic sensor is placed at the top of the garbage bin to measure the distance between the sensor and the garbage level. This sensor continuously checks the bin status and sends the collected data to the 8051 microcontroller for processing.

The microcontroller analyzes the sensor data and determines whether the garbage bin has reached its maximum capacity. When the bin becomes full, the GSM module automatically sends an alert message to the waste management authority to inform them that the bin needs to be emptied. At the same time, the LCD display shows the status of the garbage bin and the buzzer provides a local alert. This proposed system helps in real-time monitoring of waste bins, prevents overflowing garbage, and improves the efficiency of waste collection systems.



LCD (Liquid Crystal Display): A passive display that modifies light to show status messages under electrical stimulus.



Relay: An electrically operated switch used for controlling high-power circuits via low-power signals.



IV.METHODOLOGY

The proposed system automates monitoring using embedded hardware and GSM communication.

4.1 Hardware Architecture

The system consists of several integrated components:

Microcontroller (8051/Arduino): An 8-bit core with 32 I/O lines, timers, and serial ports used to process sensor data.



Ultrasonic Sensor: Used for non-contact garbage level

detection.



GSM Module: Facilitates SMS communication with authorities.

4.2 Interfacing and Communication

The system uses serial communication, transmitting data one bit at a time. The serial port converts bytes (8 bits) into a stream of ones and zeros for the GSM module to process.

4.3 Working Process


Detection: The ultrasonic sensor measures the distance from the bin lid to the waste surface.

Processing: The microcontroller calculates the fill percentage.

Thresholding: If the level exceeds 80%, an alert is triggered.

Transmission: The GSM module sends a notification to the collection authority.

Local Indication: A buzzer provides immediate audio feedback



V.RESULTS AND DISCUSSIONS

The implementation demonstrates several advantages:

Independence: No internet is required due to the GSM-based architecture.

Efficiency: Prevents bin overflow and reduces fuel costs by optimizing truck routes.

Scalability: Suitable for railway stations, hospitals, and shopping malls.

The system effectively provides a real-time alert system that is easy to maintain and suitable for various environments.

VI.CONCLUSION

The Smart Trash Collector using GSM technology provides an efficient and reliable solution to traditional Schwartz, M. (2016). Internet of Things with Arduino Cookbook. Packt Publishing. (Explains the integration of ultrasonic sensors for measuring distances in automated systems).

Predko, M. (1999). Handbook of Microcontrollers. McGraw-Hill Education. (Discusses the application of LCDs as passive light controllers and the use of relays as electrically operated switches).

waste management problems. By enabling real-time monitoring and automated alerts, the system ensures timely collection, improves hygiene, and reduces operational costs. Its simplicity and low cost make it an ideal contribution to sustainable smart city initiatives.

VII.REFERENCES

- Mazidi, M. A., Mazidi, J. G., & McKinlay, R. D. (2005). The 8051 Microcontroller and Embedded Systems: Using Assembly and C. Pearson Education. (Provides the technical foundation for the 8 bit microcontroller core developed by Intel).
- Ayala, K. J. (2004). The 8051 Microcontroller: Architecture, Programming, and Applications. Cengage Learning. (Covers the CPU with Boolean processor and 32 I/O lines used in this system).
- Faludi, R. (2010). Building Wireless Sensor Networks: with ZigBee, XBee, Arduino, and Processing. O'Reilly Media. (Foundational text for implementing sensor-based data processing and threshold comparison).
- Peatman, J. B. (1988). Design with Microcontrollers. McGraw-Hill. (Details the use of serial communication to convert bytes to streams of ones and zeros for module interfacing).
- IJSREM Standards (2024). International Journal of Scientific Research in Engineering and Management: Author Guidelines and Publication Standards.