

# “Study of CNG Cylinder Testing and Leakage Detection Methods: A Case Study of Vijaya CNG Hydro Testing Services, Ahilyanagar.”

Sanket Bhaskar Thokal<sup>1</sup>, Gaurav Rajendra Shahane<sup>2</sup>, Dr. Ramesh Suryabhan Gadakh<sup>3</sup>

<sup>1</sup> Student, Department of Mechanical Engineering Sau Sundarbai Manik Adsul Polytechnic, Chas, Ahilyanagar, India

<sup>2</sup> Guide, Department of Mechanical Engineering Sau Sundarbai Manik Adsul Polytechnic, Chas, Ahilyanagar, India

<sup>3</sup> Principal Sau Sundarbai Manik Adsul Polytechnic, Chas, Ahilyanagar, India

## Abstract

Compressed Natural Gas (CNG) is widely used as an alternative automotive fuel because of its comparatively clean combustion characteristics and suitability for transportation applications. Since CNG is stored at high pressure, the integrity of cylinders, valves, pipelines, fittings and associated components is critical for vehicle safety. Periodic inspection and testing are therefore essential for identifying leakage, deformation, corrosion and other defects.

This research paper presents a case study of **Vijaya CNG Hydro Testing Services, Ahilyanagar**, focusing on CNG cylinder testing, leakage detection, visual inspection and safety practices. The study describes the general sequence of CNG cylinder inspection, preparation, hydrostatic testing, drying, visual examination, leakage checking and certification. The paper also discusses common leakage locations such as valves, threaded connections, O-rings, hoses and fittings.

Hydrostatic testing is an important method used to assess the integrity of pressure vessels. The study proposes a systematic testing and quality-control approach consisting of identification, visual inspection, preparation, controlled testing, leakage inspection, drying, dimensional examination and documentation. The research emphasizes that testing must be conducted by authorized personnel using appropriate procedures and equipment, with safety controls suitable for high-pressure gas systems.

**Keywords:** CNG, CNG Cylinder, Hydro Testing, Leakage Detection, Pressure Testing, Safety, Inspection, CNG Vehicle, Quality Control, Ahilyanagar.

## 1. Introduction

Compressed Natural Gas (CNG) is used extensively as an automotive fuel. In a CNG vehicle, natural gas is stored in a high-pressure cylinder and supplied to the engine through

suitable valves, regulators, pipes and fittings.

Because the storage system operates at high pressure, the condition of the cylinder and associated components is extremely important.

The CNG system generally consists of:

- CNG cylinder
- Cylinder valve
- High-pressure pipe
- Filling connection
- Pressure regulator
- Pressure gauge/sensor
- Shut-off valve
- Low-pressure gas line
- Engine fuel system
- Mounting brackets

Failure of any critical component can result in gas leakage or unsafe operating conditions.

The study focuses on testing and leakage-detection practices associated with CNG cylinders at Vijaya CNG Hydro Testing Services in the Ahilyanagar region.

## 2. Organization Profile

### 2.1 Vijaya CNG Hydro Testing Services

**Vijaya CNG Hydro Testing Services** is listed in the Akolner/Chas Road area of Ahilyanagar, Maharashtra, and is categorized as a CNG fitment/testing-related business.

The industrial study can focus on:

- CNG cylinder inspection
- Hydro testing
- Leakage detection
- Valve inspection
- CNG system safety
- Cylinder condition assessment
- Testing documentation
- Quality-control practices

The detailed equipment, testing pressure, acceptance criteria and procedures should be recorded from authorized company documentation rather than assumed.

### 3. Objectives

The main objectives of this research are:

1. To study the CNG cylinder testing process.
2. To understand the importance of hydrostatic testing.
3. To study CNG leakage detection methods.
4. To identify common leakage points.
5. To study visual inspection of CNG cylinders.
6. To study valve and fitting inspection.
7. To understand safety precautions during CNG testing.
8. To study testing documentation and traceability.
9. To identify common testing-related defects.
10. To suggest quality and safety improvements.

### 4. Research Methodology

The research methodology consists of:

#### Industrial Visit



#### Study of CNG System



#### Cylinder Identification



#### Visual Inspection



#### Testing Process Study



#### Leakage Detection Study



#### Defect Identification



#### Safety Analysis



#### Quality Improvement Recommendations

Primary information may be obtained through authorized observation, discussions with technicians and examination of permitted testing records.

### 5. CNG Cylinder

The CNG cylinder is the main storage vessel in a CNG vehicle.

Its important characteristics include:

- High-pressure storage capability
- Structural strength
- Resistance to corrosion
- Resistance to mechanical damage
- Proper valve connection
- Secure vehicle mounting

Cylinder condition should be checked periodically according to the applicable regulatory and manufacturer requirements.

### 6. CNG Cylinder Testing Process

A generalized testing sequence is:

#### Cylinder Identification



#### Visual Inspection



#### Removal/Preparation



#### Cleaning



#### Hydrostatic Testing



#### Leakage Inspection



#### Drying



#### Internal/External Inspection



#### Acceptance/Rejection



#### Documentation

The exact test procedure and acceptance criteria must follow the applicable regulatory requirements and the authorized testing facility's approved procedure.

### 7. Visual Inspection

Visual inspection is an important first stage.

The cylinder should be examined for:

#### External Defects

- Corrosion
- Dents
- Scratches
- Cuts
- Bulging
- Cracks
- Fire/heat damage
- Damaged protective coating

#### Valve Area

- Valve damage
- Thread damage
- Leakage indications
- Improper fitting
- Corrosion

#### Mounting Area

- Loose mounting
- Damaged brackets
- Excessive vibration marks
- Contact damage

A cylinder showing significant damage should not proceed to further testing until evaluated according to the applicable approved procedure.

### 8. Hydrostatic Testing

Hydrostatic testing is a pressure test in which a suitable liquid, typically water, is used as the test medium.

The general principle is:

**Cylinder Filled with Test Medium → Controlled Pressurization → Pressure Holding → Observation → Pressure Release → Examination**

The use of liquid instead of compressed gas reduces the stored energy associated with the test compared with a pneumatic pressure test.

The actual test pressure, holding time, permissible expansion and acceptance criteria must be taken from the applicable standard/regulatory procedure and the cylinder's authorized test specification.

## 9. Principle of Hydro Testing

The test evaluates whether the cylinder can safely withstand the specified test pressure.

Important observations can include:

- Pressure stability
- Leakage
- Permanent deformation
- Abnormal expansion
- Visible structural defects

The test should be performed using calibrated equipment and appropriate safety controls.

## 10. Leakage Detection

Leakage detection is one of the most important aspects of CNG-system safety.

Possible leakage locations include:

1. Cylinder valve
2. Valve-to-cylinder connection
3. High-pressure pipe connections
4. Hose connections
5. O-rings/seals
6. Regulator connections
7. Filling connection
8. Shut-off valves
9. Pressure fittings

## 11. Leakage Detection Methods

### 11.1 Soap Solution Method

A suitable leak-detection solution may be applied to an accessible connection while the system is under an appropriate controlled condition.

Formation of continuous bubbles indicates a possible leak.

Advantages:

- Simple
- Low cost
- Easy to observe

Limitations:

- Requires appropriate access
- Very small leaks may require more sensitive methods
- Must be performed under safe conditions

### 11.2 Electronic Gas Detector

A gas detector can detect the presence of natural gas around suspected leakage points.

Advantages:

- Sensitive
- Fast
- Useful for localized inspection

It should be appropriately rated and maintained for the application.

### 11.3 Pressure-Drop Observation

A pressure drop over a controlled test period can indicate possible leakage, but pressure changes can also result from temperature effects and other factors. Therefore, pressure-drop results should be interpreted according to the approved test procedure.

## 12. Common Causes of CNG Leakage

| Cause                 | Possible Effect            |
|-----------------------|----------------------------|
| Damaged O-ring        | Gas leakage                |
| Loose fitting         | Gas leakage                |
| Valve-seat damage     | Leakage                    |
| Thread damage         | Improper sealing           |
| Corrosion             | Cylinder deterioration     |
| Hose damage           | Gas leakage                |
| Improper installation | Connection failure         |
| Excessive vibration   | Fitting loosening          |
| Mechanical damage     | Cylinder integrity concern |

## 13. CNG Leakage Investigation

A systematic investigation can follow:

**Leak Suspected**

↓

**Isolate the System**

↓

**Follow Approved Safety Procedure**

↓

**Identify Leakage Location**

↓

**Inspect Connection/Component**

↓

**Repair or Replace Authorized Component**

↓

**Repeat Approved Leak Test**

↓

**Record Result**

Only qualified personnel should perform work on pressurized CNG systems.

## 14. Safety Precautions

CNG testing involves high-pressure equipment and potentially flammable gas. Therefore, safety is the highest priority.

Important precautions include:

- Keep ignition sources away.
- Provide adequate ventilation.
- Use appropriate PPE.

- Restrict unauthorized access.
- Follow approved pressure-testing procedures.
- Use calibrated pressure gauges.
- Inspect hoses and connections before testing.
- Never exceed approved test limits.
- Depressurize the system before opening connections.
- Follow emergency procedures.
- Maintain appropriate fire-safety equipment.
- Display warning signs.

### 15. Inspection Instruments and Equipment

Typical equipment used in CNG inspection/testing may include:

| Equipment               | Purpose                             |
|-------------------------|-------------------------------------|
| Pressure gauge          | Pressure measurement                |
| Hydro-test equipment    | Pressure testing                    |
| Gas detector            | Leakage detection                   |
| Vernier caliper         | Dimensional measurement             |
| Weighing equipment      | Weight measurement where applicable |
| Visual inspection tools | Surface examination                 |
| Temperature indicator   | Test-condition monitoring           |

Inspection records Traceability

The actual equipment available at the organization should be recorded during the industrial visit.

### 16. Quality Control

Quality control should be implemented at each stage.

#### Stage 1 – Identification

Verify:

- Cylinder identification
- Test due status
- Applicable specification
- Previous test information

#### Stage 2 – Visual Inspection

Check:

- Corrosion
- Dents
- Damage
- Valve condition
- Mounting condition

#### Stage 3 – Pressure Testing

Verify:

- Equipment calibration
- Test setup
- Test parameters
- Pressure behavior

### Stage 4 – Leakage Testing

Verify:

- Valves
- Fittings
- Connections
- Hoses

### Stage 5 – Final Inspection

Record:

- Test result
- Defects
- Acceptance/rejection
- Test date
- Identification details

### 17. Test Record and Traceability

A test record can contain:

| Parameter                 | Record            |
|---------------------------|-------------------|
| Cylinder ID               | _____             |
| Vehicle/Component ID      | _____             |
| Cylinder type             | _____             |
| Manufacturer              | _____             |
| Test date                 | _____             |
| Previous test information | _____             |
| Visual inspection         | Pass/Fail         |
| Hydro test                | Pass/Fail         |
| Leakage test              | Pass/Fail         |
| Final status              | Accepted/Rejected |
| Inspector                 | _____             |

Actual values should be entered only from authorized test records.

### 18. Common Defects

Common defects that may be identified during inspection include:

#### Cylinder

- Corrosion
- Dent
- Crack
- Bulging
- Surface damage

#### Valve

- Leakage
- Thread damage
- Seal damage
- Valve-seat problem

#### Pipe/Fittings

- Loose connection
- Damaged thread
- Corrosion
- Hose deterioration

### 19. Root Cause Analysis

For repeated leakage problems, the 5-Why method can be used.

Example:

**Problem:** Leakage at fitting

↓

Why? → Connection is not sealing properly.

↓

Why? → Seal/O-ring is damaged.

↓

Why? → Incorrect installation/handling.

↓

Why? → Standard procedure not followed.

↓

Why? → Inadequate training or process control.

**Corrective Action:** Improve standard procedure, operator training and inspection.

## 20. Preventive Measures

The following measures can reduce leakage and testing problems:

1. Periodic inspection of cylinders.
2. Proper valve inspection.
3. Replacement of damaged seals.
4. Correct tightening procedure.
5. Inspection of high-pressure hoses.
6. Regular calibration of testing equipment.
7. Proper operator training.
8. Maintaining test records.
9. Using suitable leak-detection equipment.
10. Following approved testing procedures.

## 21. Proposed Quality Improvement Model

### Cylinder Identification

↓

**Visual Inspection**

↓

**Controlled Hydro Testing**

↓

**Leakage Detection**

↓

**Final Inspection**

↓

**Documentation**

↓

**Traceability**

↓

**Periodic Review**

↓

**Continuous Improvement**

## 22. Results and Discussion

The study shows that CNG cylinder testing is a critical safety activity because CNG systems operate at high pressure. Visual examination can identify external damage, corrosion and other visible abnormalities, while hydrostatic testing provides an important assessment of pressure-vessel integrity.

Leakage testing is equally important because even a small leak in a high-pressure CNG

system can create a significant safety concern. Leakage can occur at valves, seals, hoses and threaded connections.

A systematic combination of **visual inspection, controlled hydro testing, leakage detection, calibrated equipment and proper documentation** can improve the reliability of the testing process.

For a complete industrial research paper, actual data from Vijaya CNG Hydro Testing Services should be collected, such as number of cylinders tested, number requiring repair/rejection, leakage locations and test failures. These data can then be analyzed statistically.

## 23. Suggested Data Analysis

The following indicators can be calculated using actual industrial records:

### Rejection Rate

$$\left[ \begin{aligned} \text{Rejection Rate} = \\ \frac{\text{Rejected Cylinders}}{\text{Total Cylinders Tested}} \times 100 \end{aligned} \right]$$

### Leakage Rate

$$\left[ \begin{aligned} \text{Leakage Rate} = \\ \frac{\text{Cylinders/Systems With Detected Leakage}}{\text{Total Tested}} \times 100 \end{aligned} \right]$$

### First-Pass Acceptance Rate

$$\left[ \begin{aligned} \text{FPAR} = \\ \frac{\text{Cylinders Accepted Without Rework}}{\text{Total Tested}} \times 100 \end{aligned} \right]$$

These values should be based on actual records and not estimated.

## 24. Recommendations

1. Maintain cylinder-wise digital records.
2. Use calibrated pressure-measuring instruments.
3. Maintain equipment calibration schedules.
4. Implement standardized inspection checklists.
5. Record leakage location and root cause.
6. Analyze rejection using Pareto analysis.
7. Train technicians in CNG safety.
8. Maintain proper ventilation and fire-safety arrangements.
9. Use appropriate gas-detection equipment.
10. Periodically review testing failures and corrective actions.
11. Maintain complete test traceability.
12. Follow all applicable PESO, regulatory and manufacturer requirements.

## 25. Conclusion

This research paper presents a study of **CNG cylinder testing and leakage detection** with reference to Vijaya CNG Hydro Testing Services, Ahilyanagar.

CNG cylinders and associated high-pressure components require systematic inspection because their safe operation depends on structural integrity and leak-free connections. Visual inspection, hydrostatic testing, leakage detection and final documentation are important components of a reliable testing system.

The study demonstrates that quality and safety can be improved through **standardized testing procedures, calibrated equipment, systematic leakage inspection, operator training, preventive maintenance and proper traceability**.

Future research can use actual industrial data to analyze cylinder rejection, leakage frequency, test failures, repair requirements and process efficiency. Such quantitative analysis would strengthen the industrial case study and provide measurable evidence for quality improvement.

## References

1. Petroleum and Explosives Safety Organisation (PESO), applicable requirements for compressed-gas cylinders and pressure vessels.
2. Chief Controller of Explosives/PESO, applicable CNG cylinder inspection and testing requirements.
3. Bureau of Indian Standards, applicable standards for gas cylinders and compressed natural gas systems.
4. Automotive Research Association of India (ARAI), applicable automotive CNG system requirements.
5. ISO standards and technical literature related to gas-cylinder inspection and pressure testing.
6. Vijaya CNG Hydro Testing Services, Ahilyanagar – industrial observations and authorized test records.