

Swachh Bharat Smart Bin: Design and Development of an IoT- and Machine Learning-Based Intelligent Waste Segregation and Monitoring System

Khevender Singh

Computer Science & Engineering
Sharda University, Greater Noida, India
2022570125.khevender@ug.sharda.ac.in

Kavi Sharma

Computer Science & Engineering
Sharda University, Greater Noida, India
2021446146.kavi@ug.sharda.ac.in

Dr. Zatin Gupta

Computer Science & Engineering
Sharda University, Greater Noida, India
zatin.gupta@sharda.ac.in

Abstract—The present paper will present an IoT- and ML-based smart-bin system to help with the waste sorting when picking waste in urban areas and track the sanitation promptness. The system consists of one supervisory pipeline that is a combination of fill-level measurements, environmental measurements, event measurements, waste-state measurements, and connection tracking as well as alerting. It was tested on 8000 event records on 30 smart bins in five sizes of urban areas in 60 days. The proposed model yielded a overall classification accuracy of 91.49 percent, a median inference time value of 217.95 ms and a small error in fill-monitoring on all the fill bands that it was tested at. They were discovered to be highly discriminated Biodegradable, Plastic, Metal and Glass and the most difficult residual was the General Waste. Traditional behaviour, too, was consistent with the diverse conditions of the network and inclined towards the prioritisation of the collection, as well as maintenance visibility. This study shows that smarter bins can be used as viable informational hubs of cities to make cities achieve cleaner, faster and more accountable waste-management operations.

Keywords— smart bin, Internet of Things, machine learning, city-wide waste management, waste classification, smart sanitation, IoT monitoring.

I. INTRODUCTION

A. Urban Solid Waste Management and Smart Sanitation Context

Solid wastes management in cities in India has turned to be an issue of data rather than an issue of service and even an issue of service-governance. Anticipating more organizing the quantities of disposal, combined material blends, lessened choice in idiscipline of collections, mass accumulation of waste in space confined regions have distinct pressures on regular containerized frameworks [1]. There has been the trend of shifting policymaking towards the same. Cleanliness has now an investment logic: whereby the traceability of operation, a monitored infrastructure and quality of service to be measured all inter-relates to the cleanliness results and not just the positioning of the containers [2]. By including garbage-free performance as an aspect user-linked to, segregation, scientific management as well as responsible field Implementation, national urban sanitation programmes have assumed that position [3]. The existing mission architecture rating systems assume failing bins, delays in lifting, disposal combined, etc. but not particular visual failures [4], [5].

In your face is its technical implication. An administrative silent public bin is a bin that cannot report about any of the following: fill level, internal condition and service urgency. Such silence distorts route plans, sabotages the control over the field and slows down the response where changes in the disposal by the hour or by land have been or are changing at a rate. The most recent surveys of waste technology document the pattern of transitioning to sensor-based monitoring,

visibility and optimization of the waste collection point [6], but broader themes of artificial intelligence as applied to smart-city waste management identify smart bins, event tracking and analytics-facilitated collection as actively researchers in the field of deployment studies [7]. The present paper adopts this point of view. It considers the smart bin a surveilled urban point, rather than a passive bin. The three procedures which result in a three pronged frame is more precise than the sanitary reform of the city, but at the point where the sanitation starts to be felt at all.

B. Research Problem, Objective, and Paper Contribution

The conventional bins employed by the people lack real time status displays, situational knowledge of the garbage status of affairs and catalogued records to scrutinise the tasks undertaken. Teams of collections may work regularly or at specific time, an indicator of complaints, or a check manually. This can be drilled in estranged load and feebly heterogeneous feeble situations. In Old Delhi, the urban conditions are not only not in accordance with both of the assumptions, but are also quite unpredictable. Commercial, institutional, residential, transport and even park areas generate various disposal patterns, degree of disruption of moisture, nuisance disruptions. Perhaps, they cannot be put in standardized rules of service. Other bins are either over serviced in the past or over serviced in the future and others being served without regard to the state of waste.

Here, the author explains this gap, and this offers the readers the IoT- and ML-sourced smart-bin system of waste sorting support and feedback levels of controlled sanitation services. The integration of the fill-level sensing, the environmental sensing, the event capture, the communication, classification and the generation of the alerts would be the system logic with a single supervisory pipeline. It is also geared towards be full not by mere reporting. It is to convert what is achieved in the field into a type of interpretation such as that of collection demand, most likely waste state and servicing issue. The paper is making contributions in three ways. The first one is that, it defines an architecture between bin level sensing and action oriented outputs of municipals. Second, it normalises a database-based workflow of classification and alert reasoning, through event logs of a smart-bin system. Third, it reports with metrics that are applicable to deployment: reliability monitoring with performance, classes discrimination, communication stability and zone sensitive operational understanding. Since this contribution is an integrated sanitation intelligence loop, not a hardware prototype, is recapped in Fig. 1.1.




Fig. 1.1. Conceptual Framework of the IoT- and ML-Based Smart Bin System

II. RELATED WORK

A. IoT-Based Smart Waste Monitoring Systems

The recent literature review deems IoT-enabled waste infrastructure as an initiative aimed at transforming the municipal collection to condition-driven supervision as opposed to the current, fixed-time-based, one. Quantitative surveys show the existent strategic survey of smart bins to absorb fill progression, internal environmental change and status of communication and relay such messages to routing or service dashboards [8]. The initial survey evidence of smart dustbin systems reveals that design centre has lost its design emphasis on the accessibility of containers and to make containers visible, wireless and sensing all the events they record is a better-than-best and no longer provides optional improvements [9]. The underlying literature sees the artificial intelligence-enabled waste systems as the general service-based inversion wherein all the monitoring, collection and recycling systems have accrued a augmented forward information of the field; and an accelerated feedbacks in operations [10]. Smart-bin forecasting studies based on the smart-bin history can also be applied to support the same. Longitudinal event locations help researchers to estimate how fullness would evolve, in which the researchers can establish how they would be non-nuisance and how to contrast the progression of normal running as opposed to service stresses over the days. The methodological topicality of such conversion of the independent readings to time-takings consists in that municipal supervision is subject to tendencies, and continuity and repetition, not individual observations, however, taken outside their place and related to service books.

B. Machine Learning in Waste Classification and Decision Support

Machine learning has been seen in the literature in that sensor data streams or garbage content has to be interpreted as compared to detected by threshold. Evidence of such taxonomic reviews show a push forward of classification research beyond material recognition in simple form to structured decision support where concerns shift about on class imbalance, interpretability and operational utilization [11]. Research projects on smart-cities that involve IoTs further describe the data-driven waste infrastructures whose layers have infrastructures whose transmission is insufficient without a model logic to journey through the observation into proposed actions [12]. Large-scale surveys that follow the chain of municipal waste confirm the same trend: smart systems are valued when assisting in the extent of prediction, prioritisation and resource allocation in situations of dynamic domains [13].

More recent analytic syntheses go even further to find artificial intelligence a planning and not a sorting tool in which, especially alarming, routing, and service timing requirements must be linked together with dynamically changing waste conditions [14].

C. Research Gap and Positioning of the Proposed System

Although this development has taken place, there still exist some shortcoming. The automated classification reviews focus on the performance of algorithms, but are commonly founded on image intensive benchmark places that in truth do not give a lot when it comes to observed bins of public as a distributed service machine [15]. The reported smart segregation is still recounted in current studies regarding application Emerging application research with the majority being dedicated to institutional pilot projects or nation-in the spotlight deployment tales relative to event-level urban surveillance in thickly utilized systems [16]. The second gap is the continuity in the methods. It is possible to find a lot of studies where the sensors, connectors or a classification model have been defined on their own. Fewer of them couple them to one structure where the measurements of the fill, environmental condition and predicting the class and logic of action is applied collectively.

The system provided will be in the center of that slimmer divide. It is not a descending to ascending sorting gadget. It is a bin update fixed level monitoring and classification facilitating framework to help determine urban sanitation efforts. It contributes to the region in regards to its combination of monitoring the IoT, systemized event entries, implementing waste-state prediction with the help of machine learning and creating an alert within a single operational cycle. Such positioning problems are significant, as the usefulness of a particular model on the municipal level does not necessarily imply the usefulness of corresponding model in the fields of the field fluctuations, the communication variability, and the spatial zone variability but is whether measurements can achieve interpretable indicators of services.

III. RESEARCH METHODOLOGY

A. System Architecture and Design Logic

The system structure that was desired was a layered monitoring system where sensing, transmission, storage, inference and alert generating engines were thought of as a single chain of operations and not a free-standing entity. Predictive reasoning can be done based on the events history at the bin level, based on the work done on status-es-time estimation of smart-bins, by using measurements stored in structured format [17]. Other analyses of the IoT-based intelligent waste-management also propose that sensors and communication can be based on use only in conjunction with some supervisory logic that can transform raw readings into service states [18]. Indeed, that was the case with the existing design. All the disposal events were stored as a time-stamped record that was tied to the identity of a bin, ward, zone type, size of the zone, environmental factors, signal quality, model output and operation flags. The bin was thus defined as the material structure and a point that produces data in the city.

B. Dataset Structure and Feature Configuration

The data sets which were analyzed contained 8000 records of events which were recorded on 30 smart bins over 60 days

of surveillancing and 10 wards. It was in five categories of zones (Commercial, Institutional, Residential, Transport Hub and Public Park). The mean size of the bins was 108.78 L. This feature set had fill level before per cent, approximate item volume l, weight in grams, level of moisture and ppm of gas, temperature, percentage humidity and battery level percentage, network > rssi ppm, lid open seconds and inference time in milliseconds with material indicative sensor scores of metal, plastic, paper, organic content and transparency. System-state variables included alert-type, collection was required, overflow risk, maintenance flag, predicted class, actual class and model confidence and classification correct. Hybrid or deep models have been employed in the literature to determine material in a results of controlled conditions of sensing in the system of public-bin classification [19], [20]. The same line of thinking was modified to the example of a smart-bin event data, where the classification had to be consistent with the monitoring, and not independent of it. Data was an event based, but not route based data. This judgment preserved the local variations in the disposal behaviour, moisture regime and stability of communication which would otherwise not be known in aggregate not till the day. This was not an even balance of classes pre-design because the waste of the public-bin is not even in use. Glass and Metal had different operations and were the smallest group, hence forming the largest group was Biodegradable events. Model evaluation was thus more concerned with support conscious reporting as opposed to the end of the headline. The values of the confidence were stored with each prediction to allow them to explore any ambiguous classification, in addition to correct labels. Battery run time and network power was upheld because an accurate model that works is weak when the inference could not occur in the field. The other difference that was drawn within the workflow was the collection stress and stress of the device. One of them might be emptying a bin, some machine might require some servicing, or both. This division offered the supervisory level scope administrative clarity. It sidestepped the obliteration of communication was being interpreted as a sanitation incident and sanitation pressure could be narrowed down to a hardware Michigan. Such separation would be common in municipal deployments such that response teams and maintenance teams are often separated. Timestamp ordering made it easier to review recurring stress events due to time and locale concentration and time consistency. The data obtained would have been capable of helping in the classification and follow up audit and analysis without halting the sense-to-action network.

C. IoT Module Integration and Data Processing Workflow

The IoT process began with the event being captured in the bin and then preprocessed locally followed by the storage centrally, models being inferred and followed by the supervisory output. Some of the preprocessing involved type checking, missing-value checking, range checking and fill progression/capacity consistency checks. The study of event-level forecasting, and classification has been uncovering that data discipline has a tremendous impact on down stream model behaviour in a waste application [21], [22]. Because of which, there were clear separation of sensing variables, sensing model indicators, engineered indicators and alert states. The proxy of fill level change after which the change was compared with the

expected percentage change were the difference in fill level after percent and fill level before percent. RSSI bands were interpreted to gauge stability of communication, in the form of network condition. There was no specific point at which the operational states were to be told, synthesized information between fill, environmental readings and connectivity was taken to define the operational states.

D. Classification and Alert Generation Methodology

The classification phase diagrammed multivariable recorded event records by six categories of the waste such as Biodegradable, Plastic, Paper, General Waste, Metal and Glass. Action oriented states such as: High Fill, Odor Alert and Weak Network were then formed using the sensor and model outputs, i.e. alert logic. Stacking-based models of municipal solid waste have shown that the knack to do so is determined by the joint use of different cues as compared to prioritizing one or the other signal family [23]. Based on that logic, the proposed methodology considered model prediction and operational alerting as related and distinct layers to each other. Conditions of probable wastes were characterized by a class name; action by alert to service. The name of the collection needed was the immediate response marker and maintenance flag the communication or device-health concern. It was to be rated on four scales; fill-monitoring reliability, class-wise discrimination, operational interpretability and communication robustness. Fig. 3.1 gives a summary of all the steps of measurement to the municipal action.




Fig. 3.1. End-to-End Workflow of Data Acquisition, Classification, and Alert Generation

IV. RESULTS AND DISCUSSION

A. Experimental Setup and Evaluation Metrics

The evaluation was founded on the entire 8000 events smart-bin data and considered the system as a monitoring platform and not a separate classifier. Federated and proactive studies are increasingly taking an interest in the field of urban waste classification with the view to attain classification with service-side performance indicators such as quality of response and usability in the field opposed to the accuracy per se [24], [25]. This type of thought was taken up as well. This has investigated four metric families: coverage and speed of execution by the data set, reliability in fill-monitoring, discrimination by class, and operational behaviour which is correlated with communications.

Table 4.1. Experimental Dataset Profile and Evaluation Configuration

Metric	Value
Observation window (days)	60
Event records	8000
Smart bins	30
Wards covered	10
Zone categories	5

Mean bin capacity (L)	108.78
Median inference time (ms)	217.95
Overall classification accuracy (%)	91.49

The statistics in Table 4.1 are that of variable sized / moderate sized yet operationally disparate data. The average calculated time of inference was a quarter-second, or sufficiently fast to infer in near-real-time in the process of updating a dashboard in a monitored sanitation system. The possibility of the classification layer not being descriptive was confirmed by overall accuracy that was 91.49.

B. Fill-Level Monitoring and Sensor Performance Analysis

The difference between the average percentage change, based on event volume/bin capacity versus the actual change observed after the event, following each event was made a proxy fill-validation process. AutomL-based Waste forecasting systems have conceptually equated time sensitivity in prediction and monitoring as mutually important problems [26]. The present results resonate that notion.

Table 4.2. Fill-Level Monitoring Performance Across Tested Bands

Fill band (%)	Events	Mean actual fill (%)	Mean expected delta (%)	Mean observed delta (%)	MAE (pct. points)	RMSE (pct. points)
0-25	2766	16.98	0.89	0.93	0.12	0.17
25-50	2967	36.07	1.11	1.17	0.13	0.18
50-75	1582	61.27	1.50	1.58	0.14	0.18
75-100	685	83.10	1.89	1.97	0.13	0.18

Mistakes were also error tightly bound up in each band. There is no situation where the mean absolute error more than 0.14 percentage point and the RMSE is less than 0.17-0.18. The trend implies that even with an increase in fill pressure sensing was stable. Fig. 4.1 would indicate that there exists a close elasticity of the real against the measured fill progression in four bands.




Fig. 4.1. Actual Versus Measured Fill-Level Performance Across Fill Bands

Table 4.4. Connectivity Status, Alert Frequency, and Response Behaviour

Network band	Events	Mean RSSI (dBm)	Median inference (ms)	Weak-network alerts	Collection-required events	Maintenance events
Strong	1294	-55.41	204.20	0	9	0
Stable	3072	-65.44	214.10	0	23	0
Moderate	2761	-74.51	221.80	0	32	0
Weak	873	-84.65	234.50	329	5	329

Time latency on inference had a slight reducing dependence on the signal quality, but was practically possible in the weak band. The weak-network warnings and maintenance processes were tightly-knifed in the weakest

C. Waste-State Classification Performance

The classification layer was evaluated in six tests of wastes. Smart-city garbage sortation profound-artificial intelligence systems indicate that robust discrimination preservation is crucial both to high and low frequencies of the sorting [27].

Table 4.3. Classification Performance of the Proposed Waste-State Model

Class	Support	Precision (%)	Recall (%)	F1-score (%)
Biodegradable	2406	96.48	92.35	94.37
Plastic	1718	91.69	94.41	93.03
Paper	1316	87.49	93.54	90.41
General Waste	1206	81.66	79.35	80.49
Metal	774	100.00	95.74	97.82
Glass	580	89.80	94.14	91.92
Overall accuracy	8000	—	—	91.49

Metal, Biodegradable and Plastic had the best performance. The least separable class General Waste most mixed residual patterns is unsurprisingly contained. The bewilderment form was not randomized but controlled. The General Waste was very commonly mixed up with Biodegradable, Plastic and Paper but Metal was virtually an unconditioned cross-class leakage group. That would be the matrix and Fig. 4.2 would denote that the material adjacency was plausible, as well as not scattered, but not by chance.




Fig. 4.2. Confusion Matrix of Waste-State Classification Results

D. Connectivity, Alert Behaviour, and Operational Responsiveness

Measures of system responsiveness used were the network behaviour of RSSI-banded networks and the alert composition. The additional streaming of IoT-AI waste systems is often limited not by the rationale of models but by the reliability of communication in the sphere [28].

network regime and this suggests that the supervisory logic failed to allow that a mixture of communication and sanitation stress are combined into one opaque signal of warning. The number of odor-related alerts in the complete event stream

were more than the high fill alerts and this indicates that the same even conditions may be established before volumetric saturation. The data had 69 collection required, 329 maintenance flag and no instances of overflow risk. And the implication of that trend is namely conservative collection schedule, effective containment of pre-overflow and design of supervision customized in favor of prevention rather than detection of failure.




Fig. 4.3. Alert Distribution by Operational State

E. Comparative Discussion and Urban Deployment Significance

The deployment argument was advocated by the zone profile. The average fill level of the post event eventual ringing is 42.50% and has a commercial bin that generated 2376 event with the highest number of 34 number of required collection states. The Public Park bins yielded few events (781) and one collection was needed (state). Present profound articles of literature on waste enlightenment guarantee that location-assorted administration of operational intelligence is advantageous provided operational intelligence is both laboratory lucidity as well as transfer-learning studies has advocated the significance of sustaining the potency of various waste situation [29 and 30]. The present results are along this line. The high overall accuracy of waste states was captured in the model and the fill module reduced the error significantly and tracked the progress, whereas the high administrative validity was achieved in the beer industry despite uneven connectivity. It would be the same in space, with Fig. 4.4 illustrating it: there was no even sanitation pressure. It is significant to deployment as smart-bin value is composed of differentiation of response, and enhanced routing, as well as evidence-based planning of capacity.




Fig. 4.4. Zone-Wise Operational Performance of the Smart Bin Network

V. CONCLUSION AND FUTURE WORK

The article proposed an IoT- and ML-based system of smart-bin to support the waste collection process in the city and monitor sanitation practices. It made a very basic claim that was falsifiable: after a public bin is considered a reporting node; senses in, generates and gives interpretable states of service that are more useful to the municipal operations. The arguments presented support such a claim. The system achieved a total classification score of 91.49 per cent with a comparison with 8,000 event records on 30 bins in 60 days, and an inference time of under a second, and with a very small fill-monitoring error in all fill bands being tested. Based on such findings, bin-level intelligence does not either need to be operationally superficial but can be operationally consistent.

The practical meaning of smart sanitation is refined by the results as well. Classification did not result in the most value. It followed due to the strategic development of fill progression, and ecological notification, connection cognizance and relocation decisive yield. The most tenacious category of waste which could not be segregated was the General Waste suggesting that a known past of residual classes used in actual disposal settings existed. However, the error concentration was in a structurally plausible form unlike random numbers. Even communication degradation was considered with a punitive attitude: bad conditions of the networks were activated to enhance maintenance signs without collapsing the sanitation reasoning of the system.

The future work should have three directions to be extended in the frame work. Yes, it takes long deployments to achieve seasonal variations, peak and hard overflow conditions of a festival. Second, the feature space should be expanded in order to provide refinement and additional strong anomaly support of the left-over classes. Third, the bin smarts are to be linked with the existing good municipal operations to allow the optimisation of routes, planning of maintenance and dashboard responses to regulate d-option they directly influence labour distribution and the time of the service. All in all, it is possible to say that smart-bin systems are not mere rumors as revealed in the paper. They are smaller, well designed city information infrastructures that are towards a more responsible, better and faster waste treatment. They come in handy because they convert the random cases of waste to the perceptible local judgments.

REFERENCES

- [1] UNEP and ISWA, *Global Waste Management Outlook 2024*. Nairobi: United Nations Environment Programme and International Solid Waste Association, 2024.
- [2] World Bank, *Clean Cities, Bright Futures: Accelerating Investment and Reforms in Solid Waste Management in Developing Countries*. Washington, DC: World Bank, 2025.
- [3] Ministry of Housing and Urban Affairs, *Swachh Bharat Mission–Urban 2.0*. New Delhi: Government of India, 2021.
- [4] Swachh Bharat Mission–Urban, *Garbage Free Cities Star Rating Toolkit 2024*. New Delhi: Ministry of Housing and Urban Affairs, 2024.
- [5] Swachh Bharat Mission–Urban, *Swachh Survekshan 2024 Toolkit*. New Delhi: Ministry of Housing and Urban Affairs, 2024.
- [6] W. Czekala, J. Drozdowski, and P. Łabiak, "Modern technologies for waste management: A review," *Applied Sciences*, vol. 13, no. 15, p. 8847, 2023, doi: 10.3390/app13158847.
- [7] B. Fang, J. Yu, Z. Chen *et al.*, "Artificial intelligence for waste management in smart cities: A review," *Environmental Chemistry Letters*, vol. 21, no. 4, pp. 1959–1989, 2023, doi: 10.1007/s10311-023-01604-3.

- [8] A. Mounadel, H. Ech-cheikh, S. Lissane Elhaq *et al.*, "Application of artificial intelligence techniques in municipal solid waste management: A systematic literature review," *Environmental Technology Reviews*, vol. 12, no. 1, pp. 316–336, 2023, doi: 10.1080/21622515.2023.2205027.
- [9] M. P. Arthur, S. Shoba, and A. Pandey, "A survey of smart dustbin systems using the IoT and deep learning," *Artificial Intelligence Review*, vol. 57, article 56, 2024, doi: 10.1007/s10462-023-10646-6.
- [10] D. B. Olawade, O. Fapohunda, O. Z. Wada *et al.*, "Smart waste management: A paradigm shift enabled by artificial intelligence," *Waste Management Bulletin*, vol. 2, pp. 244–263, 2024, doi: 10.1016/j.wmb.2024.05.001.
- [11] D. V. Yevle and P. S. Mann, "Artificial intelligence based classification for waste management: A survey based on taxonomy, classification & future direction," *Computer Science Review*, vol. 56, p. 100723, 2025, doi: 10.1016/j.cosrev.2024.100723.
- [12] K. S. Al Yarubi, S. O. F. Khairy, S. M. E. Hossain, and G. Hayder, "Internet of Things-driven waste management: Paving the way for sustainable smart cities," *Processes*, vol. 13, no. 4, p. 1140, 2025, doi: 10.3390/pr13041140.
- [13] R. Rao, S. Singh, M. Salas *et al.*, "AI-powered municipal solid waste management: A comprehensive review from generation to utilization," *Frontiers in Energy Research*, vol. 13, p. 1670679, 2025, doi: 10.3389/fenrg.2025.1670679.
- [14] A. El Jaouhari, A. Samadhiya, A. Kumar *et al.*, "Turning trash into treasure: Exploring the potential of AI in municipal waste management – An in-depth review and future prospects," *Journal of Environmental Management*, vol. 373, p. 123658, 2025, doi: 10.1016/j.jenvman.2024.123658.
- [15] F. Fotovvatikhah, I. Ahmedy, R. M. Noor, and U. Munir, "A systematic review of AI-based techniques for automated waste classification," *Sensors*, vol. 25, no. 10, p. 3181, 2025, doi: 10.3390/s25103181.
- [16] A. Alfaidi, S. M. Alshraah, A. Waleed, and A. M. Hilal, "A comprehensive review of AI-powered waste segregation: Advancing the vision of smart Saudi cities," *South African Journal of Chemical Engineering*, vol. 56, p. 100833, 2026, doi: 10.1016/j.sajce.2026.01.006.
- [17] S. Ahmed, S. Mubarak, J. T. Du, and S. Wibowo, "Forecasting the status of municipal waste in smart bins using deep learning," *International Journal of Environmental Research and Public Health*, vol. 19, no. 24, p. 16798, 2022, doi: 10.3390/ijerph192416798.
- [18] M. M. Ahmed, E. Hassanein, and A. E. Hassanien, "IoT-based intelligent waste management system," *Neural Computing and Applications*, vol. 35, pp. 23551–23579, 2023, doi: 10.1007/s00521-023-08970-7.
- [19] S. Bourougaa-Tria, F. Mokhati, H. Tria, and O. Bouziane, "SPubBin: Smart public bin based on deep learning waste classification an IoT system for smart environment in Algeria," *Informatica*, vol. 46, no. 8, 2022, doi: 10.31449/inf.v46i8.4331.
- [20] N. Li and Y. Chen, "Municipal solid waste classification and real-time detection using deep learning methods," *Urban Climate*, vol. 49, p. 101462, 2023, doi: 10.1016/j.uclim.2023.101462.
- [21] Y. Song, X. He, X. Tang *et al.*, "DEEPBIN: Deep learning based garbage classification for households using sustainable natural technologies," *Journal of Grid Computing*, vol. 22, article 2, 2024, doi: 10.1007/s10723-023-09722-6.
- [22] R. Pućnik, M. Dokl, Y. Van Fan *et al.*, "A waste separation system based on sensor technology and deep learning: A simple approach applied to a case study of plastic packaging waste," *Journal of Cleaner Production*, vol. 450, p. 141762, 2024, doi: 10.1016/j.jclepro.2024.141762.
- [23] V. Jayaraman and A. R. Lakshminarayanan, "MSW-Net: A hierarchical stacking model for automated municipal solid waste classification," *Journal of the Air & Waste Management Association*, vol. 74, no. 8, pp. 569–580, 2024, doi: 10.1080/10962247.2024.2370958.
- [24] H. A. Khan, S. S. Naqvi, A. A. K. Alharbi *et al.*, "Enhancing trash classification in smart cities using federated deep learning," *Scientific Reports*, vol. 14, p. 11816, 2024, doi: 10.1038/s41598-024-62003-4.
- [25] T. Stephan, S. M. Hari Krishna, C.-C. Lin *et al.*, "ProWaste for proactive urban waste management using IoT and machine learning," *Scientific Reports*, vol. 15, p. 27790, 2025, doi: 10.1038/s41598-025-08452-x.
- [26] J. Chen, Z. Wen, and Y. Tian, "A novel IoT-based deep learning framework for real-time waste forecasting: Optimizing multi-waste categories using AutoML," *Resources, Conservation and Recycling*, vol. 220, p. 108378, 2025, doi: 10.1016/j.resconrec.2025.108378.
- [27] H. Jerbi, V. G. A. Gnana Vincy, S. Ben Aoun *et al.*, "Optimizing waste management in smart cities: An IoT-based approach using dynamic bald eagle search optimization algorithm (DBESO) and machine learning," *Journal of Urban Management*, vol. 15, no. 1, 2025, doi: 10.1016/j.jum.2025.05.015.
- [28] A. Alourani, M. U. Ashraf, and M. Aloraini, "Smart waste management and classification system using advanced IoT and AI technologies," *PeerJ Computer Science*, vol. 11, e2777, 2025, doi: 10.7717/peerj-cs.2777.
- [29] M. Nahiduzzaman, M. F. Ahamed, M. Naznine *et al.*, "An automated waste classification system using deep learning techniques: Toward efficient waste recycling and environmental sustainability," *Knowledge-Based Systems*, vol. 310, p. 113028, 2025, doi: 10.1016/j.knosys.2025.113028.
- [30] U. K. Lilhore, S. Simaiya, S. Dalal, M. Radulescu, and D. Balsalobre-Lorente, "Intelligent waste sorting for sustainable environment: A hybrid deep learning and transfer learning model," *Gondwana Research*, vol. 146, pp. 252–266, 2025, doi: 10.1016/j.gr.2024.07.014.