

# Automated Diabetic Retinopathy Detection Using Capsule Networks with Explainability

Dr G.Rosline Nesa Kumari

*professor, Dept. of CSE  
Bharath Institute of Higher  
Education and Research*

Chennai, India

[roslineenesakumari.cse@bharathuniv.ac.in](mailto:roslineenesakumari.cse@bharathuniv.ac.in)

Morri Venkatesh

*Dept. of CSE  
Bharath Institute of Higher  
Education and Research*

Chennai, India

[venkateshmorri119@gmail.com](mailto:venkateshmorri119@gmail.com)

Muddam Vivek Sai Ram

*Dept. of CSE  
Bharath Institute of Higher  
Education and Research*

Chennai, India

[viveksairamgoud@gmail.com](mailto:viveksairamgoud@gmail.com)

MuddamSetty Vishnu Charan

*Dept. of CSE  
Bharath Institute of Higher  
Education and Research*

Chennai, India

[royalvishnu746@gmail.com](mailto:royalvishnu746@gmail.com)

M Venkata Vasudeva Reddy

*Dept. of CSE  
Bharath Institute of Higher  
Education and Research*

Chennai, India

[vasudevreddy7832@gmail.com](mailto:vasudevreddy7832@gmail.com)

**Abstract**— Diabetic Retinopathy (DR) is a leading cause of blindness worldwide, requiring early detection for effective treatment. Traditional deep learning models, such as Convolutional Neural Networks (CNNs), have shown promise in automating DR detection but often lack interpretability and robustness. This study proposes a novel approach by integrating **Capsule Networks (CapsNets)** with **Explainable AI (XAI)** techniques to enhance the accuracy and transparency of DR classification. The CapsNet model was trained on a diverse dataset of retinal images, achieving an accuracy of **92%**, outperforming traditional CNN-based approaches in capturing spatial hierarchies and reducing misclassifications. **Grad-CAM visualization** was employed to highlight clinically significant regions, improving trust and interpretability in AI-driven diagnostics. The study also explores dataset expansion, model optimization, and potential clinical applications. The proposed method advances AI-driven healthcare by ensuring both high-performance and explainability, facilitating seamless integration into clinical workflows.

**Keywords**— Diabetic Retinopathy, Capsule Networks, Explainable AI, Grad-CAM, Deep Learning, Medical Image Analysis.

Diabetic Retinopathy (DR) is one of the most severe complications of diabetes and stands as a leading cause of vision impairment and blindness among the working-age population worldwide. It occurs due to damage to the small blood vessels in the retina, resulting in abnormalities such as microaneurysms, hemorrhages, and exudates. In its early stages, DR often presents with very subtle visual symptoms, making it difficult to detect without specialized medical examination. If left undiagnosed and untreated, it can progress to advanced stages, ultimately leading to irreversible vision loss. Therefore, early detection and accurate classification of DR are essential for timely medical intervention, effective treatment planning, and prevention of blindness.

Traditionally, DR diagnosis relies on manual examination of retinal fundus images by trained ophthalmologists. This process involves careful inspection of retinal structures to identify pathological features. Although effective, manual screening is time-consuming, labor-intensive, and highly dependent on the expertise of the clinician. In many regions, especially in developing countries, the shortage of skilled ophthalmologists further limits the accessibility of timely diagnosis. Additionally, the subjective nature

of manual analysis can lead to variability in diagnosis, increasing the risk of misclassification and delayed treatment. These limitations highlight the urgent need for automated, reliable, and scalable diagnostic solutions.

With the rapid advancement of Artificial Intelligence (AI) and deep learning techniques, automated DR detection systems have emerged as a promising alternative to traditional methods. Among these, Convolutional Neural Networks (CNNs) have shown significant success in medical image analysis due to their ability to automatically learn hierarchical features from images. CNN-based models have achieved high accuracy in DR classification tasks, reducing the burden on healthcare professionals and enabling faster screening processes. However, despite their effectiveness, CNNs suffer from certain critical limitations. They often fail to preserve spatial relationships between features in complex images like retinal scans, which is crucial for detecting fine-grained abnormalities such as microaneurysms. Moreover, CNNs operate as “black-box” models, providing little to no explanation for their predictions, which limits their acceptance in clinical practice where interpretability is essential.

To address these challenges, Capsule Networks (CapsNets) have been introduced as an advanced deep learning architecture that overcomes the shortcomings of traditional CNNs. CapsNets are designed to capture spatial hierarchies and relationships between features by using groups of neurons called capsules. These capsules encode both the presence and orientation of features, enabling the model to better understand the structure of retinal images. This makes CapsNets particularly suitable for medical imaging tasks where precise localization and spatial awareness are critical for accurate diagnosis.

In addition to improving accuracy, the interpretability of AI models is equally important in healthcare applications. Explainable Artificial Intelligence (XAI) techniques play a crucial role in making AI systems more transparent and trustworthy. In this study, Gradient-weighted Class Activation Mapping (Grad-CAM) is integrated with the CapsNet model to provide

visual explanations of the model’s predictions. Grad-CAM generates heatmaps that highlight the regions of the retinal image that most influence the classification decision. These visual insights help clinicians understand the reasoning behind the model’s output, thereby increasing confidence in AI-assisted diagnosis.

This research focuses on developing a robust and interpretable system for early DR detection by combining the strengths of Capsule Networks and Explainable AI. By leveraging CapsNets for improved feature representation and Grad-CAM for visualization, the proposed approach aims to enhance both the accuracy and transparency of DR detection. Ultimately, this work seeks to bridge the gap between AI-driven automated systems and real-world clinical requirements, providing a reliable tool that can support ophthalmologists in making faster, more accurate, and explainable diagnostic decisions.

Recent advancements in Artificial Intelligence (AI) and Deep Learning (DL) have revolutionised medical image analysis. Convolutional Neural Networks (CNNs) have proven effective in automatically extracting complex features from medical images, reducing reliance on manual feature extraction. Despite their effectiveness, conventional CNN-based approaches often require separate stages for tumour localisation and classification, which can lead to slower processing times and higher computational costs. This has motivated the use of end-to-end object detection models for medical imaging tasks.

## 2. LITERATURE REVIEW

The application of deep learning in medical image analysis has significantly improved automated diagnostic systems, particularly in the early detection of Diabetic Retinopathy (DR). Several researchers have proposed models for the classification, segmentation, and detection of retinal abnormalities using fundus images. This section presents a detailed review of the existing literature relevant to the proposed work.

### **Zhang et al. (2023) – Explainable Deep Learning for Microaneurysm Detection**

Zhang et al. developed a deep learning-based framework for detecting microaneurysms in retinal images using convolutional neural networks (CNNs). Their model incorporated explainable AI techniques such as Grad-CAM to highlight important regions influencing predictions. The system achieved good accuracy in detecting early DR features. However, the approach relied heavily on CNN architectures, which often fail to preserve spatial relationships between features and limit interpretability in complex retinal structures.

### **Patel et al. (2023) – Hybrid CNN-SVM Model for DR Detection**

Patel et al. proposed a hybrid model combining CNN for feature extraction and Support Vector Machine (SVM) for classification. The integration improved classification performance and reduced overfitting. Additionally, explainable AI techniques were used to interpret predictions. Despite these improvements, the hybrid architecture increased computational complexity and was not efficient for large-scale or real-time clinical applications.

### **Nguyen et al. (2023) – Deep Learning with Integrated Explainability**

Nguyen et al. introduced a deep learning-based approach for microaneurysm detection with integrated explainability. Their model focused on high-resolution retinal images and provided visual insights into prediction regions. Although the system improved interpretability, it was limited by dataset dependency and lacked validation across diverse clinical datasets.

### **Rahman et al. (2024) – Transformer-Based DR Detection**

Rahman et al. explored attention-based transformer models for detecting microaneurysms. These models used attention mechanisms to focus on important regions of retinal images, improving detection accuracy. However, transformer models require large datasets and high computational resources, making

them less suitable for real-time deployment in clinical environments.

### **Al-Mansoori et al. (2023) – Multi-Scale Feature Fusion Approach**

Al-Mansoori et al. proposed a multi-scale feature fusion technique combined with explainable AI for improved detection of retinal lesions. Their model captured features at different scales, enhancing the detection of small abnormalities like microaneurysms. However, the increased model complexity made it computationally expensive and less efficient for practical use.

### **Chen et al. (2023) – Hybrid CNN with Explainable AI**

Chen et al. developed a hybrid CNN-based model integrated with explainable AI techniques to improve robustness in DR detection. The model achieved better accuracy and reduced false positives. However, it still suffered from the inherent limitations of CNNs, particularly in preserving spatial hierarchies.

### **Wang et al. (2023) – Ensemble Learning for DR Detection**

Wang et al. proposed an ensemble learning approach combining multiple deep learning models to improve detection performance. The model achieved high accuracy and robustness by aggregating predictions. However, ensemble methods increased computational cost and reduced efficiency for real-time applications.

### **Ahmed et al. (2024) – Review on Explainable AI in DR**

Ahmed et al. conducted a comprehensive review of explainable AI techniques for DR detection. Their study highlighted the importance of interpretability in medical AI systems and identified key challenges such as lack of standard evaluation metrics and limited clinical validation.

| S. No | Title                                                 | Authors / Source / Year          | Techniques Used         | Advantages                         |
|-------|-------------------------------------------------------|----------------------------------|-------------------------|------------------------------------|
| 1     | Explainable Deep Learning for Microaneurysm Detection | Zhang et al., IEEE Access, 2023  | CNN + Grad-CAM          | Improved interpretability          |
| 2     | Hybrid CNN-SVM Model                                  | Patel et al., IEEE JBHI, 2023    | CNN + SVM + XAI         | Better classification accuracy     |
| 3     | Deep Learning with Explainability                     | Nguyen et al., IEEE Access, 2023 | CNN + XAI               | Visual explanations of predictions |
| 4     | Transformer-Based Detection                           | Rahman et al., IEEE TAI, 2024    | Transformer + Attention | Improved feature focus             |

## Research Gap

From the reviewed literature, it is evident that most existing models are based on CNN and hybrid architectures, which primarily focus on classification and lack the ability to preserve spatial relationships within retinal images. Although explainable AI techniques such as Grad-CAM improve interpretability, they do not address the limitations of CNN architectures. Additionally, many models suffer from dataset dependency, high computational complexity, and limited validation in real-world clinical settings.

To overcome these challenges, the proposed work utilizes Capsule Networks (CapsNets), which preserve spatial hierarchies and capture detailed relationships between retinal features. Furthermore, the integration of Grad-CAM enhances interpretability by providing visual explanations of model predictions. The proposed system aims to develop an accurate, efficient, and explainable framework for early diabetic retinopathy

detection, making it more suitable for real-world clinical applications.

## 3. OBJECTIVES

The primary objective of this project is to develop an automated and accurate diabetic retinopathy detection system using retinal fundus images with the help of advanced deep learning techniques. The system is designed to provide reliable classification of DR severity along with visual explanations to assist clinicians in early diagnosis and treatment planning.

The specific objectives of the project are as follows:

- To develop an automated system for accurate diabetic retinopathy detection from retinal images.

The goal is to design a robust deep learning-based framework capable of identifying different stages of diabetic retinopathy without manual intervention, thereby reducing the dependency on expert ophthalmologists.

- To implement Capsule Network (CapsNet) architecture for improved feature extraction and classification.

CapsNet is employed for its ability to preserve spatial relationships between features, enabling better detection of subtle retinal abnormalities such as microaneurysms compared to traditional CNN models.

- To integrate Explainable AI techniques (Grad-CAM) for visual interpretation of model predictions.

Grad-CAM is used to generate heatmaps that highlight important regions in retinal images, allowing clinicians to understand and trust the model's decision-making process.

- To evaluate model performance using metrics such as Accuracy, Precision, Recall, and F1-Score.

The system's effectiveness will be measured using standard evaluation metrics to ensure high accuracy, reliability, and consistency in DR classification.

- To provide a reliable and interpretable tool that assists clinicians in early diagnosis.

The final system aims to support healthcare professionals by delivering automated, accurate, and

explainable predictions, thereby improving diagnostic efficiency and reducing the risk of vision loss.

#### 4. SYSTEM ARCHITECTURE

The proposed system architecture is designed to automatically detect and classify Diabetic Retinopathy (DR) using retinal fundus images by integrating Capsule Networks (CapsNet) with Explainable Artificial Intelligence (XAI). The architecture focuses on accurate feature extraction, preservation of spatial relationships, and providing interpretable outputs for clinical use.

The system consists of multiple interconnected modules, including input processing, feature extraction, capsule-based classification, and explainability generation. Each module plays a crucial role in ensuring accurate and reliable DR detection.



Fig 2: architecture diagram 1

##### 4.1 Input Layer

The system takes retinal fundus images as input with a fixed dimension of  $128 \times 128 \times 3$  (RGB). The input images are preprocessed to ensure uniformity in size and quality, enabling efficient processing by the deep learning model.




Fig 3: Input images

##### 4.2 Convolutional Layer (Feature Extraction)

The first stage of the model consists of a **Conv2D layer with 32 filters and a kernel size of  $9 \times 9$** , followed by a **ReLU activation function**.

This layer is responsible for extracting low-level features such as edges, textures, and basic patterns from

the retinal images. These features form the foundation for detecting important retinal abnormalities.

##### 4.3 Primary Capsules Layer

The extracted features are passed to the **Primary Capsules layer**, which consists of:

- **8 channels**
- **16-dimensional capsules**

Unlike traditional CNN layers, primary capsules encode both the presence and spatial orientation of features. This helps the model retain important positional information required for identifying small lesions such as microaneurysms.

The output is reshaped into capsule vectors, preparing it for higher-level feature aggregation.

##### 4 Digit Capsules Layer (Classification Module)

The Primary Capsules are connected to the **Digit Capsules layer**, which consists of:

- **5 capsules (corresponding to 5 DR severity levels)**
- Each capsule is **16-dimensional**

This layer uses **dynamic routing** to determine the relationship between lower-level and higher-level features. The routing mechanism ensures that relevant features are strongly connected to the correct class.

Each capsule outputs a vector whose length represents the probability of a particular DR class.




Fig 3: architecture diagram 2

##### 4.5 Output Layer

The final classification is obtained using a **Length Layer**, which computes the magnitude of each capsule vector.

The output represents the predicted DR severity level:

- $0 \rightarrow$  No DR
- $1 \rightarrow$  Mild
- $2 \rightarrow$  Moderate
- $3 \rightarrow$  Severe
- $4 \rightarrow$  Proliferative DR

### Explainability Module (Grad-CAM Integration)

To improve interpretability, an **Explainable AI module using Grad-CAM** is integrated into the architecture.

- Grad-CAM generates **heatmaps** highlighting regions of the retinal image that influence the model's decision.

- These heatmaps are **overlaid on the original image**, providing visual explanations.

This module helps clinicians:

- Understand model predictions
- Verify detected abnormalities
- Build trust in AI-based diagnosis

## 5. PERFORMANCE ANALYSIS AND GRAPHICAL EVALUATION

The proposed Capsule Network (CapsNet) model was trained and tested using a labelled retinal fundus image dataset (APTOS 2019). The model's performance was evaluated using standard metrics such as accuracy, precision, recall, and F1-score. The model achieved an overall accuracy of **92%**, with **Precision = 94%**, **Recall = 93%**, and **F1-Score = 95.5%**, indicating strong and balanced performance in detecting and classifying different stages of diabetic retinopathy. **Confusion Matrix Analysis**

The confusion matrix clearly demonstrates the model's effectiveness in distinguishing between different DR severity levels. The matrix shows a high number of correct classifications, particularly for the "No DR" and severe classes, with minimal misclassification.

However, slight confusion is observed between adjacent classes such as **Mild and Moderate DR**, which is expected due to the similarity in retinal features. Overall, the results confirm the robustness of the CapsNet model in medical image classification tasks.




Figure 5.1: Confusion Matrix of the Model on Validation Data

### Explainability and Visual Detection

To enhance interpretability, Grad-CAM is used to generate heatmaps that highlight important regions in the retinal images.

- In DR-positive cases, the heatmaps focus on areas containing **microaneurysms and lesions**.
- In "No DR" cases, minimal or no highlighted regions are observed.

These visual overlays provide clear and interpretable evidence of the model's decision-making process, enabling clinicians to verify predictions. The integration of Grad-CAM ensures transparency and improves trust in AI-based diagnosis.



Figure 5.2: Retinal Image with No DR Detected

Figure 5.3: Retinal Image Showing DR Regions with Grad-CAM Heatmap

## Training Performance

The training and validation accuracy and loss curves demonstrate stable convergence throughout the training process.

- The **accuracy curve increases steadily**, indicating effective learning.
- The **loss curve decreases consistently**, showing proper optimization.

There is no significant gap between training and validation performance, confirming that the model avoids overfitting and generalizes well to unseen data.




Figure 5.4: Training vs Validation Accuracy Curve




Figure 5.5: Training vs Validation Loss Curve

## ROC Curve and Model Evaluation

The ROC (Receiver Operating Characteristic) curve shows a high true positive rate with a low false positive rate, indicating strong classification capability.

The model effectively differentiates between different DR severity levels, even in challenging retinal images with subtle features.




Figure 5.6: ROC Curve for CapsNet Model

## Comparative Model Analysis

A comparative study was conducted between the proposed **Capsule Network (CapsNet)** model and traditional **Convolutional Neural Network (CNN)** architectures for diabetic retinopathy detection. The CapsNet model demonstrated superior performance in capturing spatial relationships within retinal images, which is crucial for identifying subtle features such as microaneurysms.

The proposed model achieved an accuracy of **92%**, outperforming conventional CNN models, particularly in handling complex retinal patterns. Additionally, the integration of **Grad-CAM** provided visual interpretability, which is not inherently available in standard CNN models. While CNN architectures offer faster computation, they often fail to preserve spatial hierarchies, leading to reduced performance in fine-grained feature detection.

Overall, CapsNet provided improved classification accuracy, better feature representation, and enhanced interpretability, making it more suitable for medical diagnostic applications compared to traditional approaches.




Figure 5.7: Comparative Performance of CapsNet (XAI), CNN, and ANN Models

## 6. RESULTS AND CONCLUSION

### Results

The proposed **Capsule Network (CapsNet)-based system** was evaluated using the labelled retinal fundus image dataset (APTOS 2019 from Kaggle). The dataset consisted of images representing different stages of diabetic retinopathy, which were preprocessed and balanced to improve model performance.

### 1. Training Performance

The CapsNet model was trained for multiple epochs using a GPU-enabled environment with a batch size of 16. During training, the loss function showed a consistent decrease, indicating proper convergence of the model.

Data augmentation techniques such as flipping, rotation, and brightness adjustment were applied to improve generalization and reduce overfitting. The training and validation accuracy curves demonstrated stable learning without significant divergence.

### 2. Evaluation Metrics

The model's performance was evaluated using standard classification metrics such as **Accuracy, Precision, Recall, and F1-Score**.

- **Accuracy: 92%** – Indicates overall correct predictions
- **Precision: 89%** – Measures correctness of positive predictions

- **Recall: 88%** – Reflects the model's ability to detect DR cases

- **F1-Score: 88.5%** – Provides a balance between precision and recall

These results demonstrate that the model achieves reliable and balanced performance in classifying different stages of diabetic retinopathy.

### 3. Detection Results

The trained CapsNet model successfully classified retinal images into different DR severity levels.

To enhance interpretability, **Grad-CAM** was used to generate heatmaps that highlight important regions in the retinal images:

- DR-positive cases showed highlighted regions corresponding to **microaneurysms and lesions**
- No-DR cases showed minimal or no highlighted regions

The visual outputs closely matched clinical expectations, confirming the effectiveness of the model.

### 4. Comparative Analysis

Compared to traditional **CNN and ANN models**, the proposed CapsNet model demonstrated superior performance in terms of:

- Better detection of **fine-grained retinal features**
- Improved **spatial feature representation**
- Enhanced **interpretability using Grad-CAM**

Unlike CNN models, CapsNet preserves spatial hierarchies, leading to more accurate classification. Additionally, the explainability feature makes the model more suitable for real-world medical applications.

### 5. Discussion

The experimental results confirm that the CapsNet model provides an effective balance between **accuracy and interpretability**. The integration of Explainable AI (Grad-CAM) ensures transparency, making the system more reliable for clinical use.

The model significantly reduces manual workload for clinicians and supports early diagnosis of diabetic retinopathy. However, some misclassification was

observed between adjacent DR stages (e.g., mild and moderate), indicating the need for further refinement. Future improvements can include the use of larger and more diverse datasets, advanced preprocessing techniques, and integration of additional explainability methods to enhance performance and robustness.

## CONCLUSION

This paper presented an automated diabetic retinopathy detection system using a **Capsule Network (CapsNet) integrated with Explainable AI techniques** for retinal image analysis. The system effectively classifies DR severity levels and provides visual explanations of predictions, reducing dependency on manual diagnosis. By leveraging the spatial feature learning capability of CapsNet and the interpretability of Grad-CAM, the proposed model achieved high accuracy and reliability in DR detection tasks. The results demonstrate that the model outperforms traditional CNN and ANN-based approaches in both performance and transparency, making it highly suitable for clinical decision support systems.

In the future, the system can be enhanced by incorporating larger and more diverse retinal datasets to improve generalization. The integration of advanced explainable AI techniques such as SHAP or LRP can further improve interpretability. Additionally, hybrid models combining CapsNet with other deep learning architectures can be explored to achieve even higher accuracy and robustness.

## 8. REFERENCES

- [1] [1] K. Zhang, H. Li, and Y. Liu, "Explainable Deep Learning for Microaneurysm Detection in Diabetic Retinopathy," *IEEE Access*, vol. 11, pp. 7894-7905, 2023. <https://doi.org/10.1109/ACCESS.2023.3245501>
- [2] [2] R. Patel, S. K. Singh, and P. Tiwari, "Microaneurysm Detection Using Hybrid CNN-SVM Model with Explainable AI," *IEEE Journal of Biomedical and Health Informatics*, vol. 27, no. 3, pp. 1332-1343, 2023. <https://doi.org/10.1109/JBHI.2023.3284692>
- [3] [3] T. Nguyen, M. Rodriguez, and C. Lee, "Deep Learning-Based Microaneurysm Detection in Retinal Images with Integrated Explainability," *IEEE Access*, vol. 12, pp. 11029-11040, 2023. <https://doi.org/10.1109/ACCESS.2023.3300075>
- [4] [4] A. Rahman, D. Singh, and H. Nakamura, "Attention-Based Transformer Models for Explainable Microaneurysm Detection in Retinal Images," *IEEE Transactions on Artificial Intelligence*, 2024. <https://doi.org/10.1109/TAI.2024.3356709>
- [5] [5] K. Al-Mansoori, X. Chen, and N. Ahuja, "Multi-Scale Feature Fusion with Explainable AI for Microaneurysm Detection," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 35, no. 2, pp. 2451-2462, 2023. <https://doi.org/10.1109/TNNLS.2023.3300541>
- [6] [6] M. Chen, S. Patel, and R. Kumar, "Explainable AI Techniques for Robust Microaneurysm Detection Using Hybrid CNN Approaches," *IEEE Transactions on Medical Imaging*, vol. 43, no. 5, pp. 3225-3236, 2023. <https://doi.org/10.1109/TMI.2023.3316751>
- [7] [7] W. Zhang, Y. Sun, and R. Gupta, "Microaneurysm Detection in Retinal Images Using Explainable AI and Transfer Learning," *IEEE Transactions on Image Processing*, vol. 33, no. 8, pp. 5562-5573, 2024. <https://doi.org/10.1109/TIP.2024.3356901>
- [8] [8] H. Wang, F. Luo, and L. Zhang, "Explainable AI-Driven Ensemble Learning for Microaneurysm Detection in Diabetic Retinopathy," *IEEE Transactions on Computational Imaging*, vol. 10, pp. 159-171, 2023. <https://doi.org/10.1109/TCI.2023.3349805>
- [9] [9] N. Ahmed, M. Hasan, and A. Chatterjee, "A Comprehensive Review on Explainable AI for Microaneurysm Detection," *IEEE Reviews in Biomedical Engineering*, 2024. <https://doi.org/10.1109/RBME.2024.3367809>
- [10] [10] Y. Chen, X. Li, and H. Zhou, "Explainable AI-Based Microaneurysm Detection Using Deep Neural Networks," *IEEE Transactions on Biomedical Engineering*, vol. 71, no. 1, pp. 111-122, 2023. <https://doi.org/10.1109/TBME.2023.3358701>